

CGA

Compressed Gas Association

The Standard For Safety Since 1913

CGA G-6.2-2011 COMMODITY SPECIFICATION FOR CARBON DIOXIDE

SIXTH EDITION

Currently in preview, click buy full version

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our website, www.cganet.com.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at www.cganet.com. For more information contact CGA. Phone: 703-788-2700, ext. 799. E-mail: customerservice@cganet.com.

Work Item 08-013
Carbon Dioxide Committee

NOTE—Technical changes from the previous edition are underlined.

SIXTH EDITION: 2011
FIFTH EDITION: 2004
FOURTH EDITION: 2000
THIRD EDITION: 1994

© 2011 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

Contents	Page
1 Scope	1
2 Classification	1
2.1 Types	1
2.2 Quality verification levels	1
2.3 Quality tests	1
2.4 Typical sources	1
3 Quality verification systems	4
3.1 Source evaluations	4
3.2 Production qualification tests	5
3.3 Lot acceptance tests	6
4 Sampling	6
4.1 Sample volume	6
4.2 Gaseous samples	7
4.3 Liquid samples	7
5 Analytical procedures	7
5.1 Parameters of analysis	7
5.2 Carbon dioxide identification	8
5.3 Carbon dioxide purity	8
5.4 Acetaldehyde content	9
5.5 Ammonia content	9
5.6 Benzene content	9
5.7 Carbon monoxide content	10
5.8 Carbonyl sulfide content	10
5.9 Hydrogen cyanide content	10
5.10 Hydrogen sulfide content	10
5.11 Methanol content	11
5.12 Nitric oxide content	11
5.13 Nitrogen dioxide content	11
5.14 Nonvolatile residue content	12
5.15 Odor/taste	12
5.16 Oil/grease content	12
5.17 Oxygen content	13
5.18 Phosphine content	13
5.19 Sulfur dioxide content	13
5.20 Total hydrocarbon content	13
5.21 Total sulfur content	14
5.22 Water/dew point content	14
6 Containers	14
6.1 Carbon dioxide containers	14
6.2 Container preparation	15
6.3 Container filling	15
6.4 Carbon dioxide USP	15
6.5 Valves on carbon dioxide containers	15
7 Supplemental data	16
7.1 Pressure and temperature data	16
7.2 Moisture conversion data	16
8 References	18

Figure

Figure 1—Approximate pressure in uninsulated carbon dioxide cylinders filled to indicated densities at selected temperatures..... 2

Tables

Table 1—Directory of limiting characteristics/QVLs 3
Table 2—Typical uses..... 4
Table 3—Possible trace level impurities by source type (excluding air gases and water)..... 4
Table 4—Moisture conversion data [23] 7

Currently in preview, click buy full version

1 Scope

This publication describes the specification requirements for gaseous, liquid, and solid carbon dioxide.

The term container as used in this publication shall refer to portable compressed gas cylinders and liquid containers made in accordance with the U.S. Department of Transportation (DOT) in Title 49 of the U.S. *Code of Federal Regulations* (49 CFR) Parts 100-180; Transport Canada (TC); or the American Society of Mechanical Engineers (ASME) specifications [1, 2, 3].¹

NOTE—This publication does not recommend or establish the end usage designation for specific types or grades of products. Users requiring this kind of information should contact individual gas suppliers.

2 Classification

2.1 Types

Carbon dioxide above the triple point temperature of $-69.9\text{ }^{\circ}\text{F}$ ($-56.6\text{ }^{\circ}\text{C}$) and below the critical point temperature of $87.9\text{ }^{\circ}\text{F}$ ($31.1\text{ }^{\circ}\text{C}$) can exist in both a gaseous and a liquid state. Carbon dioxide in cylinders at ambient temperature is at relatively high pressure (see Figure 1). Bulk carbon dioxide is commonly maintained as a refrigerated low temperature liquid and vapor from 200 psig to 350 psig (1380 kPa to 2400 kPa).² Carbon dioxide can also exist as a white opaque solid with a temperature of $-109.3\text{ }^{\circ}\text{F}$ ($-78.5\text{ }^{\circ}\text{C}$) at atmospheric pressure.

2.2 Quality verification levels

Table 1 presents the component maxima in parts per million (ppm [v/v]) unless otherwise shown for the quality verification levels (QVLs) of carbon dioxide. The absence of a value in a given QVL does not imply that the limiting characteristic is or is not present but merely indicates that the test is not required for compliance with the specification. Typical uses are listed in Table 2.

QVLs E, G, H, and I generally refer to carbon dioxide as a liquid. QVL J refers to carbon dioxide as a solid (dry ice).

2.3 Quality tests

The supplier ensures by standard practice the QVL of carbon dioxide. If otherwise required, alternative control procedures are described in 3.3.1, 3.3.2, and Sections 4 and 5. Other control procedures not listed in this specification are acceptable if agreed upon between the supplier and the customer.

2.4 Typical sources

Carbon dioxide is produced as the by-product of many different natural and chemical processing mechanisms. This capability of multiple source origins makes it unique in the industrial gas market. The variation of sources results in a variety of impurities that can be expected in carbon dioxide. Typical sources and their respective anticipated impurities are listed in Table 3.

¹ References are shown by bracketed numbers and are listed in order of appearance in the reference section.

² kPa shall indicate gauge pressure unless otherwise noted as (kPa, abs) for absolute pressure or (kPa, differential) for differential pressure. All kPa values are rounded off per CGA P-11, *Metric Practice Guide for the Compressed Gas Industry* [4].