



**CGA P-16—2020  
GUIDELINE FOR  
NITROGEN PURGING OF  
CONTAINERS**

**FOURTH EDITION**

Currently in preview, click buy full version

**PLEASE NOTE:**

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA. Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 18-042

Bulk Distribution Equipment and Standards Committee

NOTE—Technical changes from the previous edition are underlined

FOURTH EDITION: 2020  
THIRD EDITION 2014  
SECOND EDITION 2006  
REAFFIRMED 2000  
FIRST EDITION: 1992

© 2020 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope .....	1
3 Definitions.....	1
4 Safety precautions for liquid nitrogen .....	2
4.1 General.....	2
4.2 Personnel protection.....	2
4.3 Mitigating asphyxiant hazards .....	2
4.4 Proper nitrogen transfer equipment.....	2
5 Nitrogen application procedure .....	3
5.1 Initial preparation .....	3
5.2 Nitrogen purge procedure.....	4
5.3 Preparation for shipment .....	9
6 References .....	9
<b>Figures</b>	
Figure 1—Typical nitrogen purge arrangement .....	5
Figure 2—Alternate nitrogen purge arrangement .....	6
Figure 3—Typical nitrogen purge setup .....	7
Figure 4—Typical nitrogen purge equipment .....	8

## 1 Introduction

Member companies of the Compressed Gas Association, Inc. (CGA) recognize the need for a guideline to safely use nitrogen vaporized from a liquid nitrogen source to purge containers.

**WARNING:** *Nitrogen is extremely cold in the liquid state and special precautions are necessary to protect equipment that might not be designed to withstand extremely low temperatures from cold purge gas. Introduction of liquid nitrogen or cold nitrogen gas into containers not designed for cryogenic liquid temperatures or cold gas, can result in a container failure or bodily harm, resulting in serious injury or death.*

**WARNING:** *Nitrogen is an asphyxiant and has no warning properties. It is undetectable because in its gaseous phase it is colorless, odorless, and tasteless. Accumulation of nitrogen in containers that are being purged and in OSHA-confined spaces where work is performed can place personnel at risk, resulting in serious injury or death.*

This publication is intended to protect personnel during the vaporization of liquid nitrogen and the subsequent use of gaseous nitrogen for purging containers. It should be read thoroughly before using nitrogen to purge a container.

## 2 Scope

This publication describes a recommended procedure for nitrogen purging of containers to ensure the safest possible work environment during the nitrogen application process. It also describes protecting the container from hazards associated with exposure to liquid nitrogen.

## 3 Definitions

For the purposes of this publication, the following definitions apply.

### 3.1 Publication terminology

#### 3.1.1 Shall

Indicates that the procedure is mandatory. It is used whenever the criterion for conformance to specific recommendations allows no deviation.

#### 3.1.2 Should

Indicates that a procedure is recommended.

#### 3.1.3 May

Indicates that the procedure is optional.

#### 3.1.4 Will

Is used only to indicate the future, not a degree of requirement.

#### 3.1.5 Can

Indicates a possibility or ability.

### 3.2 Technical definitions

#### 3.2.1 Container

Vessels of various shapes, sizes, materials of construction (cylinders or portable or stationary tanks), and designs meeting the specifications of American Society for Mechanical Engineers (ASME), Transport Canada (TC), U.S. Department of Transportation (DOT), or the applicable pressure vessel authority.

#### 3.2.2 **Maximum allowable working pressure (MAWP)**

Maximum gauge pressure permissible at the top of a vessel in its operating position for a designated temperature.