



**CGA P-92-2022**  
**STANDARD FOR PORTABLE**  
**LIQUID NITROGEN PUMPER**  
**SYSTEMS**

**FIRST EDITION**

Currently in preview, click buy full version

**PLEASE NOTE:**

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA. Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 18-103

Bulk Distribution Equipment and Standards Committee

---

FIRST EDITION: 2022

© 2022 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope .....	1
3 Definitions.....	1
4 Health and safety considerations .....	2
4.1 General.....	2
4.2 Personal protective equipment.....	2
4.3 Pressure hazards .....	3
4.4 Temperature hazards .....	3
5 Customer and supplier responsibilities.....	3
6 Site selection and preparation.....	5
6.1 Code compliance.....	5
6.2 Site surface requirements.....	5
6.3 Site utility requirements .....	6
6.4 Equipment layout.....	6
7 Pumper system equipment selection .....	6
7.1 Bulk liquid nitrogen container .....	9
7.2 Optional low pressure centrifugal boost pump .....	10
7.3 High pressure reciprocating pump.....	10
7.4 High pressure vaporizer .....	11
7.5 Check valves .....	12
7.6 Operator controls and alarms.....	12
7.7 Customer interface .....	12
8 Transportation of pumper system.....	13
8.1 Hazardous materials regulations .....	13
8.2 Securing of loose equipment.....	13
9 Pumper system installation .....	13
9.1 Pre-installation site review.....	13
9.2 Job summary sheet.....	13
9.3 Piping and hoses.....	14
9.4 Pressure relief device requirements .....	16
9.5 Grounding of equipment.....	16
9.6 Emergency shutdown (e-stop).....	17
10 Pumper system operation .....	17
10.1 Pre-startup safety review.....	17
10.2 Safety control device testing and inspection .....	17
10.3 Monitoring.....	18
11 Pumper system shutdown and equipment removal .....	18
11.1 Pump shutdown.....	18
11.2 Vaporizer shutdown.....	18
11.3 System depressurization and disassembly .....	18
11.4 Preparation of pumper system for road transport.....	19
12 References .....	19
<b>Figure</b>	
Figure 1—Example of a pumper system process and instrumentation drawing (P&ID) .....	1
Figure 2—HMIS Hazardous material label for liquid nitrogen .....	10
Figure 3—Typical piping at customer interface—Hose restraints, safety valve, isolation valve, blowdown valve, and required labeling .....	12
<b>Table</b>	
Table 1—Key to Figure 1 .....	8

## 1 Introduction

Portable liquid nitrogen pumper systems supply high pressure nitrogen gas to customers. These systems are typically used for purging, inerting, drying, or pressurizing customer systems and oilfield applications. Systems are typically temporary and not meant to serve as permanent systems.

Pumper systems can have maximum discharge pressures up to 15 000 psi (103 400 kPa) and maximum flow rates greater than 500 000 scfh (2620 m<sup>3</sup>/hr).<sup>1,2</sup> Operating temperature can range from –320 °F to 650 °F (–196 °C to 343 °C).

## 2 Scope

This standard contains minimum requirements for siting, selecting equipment for, installing, filling, starting up, operating, maintaining, and removing portable liquid nitrogen pumper systems, referred to as pumper systems in this publication.

Pumper systems can be built as any of the following configurations:

- Truck systems, where the pumper system is mounted on a straight or bobtail truck that fully supports itself with front and rear axles. The truck is driven to the customer site and parked as a complete unit;
- Semi-trailer systems, where the pumper system is mounted on a semi-trailer that supports itself only on the rear axles and the front is supported by a truck. The semi-trailer is driven to the customer site, may be disconnected from the truck, and parked without the truck; and
- Skid-mounted systems, where the pumper system is mounted on a framework that is delivered on a semi-trailer and unloaded for use at the customer site.

The scope is limited to truck and semi-trailer systems and does not include skid-mounted systems.

This standard does not apply to pumper systems that supply gases other than nitrogen.

## 3 Definitions

For the purpose of this publication, the following definitions apply.

### 3.1 Publication terminology

#### 3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

#### 3.1.2 Should

Indicates that a procedure is recommended.

#### 3.1.3 May

Indicates that the procedure is optional.

#### 3.1.4 Will

Is used only to indicate the future, not a degree of requirement.

#### 3.1.5 Can

Indicates a possibility or ability.

<sup>1</sup> psi, bar, and kPa shall indicate gauge pressure unless otherwise noted as (psia; bar, abs; and kPa, abs) for absolute pressure or (psid; bar, dif; and kPa, dif) for differential pressure. All kPa values are rounded off per CGA P-11, *Guideline for Metric Practice in the Compressed Gas Industry* [1].

<sup>2</sup> References are shown by bracketed numbers and are listed in order of appearance in the reference section.