

CGA V-15—2024

2ND EDITION

**USE OF RESIDUAL
PRESSURE VALVES**



Currently in preview, click buy full version

PREFACE

As part of a program of harmonization of industry standards, the Compressed Gas Association (CGA) has issued CGA V-15, *Use of Residual Pressure Valves*, jointly produced by members of the International Harmonization Council and originally published by the European Industrial Gases Association (EIGA) as EIGA Doc 64, *Use of Residual Pressure Valves*.

This publication is intended as an international harmonized standard for the worldwide use and application of all members of the Asia Industrial Gases Association (AIGA), Compressed Gas Association (CGA), European Industrial Gases Association (EIGA), and Japan Industrial and Medical Gases Association (JIMGA). Each association's technical content is identical, except for regional regulatory requirements and minor changes in formatting and spelling.

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, www.cganet.com.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at www.cganet.com. For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: customerservice@cganet.com.

Work Item 21-060
Cylinder Valve Committee

NOTE—Technical changes from the previous edition are underlined.

SECOND EDITION: 2024
FIRST EDITION: 2016

© 2024 – Reproduced with permission from, the European Industrial Gases Association. All rights reserved.

Contents	Page
1 Introduction.....	1
2 Scope and purpose	1
2.1 Scope	1
2.2 Purpose	1
3 Definitions.....	1
4 Residual pressure valve types	2
4.1 Type 1 RPD.....	2
4.2 Type 2 RPD.....	2
5 Benefits of residual pressure valves.....	2
6 Applications.....	3
7 Use of residual pressure valves—Filling facilities	3
7.1 Prefill inspection recommendations and requirements.....	3
7.2 Fill connectors	4
7.3 Installing residual pressure valves into cylinders.....	6
7.4 Devalving cylinders equipped with residual pressure valves	6
7.5 Inspection and maintenance	6
8 References	6
Figures	
Figure 1—Example of a filling connector with a fixed pin.....	5
Figure 2—Example of a filling connector with a retractable pin.....	5

1 Introduction

Cylinder valves that retain a residual positive pressure in a gas cylinder and some types of devices that prevent backflow of fluid by means of a non-return device, commonly referred to as residual pressure valves (RPV), have been available for many years. Important benefits of RPVs include preventing moisture ingress and contamination, which reduce the potential for internal cylinder corrosion. Additional benefits include productivity improvements in the cylinder fill operation, avoiding internal cylinder contamination that could create hazardous situations, and reducing cylinder maintenance.

In the past, industry relied on users not to allow backflow into cylinders. Fillers typically relied on prefill inspection procedures to identify potentially contaminated cylinders returned from customers. Despite these measures, incidents caused by backflow of contaminants into cylinders have occurred, which highlights the potential benefit from usage of RPVs. CGA C-17, Methods to Avoid and Detect Internal Corrosion of Gas Cylinders and Tubes describes methods to avoid and detect internal gas cylinder corrosion and EIGA Doc 908, 300 Bar Residual Pressure Valve Filling Connectors standardizes the filling connector for 300 bar RPVs [1, 2].¹

The use of RPVs generally requires a special fill connector for filling, evacuation, or both.

2 Scope and purpose

2.1 Scope

This publication is intended for use by the compressed gas industry and provides guidelines for the use of RPVs. This publication does not describe any design qualification tests of RPVs.

2.2 Purpose

The purpose of this publication is to give guidance on the selection, operation, maintenance, and installation of these valves, so common practices are established across the gas industry and these valves are beneficial to both the end user and gas cylinder filling facilities.

3 Definitions

For the purpose of this publication, the following definitions apply.

3.1 Publication terminology

3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

3.1.2 Should

Indicates that a procedure is recommended.

3.1.3 May

Indicates that the procedure is optional.

3.1.4 Will

Is used only to indicate the future, not a degree of requirement.

3.1.5 Can

Indicates a possibility or ability.

¹ References are shown by bracketed numbers and are listed in order of appearance in the reference section.