



CSA/ANSI Z21.47:21 • CSA 2.3:21
National Standard of Canada
American National Standard



Gas-fired central furnaces



scc  ccn

Legal Notice for Standards

Canadian Standards Association and CSA America Standards, Inc. (operating as "CSA Group") develop standards through a consensus standards development process approved by the Standards Council of Canada and the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus and develop a standard. Although CSA Group administers the process and establishes rules to promote fairness in achieving consensus, it does not independently test, evaluate, or verify the content of standards.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. CSA Group does not warrant the accuracy, completeness, or currency of any of the information published in this document. CSA Group makes no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL CSA GROUP, ITS VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF CSA GROUP HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, CSA Group is not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and CSA Group accepts no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

CSA Group is a private not-for-profit company that publishes voluntary standards and related documents. CSA Group has no power, nor does it undertake, to enforce compliance with the contents of the standards or other documents it publishes.

Intellectual property rights and ownership

As between CSA Group and the users of this document (whether it be in printed or electronic form), CSA Group is the owner, or the authorized licensee, of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. Without limitation, the unauthorized use, modification, copying, or disclosure of this document may violate laws that protect CSA Group's and/or others' intellectual property and may give rise to a right in CSA Group and/or others to seek legal redress for such use, modification, copying, or disclosure. To the extent permitted by licence or by law, CSA Group reserves all intellectual property rights in this document.

Patent rights

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights. CSA Group shall not be held responsible for identifying any or all such patent rights. Users of this standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.

Authorized use of this document

This document is being provided by CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in printed or paper form may be distributed only to persons who are authorized by CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and must not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



Standards Update Service

CSA/ANSI Z21.47:21 • CSA 2.3:21
May 2021

Title: *Gas-fired central furnaces*

To register for e-mail notification about any updates to this publication

- go to www.csagroup.org/store/
- click on **Product Updates**

The **List ID** that you will need to register for updates to this publication is **242825**

If you require assistance, please e-mail techsupport@csagroup.org or call 419-747-2233.

Visit CSA Group's policy on privacy at www.csagroup.org/legal to find out how we protect your personal information.

Canadian Standards Association (operating as “CSA Group”), under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users — including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

Individuals, companies, and associations across Canada indicate their support for CSA Group’s standards development by volunteering their time and skills to Committee work and supporting CSA Group’s objectives through sustaining memberships. The more than 7000 committee volunteers and the 2000 sustaining memberships together form CSA Group’s total membership from which its Directors are chosen. Sustaining memberships represent a major source of income for CSA Group’s standards development activities.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects products that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in eight countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to
CSA Group
178 Rexdale Boulevard
Toronto, Ontario, M9W 1R3
Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada’s economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

Standards Council of Canada
600-55 Metcalfe Street
Ottawa, Ontario, K1P 6L5
Canada



Cette Norme Nationale du Canada n’est disponible qu’en anglais.

Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users to judge its suitability for their particular purpose.

**A trademark of the Canadian Standards Association, operating as “CSA Group”*

CSA Group

The Canadian Standards Association (operating as "CSA Group"), under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

Individuals, companies, and associations across Canada indicate their support for CSA Group's standards development by volunteering their time and skills to Committee work and supporting CSA Group's objectives through sustaining memberships. The more than 7000 committee volunteers and the 2000 sustaining memberships together form CSA Group's total membership from which its Directors are chosen. Sustaining memberships represent a major source of income for CSA Group's standards development activities.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects product that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in eight countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to
CSA Group
178 Rexdale Boulevard, Toronto, Ontario,
Canada M9W 1R3

American National Standards Institute

The American National Standards Institute (ANSI), Inc. is the nationally recognized coordinator of voluntary standards development in the United States through which voluntary organizations, representing virtually every technical discipline and every facet of trade and commerce, organized labor and consumer interests, establish and improve the some 10,000 national consensus standards currently approved as American National Standards.

ANSI provides that the interests of the public may have appropriate participation and representation in standardization activity, and cooperates with departments and agencies of U.S. Federal, State and local governments in achieving compatibility between government codes and standards and the voluntary standards of industry and commerce.

ANSI represents the interests of the United States in international nontreaty organizations such as the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC). The Institute maintains close ties with regional organizations such as the Pacific Area Standards Congress (PASC) and the Pan American Standards Commission (COPANT). As such, ANSI coordinates the activities involved in the U.S. participation in these groups.

ANSI approval of standards is intended to verify that the principles of openness and due process have been followed in the approval procedure and that a consensus of those directly and materially affected by the standards has been achieved. ANSI coordination is intended to assist the voluntary system to ensure that national standards needs are identified and met with a set of standards that are without conflict or unnecessary duplication in their requirements.

Responsibility of approving American standards rests with the
American National Standards Institute, Inc.
25 West 43rd Street, Fourth floor
New York, NY 10036

*National Standard of Canada
American National Standard*

**CSA/ANSI Z21.47:21 • CSA 2.3:21
Gas-fired central furnaces**



IGAC

*Interprovincial
Standards Advisory Council*

*®A trademark of the Canadian Standards Association
and CSA America Standards Inc., operating as "CSA Group."*



*American National
Standards Institute, Inc.*

*Approved on April 21, 2021 by ANSI
Approved on March 25, 2021 by IGAC
Published in May 2021 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard, Toronto, Ontario, Canada M9W 1R3*

*To purchase standards and related publications, visit our Online Store at www.csagroup.org/store/
or call toll-free 1-800-463-6727 or 416-747-4044.*

*ICS 91.140.10
ISBN 978-1-4883-3001-8*

*© 2021 Canadian Standards Association
All rights reserved. No part of this publication may be reproduced in any form whatsoever
without the prior permission of the publisher.*

Contents

Interprovincial Gas Advisory Council	11
Z21/83 Technical Committee on Performance and Installation of Gas Burning Appliances and Related Accessories	13
Canadian Technical Committee on Gas Appliances and Related Accessories	16
Z21/CSA Joint Technical Subcommittee on Standards for Gas-Fired Central Furnaces	19
Preface	23
0 History of the development of <i>Gas-fired central furnaces</i>	25
1 Scope	28
2 Reference publications	29
3 Definitions	35
4 Construction	47
4.1 General construction and assembly	47
4.1.1 Equivalent performance	47
4.1.2 Asbestos	47
4.1.3 Separation of the products of combustion and the circulating air stream	47
4.1.4 Flame roll-out safety shutoff	47
4.1.5 Return air duct	47
4.1.6 Furnace with a draft hood	47
4.1.7 Sharp projections or edges and screw ends	47
4.1.8 Insulating material retention	47
4.1.9 Displacement, distortion, warping, or other damage from normal usage	48
4.1.10 Non-metallic tubing	48
4.1.11 Heating element joints	48
4.1.12 Condensate system(s) located in the return air compartment	48
4.1.13 Removable flue baffles	48
4.1.14 Removable clean-out plate fasteners	49
4.1.15 Reusable fasteners for service	49
4.1.16 Corrosion-resistant fasteners for service	49
4.1.17 Furnace base	49
4.1.18 Furnace sub-base	49
4.1.19 Down-flow furnace base and sub-base	49
4.1.20 Air filters construction	49
4.1.21 Air filter standard compliance	49
4.1.22 Furnace containing a refrigeration system	49
4.1.23 Disposal of condensate for a furnace containing a refrigeration coil	49
4.1.24 Furnace for manufactured (mobile) home installation	50
4.1.25 Category II, III, or IV furnace venting	50
4.1.26 Furnace conversion burner design	50

4.1.27	Enclosed furnace	50
4.1.28	Furnace rating plate and markings for installation outdoors	50
4.1.29	Separation of the combustion system from the living space of manufactured (mobile) home furnace	50
4.1.30	Fuel conversion requirement	51
4.1.31	Category II, III, or IV furnace special construction provisions	51
4.1.32	Horizontal venting of Category III or IV furnaces	51
4.1.33	Manufactured (mobile) home special construction provisions	51
4.1.34	Furnace convertible fuel construction	51
4.2	Materials	51
4.3	Polymeric materials in air handling compartments	55
4.4	Casings, external parts, and openings	56
4.5	Accessibility	57
4.6	Gas supply lines within a furnace	58
4.7	Orifice spuds and orifice fittings	61
4.8	Combustion air supply and control	62
4.9	Main burners and flame spreaders	63
4.10	Automatic gas ignition systems and pilot filter	65
4.11	Gas flow controls	68
4.11.1	General	68
4.11.2	Appliance main gas valve	68
4.11.3	Automatic valves	68
4.11.4	Reverse-acting gas-actuated controls	69
4.11.5	Adjustment of minimum input ratings	69
4.11.6	Gas appliance pressure regulators	69
4.11.7	Bleeds and vents	70
4.11.8	Detached gas flow controls	70
4.12	Limit and fan controls	70
4.13	Condensate disposal	72
4.14	Draft hoods, flue connections, and integral venting systems	72
4.14.1	Draft hoods	72
4.14.2	Blocked vent shutoff system	72
4.14.3	Blocked vent shutoff sensor	72
4.14.4	Detachable draft hoods	73
4.14.5	Draft hood materials	73
4.14.6	Draft hood joints	73
4.14.7	Draft hood outlet sizing	73
4.14.8	Draft hood supports	73
4.14.9	Flue connections	73
4.14.10	Draft hood construction	73
4.14.11	Manually operated dampers	73
4.14.12	Flue pipe extensions	73
4.14.13	Flue pipe extension construction	73
4.14.14	Venting system components	74
4.14.15	Extensions through blower compartments	74
4.14.16	Category II and IV vent system construction	75
4.14.17	Category I and III venting systems	75
4.14.18	Category II and IV venting systems	75
4.14.19	Negative pressure zones	75

4.14.20	Flue collar outlets	75
4.14.21	Flue gas pressure switches	75
4.14.22	Flue gas pressure switch location	75
4.14.23	Flue gas pressure switch construction	75
4.14.24	Vent terminals	75
4.15	Automatic vent damper devices	76
4.16	Motors and blowers	77
4.17	Electrical equipment and wiring	79
4.17.1	General	79
4.17.2	Approved electrical equipment and wiring	79
4.17.3	Examination of electrical components	79
4.17.4	Electrical component suitability for application	79
4.17.5	Electrical component location and protection	79
4.17.6	Electrical continuity	80
4.17.7	Electrical conductor protection	80
4.17.8	Channels and openings construction	80
4.17.9	Terminal identification	80
4.17.10	Current-carrying capacity of conductors	80
4.17.11	Line voltage grounding conductors and terminals	81
4.17.12	Grounding of metal parts	81
4.17.13	Equipment grounding connector identification, location and construction	81
4.17.14	Wire colors	81
4.17.15	Service junction box marking	81
4.17.16	Service junction box construction	82
4.17.17	Enclosure sizing	85
4.17.18	Enclosure construction	85
4.17.19	Location of splices	85
4.17.20	Protection of uninsulated electrical parts	85
4.17.21	Conductors	85
4.17.22	Plug connectors	85
4.17.23	Connections to controls	86
4.17.24	Wiring in compartments	86
4.17.25	Switch ratings	87
4.17.26	Single pole switches	87
4.17.27	Switch mounting	87
4.17.28	Blocked vent stack system terminals	87
4.17.29	Separation of conductors	87
4.17.30	Line-voltage wiring protection	87
4.17.31	Power-limited circuit protection	87
4.17.32	Factory low-voltage wiring	87
4.17.33	External low-voltage terminals	88
4.17.34	Internal low-voltage terminals	88
4.17.35	Identification of low-voltage connections	88
4.17.36	Low-voltage circuit protection	88
4.17.37	Low-voltage circuit transformers	88
4.17.38	Electric ignition system location	88
4.17.39	Electrical insulators	88
4.17.40	Transformer terminal location	89
4.17.41	Transformer terminal protection	89

4.17.42	High-tension lead and cable protection	89
4.17.43	High-tension lead and cable construction	89
4.17.44	Electrodes and bus bars	89
4.17.45	Flexible electrodes	89
4.17.46	Electrical clearances	89
4.17.47	Protection from condensate	92
4.18	Protection of service personnel	92
4.19	Furnaces for installation downstream from refrigeration systems	94
4.20	Cooling sections of furnaces with cooling units	95
4.21	Enclosed furnaces	95
4.21.1	Enclosure	95
4.21.2	Exterior grilles	95
4.22	Instructions	95
4.23	Installation manuals	96
4.24	Maintenance and service manuals	110
4.25	User's information manual	111
4.26	Furnace markings	114
4.26.1	General	114
4.26.2	Marking format	114
4.26.3	Marking classification	114
4.26.4	Rating plate(s)	115
4.26.5	Lighting and operating instruction label(s)	117
4.26.6	Markings for convertible furnaces	118
4.26.7	Markings for furnace installation	118
4.26.8	Markings for flue/vent components	119
4.26.9	Markings for vent damper	119
4.26.10	Clearance markings	120
4.26.11	Operation markings	120
4.26.12	Markings for individual components	122
4.26.13	Additional markings	123
4.26.14	Markings for manufactured (non-enameled) furnaces	123
4.26.15	Electrical diagrams	124

5 Performance 125

5.1	General	125
5.2	Basic test arrangements	126
5.3	Test ducts and plenums	130
5.4	Test gases	135
5.5	Test pressures and burner adjustments	136
5.6	Static pressure and air flow adjustments	138
5.7	Category determination	140
5.7.1	General	140
5.7.2	Method of test	140
5.8	Combustion	143
5.8.1	Pressure and input variations	143
5.8.2	Input at 4.0 in wc inlet pressure	144
5.8.3	Combustion characteristics	145
5.8.4	Flue gas leakage from compartment doors	145
5.9	Burner operating characteristics	145

- 5.9.1 General 145
- 5.9.2 Flashback 146
- 5.9.3 Proper ignition 146
- 5.9.4 Flame flashout 146
- 5.9.5 Backpressure 146
- 5.9.6 Undue noise 146
- 5.9.7 Delayed ignition 147
- 5.9.8 Voltage variation 147
- 5.9.9 Flame stability 147
- 5.10 Pilot burners and safety shutoff devices 147
 - 5.10.1 Test conditions 147
 - 5.10.2 Main burner ignition from pilot(s) 147
 - 5.10.3 Pilot carbon evaluation 148
 - 5.10.4 Ignition under reduced pilot flame size 148
 - 5.10.5 Pilot flame establishing period 149
 - 5.10.6 Main burner flame establishing period 153
 - 5.10.7 Manual operation flame establishing period 153
 - 5.10.8 Flame failure response time 153
 - 5.10.9 Flame carryover 153
 - 5.10.10 Draft protection of pilot flames 153
 - 5.10.11 Location of bleed burners 154
 - 5.10.12 Ignition system component temperature evaluation 154
 - 5.10.13 Pilots equipped with automatic igniters 154
 - 5.10.14 Ignition under reduced voltage and pilot flame size 155
- 5.11 Direct ignition systems 156
 - 5.11.1 Limitations on input for direct ignition systems 156
 - 5.11.2 Prepurge timings and automatic restart of direct ignition systems 156
 - 5.11.3 Ignition activation period 156
 - 5.11.4 Ignition of main burner(s) at normal voltage for direct ignition systems 156
 - 5.11.5 Direct ignition voltage variation ignition testing 156
 - 5.11.6 Main burner flame interruption time off 157
 - 5.11.7 Delayed ignition evaluation 157
 - 5.11.8 Direct ignition component temperatures 158
- 5.12 Proved igniter system 158
 - 5.12.1 Applicability 158
 - 5.12.2 Proved igniter evaluation 158
 - 5.12.3 Component evaluation of proved igniter systems 158
 - 5.12.4 Proved igniter operation under voltage variations 158
 - 5.12.5 Ignition under minimum operation conditions and maximum input restriction 159
 - 5.12.6 Shutdown under loss of supervised flame 159
 - 5.12.7 Delayed ignition testing of proved ignition system 159
 - 5.12.8 Maximum time off due to loss of proved igniter 160
 - 5.12.9 Maximum component temperature evaluation of proved igniter systems 160
 - 5.12.10 Pre-purge procedure for proved ignition systems 160
- 5.13 Flame roll-out safety shutoff means 160
 - 5.13.1 General 160
 - 5.13.2 Method of test 161
- 5.14 Manifold and control assembly capacity 162
 - 5.14.1 General 162

5.14.2	Method of test	162
5.15	Corrosion resistance	162
5.16	Flue gas temperature	162
5.16.1	General	162
5.16.2	Method of test	162
5.17	Allowable heating element temperatures	163
5.17.1	General	163
5.17.2	Method of test	164
5.18	Flue gas baffle temperatures	164
5.18.1	General	164
5.18.2	Method of test	164
5.19	Main burner and flame spreader temperatures	165
5.19.1	Burner structural evaluation	165
5.19.2	Flame spreader temperature evaluation	165
5.20	Blocked vent shutoff system	166
5.20.1	General	166
5.20.2	Method of test	166
5.21	Burner blocked inlet	167
5.21.1	General	167
5.21.2	Method of test	167
5.22	Draft hoods	167
5.22.1	General procedure for draft hood evaluation	167
5.22.2	Blocked vent combustion evaluation	168
5.22.3	Downdraft emission testing	168
5.22.4	Downdraft evaluation of pilot and main burner(s)	169
5.22.5	Updraft evaluation	169
5.22.6	Spillage evaluation	169
5.22.7	Drafthood structural evaluation	170
5.23	Automatic vent damper devices	170
5.23.1	General	170
5.23.2	Strength	170
5.23.3	Operation under variable voltage or variable motive power	171
5.23.4	Damper force of a thermally actuated vent damper device	171
5.23.5	Exposure to temperature extremes	172
5.23.6	Continued operation	172
5.24	Draft tests for furnaces not equipped with draft hoods	173
5.24.1	Proper operation under chimney drafts or stoppage	173
5.24.2	Blocked flue combustion evaluation	173
5.24.3	Updraft evaluation	174
5.25	Filters	174
5.26	Allowable air temperatures	175
5.26.1	Shutdown under restricted air flow	175
5.26.2	Normal operation of temperature limit	176
5.26.3	Reverse air flow evaluation	176
5.27	Wall, floor, and ceiling temperatures	177
5.27.1	General	177
5.27.2	Test enclosures	178
5.27.3	Test conditions	179
5.27.4	Furnaces for closet installation (optional)	180

5.27.5	Furnaces with optional integral venting system	180
5.27.6	Maximum metallic vent gas temperature	181
5.27.7	Maximum non-metallic vent material temperatures	181
5.27.8	Polymeric components	183
5.27.9	Furnaces equipped with a draft hood	184
5.28	Temperatures of furnaces for line contact installation	184
5.28.1	General	184
5.28.2	Method of test	184
5.29	Operational tests of electrical components and parts	185
5.29.1	Canadian regulations	185
5.29.2	Motor temperature evaluation	185
5.29.3	Electrical component temperature evaluation	188
5.29.4	Electrical leakage current evaluation	189
5.29.5	Proof voltage evaluation	189
5.30	Safety circuit analysis	191
5.30.1	General	191
5.30.2	Method of test	191
5.31	Furnaces for installation downstream from refrigeration systems	191
5.31.1	General	191
5.31.2	Method of test	191
5.32	Enclosed furnaces	191
5.32.1	Setup for enclosed furnace testing	191
5.32.2	Combustible material evaluation	191
5.32.3	Temperature evaluation of electrical components	192
5.32.4	Surface temperatures of enclosed furnaces	192
5.32.5	Enclosed furnaces 15 mph wind test	192
5.32.6	Enclosed furnaces 40 mph wind test	192
5.32.7	Load deformation testing of enclosed furnaces	193
5.33	Condensate disposal system(s)	193
5.33.1	Self-prime condensate trap(s)	193
5.33.2	Condition of a blocked condensate drain line(s)	194
5.34	Condensate drain system located in blower compartment	194
5.34.1	General	194
5.34.2	Method of test	195
5.35	Venting systems for Category II, III, or IV furnaces	195
5.35.1	General	195
5.35.2	Method of test	195
5.36	Furnaces vented horizontally through an outside wall	196
5.36.1	Wind test	196
5.36.2	Wind source calibration procedure for winds directed perpendicular to the wall	196
5.36.3	Wind test for manually ignited pilot(s)	197
5.36.4	Wind test for automatic ignition device(s)	198
5.36.5	Test for perpendicular and parallel wind	200
5.36.6	Furnace operating characteristics under wind test conditions	201
5.36.7	Furnace subjected to a simulated rainstorm	202
5.36.8	Vent terminal vertical load test	205
5.36.9	Vent terminal pendulum load test	205
5.37	Heating element cycling test	206
5.37.1	General	206

5.37.2	Method of test	207
5.38	Marking material adhesion and legibility	208
5.38.1	General	208
5.38.2	Method of test	208
5.39	Surface temperatures	209
5.39.1	General	209
5.39.2	Method of test	209
5.40	Thermal efficiency	210
5.40.1	General	210
5.40.2	Method of test	210
6	Direct vent central furnaces construction	211
6.1	Scope	211
6.2	General construction and assembly	212
6.3	Materials	213
6.4	Casings, external parts, and openings	213
6.5	Accessibility	213
6.6	Combustion air supply and control	214
6.7	Main burners and flame spreaders	214
6.8	Vent-air intake pipes	214
6.9	Instructions	216
6.10	User's information manual	217
6.11	Markings	218
6.11.1	Rating plate(s)	218
6.11.2	Installation marking	218
6.11.3	Operation markings	219
6.11.4	Service markings	219
7	Direct vent central furnaces performance	219
7.1	General	219
7.2	Basic test arrangements	219
7.3	Allowable heating element temperatures — Method of test	220
7.4	Direct vent systems	220
7.4.1	Maximum and minimum vent lengths	220
7.4.2	Wind test for manually ignited pilot(s)	220
7.4.3	Wind test for furnaces with automatic ignition device(s)	221
7.4.4	Wind test	222
7.4.5	Furnace operating characteristics under wind test conditions	222
7.4.6	Air intake or vent outlet blockage test	225
7.4.7	Flue outlet blocked condition test	226
7.4.8	Horizontal vent-air intake terminal load test	226
7.4.9	Venting system leakage test	227
7.4.10	Vent-air intake terminal simulated rainstorm test	229
7.4.11	Vent-air intake terminal pendulum load test	229
7.5	Wall, floor, and ceiling temperatures — Test enclosures	230
7.6	Temperatures of furnaces for line contact installation — method of test	230
7.7	Automatic gas ignition systems	230
7.7.1	General	230
7.7.2	Method of test	230

8	Recreational vehicle central furnaces construction	231
8.1	Scope	231
8.2	General construction and assembly	231
8.3	Accessibility	232
8.4	Gas supply lines	232
8.5	Appliance main gas valve	232
8.6	Vent-air intake pipes	232
8.7	Primary temperature limit control	232
8.8	Electrical equipment and wiring	233
8.9	Instructions	233
8.10	User's information manual	234
8.11	Markings	235
8.11.1	Rating plate(s)	235
8.11.2	Lighting/operating instruction label(s)	235
8.11.3	Convertible fuel marking	235
8.11.4	Installation marking	235
9	Recreational vehicle central furnaces performance	236
9.1	General	236
9.2	Basic test arrangements	236
9.3	Burner operating characteristics	236
9.4	Pilot burners and safety shutoff devices	237
9.5	Direct ignition systems	237
9.6	Wall, floor, and ceiling temperatures	237
9.7	Efficiency	238
9.7.1	General	238
9.7.2	Method of test	238
10	Central furnaces for outdoor installation construction	238
10.1	Scope	238
10.2	General construction and assembly	238
10.3	Casings, external parts, and openings	239
10.4	Accessibility	241
10.5	Combustion air supply and control	241
10.6	Main burners and flame spreaders	242
10.7	Integral venting systems	242
10.8	Instructions	242
10.9	Markings	242
10.9.1	Rating plate(s)	242
10.9.2	Installation marking	242
10.9.3	Clearance marking	242
11	Central furnaces for outdoor installation performance	243
11.1	General	243
11.2	Basic test arrangements	243
11.3	Test ducts and plenums	243
11.4	Wall, floor, and ceiling temperatures	244
11.4.1	Furnace enclosure test setup	244
11.4.2	Furnace enclosure test setup for down-flow or horizontal furnaces	245

- 11.5 Operational tests of electrical components and parts 245
- 11.6 Wind and rain operation 245
 - 11.6.1 Simulated rainstorm test for an outdoor installation furnace with an integral venting system 245
 - 11.6.2 Wind source configuration calibration procedure 245
 - 11.6.3 Simulated rainstorm test for a furnace with the pilot(s) and main burner(s) in operation 246
 - 11.6.4 Wind test for manually ignited pilot(s) 247
 - 11.6.5 Wind test for manually lighted pilot(s) of an automatic ignition system 248
 - 11.6.6 Furnace wind test 248
- 11.7 Marking material adhesion and legibility 249
 - 11.7.1 General 249
 - 11.7.2 Method of test 249

12 Manufacturing and production tests 250

13 Items unique to Canada 251

- 13.1 Annual fuel utilization efficiency 251
- 13.2 Instructions 251
- 13.3 French translations for quoted instructions and markings 252
- 13.4 Marking material tests 275

-
- Annex A (normative) — Outline of lighting instructions for appliances equipped with continuous pilots 276
 - Annex B (normative) — Outline of operating instructions for appliances equipped with intermittent pilot or interrupted pilot systems 279
 - Annex C (normative) — Outline of operating instructions for appliances equipped with direct ignition systems 282
 - Annex D (normative) — Outline of operating instructions for appliances equipped with continuous pilots for recreational vehicle installation only 285
 - Annex E (normative) — Outline of operating instructions for appliances equipped with intermittent or interrupted pilot systems for recreational vehicle installation only 288
 - Annex F (normative) — Outline of operating instructions for appliances equipped with direct ignition systems for recreational vehicle installation only 291
 - Annex G (normative) — Corrosion resistance criteria and test method 294
 - Annex H (normative) — Provisions for listed gas appliance conversion kits (optional) 305
 - Annex I (normative) — Flue loss calculations 308
 - Annex J (normative) — Jacket loss calculations 313
 - Annex K (normative) — Provisions for listed high altitude conversion kits (optional) 316
 - Annex L (normative) — Sample failure modes and effects analysis for component miswiring 319
 - Annex M (informative) — Recommended wire color usage 320
 - Annex N (informative) — Combustion air quality (list of contaminants) 321
 - Annex O (informative) — Pertinent references to ASME Y14.15 322
 - Annex P (informative) — Wire color designations 323
 - Annex Q (informative) — Preferred graphic symbols of commonly used items, extracted from IEEE 315 and abbreviations for these items 324
 - Annex R (informative) — Legibility and design of safety information in furnace markings and manuals 326

Preface

This is the eighth edition of CSA/ANSI Z21.47 • CSA 2.3, *Gas-fired central furnaces*. It supersedes the previous editions published in 2016, 2012, 2006, 2003, 2001, 1998, and 1993.

The major changes to this edition include the following:

- In Clause [3](#), the Definitions clause, links have been added to the definition of “flue losses”. A publication reference has been added to the definition of “heat deflection temperature”. The definition of “heating capacity” has been relocated from footnote to Clause [3](#). The definition for “air-intake pipe” has been added as recommended by the Z21/83 TC for non-metallic venting. The definition for “vent terminal (vent cap)” has been deleted. The definition for “vent terminal” has been revised.
- The clause on direct vent has been relocated from Clause [6.8.5](#) to Clause [4.2.6](#) as proposed by the Z21/83 TC for non-metallic venting.
- Clause [4.10.1](#) has incorporated an interim provision for significant updates to ANSI Z21.20.
- In Clause [4.11.2](#), existing requirement has been clarified. The current requirements continue only to allow an accessible switch that is integral to the gas control and the only change to the clause is the change from “manually” to “directly” for interrupting electric power to automatic valves. For clarification of the intent of the switch, the term “manually activated” has been proposed to describe the type of switch.
- To accommodate higher discharge air temperatures, Clause [8.7](#) has been modified for recreational vehicles. If all testing can be passed at the higher temperatures, the restrictions found in the current Clause [4.12.4](#) for residential style furnaces can safely be eliminated.
- Clause [4.14.14.2](#), method of test for venting components, has been modified to comply with the Z21/83 TC proposal for non-metallic venting.
- Clause [4.23](#) on installation manuals has been modified to clarify the conditions under which the furnace must operate when used during the last stages of construction (finishing heat) and prior to occupancy.
- Clarification has been added to Clause [4.23.4](#) to exclude the use of an external pressure test port.
- In Clause [4.23.6](#), guidance has been added on testing non-metallic vent pipe without or with thermal insulation, minimum distance from adjacent public walkways, adjacent buildings, openable windows, building openings, protecting building materials from degradation by flue gas, instructions for maximum and minimum vent equivalent length, and instruction to cover building wall penetrations.
- In Clause [5.4](#) on test gases, an option has been added to conduct burner operating characteristic tests with Test Gas G or H.
- In Clause [5.27.7.2](#), an option has been added to allow the elbow to be installed inside the enclosure and to allow the use of materials not listed in Table [15](#) that are tested to ASTM D648. Materials have been removed from Table [15](#) that are not commonly used.
- In Clause [5.29.4.2](#), on the method of test for electrical leakage current evaluation, UL 1995 has been replaced with UL 60335-2-40.
- In Clause [5.35.2](#), on the method of test on venting systems for Category II, III, or IV furnaces, the calculation for allowable leakage rate has been corrected.
- In Clause [6.11.1](#), on rating plates, an option has been added to list “direct or non-direct vent forced air furnace” as a configuration.
- Clause [7.4.11](#), on vent-air intake terminal pendulum load test, has been added based on the Z21/83 TC proposal for non-metallic venting with modifications for furnaces.
- In Clause [8.11.4](#), on installation marking, the specification for insulation ductwork needed to comply with Clause [9.6](#) has been added.
- In Clause [13](#), on items unique to Canada, reference to 3 phase furnaces has been corrected.

This Standard is considered suitable for use for conformity assessment within the stated scope of the Standard.

This Standard was prepared by the Z21/CSA Joint Technical Subcommittee on Standards for Gas-Fired Central Furnaces, under the jurisdiction of the Z21/83 Technical Committee on Performance and Installation of Gas Burning Appliances and Related Accessories, the Canadian Technical Committee on Gas Appliances and Related Accessories, and the Fuels and Appliances Strategic Steering Committee, and had been formally approved by the Technical Committees and the Interprovincial Gas Advisory Council.

This Standard has been developed in compliance with Standards Council of Canada requirements for National Standards of Canada. It has been published as a National Standard of Canada by CSA Group.

This Standard has been approved by the American National Standards Institute (ANSI) as an American National Standard.

Interpretations: The Fuels and Appliances Strategic Steering Committee has provided the following direction for the interpretation of standards under its jurisdiction: “The literal text shall be used in judging compliance of products with the safety requirements of this Standard. When the literal text cannot be applied to the product, such as for new materials or construction, and when a relevant committee interpretation has not already been published, CSA Group’s procedures for interpretation shall be followed to determine the intended safety principle.”

Notes:

- 1) *Use of the singular does not exclude the plural (and vice versa) when the sense allows.*
- 2) *Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.*
- 3) *This Standard was developed by consensus, which is defined by CSA Policy governing standardization — Code of good practice for standardization as “substantial agreement. Consensus implies much more than a simple majority, but not necessarily unanimity”. It is consistent with this definition that a member may be included in the Technical Committee list and yet not be in full agreement with all clauses of this Standard.*
- 4) *To submit a request for interpretation of this Standard, please send the following information to inquiries@csagroup.org and include “Request for interpretation” in the subject line:*
 - a) *define the problem, making reference to the specific clause, and, where appropriate, include an illustrative sketch;*
 - b) *provide an explanation of circumstances surrounding the actual field condition; and*
 - c) *where possible, phrase the request in such a way that a specific “yes” or “no” answer will address the issue.*

Committee interpretations are processed in accordance with the CSA Directives and guidelines governing standardization and are available on the Current Standards Activities page at standardsactivities.csa.ca.

- 5) *This Standard is subject to review within five years from the date of publication. Suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include “Proposal for change” in the subject line:*
 - a) *Standard designation (number);*
 - b) *relevant clause, table, and/or figure number;*
 - c) *wording of the proposed change; and*
 - d) *rationale for the change.*

CSA/ANSI Z21.47:21 • CSA 2.3:21

Gas-fired central furnaces

0 History of the development of Gas-fired central furnaces

Note: *This history is informative and is not part of the Standard.*

With the onset of the Free Trade Agreement between the United States and Canada on January 2, 1988, significant attention was given to the harmonization of the United States and Canadian safety standards addressing gas-fired equipment for residential, commercial, and industrial applications. It was believed that the elimination of the differences between the standards would remove potential trade barriers and provide an atmosphere in which North American manufacturers could market more freely in the United States and Canada. The harmonization of these standards was also seen as a preliminary step toward harmonization with international standards, which was to become a necessity as Europe moved toward its goal to form an economic United States of Europe (EC) by the early 1990s.

A Z21/CGA joint working group on harmonizing central furnace standards was established. On May 4, 1989, the joint working group reviewed an initial comparison of the construction sections of the Standard for *Gas-Fired Central Furnaces (Except Direct Vent Central Furnaces)*, ANSI Z21.47-1987, and the National Standard of Canada, CAN/CGA-2.3-M86. It was agreed that a consultant should be used to draft a complete unitary standard to address gas-fired central furnaces, including direct vent central furnaces. As a result, several drafts, based on the current Standards for *Gas-Fired Central Furnaces (Except Direct Vent Central Furnaces)* (ANSI Z21.47-1990 and Z21.47a-1990, ANSI Z21.64-1990, and CAN/CGA 2.3-M86) were subsequently developed by the consultant and reviewed by the joint working group between 1989 and 1991.

A joint Z21/CGA Joint Subcommittee on Standards for Gas-Fired Central Furnaces was then established, based on memberships of the Z21 Subcommittee on Standards for Gas-Fired Central Furnaces and the CGA 2.3-2.9 Committee on Standards for Central Furnaces, Duct Furnaces, and Unit Heaters. Membership encompasses representatives from the U.S. and Canadian manufacturing industry, gas suppliers (natural and LP), regulatory authorities and general interest with the intent that each country is equally represented.

The first meeting of the Z21/CGA Joint Central Furnace Subcommittee was held on July 10–12, 1992. At that meeting a third draft of a harmonized central furnace standard was considered and modified. A fourth draft was subsequently adopted for industry review during November 1991.

With the formation of joint subcommittees, a Canadian Gas Association Standards Steering Committee on Gas Burning Appliances and Related Accessories was established to parallel Accredited Standards Committees Z21 and Z83. Also, to support the formation of joint subcommittees, operating procedures for joint subcommittees in accordance with American National Standards Institute procedures were developed and subsequently approved by ANSI on April 1, 1993.

Following reconsideration and modification of the proposed draft standard for gas-fired central furnaces in light of comments received, the joint central furnace subcommittee, at its February 11–13, 1992 meeting, recommended the proposed fourth draft to the Z21 Committee and the CGA Standards Steering Committee for approval.

The Z21 Committee, at its April 9, 1992 meeting, approved the proposed fourth draft of the harmonized standard for central furnaces, as modified by the joint subcommittee. The CGA Standards Steering

Committee concurred with the actions of the Z21 Committee but further modified the standard to better address bilingual instructions and markings and other issues unique to one country. The additional modifications by the CGA Committee were subsequently adopted by the Z21 Committee by letter ballot dated June 16, 1992.

The first edition of the harmonized Standard for *Gas-Fired Central Furnaces*, ANSI Z21.47/CGA 2.3, incorporated coverage from the Standard for *Direct Vent Central Furnaces*, ANSI Z21.64, coverage for recreational vehicle central furnaces, and central furnaces for outdoor installation. The first edition of the harmonized standard was approved by the Standards Advisory Committee and the Standards Council of Canada on March 31, 1993, and by the American National Standards Institute, Inc., on May 26, 1993.

At their respective meetings on April 10 and April 11, 1996, and by letter ballot dated May 16, 1996, members of the Z21 Accredited Standards Committee and the Z83 Accredited Standards Committee unanimously approved the merger of the two committees. By letter ballot dated October 8, 1996, the members of the Z21 Committee and the Z83 Committee unanimously approved the title and procedures of the new committee as Accredited Standards Committee Z21/83 on Performance and Installation of Gas-Burning Appliances and Related Accessories.

The Z21/83 Committee, at its April 17, 1997 meeting, approved proposed revisions to the harmonized central furnace standard. The Canadian Standards Steering Committee concurred with the actions of the Z21/83 Committee and approved the proposed revisions to the harmonized central furnace standard. The second edition of the harmonized central furnace standard was approved by the Interprovincial Gas Advisory Council on December 21, 1998, and the American National Standards Institute, Inc. on June 9, 1998.

The third edition of the harmonized central furnace standard was approved by the Interprovincial Gas Advisory Council on September 4, 2001, and the American National Standards Institute, Inc. on September 27, 2000.

The fourth edition of the harmonized central furnace standard was approved by the Interprovincial Gas Advisory Council on August 28, 2003, and the American National Standards Institute, Inc. on September 17, 2003.

The fifth edition of the harmonized central furnace standard was approved by the Interprovincial Gas Advisory Council on December 1, 2006, and the American National Standards Institute, Inc. on July 27, 2006.

The sixth edition of the harmonized central furnace standard was approved by the Interprovincial Gas Advisory Council on March 22, 2012, and the American National Standards Institute, Inc. on March 27, 2012.

The seventh edition of the central furnace standard was distributed for industry review during October 2012, June 2014, December 2014, and May 2015; approved by the Z21/83 Technical Committee on Performance and Installation of Gas Burning Appliances and Related Accessories on March 6, 2016, March 25, 2016, and July 11, 2016; the CSA Technical Committee on Gas Appliances and Related Accessories on March 6, 2016, March 25, 2016, and July 11, 2016; by the American National Standards Institute, Inc. on October 28, 2016; and by the Interprovincial Gas Advisory Council on August 22, 2016.

The eighth edition of the Gas-fired central furnaces Standard, was distributed for industry review on September 24, 2019; approved by the Z21/83 Technical Committee on Performance and Installation of

Gas Burning Appliances and Related Accessories on February 17, 2021; and the CSA Technical Committee on Gas Appliances and Related Accessories on November 24, 2020.

Previous editions of the central furnace standard, and addenda thereto, approved by the American National Standards Institute or its predecessor organizations are as follows:

Z21.13–1934		
Z21.13–1936		
Z21.13–1938		
Z21.13–1940	Z21.13a-1940	
Z21.13–1943		
Z21.13–1945	Z21.13a-1950	Z21.13b-1950
Z21.13.2–1951	Z21.13.2a-1952	Z21.13.2b-1954
Z21.13.2–1955		
Z21.13.2–1956	Z21.13.2a–1957	
Z21.13.2–1958	Z21.13.2a-1959	Z21.13.2b-1960
Z21.13.2–1960		
Z21.13.2–1961	Z21.13.2a-1962	Z21.13.2b-1963
Z21.47–1964	Z21.47a-1965	Z21.47b-1967
Z21.47–1968	Z21.47a-1969	
Z21.47–1971	Z21.47a-1972	
Z21.47–1973	Z21.47a-1974	Z21.47b-1975
Z21.47–1978	Z21.47a-1980	Z21.47b-1982
Z21.47–1983	Z21.47a-1985	Z21.47b-1986
Z21.47–1987	Z21.47a-1988	Z21.47b-1989

Previous editions of the harmonized central furnace standard, and addenda thereto, approved by the Interprovincial Gas Advisory Council and the American National Standards Institute are as follows:

ANSI Z21.47-1993 • CAN/CGA 2.3-M93	ANSI Z21.47a-1995 • CGA 2.3a-M95	ANSI Z21.47b-1997 • CGA 2.3b-M97
ANSI Z21.47-1998 • CSA 2.3-M98	ANSI Z21.47a-1999 • CSA 2.3a-M99	ANSI Z21.47b-2000 • CSA 2.3b-M00
ANSI Z21.47-2001 • CSA 2.3-2001	ANSI Z21.47a-2001 • CSA 2.3a-2001	ANSI Z21.47b-2002 • CSA 2.3b-2002
ANSI Z21.47-2003 • CSA 2.3-2003	ANSI Z21.47a-2004 • CSA 2.3a-2004	ANSI Z21.47b-2006 • CSA 2.3b-2006
ANSI Z21.47-2006 • CSA 2.3-2006	ANSI Z21.47a-2007 • CSA 2.3a-2007	ANSI Z21.47b-2008 • CSA 2.3b-2008
ANSI Z21.47-2012 • CSA 2.3-2012		
ANSI Z21.47-2016 • CSA 2.3-2016		

1 Scope

1.1

This Standard applies to automatically operating gas-fired central furnaces (see Clause [3](#)), hereinafter referred to as furnaces, for installation in residential, commercial, and industrial structures including furnaces for direct vent, recreational vehicle, outdoor, and manufactured (mobile) homes. These furnaces can include a cooling unit. All units are to be constructed entirely of new, unused parts and materials.

1.2

In Canada, this Standard applies to gas-fired central furnaces having inputs up to and including 400 000 Btu/h (117 228 W).

1.3

This Standard applies to Category I, Category II, Category III, and Category IV central furnaces. See Clause [3](#).

1.4

This Standard applies to furnaces of the types defined in Clause [3](#), which are designed to supply heated air through ducts to spaces remote from or adjacent to the furnace location. Location and use of such furnaces with respect to the spaces being heated necessitates automatic operation of the appliance.

1.5

This Standard covers the thermal efficiency (see Clause [5.40](#)) and related markings of only those furnaces whose efficiencies are not regulated in the U.S.A. by the Energy Policy Act and Conservation Act of 1975 and the National Energy Conservation Policy of 1978* or not covered in Canada by Clause [13](#) when connected to a single phase electrical supply.

Note: * At the time of printing, Federal energy acts in the U.S.A. regulate the efficiency (heating capacity) of furnaces having input ratings less than 225 000 Btu/h (65 941 W).

1.6

A furnace of a type not specifically defined in this Standard may be subjected to such examination and tests as deemed necessary by the testing agency to determine compliance with the intent of this Standard.

1.7

This Standard also applies to a furnace that is factory equipped with both a draft hood and an automatic vent damper device (see Clause [3](#)), hereinafter referred to as vent damper device.

1.8

If a value for measurement as given in this Standard is followed by an equivalent value in other units, the first stated value is regarded as the specification, except as noted in Clauses [4.22.1](#) and [4.26.2](#).

1.9

All references to “psi” throughout this Standard are considered gauge pressures, unless otherwise specified.

1.10

Special construction provisions applicable to a furnace designed for use with an optional listed conversion kit are outlined under Annex [H](#).

1.11

Clause [2](#) contains a list of standards specifically referenced in this Standard.

Clause [2](#) includes both U.S. and Canadian reference standards where applicable. It is the responsibility of the user of this Standard to determine which referenced standard applies based on the requirements of the authority having jurisdiction at the location of the installation. However, a furnace for use in a particular country only should comply with the applicable referenced standard for that country.

1.12

Clause [4.17](#) is unique to United States. The Canadian electrical equipment and wiring provisions are contained in CSA C22.2 No. 3 or CAN/CSA-C22.2 No. 60335-2-102.

1.13

Special construction provisions applicable to furnaces designed to operate at altitudes over 2000 ft (610 m) are outlined in Annex [K](#).

1.14

In this Standard, “shall” is used to express a requirement, i.e. a provision that the user is obliged to satisfy in order to comply with the Standard; “should” is used to express a recommendation or that which is advised but not required; and “may” is used to express an option or that which is permissible within the limits of the Standard.

Notes accompanying clauses do not include requirements or alternative requirements; the purpose of a note accompanying a clause is to separate from the text explanatory or informative material.

Notes to tables and figures are considered part of the table or figure and may be written as requirements.

Annexes are designated normative (mandatory) or informative (non-mandatory) to define their application.

2 Reference publications

This Standard refers to the following publications, and where such reference is made, it shall be to the edition listed below, including all amendments published thereto.

CSA Group

ANSI Z21.15-2009 (R2019) • CSA 9.1-2009 (R2019)

Manually operated gas valves for appliances, appliance connector valves and hose end valves

ANSI Z21.17-1998 (R2019) • CSA 2.7-M98 (R2019)

Domestic gas conversion burners

CSA/ANSI Z21.18:19 • CSA 6.3:19

Gas appliance pressure regulators