



CSA B1800:24
National Standard of Canada



Thermoplastic nonpressure piping compendium



Legal Notice for Standards

Canadian Standards Association (operating as “CSA Group”) develops standards through a consensus standards development process approved by the Standards Council of Canada. This process brings together volunteers representing varied viewpoints and interests to achieve consensus and develop a standard. Although CSA Group administers the process and establishes rules to promote fairness in achieving consensus, it does not independently test, evaluate, or verify the content of standards.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document’s fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party’s intellectual property rights. CSA Group does not warrant the accuracy, completeness, or currency of any of the information published in this document. CSA Group makes no representations or warranties regarding this document’s compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL CSA GROUP, ITS VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF CSA GROUP HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, CSA Group is not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and CSA Group accepts no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

CSA Group is a private not-for-profit company that publishes voluntary standards and related documents. CSA Group has no power, nor does it undertake, to enforce compliance with the contents of the standards or other documents it publishes.

Intellectual property rights and ownership

As between CSA Group and the users of this document (whether it be in printed or electronic form), CSA Group is the owner, or the authorized licensee, of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. Without limitation, the unauthorized use, modification, copying, or disclosure of this document may violate laws that protect CSA Group’s and/or others’ intellectual property and may give rise to a right in CSA Group and/or others to seek legal redress for such use, modification, copying, or disclosure. To the extent permitted by treaty or by law, CSA Group reserves all intellectual property rights in this document.

Patent rights

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights. CSA Group shall not be held responsible for identifying any or all such patent rights. Users of this standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.

Authorized use of this document

This document is being provided by CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way, or remove this Legal Notice from the attached standard;
- sell this document without authorization from CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.



Standards Update Service

CSA B1800:24
March 2024

Title: *Thermoplastic nonpressure piping compendium*

To register for e-mail notification about any updates to this publication

- go to www.csagroup.org/store/
- click on **CSA Update Service**

The **List ID** that you will need to register for updates to this publication is **270115**

If you require assistance, please e-mail techsupport@csagroup.org or call 416-747-2233.

Visit CSA Group's policy on privacy at www.csagroup.org/legal to find out how we protect your personal information.

Canadian Standards Association (operating as “CSA Group”), under whose auspices this National Standard has been produced, was chartered in 1919 and accredited by the Standards Council of Canada to the National Standards system in 1973. It is a not-for-profit, nonstatutory, voluntary membership association engaged in standards development and certification activities.

CSA Group standards reflect a national consensus of producers and users — including manufacturers, consumers, retailers, unions and professional organizations, and governmental agencies. The standards are used widely by industry and commerce and often adopted by municipal, provincial, and federal governments in their regulations, particularly in the fields of health, safety, building and construction, and the environment.

More than 10 000 members indicate their support for CSA Group’s standards development by volunteering their time and skills to Committee work.

CSA Group offers certification and testing services in support of and as an extension to its standards development activities. To ensure the integrity of its certification process, CSA Group regularly and continually audits and inspects products that bear the CSA Group Mark.

In addition to its head office and laboratory complex in Toronto, CSA Group has regional branch offices in major centres across Canada and inspection and testing agencies in fourteen countries. Since 1919, CSA Group has developed the necessary expertise to meet its corporate mission: CSA Group is an independent service organization whose mission is to provide an open and effective forum for activities facilitating the exchange of goods and services through the use of standards, certification and related services to meet national and international needs.

For further information on CSA Group services, write to
CSA Group
178 Rexdale Boulevard
Toronto, Ontario, M9W 1R3
Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada’s economic competitiveness and social wellbeing, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

Standards Council of Canada
600-55 Metcalfe Street
Ottawa, Ontario, K1P 6L5
Canada



Cette Norme Nationale du Canada n’est disponible qu’en anglais.

Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users to judge its suitability for their particular purpose.

®A trademark of the Canadian Standards Association, operating as “CSA Group”

National Standard of Canada

CSA B1800:24

***Thermoplastic nonpressure piping
compendium***



*®A trademark of the Canadian Standards Association,
operating as "CSA Group"*



*Published in March 2024 by CSA Group
A not-for-profit private sector organization
178 Rexdale Boulevard, Toronto, Ontario, Canada M9W 1R3*

*To purchase standards and related publications, visit our Online Store at
www.csagroup.org/store/ or call toll-free 1-800-463-6727 or 416-747-4044.*

*ICS 23.040.45
ISBN 978-1-4883-4929-4*

*© 2024 Canadian Standards Association
All rights reserved. No part of this publication may be reproduced in any form whatsoever
without the prior permission of the publisher.*

Contents

Technical Committee on Plastic Nonpressure Piping 30

Preface 34

CSA B181.0:24, Definitions, general requirements, and methods of testing for thermoplastic nonpressure piping

1 Scope 38

- 1.1 Scope of the B1800 compendium 38
- 1.2 Scope of this Standard 38
- 1.3 Intent of this Standard 38
- 1.4 Terminology 38

2 Reference publications 39

3 Definitions and abbreviations 44

- 3.1 Definitions 44
- 3.2 Abbreviations 47

4 Material requirements 48

- 4.1 Compounds 48
 - 4.1.1 General 48
 - 4.1.2 Virgin compounds 48
 - 4.1.3 Reworked material 48
 - 4.1.4 Recycled plastic and industrial plastic scrap 48
 - 4.1.5 Stabilizers, lubricants, and pigments 48
- 4.2 Chemical resistance 48
- 4.3 Environmental stress cracking 48
- 4.4 Ultraviolet (UV) radiation protection 49
- 4.5 Graphitic materials 49

5 Manufactured pipe and fittings 49

- 5.1 Quality of work 49
- 5.2 Cleanouts 49
 - 5.2.1 General 49
 - 5.2.2 Threads 49
 - 5.2.3 Plugs 50
 - 5.2.4 Hole openings 50
 - 5.2.5 Sealing 50
 - 5.2.6 Thread integrity 50
- 5.3 Traps 50
 - 5.3.1 Dimensions 50
 - 5.3.2 Union joints 50
 - 5.3.3 Trap slip joints 51
 - 5.3.4 Trap cleanout plugs 51
- 5.4 Expansion joints 52
 - 5.4.1 Piston expansion joints for vertical and horizontal applications 52

5.4.2	Elastomeric bellows expansion joints	52
5.5	Closet flanges	53
5.5.1	General	53
5.5.2	Maximum deflection	54
5.5.3	Misalignment test	54
5.5.4	Uniform loading test	54
5.5.5	Weld test	54
5.6	Backwater valves	54
5.6.1	Classification	54
5.6.2	Installation instructions	54
5.6.3	Sealing elements	54
5.6.4	Size	55
5.6.5	Operation	56
5.6.6	Watertightness	56
5.6.7	Water flow	56
5.7	Elastomeric end closures	56
5.8	Elastomeric gaskets	56
5.8.1	General	56
5.8.2	Jointing procedure	57
5.8.3	Joint tightness	57
5.9	DWV push-fit fittings	57
5.9.1	General	57
5.9.2	Dimensions	58
5.9.3	Elastomers	58
5.9.4	Stainless steel	58
6	Test methods	58
6.1	Conditioning and test specimens	58
6.1.1	General	58
6.1.2	Conditioning for the impact resistance test	58
6.1.3	Conditioning for fabricated fittings	58
6.1.4	Conditions for conducting tests	59
6.1.5	Selection of test specimens	59
6.1.6	Reuse of test specimens	59
6.2	Measurement of centreline radius of curvature	59
6.2.1	General	59
6.2.2	Cutting the specimen	59
6.2.3	Procedure	59
6.2.4	Location of the centre of the radius of curvature	60
6.2.5	A/B ratio	60
6.2.6	C/D ratio	60
6.2.7	Number of measurements	60
6.2.8	Average A/B ratio	60
6.2.9	Average C/D ratio	60
6.3	Fabricated fittings	61
6.3.1	Bending test	61
6.3.2	Lap shear test	61
6.3.3	Tensile and bend-back tests	61
6.4	Chemical resistance test	62

6.4.1	Chemical reagents	62
6.4.2	General requirements	62
6.4.3	General procedure	62
6.4.4	Procedure (as specified in the applicable product standard)	62
6.5	Water resistance test	62
6.6	Dimensional stability test	62
6.6.1	Specimens	62
6.6.2	Procedure	63
6.7	Mechanical joint pressure test	63
6.8	Cleanout tests	63
6.8.1	Cleanout sealing test	63
6.8.2	Cleanout thread integrity test	63
6.9	Corrosion resistance of metallic parts	63
6.10	Expansion joint tests	64
6.10.1	Cycling test	64
6.10.2	Breakaway force test	64
6.10.3	Offset test for piston expansion joints	64
6.10.4	Hydrostatic pressure test for elastomeric bellows expansion joints	64
6.11	Closet flange tests	65
6.11.1	General	65
6.11.2	Closet bolt pullout test	65
6.11.3	Misalignment test	65
6.11.4	Uniform loading test	66
6.11.5	Weld tests	66
6.12	Backwater valve tests	66
6.12.1	Watertightness test	66
6.12.2	Waterflow test (Types II and III backwater valves)	67
6.13	Elastomeric end closure test	67
6.14	Impact resistance test for DWV pipe	67
6.14.1	Apparatus	67
6.14.2	Specimens	67
6.14.3	Procedure	67
6.14.4	Failure criteria	67
6.14.5	Examination of specimens	67
6.15	Compression test for pipe	68
6.16	Impact resistance test for sewer pipe	68
6.16.1	Apparatus	68
6.16.2	General	68
6.16.3	Specimens	68
6.16.4	Procedure	68
6.16.5	Performance requirements	68
6.16.6	Failure criteria	68
6.16.7	Examination of specimens	69
6.17	Apparent tensile properties (ring tensile test)	69
6.17.1	General	69
6.17.2	Universal testing machine	69
6.17.3	Test specimen	70
6.17.4	Procedure	70
6.17.5	Calculations	70

6.18	Carbon black dispersion	71
6.18.1	Apparatus	71
6.18.2	Specimens	71
6.18.3	Procedure	71
6.18.4	Assessment of the slides	72
6.19	Tensile, compressive, and flexural creep and creep rupture strength test	72
6.19.1	General	72
6.19.2	Apparatus	72
6.19.3	Specimens	72
6.19.4	Procedure	72
6.19.5	Report	73
6.20	DWV push-fit fitting tests	73
6.20.1	Unrestrained hydrostatic test	73
6.20.2	Shear test	74
6.20.3	Deflection test	74
6.20.4	Crush resistance (deflection load) test	74
6.20.5	Impact resistance test for DWV push-fit fittings	74

7 Markings 75

7.1	Pipe	75
7.1.1	General	75
7.1.2	Marking quality and characteristics	76
7.2	Fittings	76
7.2.1	General	76
7.2.2	Marking quality and characteristics	76
7.2.3	DWV push-fit fittings	76
7.2.4	Fabricated fittings	76
7.3	Expansion joints	76
7.3.1	General	76
7.3.2	Marking quality and characteristics	77
7.4	Closet flanges	77
7.5	Backwater valves	77
7.6	Solvent cement	77

Annexes

Annex A (informative)	— Typical horizontal expansion joint installation	104
Annex B (informative)	— Examples of positive gasket restraint	105

CSA B181.1:24 Acrylonitrile-butadiene-styrene (ABS) drain, waste, and vent pipe and pipe fittings

1	Scope	107
1.1	General	107
1.2	Terminology	107
2	Reference publications	107
3	Definitions and abbreviations	107
4	General requirements	108

4.1	ABS compounds	108
4.2	Reworked material	108
4.3	Blending resins	108
4.3.1	Final compound requirements	108
4.3.2	Blending resin requirements	108
5	Manufactured pipe, fittings, accessories, and solvent cement	108
5.1	General	108
5.2	Dimensions of pipe	108
5.2.1	Diameter	108
5.2.2	Out-of-roundness	108
5.2.3	Wall thickness	108
5.3	Dimensions and configurations of fittings	109
5.3.1	Wall thickness	109
5.3.2	Sockets	109
5.3.3	Lay lengths and configurations	109
5.4	Carbon black dispersion	111
5.4.1	General	111
5.4.2	Carbon black	111
5.5	Chemical resistance of pipe, fittings, and accessories	111
5.6	Water resistance of pipe, fittings, and accessories	111
5.7	Dimensional stability of pipe, fittings, and accessories	111
5.8	Tightness of mechanical joints used downstream of traps	111
5.9	Cleanouts	111
5.10	Traps	111
5.11	Expansion joints	111
5.12	Closet flanges	112
5.13	Backwater valves	112
5.14	Elastomeric end closures	112
5.15	DWV push-fit fittings	112
5.15.1	Unrestrained hydrostatic test	112
5.15.2	Shear test	112
5.15.3	Deflection test	112
5.15.4	Crush resistance (deflection load) test	112
5.15.5	Impact resistance test	112
5.16	Solvent cements	113
5.16.1	Solvent cements for ABS joints	113
5.16.2	Solvent cements for joining ABS to PVC	113
5.17	Quality control	113
5.17.1	General	113
5.17.2	Impact resistance of ABS pipe	113
5.17.3	Crush resistance of fittings	114
6	Test methods	114
6.1	Conditioning	114
6.1.1	General	114
6.1.2	Conditioning for low-temperature impact	114
6.1.3	Test conditions	114
6.2	Dimensions	114

- 6.2.1 General 114
- 6.2.2 Diameter 114
- 6.2.3 Wall thickness 114
- 6.3 Crush resistance test for fittings 114

7 Markings 115

- 7.1 Pipe 115
- 7.2 Fittings 115
- 7.3 Expansion joints 115
- 7.4 Closet flanges 115
- 7.5 Backwater valves 115
- 7.6 Solvent cement 115

Annexes

- Annex A (informative) — Standard practice for the installation of ABS drain, waste, and vent pipe and pipe fittings 122

CSA B181.2:24, Polyvinylchloride (PVC) and chlorinated polyvinylchloride (CPVC) drain, waste, and vent pipe and pipe fittings

1 Scope 131

- 1.1 General 131
- 1.2 Terminology 131

2 Reference publications 131

3 Definitions and abbreviations 131

4 General requirements 132

- 4.1 PVC and CPVC compounds 132
 - 4.1.1 PVC compounds 132
 - 4.1.2 CPVC compounds 132
 - 4.1.3 PVC compounds for a fire stop 132
 - 4.1.4 Pigment 132
- 4.2 Reworked material 132
- 4.3 Fire test for fire-stop fittings 132
- 4.4 Coated pipe 132

5 Manufactured pipe, fittings, and accessories 132

- 5.1 General 132
- 5.2 Dimensions of pipe 133
 - 5.2.1 Coatings 133
 - 5.2.2 Diameter 133
 - 5.2.3 Out-of-roundness 133
 - 5.2.4 Wall thickness 133
 - 5.2.5 Bell ends 133
- 5.3 Dimensions and configurations of fittings 133
 - 5.3.1 Wall thickness 133
 - 5.3.2 Socket dimensions 134

- 5.3.3 Lay lengths and configurations of moulded fittings 134
- 5.4 Chemical resistance of pipe, fittings, and accessories 135
- 5.5 Water resistance of pipe, fittings, and accessories 135
- 5.6 Dimensional stability of pipe, fittings, and accessories in sizes through NPS-8 135
- 5.7 Tightness of mechanical joints used downstream of trap seals 135
- 5.8 Cleanouts 135
- 5.9 Traps 136
- 5.10 Expansion joints 136
- 5.11 Closet flanges 136
- 5.12 Backwater valves 136
- 5.13 Elastomeric end closures 136
- 5.14 Solvent cements 136
 - 5.14.1 Solvent cements for PVC joints 136
 - 5.14.2 Solvent cements for joining ABS to PVC 136
 - 5.14.3 Solvent cements for CPVC joints and for joining CPVC to PVC 137
- 5.15 Quality control 137
 - 5.15.1 General 137
 - 5.15.2 Impact resistance of PVC pipe 137
 - 5.15.3 Compression strength of pipe 137
 - 5.15.4 Extrusion quality of pipe 137
 - 5.15.5 Heat reversion in PVC moulded fittings 138
- 5.16 Fabricated fittings 138
 - 5.16.1 Resistance to bending 138
 - 5.16.2 Cemented joint strength of solvent-cemented fittings 138
 - 5.16.3 Welded joint strength of welded fittings 138
- 5.17 DWV push-fit fittings 139
 - 5.17.1 Unrestrained hydrostatic test 139
 - 5.17.2 Shear test 139
 - 5.17.3 Deflection test 139
 - 5.17.4 Crush resistance (deflection load) test 139
 - 5.17.5 Impact resistance test 139

6 Test methods 139

- 6.1 Conditioning 139
 - 6.1.1 General 139
 - 6.1.2 Impact resistance 140
 - 6.1.3 Testing conditions 140
- 6.2 Dimensions 140
 - 6.2.1 General 140
 - 6.2.2 Diameter 140
 - 6.2.3 Wall thickness 140

7 Markings 140

- 7.1 Pipe 140
- 7.2 Fittings 140
- 7.3 Expansion joints 140
- 7.4 Closet flanges 140
- 7.5 Backwater valves 140
- 7.6 Solvent cement 140

7.7 Coated pipe and fittings 141

Annexes

Annex A (informative) — Standard practice for the installation of PVC- and CPVC-DWV pipe and pipe fittings 148

CSA B181.3:24, Polyolefin and polyvinylidene fluoride (PVDF) laboratory drainage systems

1 Scope 159

- 1.1 General 159
- 1.2 Joining method 159
- 1.3 Transitioning between different manufacturers' products 159
- 1.4 Differing or additional characteristics 159
- 1.5 Terminology 159

2 Reference publications 160

3 Definitions and abbreviations 160

4 Pipe classification 160

5 General requirements 160

- 5.1 Compounds 160
 - 5.1.1 Polyethylene (PE) 160
 - 5.1.2 Polypropylene (PP) 160
 - 5.1.3 Polyvinylidene fluoride (PVDF) 160
 - 5.1.4 Stabilizers, antioxidants, pigments, and fillers 160
 - 5.1.5 Reworked material 160
- 5.2 Manufactured pipe and fittings 160

6 Test requirements 160

- 6.1 Dimensions — Pipe and fittings 160
 - 6.1.1 General 160
 - 6.1.2 Pipe 161
 - 6.1.3 Fittings 161
- 6.2 Fitting configurations 161
 - 6.2.1 One-quarter bends 161
 - 6.2.2 Sanitary tees 161
 - 6.2.3 45° Y-branch fittings 161
 - 6.2.4 Increases 162
- 6.3 Cleanouts 162
 - 6.3.1 Female threads 162
 - 6.3.2 Thread size and depth 162
- 6.4 Traps 162
- 6.5 Chemical resistance 162
- 6.6 Water resistance 162
- 6.7 System integrity 162
 - 6.7.1 Fused joints 162
 - 6.7.2 Other joints 162

6.7.3	Restraint for non-fused joints	162
6.7.4	Joint pullout for non-fused joints	162
6.8	Stainless steel	163
6.9	Sealing rings	163
7	Test methods	163
7.1	Conditioning	163
7.1.1	General	163
7.1.2	Test conditions	163
7.2	Dimensions and tolerances	163
7.3	Chemical resistance	163
7.4	Hydrostatic pressure tests	163
7.4.1	Hydrostatic joint integrity	163
7.4.2	Non-fusion joint pressure test	163
7.4.3	Minimum hydrostatic burst pressure	164
7.5	Joint pullout test	164
7.5.1	Procedure	164
7.5.2	Force	164
8	Quality control	164
8.1	PE pipe	164
8.2	PP and PVDF pipe	164
9	Instructions	164
9.1	General	164
9.2	Installation	165
10	Markings	165
10.1	Pipe	165
10.2	Fittings	165

Annexes

Annex A (informative) — Supplementary information	168
---	-----

CSA B181.5:24, *Coextruded acrylonitrile-butadiene-styrene/polyvinylchloride (ABS/PVC) drain, waste, and vent pipe*

1	Scope	170
1.1	General	170
1.2	Intent of this Standard	170
1.3	Terminology	170
2	Reference publications	170
3	Definitions and abbreviations	170
4	General requirements	171
4.1	Materials	171
4.1.1	ABS compound	171

4.1.2	PVC compound	171
4.2	Reworked material	171
5	Requirements for manufactured pipe	171
5.1	General	171
5.1.1	Pipe	171
5.1.2	Adjacent layers	171
5.2	Dimensions of pipe	171
5.2.1	Diameter	171
5.2.2	Out-of-roundness	171
5.2.3	Wall thickness	172
5.2.4	Thickness of the outer layer	172
5.3	Chemical resistance	172
5.4	Water resistance	172
5.5	Dimensional stability	172
5.6	Bond strength	172
5.7	Compression strength	172
5.8	Solvent-cemented joint tightness	172
5.9	Quality control	172
5.9.1	General	172
5.9.2	Low-temperature impact strength of pipe	172
5.9.3	Extrusion quality	173
6	Test methods	173
6.1	Conditioning	173
6.1.1	General	173
6.1.2	Conditioning for impact resistance	173
6.1.3	Test conditions	173
6.2	Dimensions	173
6.2.1	General	173
6.2.2	Outside diameter	173
6.2.3	Wall thickness	173
6.2.4	Thickness of the outer layer	173
6.3	Compression strength test	174
6.3.1	Test 1	174
6.3.2	Test 2	174
6.4	Solvent-cemented joint test	174
7	Markings	174

CSA B182.1:24, Plastic drain and sewer pipe and pipe fittings

1	Scope	177
1.1	General	177
1.2	Terminology	177
2	Reference publications	177
3	Definitions and abbreviations	177

4	General requirements	178
4.1	Compounds	178
4.1.1	Pipe	178
4.1.2	Fittings	178
4.2	Manufactured pipe, fittings, and accessories	178
4.2.1	General	178
4.2.2	Reworked material	178
4.2.3	Industrial plastic scrap	179
4.3	Elastomeric gaskets	179
4.4	Pipe threads	179
4.4.1	General	179
4.4.2	Moulded threads	179
4.4.3	Taper pipe threads	179
4.5	Solvent cements	179
4.5.1	Solvent cements for PVC pipe and fittings	179
4.5.2	Solvent cements for ABS pipe and fittings	179
4.5.3	Solvent cements for joining ABS to PVC	180
5	Detailed requirements	180
5.1	Dimensions and tolerances	180
5.1.1	Non-perforated pipe	180
5.1.2	Perforated pipe	180
5.1.3	Out-of-roundness of pipe	180
5.1.4	Pipe bell ends	180
5.1.5	Holes in perforated pipe	181
5.1.6	Fittings	181
5.1.7	Dimensions of elastomeric gasket joints	181
5.1.8	Thickness of the surface layers of coextruded pipe	182
5.2	Compression test for pipe	182
5.3	Chemical resistance	182
5.4	Pipe stiffness	182
5.4.1	Non-perforated pipe	182
5.4.2	Perforated pipe	182
5.5	Impact resistance of pipe	182
5.6	Heat reversion in PVC moulded fittings	182
5.7	Solvent-welded joint tightness	182
5.8	Elastomeric gasket joint tightness	183
5.9	Cleanout assembly tightness	183
5.10	Controlled settlement joints	183
5.10.1	Joint qualification	183
5.10.2	Resistance test	183
5.11	Backwater valves	183
5.11.1	General	183
5.11.2	Wall thickness	183
5.12	Pipe stop load support	183
5.13	Extrusion quality of pipe	183
5.14	Bond integrity of coextruded pipe	184
6	Test methods	184

- 6.1 Conditioning 184
 - 6.1.1 General 184
 - 6.1.2 Conditioning for impact resistance 184
 - 6.1.3 Test conditions 184
- 6.2 Dimensions 184
- 6.3 Tensile test 184
- 6.4 Chemical resistance test 184
- 6.5 Solvent-welded joint test 184
- 6.6 Elastomeric gasket joint tests 184
 - 6.6.1 Preparation 184
 - 6.6.2 Hydrostatic test 185
 - 6.6.3 Vacuum test 185
 - 6.6.4 Shear load test 185
- 6.7 Controlled-settlement resistance test 185
- 6.8 Thickness of the surface layers of coextruded pipe 185
- 6.9 Bond integrity test of coextruded pipe 186
- 6.10 Pipe stop load support test 186

7 Markings 186

- 7.1 Pipe 186
 - 7.1.1 General 186
 - 7.1.2 Perforated pipe 186
- 7.2 Fittings 186
- 7.3 Backwater valves 186
- 7.4 Solvent cement 186

Annexes

- Annex A (informative) — Relationship between pipe stiffness and the end use of the pipe 195
- Annex B (informative) — Fitting patterns 198

CSA B182.2:24, PSM type polyvinylchloride (PVC) sewer pipe and fittings

1 Scope 203

- 1.1 General 203
- 1.2 Multilayer construction 203
- 1.3 Terminology 203

2 Reference publications 203

3 Definitions and abbreviations 203

4 General requirements 204

- 4.1 PVC compounds 204
 - 4.1.1 Pipe 204
 - 4.1.2 Moulded fittings 204
 - 4.1.3 Different cell classifications 204
- 4.2 Reworked material 204
 - 4.2.1 General 204
 - 4.2.2 Reworked PVC from multilayer pipe 204

- 4.3 Industrial plastic scrap 204
- 4.4 Recycled PVC in multilayer pipe 204
 - 4.4.1 General 204
 - 4.4.2 Cell classification 204
- 5 Manufactured pipe and fittings 205**
 - 5.1 Quality of work 205
 - 5.2 Pipe dimensions 205
 - 5.2.1 General 205
 - 5.2.2 Diameter 205
 - 5.2.3 Wall thickness 205
 - 5.2.4 Out-of-roundness 205
 - 5.2.5 Centre layer colour 205
 - 5.2.6 Holes in perforated pipe 205
 - 5.3 Socket dimensions 206
 - 5.3.1 Socket dimensions for solvent-cemented joints 206
 - 5.3.2 Socket dimensions for gasket joints 206
 - 5.4 Fitting dimensions 206
 - 5.4.1 General 206
 - 5.4.2 Wall thickness of fittings 206
 - 5.4.3 Ninety-degree elbows 206
 - 5.4.4 Centreline radius 206
 - 5.5 Pipe stiffness 207
- 6 Jointing systems 207**
 - 6.1 Solvent-cemented joints 207
 - 6.1.1 General 207
 - 6.1.2 Solvent cements 207
 - 6.1.3 Jointing procedure 207
 - 6.1.4 Joint tightness 207
 - 6.2 Elastomeric gaskets 207
- 7 Moulded fittings 208**
 - 7.1 Heat reversion in PVC moulded fittings 208
 - 7.2 Pipe-stop load support 208
- 8 Fabricated fittings 208**
 - 8.1 Solvent-cemented joints 208
 - 8.1.1 Resistance to bending 208
 - 8.1.2 Lap shear 208
 - 8.1.3 Bond area 208
 - 8.2 Welded joints 208
 - 8.2.1 Resistance to bending 208
 - 8.2.2 Tensile strength 209
 - 8.2.3 Bend back 209
 - 8.3 Mechanical joints 209
 - 8.3.1 Short-term bending test 209
 - 8.3.2 Long-term bending test 209
- 9 Pipe 209**

9.1	Compression strength	209
9.2	Impact resistance of pipe	209
9.3	Extrusion quality of pipe	209
9.4	Bond integrity of multilayer pipe	209
10	Test methods	210
10.1	Conditioning	210
10.1.1	General	210
10.1.2	Conditioning for impact resistance	210
10.1.3	Test conditions	210
10.2	Solvent-cemented joint test	210
10.3	Pipe-stop load support — Moulded fittings	210
10.4	Mechanical joints	210
10.4.1	Short-term bending test	210
10.4.2	Long-term bending test	210
10.5	Bond integrity test for multilayer pipe	210
11	Markings	211
11.1	Pipe	211
11.2	Fittings	211
11.2.1	General	211
11.2.2	Fabricated fittings	211
11.3	Solvent cement	211

Annexes

Annex A (informative)	— Recommended quality control criteria	222
Annex B (informative)	— Base inside diameters	223
Annex C (informative)	— Fitting patterns	225

CSA B182.4:24, *Profile polyvinylchloride (PVC) sewer pipe and fittings*

1	Scope	230
1.1	General	230
1.2	Terminology	230
2	Reference publications	230
3	Definitions and abbreviations	230
4	General requirements	231
4.1	PVC compounds	231
4.1.1	Pipe and fittings	231
4.1.2	Different cell classifications	231
4.1.3	UV stabilization	231
4.2	Reworked material	231
4.3	Chemical resistance	231
5	Manufactured pipe and fittings	231
5.1	Quality of work	231

- 5.1.1 General 231
- 5.1.2 Spiral winding seam 231
- 5.2 Pipe dimensions 231
 - 5.2.1 Diameter 231
 - 5.2.2 Wall thickness 231
 - 5.2.3 Out-of-roundness 232
- 5.3 Dimensions of bell for gasket joints 232
- 5.4 Pipe stiffness 232
 - 5.4.1 General 232
 - 5.4.2 Circumferentially ribbed pipe 232
 - 5.4.3 Spirally ribbed pipe 232
- 5.5 Fabricated fittings 232
 - 5.5.1 Materials 232
 - 5.5.2 Fittings with solvent-cemented components 233
 - 5.5.3 Pipe or fittings with mitred, lapped, or reinforced components 233
 - 5.5.4 Resistance to bending 233
- 5.6 Moulded fittings 233
 - 5.6.1 Dimensions 233
 - 5.6.2 Stiffness 233
 - 5.6.3 CSA B182.1 and CSA B182.2 moulded fittings 234
 - 5.6.4 Joining different types of plastic pipe 234

6 Elastomeric gaskets 234

- 6.1 General 234
- 6.2 Location 234

7 Quality control 234

- 7.1 Compression strength of pipe 234
- 7.2 Impact resistance of pipe 234
- 7.3 Extrusion quality of pipe 234
- 7.4 Airtightness of spirally wound pipe 235
- 7.5 Heat reversion in PVC moulded fittings 235
- 7.6 Bond strength of DWC-PVC sewer pipe 235

8 Test methods 235

- 8.1 Conditioning 235
 - 8.1.1 General 235
 - 8.1.2 Conditioning for impact resistance 235
 - 8.1.3 Test conditions 235
- 8.2 Compression strength test 235
 - 8.2.1 Specimens 235
 - 8.2.2 Baseline 236
 - 8.2.3 Positioning of specimens 236
 - 8.2.4 Positioning of the baseline 236
 - 8.2.5 Loading rate 236
 - 8.2.6 Performance requirements and failure criteria 236
 - 8.2.7 Examination of specimens 236
- 8.3 Impact resistance test for pipe 236
 - 8.3.1 Apparatus and specimens 236
 - 8.3.2 General 236

- 8.3.3 Procedure 236
- 8.3.4 Performance requirements 237
- 8.3.5 Failure criteria 237
- 8.4 Airtightness test 237
 - 8.4.1 General 237
 - 8.4.2 Procedure 237
 - 8.4.3 Failure criteria 238
- 8.5 Bond strength of DWC-PVC sewer pipe 238
- 8.6 Chemical resistance test 238

9 Markings 238

- 9.1 Pipe 238
- 9.2 Fittings 238
 - 9.2.1 General 238
 - 9.2.2 Fabricated fittings 238

Annexes

- Annex A (informative) — Recommended quality control criteria 246
- Annex B (informative) — Base inside diameters 247
- Annex C (informative) — Fitting patterns 249

CSA B182.6:24, Profile polyethylene (PE) sewer pipe and fittings for leak-proof sewer applications

1 Scope 253

- 1.1 General 253
- 1.2 Terminology 253

2 Reference publications 253

3 Definitions and abbreviations 253

4 General requirements 254

- 4.1 PE compounds 254
 - 4.1.1 Pipe and fittings 254
 - 4.1.2 Rotationally moulded accessories 254
 - 4.1.3 Extruded (blow-moulded) or machined (lathed) accessories 254
 - 4.1.4 Injection-moulded accessories 254
 - 4.1.5 Thermal stability 254
- 4.2 Other compounds 254
- 4.3 Reworked material 254
- 4.4 Vent openings at pipe ends 254

5 Manufactured pipe and fittings 255

- 5.1 Quality of work 255
- 5.2 Pipe dimensions 255
 - 5.2.1 Diameter 255
 - 5.2.2 Wall thickness 255
 - 5.2.3 Out-of-roundness 255
- 5.3 Dimensions of bell for gasket joints 255

- 5.4 Pipe stiffness 255
- 5.5 Fabricated PE fittings 255
 - 5.5.1 General 255
 - 5.5.2 Resistance to bending 256
 - 5.5.3 Fittings with welded or reinforced components 256
 - 5.5.4 Fittings with bell and gasket joints 256
- 5.6 PE accessories 256
- 5.7 Fabricated and moulded PVC fittings 256
 - 5.7.1 Fabricated PVC fittings 256
 - 5.7.2 Moulded PVC fittings 256

6 Jointing systems 257

- 6.1 Elastomeric gasket joints 257
 - 6.1.1 General 257
 - 6.1.2 Joint tightness 257
- 6.2 Heat fusion 257
- 6.3 Plain end extrusion weld 257
- 6.4 Other jointing systems 257

7 Quality control 257

- 7.1 Compression strength of pipe 257
- 7.2 Impact resistance of pipe 257
- 7.3 Weld integrity of welded bells and spigots 257
- 7.4 Bond strength 258
 - 7.4.1 General 258
 - 7.4.2 Bond strength 258

8 Test methods 258

- 8.1 Conditioning 258
 - 8.1.1 General 258
 - 8.1.2 Conditioning for impact resistance 258
 - 8.1.3 Conditioning for fabricated fittings 258
 - 8.1.4 Test conditions 258
- 8.2 Pipe stiffness 258
 - 8.2.1 Specimens 258
 - 8.2.2 Test position 258
- 8.3 Compression strength test of pipe 259
 - 8.3.1 Flattening 259
 - 8.3.2 Buckling 259
 - 8.3.3 Test evaluation 259
 - 8.3.4 Retesting 259
- 8.4 Bond strength test for pipe 259
- 8.5 Fabricated PE fitting tests 260
 - 8.5.1 Bending test 260
 - 8.5.2 Tensile and bend-back tests 260
- 8.6 Slow crack-growth resistance of PE pipe (NCLS) 260
 - 8.6.1 General 260
 - 8.6.2 Procedure 260
 - 8.6.3 Stress 260

8.6.4 Specimens 260

8.6.5 Criteria 260

9 Markings 261

9.1 Pipe 261

9.2 Fittings 261

9.2.1 General 261

9.2.2 Fabricated fittings 261

Annexes

Annex A (informative) — Recommended quality control criteria 264

Annex B (informative) — Base inside diameters 265

Annex C (informative) — Fitting patterns 266

Annex D (informative) — Purchase ordering 269

CSA B182.8:24, Profile polyethylene (PE) storm sewer and drainage pipe and fittings

1 Scope 271

1.1 General 271

1.2 Exclusions 271

1.3 Terminology 271

2 Reference publications 271

3 Definitions and abbreviations 271

4 General requirements 272

4.1 PE compounds 272

4.1.1 Pipe and fittings 272

4.1.2 Rotationally moulded accessories 273

4.1.3 Extruded (blow-moulded) or machined (lathed) accessories 273

4.1.4 Injection-moulded accessories 273

4.1.5 Thermal stability 273

4.2 Other compounds 273

4.3 Reworked material 273

4.4 Vent openings at pipe ends 273

5 Manufactured pipe and fittings 273

5.1 Quality of work 273

5.2 Pipe dimensions 274

5.2.1 Diameter 274

5.2.2 Wall thickness 274

5.2.3 Out-of-roundness 274

5.2.4 Perforations 274

5.3 Dimensions of bell for gasket joints 274

5.4 Pipe stiffness 274

5.5 Fabricated PE fittings 274

5.5.1 General 274

5.5.2 Resistance to bending 275

5.5.3	Fittings with welded or reinforced components	275
5.5.4	Fittings with bell and gasket joints	275
5.6	PE accessories	275
5.7	Fabricated and moulded PVC fittings	275
5.7.1	Fabricated PVC fittings	275
5.7.2	Moulded PVC fittings	275
6	Jointing systems	276
6.1	Elastomeric Type 1 watertight gasket joints	276
6.1.1	General	276
6.1.2	Jointing procedures	276
6.1.3	Bell and gasket joint tightness	276
6.2	Elastomeric Type 2 silt-tight gasket joints	276
6.2.1	General	276
6.2.2	Jointing procedures	276
6.2.3	Joint tightness	276
6.3	Type 3 soil-tight non-gasketed coupling joints	276
6.3.1	General	276
6.3.2	Compounds	277
6.3.3	Seating fit and function	277
6.3.4	Closure devices	277
6.3.5	Location and installation procedure	277
6.4	Heat fusion	277
6.5	Plain end extrusion weld	277
6.6	Other jointing systems	277
7	Quality control	278
7.1	Compression strength of pipe	278
7.2	Impact resistance of pipe	278
7.3	Weld integrity of welded bells and spigots	278
7.4	Bond strength of pipe	278
8	Test methods	278
8.1	Conditioning	278
8.1.1	General	278
8.1.2	Conditioning for impact resistance	278
8.1.3	Conditioning for fabricated fittings	278
8.1.4	Test conditions	278
8.2	Pipe stiffness	278
8.2.1	Specimens	278
8.2.2	Test position	279
8.3	Compression strength test for pipe	279
8.3.1	Flattening	279
8.3.2	Buckling	279
8.3.3	Test evaluation	279
8.3.4	Retesting	279
8.4	Bond strength test for pipe	280
8.5	Slow crack-growth resistance of PE pipe (NCLS)	280
8.5.1	General	280
8.5.2	Procedure	280

8.5.3	Stress	280
8.5.4	Specimens	280
8.5.5	Criteria	280
8.6	Fabricated PE fitting tests	280
8.6.1	Bending test	280
8.6.2	Tensile and bend-back tests	280
8.7	Determination of crack initiation and service life prediction of pipes manufactured with recycled materials	281
8.7.1	General	281
8.7.2	Procedure	281
8.7.3	Stress	281
8.7.4	Specimens	281
8.7.5	Criteria	281
8.8	Determination of PP content for recycled materials	281
8.9	Determination of ash content in recycled materials	281
8.10	OIT	281

9 Markings 281

9.1	Pipe	281
9.2	Fittings	282
9.2.1	General	282
9.2.2	Fabricated fittings	282
9.3	Jointing systems	282

Annexes

Annex A (informative)	— Recommended quality control criteria	286
Annex B (informative)	— Base inside diameters	287
Annex C (informative)	— Fitting patterns	288
Annex D (informative)	— Perforation details	291
Annex E (informative)	— External split couplings	292
Annex F (informative)	— Purchase ordering	293
Annex G (normative)	— Additional minimum quality control criteria for pipes with recycled materials	294

CSA B182.11:24, Standard practice for the installation of thermoplastic drain, storm, and sewer pipe and fittings

1 Scope	296
1.1	General 296
1.2	Applicability 296
1.3	Exclusions 296
1.4	Terminology 296
2 Reference publications	297
3 Definitions and abbreviations	297
4 Receiving, unloading, and storing	297
4.1	Receiving 297

4.2	Unloading	297
4.3	Storing	298
5	Trench construction	298
5.1	Trench excavation and support	298
5.2	Types of trench construction	298
5.2.1	General	298
5.2.2	Narrow, unsupported, vertical-walled trench	298
5.2.3	Unsupported subditch trench	298
5.2.4	Wide trench	299
5.2.5	Supported trench	299
5.3	Trench bottom	300
5.3.1	General	300
5.3.2	Special trench foundation	300
5.3.3	Overexcavation	300
5.3.4	Rock subgrade	300
5.3.5	Bedding	300
5.3.6	Haunching	300
5.3.7	Initial backfill	300
5.4	Embedment materials	301
5.4.1	Classifications	301
5.4.2	Methods of placing embedment materials	301
5.4.3	Tamping and vibrating	301
5.4.4	Saturation	302
6	Laying and joining thermoplastic pipe and fittings	302
6.1	General procedure	302
6.2	Handling	302
6.3	Joining pipe and fittings	302
6.3.1	Cutting and bevelling pipe	302
6.3.2	Assembly of joints	302
6.3.3	Solvent-cemented joints	303
6.4	Service lines/connections	303
6.4.1	Fittings	303
6.4.2	Storm and sewer laterals	303
6.4.3	Pipe caps and plugs	304
6.4.4	Installing pipe through casings	304
7	Final backfill	304
7.1	Backfill material	304
7.2	Backfill compaction	304
7.3	Minimum cover over pipe	304
7.4	Deflection	304
8	Field performance and acceptance tests	305
8.1	General	305
8.2	Cleaning	305
8.3	Visual test	305
8.4	Leakage test	305
8.4.1	General	305

- 8.4.2 Low-pressure air testing 305
- 8.4.3 Infiltration testing using water 305
- 8.4.4 Exfiltration testing using water 305
- 8.5 Deflection testing 306

Annexes

- Annex A (informative) — Long-term deflection of PVC pipes 312

CSA B182.12:24, *Profile polypropylene (PP) storm sewer pipe and fittings*

- 1 Scope 315**
 - 1.1 General 315
 - 1.2 Terminology 315
- 2 Reference publications 315**
- 3 Definitions and abbreviations 315**
- 4 General requirements 316**
 - 4.1 PP compounds 316
 - 4.1.1 Pipe and fittings 316
 - 4.1.2 Creep rupture strength 316
 - 4.1.3 Creep modulus 316
 - 4.2 Reworked material 316
 - 4.3 Vent openings at pipe ends 316
- 5 Manufactured pipe and fittings 316**
 - 5.1 Quality of work 316
 - 5.2 Pipe dimensions 317
 - 5.2.1 Diameters 317
 - 5.2.2 Wall thickness 317
 - 5.2.3 Out-of-roundness 317
 - 5.2.4 Perforations 317
 - 5.3 Dimensions of bell for gasket joints 317
 - 5.4 Pipe stiffness 317
 - 5.4.1 General 317
 - 5.4.2 Length of test specimens 317
 - 5.5 Fabricated PP fittings 318
 - 5.5.1 General 318
 - 5.5.2 Resistance to bending 318
 - 5.5.3 Fittings with welded or reinforced components 318
 - 5.5.4 Fittings with bell and gasket joints 318
 - 5.6 PP accessories 318
 - 5.7 Fabricated and moulded PVC fittings 318
 - 5.7.1 Fabricated PVC fittings 318
 - 5.7.2 Moulded PVC fittings 318
- 6 Jointing systems 319**
 - 6.1 Elastomeric watertight gasket joints 319

- 6.1.1 General 319
- 6.1.2 Jointing procedures 319
- 6.1.3 Bell and gasket joint tightness 319
- 6.2 Heat fusion 319
- 6.3 Plain end extrusion weld 319
- 6.4 Other jointing systems 319

- 7 Quality control 319**
 - 7.1 Compression strength of pipe 319
 - 7.2 Impact resistance of pipe 319
 - 7.3 Bond strength of pipe 320
 - 7.4 Weld integrity of welded bells and spigots 320

- 8 Test methods 320**
 - 8.1 Conditioning 320
 - 8.1.1 General 320
 - 8.1.2 Conditioning for impact resistance 320
 - 8.1.3 Conditioning for fabricated fittings 320
 - 8.1.4 Test conditions 320
 - 8.2 Pipe stiffness 320
 - 8.2.1 Specimens 320
 - 8.2.2 Test position 320
 - 8.3 Compression strength test of pipe 321
 - 8.3.1 Flattening 321
 - 8.3.2 Buckling 321
 - 8.3.3 Test evaluation 321
 - 8.3.4 Retesting 321
 - 8.4 Bond strength test for pipe 321
 - 8.5 Fabricated PP fitting tests 322
 - 8.5.1 Bending test 322
 - 8.5.2 Tensile and bend-back tests 322
 - 8.6 Creep rupture strength test for pipe 322
 - 8.6.1 General 322
 - 8.6.2 Procedure 322
 - 8.6.3 Failure criteria 322
 - 8.7 Creep modulus test for pipe 322
 - 8.7.1 General 322
 - 8.7.2 Procedure 323
 - 8.7.3 Failure criteria 323

- 9 Markings 323**
 - 9.1 Pipe 323
 - 9.2 Fittings 323

Annexes

- Annex A (informative) — Recommended quality control test frequencies 326
- Annex B (informative) — Base inside diameters 327
- Annex C (informative) — Fitting patterns 328
- Annex D (informative) — Perforation details 331
- Annex E (informative) — Purchase ordering 332

CSA B182.13:24, Profile polypropylene (PP) sewer pipe and fittings for leak-proof sewer applications

- 1 Scope 334**
 - 1.1 General 334
 - 1.2 Terminology 334
- 2 Reference publications 334**
- 3 Definitions and abbreviations 334**
- 4 General requirements 335**
 - 4.1 PP compounds 335
 - 4.1.1 Pipe and fittings 335
 - 4.1.2 Creep rupture strength 335
 - 4.1.3 Creep modulus 335
 - 4.2 Reworked material 335
 - 4.3 Vent openings at pipe ends 335
- 5 Manufactured pipe and fittings 336**
 - 5.1 Quality of work 336
 - 5.2 Pipe dimensions 336
 - 5.2.1 Diameters 336
 - 5.2.2 Wall thickness 336
 - 5.2.3 Out-of-roundness 336
 - 5.3 Dimensions of bell for gasket joints 336
 - 5.4 Pipe stiffness 336
 - 5.4.1 General 336
 - 5.4.2 Annular profile 336
 - 5.5 Fabricated PP fittings 337
 - 5.5.1 General 337
 - 5.5.2 Resistance to bending 337
 - 5.5.3 Fittings with welded or reinforced components 337
 - 5.5.4 Fittings with bell and gasket joints 337
 - 5.6 PP accessories 337
 - 5.7 Fabricated and moulded PVC fittings 337
 - 5.7.1 Fabricated PVC fittings 337
 - 5.7.2 Moulded PVC fittings 337
- 6 Jointing systems 338**
 - 6.1 Elastomeric gasket joints 338
 - 6.1.1 General 338
 - 6.1.2 Joint tightness 338
 - 6.1.3 Joint proof-of-design validation 338
 - 6.2 Heat fusion 338
 - 6.3 Plain end extrusion weld 338
 - 6.4 Other jointing systems 338

- 7 Quality control 338**
- 7.1 Compression strength of pipe 338
- 7.2 Impact resistance of pipe 339
- 7.3 Bond strength of pipe 339
- 7.4 Weld integrity of welded bells and spigots 339

- 8 Test methods 339**
- 8.1 Conditioning 339
 - 8.1.1 General 339
 - 8.1.2 Conditioning for impact resistance 339
 - 8.1.3 Conditioning for fabricated fittings 339
 - 8.1.4 Test conditions 339
- 8.2 Pipe stiffness 339
 - 8.2.1 Specimens 339
 - 8.2.2 Test position 339
- 8.3 Compression strength test of pipe 340
 - 8.3.1 Flattening 340
 - 8.3.2 Buckling 340
 - 8.3.3 Test evaluation 340
 - 8.3.4 Retesting 340
- 8.4 Bond strength test for pipe 340
- 8.5 Fabricated PP fitting tests 341
 - 8.5.1 Bending test 341
 - 8.5.2 Tensile and bend-back tests 341
- 8.6 Creep rupture strength test for pipe 341
 - 8.6.1 General 341
 - 8.6.2 Procedure 341
 - 8.6.3 Failure criteria 341
- 8.7 Creep modulus test for pipe 341
 - 8.7.1 General 341
 - 8.7.2 Procedure 342
 - 8.7.3 Failure criteria 342

- 9 Markings 342**
- 9.1 Pipe 342
- 9.2 Fittings 342

Annexes

- Annex A (informative) — Recommended quality control test frequencies 345
- Annex B (informative) — Base inside diameters 346
- Annex C (informative) — Fitting patterns 348
- Annex D (informative) — Purchase ordering 351

CSA B182.14:24, Profile steel reinforced polyethylene (SRPE) storm sewer pipe and fittings

- 1 Scope 353**
- 1.1 General 353
- 1.2 Terminology 353

2	Reference publications	353
3	Definitions and abbreviations	353
4	General requirements	354
4.1	PE compounds	354
4.1.1	Pipe and fittings	354
4.1.2	Rotationally moulded accessories	354
4.1.3	Extruded (blow- or injection-moulded) or machined (lathed) accessories	354
4.1.4	Thermal stability	354
4.2	Other compounds	354
4.3	Reworked material	354
4.4	Steel	354
5	Manufactured pipe and fittings	355
5.1	Quality of work	355
5.2	Helical winding seams	355
5.3	Pipe dimensions	355
5.3.1	Diameter	355
5.3.2	Wall thickness	355
5.3.3	Reinforcing ribs	355
5.3.4	Out-of-roundness	355
5.3.5	Perforations	356
5.4	Dimensions of bell for gasket joints	356
5.5	Pipe stiffness	356
5.6	Fabricated SRPE fittings	356
5.6.1	General	356
5.6.2	Resistance to bending	356
5.6.3	Fittings with welded or reinforced components	356
5.6.4	Fittings with bell and gasket joints	357
5.7	PE accessories	357
5.8	Fabricated and moulded PVC fittings	357
6	Jointing systems	357
6.1	General	357
6.2	Elastomeric Type 1 watertight gasket joints	357
6.2.1	Gaskets	357
6.2.2	Jointing procedures	357
6.2.3	Bell and gasket joint tightness	357
6.3	Elastomeric Type 2 silt-tight gasket joints	357
6.3.1	Gaskets	357
6.3.2	Jointing procedures	357
6.3.3	Bell and gasket joint tightness	357
6.4	Type 3 non-gasketed coupling joints	358
6.4.1	General	358
6.4.2	Seating fit and function	358
6.4.3	Location and installation procedure	358
6.5	Heat fusion joints	358
6.6	Plain end extrusion weld	358
6.7	Other jointing systems	358

7	Quality control	359
7.1	Compression strength of pipe	359
7.2	Impact resistance of pipe	359
7.3	Weld integrity of spirally wound pipe, welded bells, and spigots	359
7.4	Fabricated SRPE fittings	359
8	Test methods	359
8.1	Conditioning	359
8.1.1	General	359
8.1.2	Conditioning for impact resistance	359
8.1.3	Conditioning for fabricated fittings	359
8.1.4	Test conditions	359
8.2	Compression strength test for pipe	359
8.2.1	Flattening	359
8.2.2	Test evaluation	360
8.2.3	Retesting	360
8.3	Slow crack-growth resistance of SRPE pipe (NCLS)	360
8.3.1	General	360
8.3.2	Procedure	360
8.3.3	Stress	360
8.3.4	Specimens	360
8.3.5	Criteria	360
9	Markings	360
9.1	Pipe	360
9.2	Fittings	360
9.3	Jointing systems	361

Annexes

Annex A (informative)	— Recommended quality control test frequencies	366
Annex B (informative)	— Base inside diameters	367
Annex C (informative)	— Fitting patterns	368
Annex D (informative)	— Type 3 non-gasketed coupling joints	371
Annex E (informative)	— Recommendations for purchase ordering	373

CSA B182.15:24, *Profile steel reinforced polyethylene (SRPE) sewer pipe and fittings*

1	Scope	375
1.1	General	375
1.2	Terminology	375
2	Reference publications	375
3	Definitions and abbreviations	375
4	General requirements	376
4.1	PE compounds	376
4.1.1	Pipe and fittings	376
4.1.2	Rotationally moulded accessories	376

- 4.1.3 Extruded (blow- or injection-moulded) or machined (lathed) accessories 376
- 4.1.4 Thermal stability 376
- 4.2 Other compounds 376
- 4.3 Reworked material 376
- 4.4 Steel 376

5 Manufactured pipe and fittings 377

- 5.1 Quality of work 377
- 5.2 Helical winding seams 377
- 5.3 Pipe dimensions 377
 - 5.3.1 Diameters 377
 - 5.3.2 Wall thickness 377
 - 5.3.3 Reinforcing ribs 377
 - 5.3.4 Out-of-roundness 377
- 5.4 Dimensions of bell for gasket joints 378
- 5.5 Pipe stiffness 378
- 5.6 Fabricated SRPE fittings 378
 - 5.6.1 General 378
 - 5.6.2 Resistance to bending 378
 - 5.6.3 Fittings with welded or reinforced components 378
 - 5.6.4 Fittings with bell and gasket joints 378
- 5.7 PE accessories 379
- 5.8 Fabricated and moulded PVC fittings 379

6 Jointing systems 379

- 6.1 General 379
- 6.2 Elastomeric watertight gasket joints 379
 - 6.2.1 Gaskets 379
 - 6.2.2 Jointing procedure 379
 - 6.2.3 Bell and gasket joint tightness 379
- 6.3 Heat fusion joints 379
- 6.4 Plain end extrusion weld 379
- 6.5 Other jointing systems 379

7 Quality control 380

- 7.1 Compression strength of pipe 380
- 7.2 Impact resistance of pipe 380
- 7.3 Weld integrity of spirally wound pipe, welded bells, and spigots 380
- 7.4 Fabricated SRPE fittings 380

8 Test methods 380

- 8.1 Conditioning 380
 - 8.1.1 General 380
 - 8.1.2 Conditioning for impact resistance 380
 - 8.1.3 Conditioning for fabricated fittings 380
 - 8.1.4 Test conditions 380
- 8.2 Compression strength test for pipe 380
 - 8.2.1 Flattening 380
 - 8.2.2 Test evaluation 381
 - 8.2.3 Retesting 381

8.3	Slow crack-growth resistance of SRPE pipe (NCLS)	381
8.3.1	General	381
8.3.2	Procedure	381
8.3.3	Stress	381
8.3.4	Specimens	381
8.3.5	Criteria	381
9	Markings	381
9.1	Pipe	381
9.2	Fittings	381
9.3	Jointing systems	382
Annexes		
Annex A (informative)	— Recommended quality control test frequencies	387
Annex B (informative)	— Base inside diameters	388
Annex C (informative)	— Fitting patterns	389
Annex D (informative)	— Recommendations for purchase ordering	392

Technical Committee on Plastic Nonpressure Piping

S. Piper	Galaxy Plastics, Barrie, Ontario, Canada <i>Category: Producer Interest</i>	<i>Chair</i>
C. F. Baker	Shell Chemical LP, Angleton, Texas, USA <i>Category: General Interest/Raw Material Supplier</i>	<i>Vice-Chair</i>
A. Navarro	Advanced Drainage Systems Inc., Mississauga, Ontario, Canada <i>Category: Producer Interest</i>	<i>Vice-Chair</i>
S. Adams	City of Charlottetown, Charlottetown, Prince Edward Island, Canada <i>Category: User Interest/Regulatory Authority</i>	
E. Amiralaei	Intertek, Coquitlam, British Columbia, Canada	<i>Non-voting</i>
M. Barrette	Kanaflex Corp., Vernon Hills, Illinois, USA <i>Category: Producer Interest</i>	
R. Blundell	George Brown College, Toronto, Ontario, Canada <i>Category: User Interest/Regulatory Authority</i>	
M. Conrad	NSF International, Ann Arbor, Michigan, USA	<i>Non-voting</i>
D. Currence	Plastics Pipe Institute, Irving, Texas, USA <i>Category: General Interest</i>	
A. De Francesca	City of Toronto, Toronto, Ontario, Canada <i>Category: User Interest/Regulatory Authority</i>	
C. Diez	Soleno Inc., Saint-Jean-sur-Richelieu, Québec, Canada <i>Category: Producer Interest</i>	

L. Douglas	NOVA Chemicals Corp., Calgary, Alberta, Canada	<i>Non-voting</i>
D. Doyle	The Dow Chemical Co., Freeport, Texas, USA	<i>Non-voting</i>
K. Ernst	Oakville Stamping and Bending Ltd., Oakville, Ontario, Canada <i>Category: General Interest/Raw Material Supplier</i>	
W. Fallow	Technical Inspection Services, Department of Public Safety, Fredericton, New Brunswick, Canada <i>Category: User Interest/Regulatory Authority</i>	
D. Gervais	Armtec, Saint-Clet, Québec, Canada	<i>Non-voting</i>
L. Gill	IPEX USA LLC, Oakville, Ontario, Canada	<i>Non-voting</i>
G. L. Groen	Infra Pipe Solutions Ltd., Mississauga, Ontario, Canada	<i>Non-voting</i>
P. Guttilla	Bow Plumbing Group Inc., Montréal, Québec, Canada <i>Category: Producer Interest</i>	
F. Hampton III	Lubrizol Advanced Materials Inc., Cleveland, Ohio, USA <i>Category: General Interest/Raw Material Supplier</i>	
B. E. Hauger	Bryan Hauger Consulting Inc., Boulder, Colorado, USA	<i>Non-voting</i>
E. Ho	IAPMO Group, Markham, Ontario, Canada	<i>Non-voting</i>
K. S. Hui	Ontario Ministry of Municipal Affairs, Toronto, Ontario, Canada <i>Category: User Interest/Regulatory Authority</i>	
N. Ketabi	NanoXplore Inc., Montréal, Québec, Canada	<i>Non-voting</i>

W. Korrall	Wayne Korrall Consulting, Edmonton, Alberta, Canada <i>Category: General Interest/Raw Material Supplier</i>	
J. Kurdziel	Advanced Drainage Systems Inc., Fort Wayne, Indiana, USA	<i>Non-voting</i>
A. Lathia	CSA Group, Cleveland, Ohio, USA	<i>Non-voting</i>
S. Leroux	IPEX Management Inc., Verdun, Québec, Canada <i>Category: Producer Interest</i>	
J. Littlefield	IPEX, Oakville, Ontario, Canada	<i>Non-voting</i>
R. Mata	International Code Council, Washington, DC, USA	<i>Non-voting</i>
M. Mohammed	Reliance Worldwide Corp., Vaughan, Ontario, Canada	<i>Non-voting</i>
A. I. Murra	Abraham Murra Consulting, Santa Margarita, California, USA <i>Category: General Interest/Raw Material Supplier</i>	
C. Neath	ADS Canada, Guelph, Ontario, Canada	<i>Non-voting</i>
H. Nurwadi	Charlotte Pipe and Foundry Company, Monroe, North Carolina, USA <i>Category: Producer Interest</i>	
G. F. Palermo	Palermo Plastics Pipe Consulting, Bluffton, South Carolina, USA <i>Category: General Interest/Raw Material Supplier</i>	
D. Pavlovic	Infra Pipe Solutions Ltd., Mississauga, Ontario, Canada <i>Category: Producer Interest</i>	
F. P. Pozzebon	City of Sault Ste. Marie/Engineering Department/ Building Division, Sault Ste. Marie, Ontario, Canada <i>Category: User Interest/Regulatory Authority</i>	

V. Rohatgi	Chevron Phillips Chemical Co., Bartlesville, Oklahoma, USA <i>Category: General Interest/Raw Material Supplier</i>	
D. Sanders	Contech Engineered Solutions LLC, West Chester, Ohio, USA <i>Category: Producer Interest</i>	
L. Schell	NSF International, Ann Arbor, Michigan, USA	<i>Non-voting</i>
S. Scott	NAPCO Royal Pipe and Fittings, a Westlake Chemical Company, Woodbridge, Ontario, Canada <i>Category: Producer Interest</i>	
P. Sharma	Hamilton Kent, Toronto, Ontario, Canada <i>Category: Producer Interest</i>	
M. St-Louis	Soleno, Saint-Jean-sur-Richelieu, Québec, Canada	<i>Non-voting</i>
T. Wilkinson	Toronto Facilities, Keswick, Ontario, Canada <i>Category: User Interest/Regulatory Authority</i>	
K. Wong	Uponor, Mississauga, Ontario, Canada <i>Category: General Interest/Raw Material Supplier</i>	
S. Chung	CSA Group, Toronto, Ontario, Canada	<i>Project Manager</i>

Preface

This is the eighth edition in the form of a compendium of the CSA B181 and CSA B182 series of Standards, published as CSA B1800, *Thermoplastic nonpressure piping compendium*. It supersedes the previous editions of the compendium, published in 2021, 2018, 2015, 2011, 2006, 2002, and 1999.

This compendium consists of the following Standards:

- the sixth edition of CSA B181.0, *Definitions, general requirements, and methods of testing for thermoplastic nonpressure piping*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, and 2006;
- the thirteenth edition of CSA B181.1, *Acrylonitrile-butadiene-styrene (ABS) drain, waste, and vent pipe and pipe fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1996, 1990, 1985, 1973, and 1967;
- the fourteenth edition of CSA B181.2, *Polyvinylchloride (PVC) and chlorinated polyvinylchloride (CPVC) drain, waste, and vent pipe and pipe fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1996, 1990, 1987, 1985, 1973, and 1967;
- the tenth edition of CSA B181.3, *Polyolefin and polyvinylidene fluoride (PVDF) laboratory drainage systems*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1986, and 1971;
- the tenth edition of CSA B181.5, *Coextruded acrylonitrile-butadiene-styrene/polyvinylchloride (ABS/PVC) drain, waste, and vent pipe*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1995, and 1994;
- the fourteenth edition of CSA B182.1, *Plastic drain and sewer pipe and pipe fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1996, 1992, 1987, 1983, 1977, and 1967;
- the eleventh edition of CSA B182.2, *PSM type polyvinylchloride (PVC) sewer pipe and fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1995, 1990, and 1983;
- the twelfth edition of CSA B182.4, *Profile polyvinylchloride (PVC) sewer pipe and fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1997, 1992, 1990, and 1983;
- the ninth edition of CSA B182.6, *Profile polyethylene (PE) sewer pipe and fittings for leak-proof sewer applications*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, and 1992;
- the seventh edition of CSA B182.8, *Profile polyethylene (PE) storm sewer and drainage pipe and fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, and 2002;
- the tenth edition of CSA B182.11, *Standard practice for the installation of thermoplastic drain, storm, and sewer pipe and fittings*, which supersedes the previous editions published in 2021, 2018, 2015, 2011, 2006, 2002, 1999, 1995, and 1967;
- the second edition of CSA B182.12, *Profile polypropylene (PP) storm sewer pipe and fittings*, which supersedes the previous edition published in 2021;
- the fifth edition of CSA B182.13, *Profile polypropylene (PP) sewer pipe and fittings for leak-proof sewer applications*, which supersedes the previous editions published in 2021, 2018, 2015, and 2011;
- the fourth edition of CSA B182.14, *Profile steel reinforced polyethylene (SRPE) storm sewer pipe and fittings*, which supersedes the previous edition published in 2021, 2018, and 2015; and
- the fourth edition of CSA B182.15, *Profile steel reinforced polyethylene (SRPE) sewer pipe and fittings*, which supersedes the previous edition published in 2021, 2018, and 2015.