

# INTERNATIONAL STANDARD

# IEC 60708

First edition  
2005-06

---

---

## Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

U

*For price, see current catalogue*

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Quality assurance.....	7
4 Cable construction.....	7
4.1 Conductor.....	7
4.1.1 Conductor material.....	7
4.1.2 Type of conductor.....	7
4.1.3 Conductor-finish.....	7
4.1.4 Continuity of conductor.....	7
4.2 Insulation.....	8
4.2.1 Insulation material.....	8
4.2.2 Insulation thickness.....	8
4.2.3 Colour of insulated conductor.....	8
4.3 Cabling element.....	8
4.4 Stranding.....	8
4.5 Colour code.....	8
4.5.1 General.....	8
4.5.2 Sub-units, units and cables up to and including 100 pairs or 100 quads.....	9
4.5.3 Cables of more than 100 pairs or 100 quads.....	9
4.6 Spare pairs or quads.....	10
4.7 Filling.....	10
4.8 Core protection.....	10
4.9 Sheath.....	10
4.9.1 Sheath material.....	10
4.9.2 Application of the sheath.....	10
4.10 Cable protection.....	11
4.11 Finished cable.....	11
4.11.1 Overall diameter.....	11
4.11.2 Sheath marking.....	11
4.11.3 Sealing of ends.....	12
4.12 Delivery.....	12
5 Mechanical requirements.....	12
5.1 Conductor.....	12
5.2 Insulation.....	12
5.3 Sheath.....	12
5.3.1 Tensile strength and elongation.....	12
5.3.2 Adhesion of aluminium tape to the polyethylene.....	12
5.3.3 Adhesion of aluminium tape at the overlap.....	13
5.4 Finished cable.....	13
5.4.1 Sheath integrity.....	13
5.4.2 Resistance to water penetration.....	13
5.4.3 Cable drip.....	13

6	Thermal stability and environmental requirements .....	13
6.1	Insulation .....	13
6.1.1	Thermal oxidative stability (OIT-test) .....	13
6.1.2	Shrinkage .....	14
6.1.3	Wrapping test of insulation after thermal aging .....	14
6.1.4	Bending test at low temperature .....	14
6.2	Sheath .....	14
6.2.1	Elongation at break after ageing .....	14
6.2.2	Resistance to weathering .....	14
6.2.3	Resistance to environmental stress cracking .....	14
7	Electrical requirements .....	14
7.1	General .....	14
7.2	Electrical resistance of conductor .....	14
7.3	Electrical resistance unbalance .....	15
7.4	Dielectric strength .....	15
7.5	Insulation resistance .....	15
7.6	Mutual capacitance .....	15
7.7	Capacitance unbalance .....	16
7.8	Transmission characteristics (when used for digital communication).....	17
7.8.1	Attenuation .....	17
7.8.2	Near End Crosstalk (NEXT) .....	17
7.8.3	Equal Level Far-end Crosstalk (ELFEXT) .....	17
7.8.4	Power sum (PS) of crosstalk loss .....	17
7.8.5	Characteristic impedance .....	17
7.8.6	Velocity of propagation .....	17
	Annex A (normative) Colour code: 10 pair or 5 quad count.....	19
	Annex B (normative) Colour code: sub-unit identification for 50 pair (25 quad) and 100 pair (50 quad) cables or units, using 10 pair or 5 quad count .....	20
	Annex C (normative) Colour code: 25 pair count .....	21
	Annex D (normative) Colour code: unit identification for 50 pair or quad and 100 pair or quad cables or units, using 10 pair or 5 quad count .....	22
	Annex E (normative) Colour code: 25 quad count .....	23
	Annex F (normative) Colour code: unit identification for cables with more than 100 pairs, 25 pair count .....	24
	Annex G (normative) Colour code: unit identification for cables with more than 100 pairs or 50 quads, using 10 pair or 5 quad count or 25 quad count.....	26

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**LOW-FREQUENCY CABLES WITH POLYOLEFIN INSULATION  
AND MOISTURE BARRIER POLYOLEFIN SHEATH**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative References cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60708 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

IEC 60708 cancels and replaces IEC 60708-1 published in 1981 and amendment 3(1988). This edition constitutes a technical revision.

IEC 60708 has been completely revised technically and structurally. IEC 60708 now comprises only one single standard dealing with general design details and requirements. The old IEC 60708-2(1981), IEC 60708-3(1981) and IEC 60708-4(1983) have already been withdrawn because they are not used anymore. Although IEC 60708 addresses low frequency cables, these cables are often used for digital communications up to 2 Mbit/s or 1 MHz. Therefore a Subclause 7.8 has been added, which provides transmission characteristics for the cable when used for digital communication. Furthermore, Annex H of IEC 60708-1(1981) was deleted: The requirements for filling compounds are not needed anymore since they are covered by the cable performance requirements.

The text of this standard is based on the following documents:

FDIS	Report on voting
46C/713/FDIS	46C/728/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above Table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

# LOW-FREQUENCY CABLES WITH POLYOLEFIN INSULATION AND MOISTURE BARRIER POLYOLEFIN SHEATH

## 1 Scope

This standard is intended to define polyolefin-insulated cables for insertion into local outdoor networks.

This standard is applicable to polyolefin insulated and moisture barrier polyolefin sheathed telephone cables, filled or unfilled with copper conductors, and used as:

- a) Cables suitable for installation in ducts.
- b) Cables suitable for direct burial in the ground.
- c) Cables with integral suspension strand for aerial installations.

This standard is in accordance with ITU-T Recommendations.

This standard includes general design details and requirements for dimensions and other constructional details as well as mechanical, electrical and environmental characteristics for all types of low-frequency cables with polyolefin insulation (solid or cellular), filled or unfilled, and moisture barrier polyolefin sheath (with integral suspension strand).

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60028, *International Standard of Resistance for Copper*

IEC 60189-1, *Low-frequency cables and wires with PVC Insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60794-1-2, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60811-1-1, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section 1: Measurement of thickness and overall dimensions – Tests for determining the mechanical properties*

IEC 60811-1-2, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section Two: Thermal ageing methods*

IEC 60811-1-3, *Insulating and sheathing materials of electric cables – Part 1: General application – Section 3: Methods for determining the density – Water absorption tests – Shrinkage test*

IEC 60811-1-4, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section Four – Test at low temperature*

IEC 60811-4-1, *Insulating and sheathing materials of electric and optical cables – Common test methods – Part 4-1: Methods specific to polyethylene and polypropylene compounds – Resistance to environmental stress cracking – Measurement of the melt flow index – Carbon black and/or mineral filler content measurement in polyethylene by direct combustion – Measurement of carbon black content by thermogravimetric analysis (TGA) – Assessment of carbon black dispersion in polyethylene using a microscope*

IEC 60811-4-2, *Insulating and sheathing materials of electric and optical cables – Common test methods – Part 4-2: Methods specific to polyethylene and polypropylene compounds – Tensile strength and elongation at break after conditioning at elevated temperature – Wrapping test after conditioning at elevated temperature – Wrapping test after thermal ageing in air – Measurement of mass increase – Long-term stability test – Test method for copper-catalyzed oxidative degradation*

IEC 60811-5-1, *Common test methods for insulating and sheathing materials of electric cables – Part 5-1: Methods specific to filling compounds – Drop point – Separation from oil – Lower temperature brittleness – Total acid number – Absence of corrosive components – Permittivity at 23 °C – DC resistivity at 23 °C and 100 °C*

IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

ITU-T L.3, *Armouring of cables*