

INTERNATIONAL STANDARD

IEC 60728-11

Second edition
2005-01

Cable networks for television signals, sound signals and interactive services –

Part 11: Safety

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

X

For price, see current catalogue

CONTENTS

FOREWORD	5
1 Scope	10
2 Normative references	10
3 Terms, definitions, symbols and abbreviations	11
3.1 Terms and definitions	11
3.2 Symbols	15
3.3 Abbreviations	15
4 General requirements	15
4.1 General	15
4.2 Mechanical requirements	16
4.3 Accessible parts	16
4.4 Laser radiation	16
5 Protection against environmental influences	16
6 Equipotential bonding and earthing	16
6.1 General requirements	16
6.2 Equipotential bonding mechanisms	17
6.3 Equipotential bonding in meshed systems	18
6.3.1 References to other standards	18
6.3.2 General on a.c. mains	18
6.3.3 AC power distribution and connection of the protective conductor	18
6.3.4 Dangers and malfunction	19
6.3.5 Measures	19
7 Mains-supplied equipment	19
8 Remote power feeding in cable networks	20
8.1 Remote power feeding	20
8.1.1 Maximum allowed voltages	20
8.1.2 General provisions for equipment	20
8.1.3 Current-carrying capacity and dielectric strength of the components	20
8.2 Remote power feeding from subscriber premises	21
9 Protection against contact and proximity to electric power distribution systems	21
9.1 General	21
9.2 Overhead lines	21
9.2.1 Overhead lines up to 1 000 V	21
9.2.2 Overhead lines above 1 000 V	21
9.3 House installations up to 1 000 V	21
10 System outlets and transfer points	22
10.1 General	22
10.2 System outlet	22
10.2.1 Fully isolated system outlet	22
10.2.2 Semi-isolated system outlet	22
10.2.3 Non-isolated system outlet with protective element	22
10.2.4 Non-isolated system outlet without protective element	23
10.3 Transfer point	23

11	Protection against atmospheric over-voltages and elimination of potential differences	23
11.1	General	23
11.2	Protection of the antenna system	23
11.2.1	Building equipped with a lightning protection system (LPS).....	23
11.2.2	Building not equipped with an LPS	24
11.3	Earthing and bonding of the antenna system.....	24
11.3.1	Earthing and bonding mechanisms	24
11.3.2	Earth termination system	24
11.3.3	Earthing conductors	24
11.4	Over-voltage protection	25
12	Mechanical stability	25
12.1	General requirements	25
12.2	Bending moment	25
12.3	Wind-pressure values	25
12.4	Mast construction	26
12.5	Data to be published.....	26
	Annex A (informative) Use of shield wires to protect installations with coaxial cables	42
	Annex B (informative) Special conditions using IT power line networks.....	45
	Bibliography	50
	Figure 1 – Example of equipotential bonding and earthing of a metal enclosure	27
	Figure 2 – Example of equipotential bonding and indirect earthing of a metal enclosure via a voltage-dependent protective device (in case of balancing currents)	28
	Figure 3 – Example of equipotential bonding and earthing of a building installation (underground connection).....	29
	Figure 4 – Example of equipotential bonding and earthing a building installation (above ground connection)	30
	Figure 5 – Example of equipotential bonding with a galvanic isolated cable entering a building (underground connection).....	31
	Figure 6 – Example of maintaining of equipotential bonding whilst a unit is removed.....	32
	Figure 7 – Example of external safety equipotential bonding	33
	Figure 8 – Example of equipotential bonding antennas and head ends	34
	Figure 9 – Example of antenna-outdoor-mounting on buildings, where earthing is not required but recommended	35
	Figure 10 – Examples of earthing mechanisms.....	36
	Figure 11 – Example of an over-voltage protective device	37
	Figure 12 – Example of application of a coaxial over-voltage protective device	38
	Figure 13 – Example of bending moment of an antenna mast	39
	Figure 14 – Example of the installation of a safety terminal in Japan	40
	Figure 15 – Examples of installation of a lightning protection system in Japan	41
	Figure 16 – Examples of earth electrodes in Finland	41
	Figure A.1 –Principle of Single Shield Wire	43
	Figure A.2 –Principle of Two Shield Wires.....	44

Figure B.1 – IT power distribution systems in Norway.....	46
Figure B.2 – Installation of a cabinet in the vicinity of the transforming station.....	46
Figure B.3 – Example of installations located closer than 20 m to a transforming station.....	47
Figure B.4 – Installations in a building.....	47
Figure B.5 – Installations between buildings.....	48
Figure B.6 – Cabinets for cable network and mains placed less than 2 m apart.....	48
Figure B.7 – Cabinets for cable network and mains placed more than 2 m apart.....	49
Table 1 – Maximum operation voltage and maximum currents for coaxial cables in different cable network applications.....	27
Table A.1 –Conductivity of different types of soil.....	42
Table A.2 – Protections factors (K_p) of protection measures against direct lightning strokes for buried cables.....	43

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –****Part 11: Safety**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-11 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 1997 and its amendment 1 (2000). This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Clause 6, Equipotential bonding and earthing, has been rewritten.
- b) Clause 8, Remote power feeding in cable networks, has been rewritten.
- c) New informative Annex A: Use of shield wires to protect installations with coaxial cables
- d) New informative Annex B: Special conditions using IT power line networks

The text of this standard is based on the following documents:

FDIS	Report on voting
100/847A/FDIS	100/896/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60728 consists of the following parts, under the general title *Cable networks for television signals, sound signals and interactive services*:

- Part 1: Methods of measurement and system performance
- Part 2: Electromagnetic compatibility for equipment
- Part 3: Active coaxial wideband distribution equipment
- Part 4: Passive coaxial wideband distribution equipment
- Part 5: Headend equipment
- Part 6: Optical equipment
- Part 7: Hybrid fibre coax outside plant status monitoring
- Part 9: Interfaces of cabled distribution systems for digitally modulated signals
- Part 10: System performance of return path
- Part 11: Safety (this publication)
- Part 12: Electromagnetic compatibility of systems

The following differences exist in some countries:

Clause 6:

- The following parts of the standard cannot be used in areas with an IT power distribution system:
 - Examples of installations inside buildings described in 6.2g) and shown in Figures 3 and 4 cannot be used in areas with an IT-network (Norway).
 - Examples of installations inside buildings described in 6.2i) and shown in Figure 6 should be equipped with a galvanic isolator separating local earth from the cable network distribution lines (Norway).
 - Examples of installations inside buildings described in 6.2.11 and shown in Figure 7 should be equipped with a galvanic isolator separating local earth from the cable network distribution lines (Norway).
 - Subclauses 6.3.4, 6.3.4.1, 6.3.4.2 and 6.3.5 have no relevance for cable networks in areas with an IT power distribution system (Norway).
- Common earthing is not permitted due to electrical earthing conditions (France).

Subclause 6.2:

- Galvanic isolation should withstand a voltage of 1 kV r.m.s. during 1 min (France).
- The equipotential bonding method is not used in Japan (Japan).
- Earthing to gas networks as shown in Figures 3 and 4 is not admitted (Japan, Poland).

Subclause 8.1:

- Remote power feeding voltage shall not exceed 90 V AC r.m.s and the line-powering current shall not exceed 15 A (Japan).

Clause 9:

- The French regulation (arrêté interministériel, 2 April 1991) specifies, among many other parameters, the minimum distance between electric supply wires (isolated and non-isolated, low-voltage and high-voltage) and any other installation (for example, buildings, antennas, telecommunication lines, etc.). The main clauses of this regulation, which concern the cable networks, are Clauses 12, 25, 26, 33, 33bis, 38, 49, 51, 52 and 63. Clause 9 of this standard specifies distances of 10 mm (indoors) and 20 mm (outdoors), and this is not sufficient to cover overhead cables. As an example, the minimum distance between an overhead telecommunication line and an overhead low-voltage (up to 1 kV) electricity supply line should be 1 m (Clause 33). This distance may be reduced under specific conditions (Clauses 51, 52 and 63). This regulation specifies also the minimum distance from high-voltage lines. This distance varies from 1 m to 4 m depending on the voltage, on the isolation of the cable and on the location (built-up area or not) (Clauses 33 and 63) (France).
- For antennas in proximity of voltages up to 7 000 V, the following applies in Japan:
 1. Low voltage: ≤ 600 V a.c. or ≤ 750 V d.c.;
 Cable: ≥ 30 cm distance;
 Isolated wire: ≥ 60 cm distance.
 2. High voltage: > 600 V a.c. or > 750 V d.c.;
 Cable: ≥ 40 cm distance;
 Isolated wire: ≥ 80 cm distance.

Clause 10:

- The resistance to the equipotential point is not applied, because the bonding method is not used in Japan. Japanese regulations specify applying the safety terminal. The safety terminal withstands a continuous test voltage of 1 000 V for a period of not less than 1 min and maintains an insulation resistance of not less than 1,0 M Ω . Installation of a safety terminal at the junction point between the indoor cabling and the feeder cable of the distribution system is shown in Figure 14 (Japan).

Clause 11:

- A lightning protection system is applied in Japan for protection against atmospheric over-voltages and for the elimination of potential differences. In Japan, installation of a lightning protection system is necessary in the case where the topmost height of the construction exceeds 20 m, except in those cases where the construction is inside the safety zone of another lightning protection system (see Figure 15) (Japan).

Subclause 11.1.1:

- An equipotential bonding conductor is not used, because the bonding method is not used in Japan (Japan).

Subclause 11.2.2:

- An earth termination system is not used in Japan. Only a lightning protection system is applied (see Figure 15) (Japan).
- As the conductivity of earth in Finland is lower than what is normal in many other countries, the earthing electrodes in 11.2.2 should be as shown in Figures 16 a), 16 b) or 16 c) (Finland).

- The earthing conductors have the following requirements (Japan):
 - a) Conductors for a lightning rod: $\geq 30 \text{ mm}^2 \text{ Cu}$.
 - b) For an earthing resistance of $\leq 10 \Omega$, the diameter has to be at least 2,6 mm Cu.
 - c) For an earthing resistance of $\leq 100 \Omega$, indoors, the diameter has to be at least 1,6 mm Cu or the cross-sectional area has to be at least $2 \text{ mm}^2 \text{ Cu}$
 - d) For an earthing resistance of $\leq 100 \Omega$, outdoors, the diameter has to be at least 2,6 mm Cu or the cross-sectional area has to be at least $5,5 \text{ mm}^2 \text{ Cu}$.

Subclause 12.2:

- The bending moment of a mast up to 6 m is not applied in Japan. In Japan, the mast shall not be destroyed by the following wind pressures (Japan):
 1. For an antenna height $h < 16 \text{ m}$, the wind pressure is $60 \sqrt{h}$, in kg per m^2 .
 2. For an antenna height $h \geq 16 \text{ m}$, the wind pressure is $120 \sqrt[4]{h}$, in kg per m^2 .

Subclause 12.3:

- The required wind pressure value is 700 N/m^2 for buildings up to 20 m (Finland).

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for head-end reception, processing and distribution of television signals, sound signals, interactive multimedia signals, interfaces and their associated data signals, using all applicable transmission media.

This includes

- CATV networks;
- MATV networks and SMATV networks;
- individual receiving networks;

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardization work is from the antennas, special signal source inputs to the head-end or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e. tuners, receivers, decoder terminals, etc.) as well as of any coaxial and optical cables and accessories thereof is excluded.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 11: Safety

1 Scope

This part of IEC 60728 deals with the safety requirements applicable to fixed sited systems and equipment. As far as applicable, it is also valid for mobile and temporarily installed systems, for example, caravans.

Additional requirements may be applied, for example, referring to

- electrical installations of buildings and overhead lines;
- other telecommunication services distribution systems;
- water distribution systems;
- gas distribution systems;
- lightning systems.

This standard is intended to provide specifically for the safety of the system, personnel working on it, subscribers and subscriber equipment. It deals only with safety aspects and is not intended to define a standard for the protection of the equipment used in the system.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60065:2001, *Audio, video and similar electronic apparatus – Safety requirements*

IEC 60364 (all parts), *Electrical installations of buildings*

IEC 60529:2001, *Degrees of protection provided by enclosures (IP Code)*

IEC 60825-1:2001, *Safety of laser products – Part 1: Equipment classification, requirements and user's guide*

IEC 60825-2:2000, *Safety of laser products – Part 2: Safety of optical fibre communication systems (OFCS)*

IEC 60950-1:2001, *Information technology equipment – Safety – Part 1: General requirements*

IEC 61024-1:1990, *Protection of structures against lightning – Part 1: General principles*

ISO 3864:2002, *Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs in workplaces and public areas*

EN 50117 (all parts), *Coaxial cables used in cabled distribution networks*