

INTERNATIONAL STANDARD

IEC
60728-3

Third edition
2005-06

Cable networks for television signals, sound signals and interactive services –

Part 3: Active wideband equipment for coaxial cable networks

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

XA

For price, see current catalogue

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	8
3 Terms, definitions, symbols and abbreviations.....	9
3.1 Terms and definitions.....	9
3.2 Symbols.....	13
3.3 Abbreviations.....	14
4 Methods of measurement.....	14
4.1 Linear distortion.....	15
4.2 Non-linear distortion.....	17
4.3 Automatic gain and slope control step response.....	32
4.4 Noise figure.....	34
4.5 Crosstalk attenuation.....	34
4.6 Signal level for digitally modulated signals.....	36
4.7 Method of measurement for non-linearity of return path equipment carrying only digital modulated signals [Measurement of composite intermodulation noise ratio (CINR)].....	36
5 Equipment requirements.....	40
5.1 General requirements.....	40
5.2 Safety.....	40
5.3 Electromagnetic compatibility (EMC).....	40
5.4 Frequency range.....	40
5.5 Impedance and return loss.....	40
5.6 Gain.....	41
5.7 Flatness.....	41
5.8 Test points.....	42
5.9 Group delay.....	42
5.10 Noise figure.....	42
5.11 Non-linear distortion.....	42
5.12 Automatic gain and slope control.....	43
5.13 Hum modulation.....	43
5.14 Power supply.....	44
5.15 Environmental.....	44
5.16 Marking.....	44
5.17 Mean operating time between failure (MTBF).....	45
5.18 Requirements for multi-switches.....	45
Annex A (normative) Test carriers, levels and intermodulation products.....	46
Annex B (normative) Checks on test equipment.....	48
Annex C (informative) Test frequency plan for composite triple beat (CTB), composite second order (CSO) and crossmodulation (XMOD) measurement.....	49
Annex D (informative) Measurement errors which occur due to mismatched equipment.....	50
Annex E (informative) Examples of signals, methods of measurement and network design for return paths.....	52
Bibliography.....	59

Figure 1 – Maximum error a for measurement of return loss using VSWR-bridge with directivity $D = 46$ dB and 26 dB test port return loss.....	16
Figure 2 – Measurement of return loss.....	16
Figure 3 – Basic arrangement of test equipment for evaluation of the ratio of signal to intermodulation product.....	20
Figure 4 – Connection of test equipment for the measurement of non-linear distortion by composite beat.....	23
Figure 5 – Connection of test equipment for the measurement of composite crossmodulation.....	27
Figure 6 – Carrier/hum ratio.....	29
Figure 7 – Test set-up for local-powered objects.....	30
Figure 8 – Test set-up for remote-powered objects.....	30
Figure 9 – Oscilloscope display.....	31
Figure 10 – Time constant T_c	32
Figure 11 – Measurement of AGC step response.....	33
Figure 12 – Measurement of noise figure.....	34
Figure 13 – Measurement of crosstalk attenuation for loop through ports of multi-switches.....	35
Figure 14 – Characteristic of the noise filter.....	38
Figure 15 – Test setup for the non-linearity measurement.....	38
Figure 16 – Presentation of the result of $CINR$	39
Figure A.1 – An example showing products formed when $2f_a > f_b$	46
Figure A.2 – An example showing products formed when $2f_a < f_b$	47
Figure A.3 – Products of the form $f_a \pm f_b \pm f_c$	47
Figure D.1 – Error concerning return loss measurement.....	50
Figure D.2 – Maximum ripple.....	50
Figure E.1 – Spectrum of a QPSK-modulated signal.....	52
Figure E.2a – Loading with digital channels can be simulated with wideband noise.....	54
Figure E.2b – Non-linearity decreases the S/N at high levels.....	54
Figure E.3 – Network used in the design example.....	55
Figure E.4 – A test result measured from a real 20 dB return amplifier.....	56
Figure E.5 – The $CINR$ curve of one amplifier is modified to represent the $CINR$ of the whole coaxial section of the network.....	57
Figure E.6 – The $CINR$ of an optical link as a function of OMI , example.....	58
Table 1 – Correction factors where the modulation used is other than 100 %.....	25
Table 2 – Notch filter frequencies.....	37
Table 3 – Return loss requirements for all equipment.....	41
Table C.1 – Frequency allocation plan.....	49
Table E.1 – Application of methods of measurement in IEC 60728-3 for return path equipment.....	53
Table E.2 – Application of methods of measurement in IEC 60728-6 for return path equipment.....	53

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –****Part 3: Active wideband equipment for coaxial cable networks**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-3 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition published in 2000 of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- New methods of measurement:
 - crosstalk attenuation, 4.5,
 - signal level for digitally modulated signals, 4.6,

- method of measurement for non-linearity of return path equipment carrying only digital modulated signals [Measurement of composite intermodulation noise ratio (CINR)], 4.7;
- New requirements for multi-switches, 5.18;
- New informative Annex E: Examples of signals, methods of measurement and network design for return paths

The text of this standard is based on the following documents:

FDIS	Report on voting
100/946/FDIS	100/976/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60728 consists of the following parts, under the general title *Cable networks for television signals, sound signals and interactive services*:

- Part 1: Methods of measurement and system performance
- Part 2: Electromagnetic compatibility for equipment
- Part 3: Active wideband equipment for coaxial cable networks
- Part 4: Passive coaxial wideband distribution equipment (Under consideration)
- Part 5: Headend equipment
- Part 6: Optical equipment
- Part 7-1: Hybrid fibre coax outside plant status monitoring – Physical (PHY) layer specification
- Part 7-2: Hybrid fibre coax outside plant status monitoring – Media access control (MAC) layer specification
- Part 7-3: Hybrid fibre coax outside plant status monitoring – Power supply to transponder interface bus (PSTIB) specification
- Part 9: Interfaces for CATV, MATV headends and similar professional equipment for DVB/MPEG-2 transport streams
- Part 10: System performance of return path
- Part 11: Safety
- Part 12: Electromagnetic compatibility of systems

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals, interactive multimedia signals, interfaces and their associated data signals, using all applicable transmission media.

This includes:

- CATV networks;
- MATV networks and SMATV networks;
- individual receiving networks,

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardization work is from the antennas, special signal source inputs to the headend or other interface points to the network up to the terminal.

The standardization of any user terminals (i.e. tuners, receivers, decoders, terminals, etc.) as well as of any coaxial and optical cables and accessories thereof is excluded.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 3: Active wideband equipment for coaxial cable networks

1 Scope

This part of IEC 60728 lays down the measuring methods, performance requirements and data publication requirements for active coaxial wideband distribution equipment of cable networks for television and sound signals.

This standard applies to all broadband amplifiers used in cable networks and covers the frequency range 5 MHz to 3 000 MHz. It also applies to one-way and two-way equipment.

NOTE The upper limit of 3 000 MHz is an example, but not a strict value. The frequency range, or ranges, over which the equipment is specified, should be published.

All requirements and published data are understood as guaranteed values within the specified frequency range and in well-matched conditions.

This standard

- applies to all broadband amplifiers used in cable networks;
- covers the frequency range 5 MHz to 3 000 MHz;
- applies to one-way and two-way equipment;
- lays down the basic methods of measurement of the operational characteristics of the active equipment in order to assess the performance of this equipment;
- identifies the performance specifications that shall be published by the manufacturers;
- states the minimum performance requirements of certain parameters.

Amplifiers are divided into the following two quality levels:

Grade 1: amplifiers typically intended to be cascaded.

Grade 2: amplifiers for use typically within an apartment block, or within a single residence, to feed a few outlets.

Practical experience has shown these types meet most of the technical requirements necessary for supplying a minimum signal quality to the subscribers. This classification shall not be considered as a requirement but as the information for users and manufacturers on the minimum quality criteria of the material required to install networks of different sizes. The system operator has to select appropriate material to meet the minimum signal quality at the subscriber's outlet, and to optimise cost/performance, taking into account the size of the network and local circumstances.

All requirements and published data are understood as guaranteed values within the specified frequency range and in well-matched conditions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*
Amendment 1 (1992)

IEC 60068-2-1:1990), *Environmental testing – Part 2: Tests. Tests A: Cold*
Amendment 1 (1993)
Amendment 2 (1994)

IEC 60068-2-2:1974, *Environmental testing – Part 2: Tests. Tests B: Dry heat*
Amendment 1 (1993)
Amendment 2 (1994)

IEC 60068-2-6:1995, *Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14:1984, *Environmental testing – Part 2: Tests. Test N: Change of temperature*
Amendment 1 (1986)

IEC 60068-2-27:1987, *Environmental testing – Part 2: Tests. Test Ea and guidance: Shock*

IEC 60068-2-29:1987, *Environmental testing – Part 2: Tests. Test Eb and guidance: Bump*

IEC 60068-2-30:1980, *Environmental testing – Part 2: Tests. Test Db and guidance: Damp heat, cyclic (12 + 12-hour cycle)*
Amendment 1 (1985)

IEC 60068-2-31:1969, *Environmental testing – Part 2: Tests. Test Ec: Drop and topple, primarily for equipment-type specimens*
Amendment 1 (1982)

IEC 60068-2-32:1975, *Environmental testing – Part 2: Tests. Test Ed: Free fall (Procedure 1)*
Amendment 2 (1990)

IEC 60068-2-40:1976, *Environmental testing – Part 2: Tests. Test Z/AM: Combined cold/low air pressure tests*
Amendment 1 (1983)

IEC 60068-2-48:1987, *Environmental testing – Part 2: Tests. Guidance on the application of the tests of IEC 68 to simulate the effects of storage*

IEC 60169-2-1:1985, *Radio-frequency connectors. Part 2: Coaxial unmatched connector*
Amendment 1 (1982)

IEC 60169-2-24:1991, *Radio frequency connectors – Part 24: Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable distribution systems (Type F)*

IEC 60417-DB:2002¹ *Graphical symbols for use on equipment*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP Code)*
Amendment 1 (1999)

¹ "DB" refers to the IEC on-line database.

IEC 60617-DB, 2001² *Graphical symbols for diagrams – database comprising parts 2 to 13 of IEC 60617*

IEC 60728-1:2001, *Cable networks for television signals, sound signals and interactive services – Part 1: Methods of measurement and system performance*

IEC 60728-2:2002, *Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment*

IEC 60728-4:2000, *Cable networks for television signals, sound signals and interactive services – Part 4: Passive coaxial wideband distribution equipment*

IEC 60728-5:2001, *Cable networks for television signals, sound signals and interactive services – Part 5: Headend equipment*

IEC 60728-6:2003, *Cable networks for television signals, sound signals and interactive services – Part 6: Optical equipment*

IEC 60728-10:2001, *Cable networks for television signals, sound signals and interactive services – Part 10: System performance of return path*

IEC 60728-11:2005, *Cable networks for television signals, sound signals and interactive services – Part 11: Safety*

IEC 61319-1:1995, *Interconnections of satellite receiving equipment – Part 1: Europe*

IEC 61319-2:1997 *Interconnections of satellite receiving equipment – Part 2: Japan*

IEC 80416 (series), *Basic principles for graphical symbols for use on equipment*

ES 200 800 V1.3.12001, *Digital Video Broadcasting (DVB); DVB interaction channel for Cable TV distribution systems (CATV)*

² "DB" refers to the IEC on-line database.