

INTERNATIONAL STANDARD

IEC
60748-4-3

First edition
2006-08

Semiconductor devices – Integrated circuits –

Part 4-3: Interface integrated circuits – Dynamic criteria for analogue-digital converters (ADC)

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Characteristics	7
5 Measuring methods	9
5.1 Dynamic testing with sinusoidal signals.....	9
5.2 Dynamic tests with wideband signals.....	22
5.3 Linearity error of a linear ADC (E_L) ($E_{L(adj)}$) (E_T).....	24
5.4 Differential linearity error (E_D)	30
Annex A (informative) Mathematical derivations.....	32
Annex B (informative) Wideband signal generation and analysis.....	35
Bibliography.....	36
Figure 1 – Test arrangement for measurements on ADCs under dynamic conditions.....	9
Figure 2 – Test arrangement for measurements on ADCs, using wideband signals	22
Figure 3 – Record size versus total noise, for various numbers of records, ramp waveform input	25
Figure 4 – Record size versus total noise, for various numbers of records, sine wave input	28
Table 1 – Confidence level versus range of variable (in standard deviations).....	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SEMICONDUCTOR DEVICES –
INTEGRATED CIRCUITS –****Part 4-3: Interface integrated circuits –
Dynamic criteria for analogue-digital converters (ADC)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60748-4-3 has been prepared by subcommittee 47A: Integrated circuits, of IEC technical committee 47: Semiconductor devices.

The text of this standard is based on the following documents:

FDIS	Report on voting
47A/750/FDIS	47A/758/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60748 series, under the general title *Semiconductor devices – Integrated circuits*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

INTRODUCTION

The use of ADCs has increased significantly in the last few years with the large increase in the use of digital signal processing. The majority of the processing of analogue signals now takes place in the digital domain, and this requires high precision in the conversion of signals from the analogue to the digital form. Consequently, the characterization of ADCs is of great importance.

IEC 60748-4 contains measuring methods for ADCs in which the test conditions are either static or change very slowly. However, some of the characteristics of an ADC can change to some degree with the rate of change of the input signal, and there are other characteristics that cannot be measured except under dynamic conditions. Consequently, a set of dynamic tests is required in order to obtain the response of an ADC when operated under dynamic conditions.

The output of a dynamic test consists of the set of output code values obtained during the test. This record, being the sequence in time of a set of values, gives information in the “time-domain”. The result of applying the Fourier Transform to the record is information that is in the “frequency domain”, and this contains the spectrum of the output over the range of frequencies of interest. In particular, distortion, noise and spurious output frequencies can then be evaluated.

This International Standard introduces a set of dynamic methods, which are now coming into use in industry and which rely mostly on measurements made with sinusoidal input signals, and of which the results are suitable for analysis in the frequency domain. It also includes a further dynamic method that uses a wide-band input signal. For the reasons explained below, industry has shown great interest in this particular method.

Linearity errors of an ADC are dependent on the amplitude of the input signal and its rate of change. Not so well known is that linearity errors also depend on the instantaneous amplitude distribution, i.e. amplitude probability density function (APDF) of the input signal. This source of error is usually a result of localized creating effects in the integrated circuit and is dependent on ADC architecture and internal circuit layout.

Single-frequency signals have an APDF concentrated at the extremes and therefore exaggerate the effect of errors at the ends of the input range compared to those nearer the centre. Conversely, a wide-band signal has an APDF concentrated more around the centre of the input range. A wide-band signal is much closer to the typical input signal in the majority of ADC applications than a single-frequency signal. Therefore, measurements made with such a signal will give more realistic error estimates.

A wide-band signal can be generated from a pseudo-random binary sequence. Although such a signal appears to be noisy, it contains only a set of defined frequencies and is therefore suitable for measuring errors.

SEMICONDUCTOR DEVICES – INTEGRATED CIRCUITS –

Part 4-3: Interface integrated circuits – Dynamic criteria for analogue-digital converters (ADC)

1 Scope

This part of IEC 60748 specifies a set of measuring methods and requirements for testing ADCs under dynamic conditions, together with associated terminology and characteristics.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60748-4:1997, *Semiconductor devices – Integrated circuits – Part 4: Interface integrated circuits*

IEC 60268-10:1991, *Sound system equipment – Part 10: Peak programme level meters*