IEC 60990

Edition 3.0 2016-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Methods of measurement of touch current and protective conductor current

Méthodes de mesure du courant de contact et du courant dans le conducteur de protection

IEC 60990:2016-05(en-fr)

currently in preview, click buy full versi

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org
Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

currently in preview - click buy full version

IEC 60990

Edition 3.0 2016-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Methods of measurement of touch current and protective conductor current

Méthodes de mesure du courant de contact et du courant dans le conducteur de protection

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 17.220, 35.020

ISBN 978-2-8322-3420-4

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

currently in preview, click buy full version

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 10
2 Normative references 10
3 Terms and definitions 11
4 Test site 11
4.1 Test site environment 11
4.2 Test transformer 12
4.3 Earthed neutral conductor 12
5 Measuring equipment 13
5.1 Selection of measuring network 13
5.1.1 General 13
5.1.2 Perception and startle-reaction 14
5.1.3 Letgo-immobilization 14
5.1.4 Electric burn (a.c.) 14
5.1.5 Ripple-free d.c. 14
5.2 Test electrodes 15
5.2.1 Construction 15
5.2.2 Connection 15
5.3 Configuration 15
5.4 Power connections during test 15
5.4.1 General 15
5.4.2 Equipment for use only on TN or TT star power distribution systems 19
5.4.3 Equipment for use on IT power distribution systems including unearthed delta systems 19
5.4.4 Equipment for use on single-phase centre-earthed power supply systems or on centre-earthed delta power supply systems 20
5.5 Supply voltage and frequency 20
5.5.1 Supply voltage 20
5.5.2 Supply frequency 20
6 Test procedure 20
6.1 General 20
6.1.1 Touch current measurements 20
6.1.2 Control switches, equipment and supply conditions 21
6.1.3 Use of measuring networks 21
6.2 Normal and fault conditions of equipment 21
6.2.1 Normal operation of equipment 21
6.2.2 Equipment and supply fault conditions 21
7 Evaluation of results 23
7.1 Perception, startle-reaction and letgo-immobilization 23
7.2 Electric burn 23
8 Measurement of protective conductor current 23
8.1 General 23
8.2 Multiple equipment 24
8.3 Measuring method 24

currently in preview, click buy full version

Annex A (normative) Equipment 25
Annex B (normative) Use of a conductive plane 26
Annex C (normative) Incidentally connected parts 27
Annex D (informative) Choice of current limits 28
D.1 General 28
D.2 Limit examples 28
D.2.1 Ventricular fibrillation 28
D.2.2 Inability to letgo-immobilization 28
D.2.3 Startle-reaction 28
D.2.4 Perception threshold 28
D.2.5 Special applications 29
D.3 Choice of limits 29
D.4 Electric burn effects of touch current 30
Annex E (informative) Networks for use in measurement of touch current 31
E.1 General 31
E.2 Body impedance network – Figure 3 31
E.3 Startle-reaction (and body impedance) network – Figure 4 31
E.4 Letgo-immobilization (and body impedance) network – Figure 5 32
Annex F (informative) Measuring network limitations and construction 33
Annex G (informative) Construction and application of touch current measuring instruments 35
G.1 Considerations for selection of components 35
G.1.1 General 35
G.1.2 Power rating and inductance for R_S and R_B 35
G.1.3 Capacitor C_S 35
G.1.4 Resistors R1, R2 and R3 36
G.1.5 Capacitors C1, C2 and C3 36
G.2 Voltmeter 36
G.3 Accuracy 36
G.4 Calibration and application of measuring instruments 37
G.5 Records 37
G.6 Confirmation systems 37
Annex H (informative) Analysis of frequency filtered touch current circuit measurements 39
Annex I (informative) AC power distribution systems (see 5.4) 47
I.1 General 47
I.2 TN power systems 48
I.3 TT power systems 50
I.4 IT power systems 51
Annex J (informative) Routine and periodic touch current tests, and tests after repair or modification of mains operated equipment 53
Annex K (normative) Network performance and calibration 54
K.1 Network or instrument performance and initial calibration 54
K.2 Calibration in a confirmation system 56
K.2.1 General 56
K.2.2 Measurement of input resistance 56
K.2.3 Measurement of instrument performance 56
Bibliography 59

currently in preview, click buy full version

Figure 1 – Example of earthed neutral, direct supply 12
Figure 2 – Example of earthed neutral, with transformer for isolation 13
Figure 3 – Measuring network, unweighted touch current 13
Figure 4 – Measuring network, touch current weighted for perception or startle-reaction 14
Figure 5 – Measuring network, touch current weighted for letgo-immobilization 14
Figure 6 – Single-phase equipment on star TN or TT system 16
Figure 7 – Single-phase equipment on centre-earthed TN or TT system 16
Figure 8 – Single-phase equipment connected line-to-line on star TN or TT system 17
Figure 9 – Single-phase equipment connected line-to-neutral on star IT system 17
Figure 10 – Single-phase equipment connected line-to-line on star IT system 17
Figure 11 – Three-phase equipment on star TN or TT system 18
Figure 12 – Three-phase equipment on star IT system 18
Figure 13 – Unearthed delta system 19
Figure 14 – Three-phase equipment on centre-earthed delta system 19
Figure A.1 – Equipment 25
Figure B.1 – Equipment platform 26
Figure F.1 – Frequency factor for electric burn 33
Figure F.2 – Frequency factor for perception or startle-reaction 33
Figure F.3 – Frequency factor for letgo-immobilization 34
Figure H.1 – Triangular waveform touch current, startle-reaction 40
Figure H.3 – 1 ms rise time pulse response, startle-reaction 41
Figure H.4 – 1 ms rise time pulse response, letgo-immobilization 41
Figure H.5 – Touch current vs. rise time pulse, 20 ms square wave 42
Figure H.6 – PFC SMPS touch current waveform 42
Figure H.7 – 50 Hz square wave, 0,1 ms rise time, startle-reaction 43
Figure H.8 – 50 Hz square wave, 0,1 ms rise time, letgo-immobilization 43
Figure H.9 – IEC TS 60479-2 let-go threshold for AC and DC combinations augmented by additional data, mA each axis 44
Figure H.10 – Ex1 case: showing r.m.s. window 45
Figure H.11 – Waveform ex2 case: showing r.m.s. window 45
Figure I.1 – Examples of TN-S power system 48
Figure I.2 – Example of TN-C-S power system 49
Figure I.3 – Example of TN-C power system 49
Figure I.4 – Example of single-phase, 3-wire TN-C power system 50
Figure I.5 – Example of 3-line and neutral TT power system 50
Figure I.6 – Example of 3-line TT power system 51
Figure I.7 – Example of 3-line (and neutral) IT power system 51
Figure I.8 – Example of 3-line IT power system 52

Table H.1 – Triangular waveform response comparison 40
Table H.2 – Square wave touch current response 41

currently in preview, click buy full version

Table H.3 – Square wave monopolar touch current response 43
Table H.4 – Mixed ACnDC waveform evaluation, ex1 45
Table H.5 – Mixed ACnDC waveform evaluation, ex2 46
Table K.1 – Calculated input impedance and transfer impedance for unweighted touch current measuring network (Figure 3).....54
Table K.2 – Calculated input impedance and transfer impedance for startle-reaction touch current measuring network (Figure 4) 55
Table K.3 – Calculated input impedance and transfer impedance for letgo-immobilization current measuring network (Figure 5).....55
Table K.4 – Output voltage to input voltage ratios for unweighted touch current measuring network (Figure 3) 57
Table K.5 – Output voltage to input voltage ratios for startle-reaction measuring network (Figure 4) 57
Table K.6 – Output voltage to input voltage ratios for letgo-immobilization measuring network (Figure 5) 58

urrently in preview, click buy full versi

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

METHODS OF MEASUREMENT OF TOUCH CURRENT AND PROTECTIVE CONDUCTOR CURRENT

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60990 has been prepared by TC 108: Safety of electronic equipment within the field of audio/video, information technology and communication technology.

This third edition cancels and replaces the second edition published in 1999. It constitutes a technical revision.

The principal changes in this edition as compared with the second edition are as follows:

- the effects names have been updated to reflect increased understanding of the range of effects and is in concert with present usage;
– the conditions of use invoking a GRIPPABLE PART have been reduced in the application of the requirements based upon the current understanding of this effect;
– the references to ISO 10012-1, which has been replaced by management standard of the same number, have been replaced with explanatory text, where needed to maintain the sense of the document;

currently in preview, click buy for full version

– former informative Annex H (GRIPPABLE PART) has been deleted from this update as it does not properly represent the full set of conditions under which immobilization can occur. A new informative Annex H (Analysis of frequency filtered touch current circuits measurement) has been added;

– the Bibliography (formerly Annex M) has been updated with additional references for completeness.

The text of this standard is based on the following documents:

FDIS	Report on voting
108/630/FDIS	108/640/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types or formats are used:

– requirements proper and normative annexes: in roman type;

– compliance statements and test specifications: *in italic type*;

– notes/explanatory matter: in smaller roman type;

– normative conditions within tables: in smaller roman type;

– terms defined in Clause 3: SMALL CAPITALS.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

reconfirmed,

withdrawn,

replaced by a revised edition, or

amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

currently in preview, click buy full version

INTRODUCTION

This International Standard was developed as a response to concerns arising from the advent of electronic switching techniques being broadly applied to power systems and within EQUIPMENT, giving rise to high-frequency harmonic voltages and currents.

This standard is intended for the guidance of EQUIPMENT committees in preparing or amending the test specifications in their standards for measurement of leakage current. However the term "leakage current" is not used for reasons explained below.

This standard was initially prepared under the basic safety function assigned to TC 74 (now TC 108), as follows:

Methods of measuring leakage current

This includes, for various types of EQUIPMENT, all aspects of what is referred to as "leakage current", including methods of measurement of current with regard to physiological effects and for installation purposes, under normal conditions and under certain fault conditions.

The methods of measurement of leakage current described herein result from the review of IEC TS 60479-1 and other publications, including descriptions of earlier methods of measurement.

The following conclusions were derived from a review of the effects of leakage current:

– the primary concern for safety involves possible flow of harmful current through the human body (this current is not necessarily equal to the current flowing through a protective conductor);
– the effect of electric current on a human body is found to be somewhat more complex than was assumed during the development of earlier standards in that there are several body responses which should be considered. The most significant responses for setting limits for continuous waveforms are
  - perception,
  - startle-reaction,
  - letgo-immobilization, and
  - ELECTRIC BURN.

Each of these four body responses has a unique threshold level. There are also significant differences in the manner in which some of these thresholds vary with frequency.

Two types of current have been identified as needing separate measuring methods: TOUCH CURRENT and PROTECTIVE CONDUCTOR CURRENT.

TOUCH CURRENT only exists when a human body or a body model is a current pathway.

It was also noted that the term "leakage current" has already been applied to several different concerns: TOUCH CURRENT, PROTECTIVE CONDUCTOR CURRENT, insulation properties, etc. Therefore, in this standard, the term "leakage current" is not used.

Measurement of TOUCH CURRENT

In the past, EQUIPMENT standards have used two traditional techniques for measurement of leakage current. Either the actual current in the protective conductor was measured, or a simple resistor-capacitor network (representing a simple body model) was used, the leakage current being defined as the current through the resistor.

currently in preview, click buy full version

This standard provides measuring methods for the four body responses to the electric current noted above, using a more representative body model.

This body model was chosen for most common cases of electric shock in the general sense. With respect to the path of current flow and conditions of contact, a body model approximating full hand-to-hand or hand-to-foot contact in normal conditions is used. For small areas of contact (for example, small, finger contact), a different model may be appropriate but is not covered here.

Of the four responses, startle-reaction and letgo-immobilization are related to the peak value of TOUCH CURRENT and vary with frequency. Traditionally, concerns for electric shock have dealt with sinusoidal waveforms, for which r.m.s. measurements are most convenient. Peak measurements are more appropriate for non-sinusoidal waveforms where significant values of TOUCH CURRENT are expected, but are equally suitable for sinusoidal waveforms. The networks specified for the measurement of startle-reaction and letgo-immobilization are frequency-responsive and are so weighted that single limit power-frequency values can be specified and referenced.

ELECTRIC BURNS, however, are related to the r.m.s. value of TOUCH CURRENT, and are relatively independent of frequency. For EQUIPMENT where ELECTRIC BURNS may be of concern (see 7.2), two separate measurements are made, one in peak value for electric shock and a second in r.m.s. value for ELECTRIC BURNS each using the appropriate test circuit.

EQUIPMENT committees should decide which physiological effects are acceptable and which are not, and then decide on limit values of current. Committees for certain types of EQUIPMENT may adopt simplified procedures based upon this standard. A discussion of limit values, based upon earlier work by various IEC EQUIPMENT committees, is provided in Annex D.

Measurement of PROTECTIVE CONDUCTOR CURRENT

In certain cases, measurement of the PROTECTIVE CONDUCTOR CURRENT of EQUIPMENT under normal operating conditions is required. Such cases include:

– selection of a residual current protection device,
– determination when a high integrity protective earth circuit is required,
– prevent excessive PROTECTIVE CONDUCTOR CURRENT overload in the electrical installation.

The PROTECTIVE CONDUCTOR CURRENT is measured by inserting an ammeter of negligible impedance in series with the EQUIPMENT protective earthing conductor.

METHODS OF MEASUREMENT OF TOUCH CURRENT AND PROTECTIVE CONDUCTOR CURRENT

1 Scope

This International Standard defines measurement methods for

– d.c. or a.c. current of sinusoidal or non-sinusoidal waveform, which could flow through the human body, and

– current flowing through a protective conductor.

The measuring methods recommended for TOUCH CURRENT are based upon the possible effects of current flowing through a human body. In this standard, measurements of current through networks representing the impedance of the human body are referred to as measurements of TOUCH CURRENT. These networks are not necessarily valid for the bodies of animals.

The specification or implication of specific limit values is not within the scope of this standard. IEC TS 60479 series provides information regarding the effects of current passing through the human body from which limit values may be derived.

This standard is applicable to all classes of EQUIPMENT, according to IEC 61140.

The methods of measurement in this standard are not intended to be used for

– TOUCH CURRENTS having less than 1 s duration,

– patient currents as defined in IEC 60601-1,

– a.c. at frequencies below 15 Hz, and

– currents above those chosen for ELECTRIC BURN limits.

This basic safety publication is primarily intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51. It is not intended for use by manufacturers or certification bodies independent of product standards.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications. The requirements, test methods or test conditions of this basic safety publication only apply when specifically referred to or included in the relevant publications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 60479-1:2005, *Effects of current on human beings and livestock – Part 1: General aspects*

IEC TS 60479-2:2007, *Effects of current on human beings and livestock – Part 2: Special aspects*