

INTERNATIONAL STANDARD

IEC
61000-2-13

First edition
2005-03

BASIC EMC PUBLICATION

Electromagnetic compatibility (EMC) –

Part 2-13:

Environment –

High-power electromagnetic (HPEM)

environments –

Radiated and conducted

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope	7
2 Normative references	8
3 Terms and definitions	8
4 General	11
5 Description of radiated environments	13
6 Description of conducted HPEM environments	23
Annex A (informative) Four types of intentional electromagnetic environment interactions	27
Annex B (informative) Examples of low, medium and high-tech generators of HPEM	28
Annex C (informative) Examples of typical HPEM waveforms (conducted and radiated).....	31
Annex D (informative) Determination of the bandwidth of typical HPEM waveforms	35
Bibliography	39
Figure 1 – Several types of HPEM environments compared with the IEC HEMP waveform.....	12
Figure 2 – A damped sinusoidal waveform for hyperband and mesoband HPEM environments.....	18
Figure 3 – The spectral magnitude of the time waveform in Figure 2	19
Figure 4 – Hyperband HPEM environment waveforms for variations in range in metres	21
Figure 5 – Hyperband spectral magnitude of HPEM environments from Figure 4	21
Figure 6 – Effective coupling length for a 1 m metallic cable	22
Figure 7 – Building used for HPEM conducted propagation experiments	24
Figure 8 – Examples of briefcase generators for producing conducted environments: CW generator (left) and impulse generator (right) [15]	26
Figure B.1 – Line schematic of a reflector type of an impulse radiating antenna (IRA)	30
Figure C.1 – Half-sinusoid at $f_0 = 1$ GHz	31
Figure C.2 – Full sinusoid at $f = 1$ GHz	32
Figure C.3 – 20 cycles of sinusoid at $f = 1$ GHz ($N = 20$)	32
Figure C.4 – Difference of exponential waveform	33
Figure C.5 – Gaussian waveform	33
Figure C.6 – Sinusoidal waveform with a Gaussian-amplitude modulation	34
Figure D.1 – A waveform spectrum with a large dc content (e.g. the early-time HEMP from IEC 61000–2-9)	36
Figure D.2 – A waveform with a multi peaked spectral magnitude in units of 1/Hz.....	36
Figure D.3 – Spectral magnitude of a damped sinusoidal waveform with a low Q and a bandratio value computed using the 3 dB frequency points	37
Figure D.4 – Spectral magnitude of a damped sinusoidal waveform with a high Q and a bandratio value computed using the 3 dB frequency points	38

Table 1 – Definitions for bandwidth classification	14
Table 2 – Range of radiated electric field at various frequencies and power levels	15
Table 3 – Typical HPEM standard environments in the hypoband (or narrowband) and mesoband regimes	20
Table B.1 – Radiated fields from a microwave oven magnetron fitted with different antennas	28
Table B.2 – Radiated peak electric fields from a commercial HPEM generator.....	29
Table B.3 – Examples of reflector types of impulse radiating antennas.....	30

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMAGNETIC COMPATIBILITY (EMC) –**Part 2-13: Environment –
High-power electromagnetic (HPEM) environments –
Radiated and conducted**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61000-2-13 has been prepared by subcommittee 77C: High power transient phenomena, of IEC technical committee 77: Electromagnetic compatibility.

It has the status of a basic EMC publication in accordance with IEC Guide 107.

The text of this standard is based on the following documents:

FDIS	Report on voting
77C/153/FDIS	77C/155/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

Part 1: General

General considerations (introduction, fundamental principles)

Definitions, terminology

Part 2: Environment

Description of the environment

Classification of the environment

Compatibility levels

Part 3: Limits

Emission limits

Immunity limits (in so far as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

Measurement techniques

Testing techniques

Part 5: Installation and mitigation guidelines

Installation guidelines

Mitigation methods and devices

Part 6: Generic standards

Part 9: Miscellaneous

Each part is further subdivided into several parts, published either as International Standards or as technical specifications or technical reports, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision (example: 61000-6-1).

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 2-13: Environment – High-power electromagnetic (HPEM) environments – Radiated and conducted

1 Scope

This part of IEC 61000 defines a set of typical radiated and conducted HPEM environment waveforms that may be encountered in civil facilities. Such threat environments can produce damaging effects on electrical and electronic equipment in the civilian sector, as described in IEC 61000-1-5. It is necessary to define the radiated and conducted environments, in order to develop protection methods.

For the purposes of this standard, high-power conditions are achieved when the peak electric field exceeds 100 V/m, corresponding to a plane-wave free-space power density of 26,5 W/m². This criterion is intended to define the application of this standard to EM radiated and conducted environments that are substantially higher than those considered for "normal" EMC applications, which are covered by the standards produced by IEC 3C 77B.

The HPEM environment can be:

- radiated or conducted;
- a single pulse envelope with many cycles of a single frequency (an intense narrowband signal that may have some frequency agility and the pulse envelope may be modulated);
- a burst containing many pulses, with each pulse envelope containing many cycles of a single frequency;
- an ultrawideband transient pulse (spectral content from tens of MHz to several GHz);
- a burst of many ultrawideband transient pulses.

The HPEM signal could be from sources such as radar or other transmitters in the vicinity of an installation or from an intentional generator system targeting a civilian facility. Radiated signals can also induce conducted voltages and currents through the coupling process. In addition, conducted HPEM environments may also be directly injected into the wiring of an installation.

There is a critical distinction between the HEMP (high-altitude electromagnetic pulse) environment and the HPEM environment, in terms of the range or the distance of the affected electrical or electronic components from the source. In the context of HEMP, the range is immaterial, as the HEMP environment propagates downward from space to the earth's surface and is therefore relatively uniform over distances of 1 000 km. On the other hand, in the HPEM context the environment and its effects decrease strongly with range. In addition, the HEMP waveshape is a series of time domain pulses while the HPEM environment may have a wide variety of waveshapes.

Consequently, the standardization process for HPEM environments is more difficult. The recommended approach is to investigate the various types of HPEM environments that have been produced to date and are likely to be feasible in the near future, and then to develop suitable HPEM standard waveforms from such a study. Such HPEM environment standard waveforms can be amended in due course, depending on emerging technologies that make it possible to produce them.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

IEC 61000-1-5, *Electromagnetic compatibility (EMC) – Part 1-5: General – High power electromagnetic (HPEM) effects on civil systems*

IEC 61000-2-9, *Electromagnetic compatibility (EMC) – Part 2: Environment – Section 9: Description of HEMP environment – Radiated disturbance*

IEC 61000-2-10, *Electromagnetic compatibility (EMC) – Part 2-10: Environment – Description of HEMP environment – Conducted disturbance*

IEC 61000-2-11, *Electromagnetic compatibility (EMC) – Part 2-11: Environment – Classification of HEMP environments*

IEC 61000-4-3, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-4-4, *Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Section 4: Electrical fast transient/burst immunity test.*

IEC 61000-4-5, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 5: Surge immunity test*

IEC 61000-4-6, *Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields*

IEC 61000-4-12, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 12: Oscillatory waves immunity test*