

INTERNATIONAL STANDARD

**Global maritime distress and safety system (GMDSS) -
Part 2: Cospas-Sarsat EPIRB – Emergency position indicating radio beacon
operating on 406 MHz – Operational and performance requirements, methods of
testing and required test results**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

INTERNATIONAL STANDARD

**Global maritime distress and safety system (GMDSS) -
Part 2: Cospas-Sarsat EPIRB – Emergency position indicating radio beacon
operating on 406 MHz – Operational and performance requirements, methods of
testing and required test results**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8322-9925-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	11
3.1 Terms and definitions.....	11
3.2 Abbreviated terms.....	11
4 Performance requirements.....	11
4.1 Compliance.....	11
4.2 General.....	11
4.3 Operational.....	14
4.3.1 Prevention of inadvertent activation.....	14
4.3.2 Immersion, buoyancy and drop into water.....	14
4.3.3 Activation.....	14
4.3.4 Self-test.....	14
4.3.5 Colour and retro-reflecting material.....	16
4.3.6 Lanyard.....	16
4.3.7 Exposure to the marine environment.....	17
4.3.8 Ergonomics.....	17
4.3.9 Indication of insufficient battery energy.....	18
4.4 Control and indicator functions.....	18
4.4.1 Control functions.....	18
4.4.2 Indicator functions.....	18
4.5 Float-free arrangements.....	19
4.5.1 General.....	19
4.5.2 External power or data connection.....	19
4.5.3 Ability to check the automatic release.....	19
4.5.4 Manual release.....	20
4.6 Environment for EPIRB.....	20
4.6.1 General.....	20
4.6.2 Temperature and icing.....	20
4.6.3 Wind speed.....	20
4.6.4 Stowage.....	20
4.6.5 Shock, vibration and other environmental conditions.....	20
4.7 Environment for float-free arrangement.....	20
4.8 Interference – Electromagnetic compatibility.....	21
4.9 Maintenance.....	21
4.10 Safety precautions.....	21
4.11 Equipment manuals.....	22
4.12 Labelling.....	23
4.12.1 Equipment labelling.....	23
4.12.2 Float-free arrangement labelling.....	24
4.12.3 Battery labelling.....	24
4.13 Installation.....	24
5 Technical characteristics.....	24
5.1 Transmitted frequency.....	24
5.2 Signal and message format.....	24
5.3 Distress message memory.....	25

5.4	Beacon identification code	25
5.5	121,5 MHz homing signal	25
5.6	AIS locating signal	26
5.7	GNSS receiver and position reporting	27
5.8	RLS	27
5.8.1	RLS capability	27
5.8.2	RLS self-test	27
5.9	Power source	28
5.9.1	General	28
5.9.2	Battery life and expiry date	28
5.9.3	Expiry date indication	28
5.9.4	Reverse polarity protection	28
5.10	Antenna characteristics	29
6	Methods of testing and required test results	29
6.1	General	29
6.1.1	Purpose	29
6.1.2	Type approval of EPIRBs operating in the Cospas-Sarsat system	29
6.1.3	Power supply	30
6.1.4	Warm-up period	30
6.1.5	Instructions	30
6.1.6	Additional facilities	30
6.1.7	Audible and visual indications	30
6.1.8	Preparation of EPIRB for type-approval testing	30
6.1.9	Test conditions	30
6.1.10	Test sequence	31
6.1.11	Performance check	31
6.1.12	Performance test	31
6.2	General tests	32
6.2.1	EPIRB	32
6.2.2	Float-free arrangements	32
6.3	Operational tests	33
6.3.1	Prevention of inadvertent activation	33
6.3.2	Immersion, buoyancy and drop into water	33
6.3.3	Activation	34
6.3.4	Self-test	36
6.3.5	Exterior, colour and retro-reflecting material	37
6.3.6	Lanyard	37
6.3.7	Exposure to marine environment	37
6.3.8	Ergonomics	38
6.3.9	Indication of insufficient battery energy	38
6.4	Control and indicator functions	38
6.5	Float-free arrangements	39
6.5.1	Release	39
6.5.2	Test to prevent release when sea water washes over the unit	39
6.5.3	Construction materials	39
6.5.4	External power or data connection	39
6.5.5	Ability to check the automatic release	39
6.5.6	Manual release	39
6.6	Environment	39

6.6.1	Temperature	40
6.6.2	Icing	40
6.6.3	Wind speed	40
6.6.4	Stowage	40
6.6.5	Shock, vibration and other environmental conditions.....	40
6.7	Environment for float-free arrangement.....	40
6.8	Interference – Electromagnetic compatibility	40
6.9	Maintenance	40
6.10	Safety precautions	40
6.11	Equipment manuals	40
6.12	Labelling	41
6.12.1	Equipment labelling	41
6.12.2	Float-free arrangement labelling	41
6.12.3	Battery labelling.....	41
6.13	Installation	41
6.14	Technical characteristics.....	41
6.14.1	406 MHz signal characteristics	41
6.14.2	121,5 MHz homing signal.....	41
6.14.3	AIS locating signal	41
6.14.4	GNSS receiver and position reporting	41
6.14.5	RLS	42
6.15	Power source.....	42
6.15.1	Battery capacity test	42
6.15.2	Expiry date indication	43
6.15.3	Reverse polarity protection	43
6.15.4	User-replaceable battery	43
6.16	Antenna characteristics.....	43
6.17	Environment	43
6.17.1	General	43
6.17.2	Dry heat cycle, of IEC 60945	43
6.17.3	Damp heat cycle, of IEC 60945.....	44
6.17.4	Low-temperature cycle, of IEC 60945	44
6.17.5	Thermal shock tests.....	44
6.17.6	Drops test for portable equipment, of IEC 60945	44
6.17.7	Vibration test, of IEC 60945.....	45
6.17.8	Rockedness test.....	45
6.17.9	Immersion test, of IEC 60945.....	45
6.17.10	Solar radiation test, of IEC 60945	46
6.17.11	Oil resistance test, of IEC 60945	46
6.17.12	Corrosion test, of IEC 60945.....	46
6.18	Interference testing	46
6.19	Spurious emissions.....	46
6.20	Compass safe distance	47
6.21	Conducted interference.....	47
Annex A (normative)	Sequence of tests	48
A.1	Compulsory sequence of tests	48
A.2	Additional tests	49
Annex B (normative)	Internal and external navigation devices GNSS receivers.....	50
B.1	General.....	50

B.2	External navigation devices	50
B.3	Internal navigation receivers	51
B.4	Internal navigation device tests	52
B.4.1	General	52
B.4.2	Test description	52
B.4.3	Test facility requirements, test set-up and calibration	54
B.4.4	Method of measurement	59
B.4.5	Required results	59
B.4.6	Test results	60
Annex C	(normative) Standards for an EPIRB without a float-free mechanism	63
C.1	Requirements	63
C.2	Tests	64
Annex D	(normative) Technical standards for 121,5 MHz homing device	65
D.1	General	65
D.2	Performance requirements	65
D.3	Technical characteristics	65
D.4	Methods of testing and required test results	66
D.4.1	General	66
D.4.2	Carrier frequency	66
D.4.3	Peak effective radiated power	66
D.4.4	Off-ground plane radiated power test	67
D.4.5	Transmitter duty cycle	68
D.4.6	Modulation characteristics	68
Annex E	(normative) AIS locating signal specification	72
E.1	General	72
E.2	Performance characteristics	72
E.2.1	Requirement	72
E.2.2	Interoperability	72
E.2.3	Operational function	72
E.2.4	Unique identifier (User ID)	73
E.2.5	AIS and other EPIRB transmissions	73
E.2.6	Output power	73
E.2.7	Transmission performance	73
E.2.8	Position source and data	76
E.3	Technical characteristics	76
E.3.1	Transmitter requirements and characteristics	76
E.3.2	Link layer requirements	76
E.4	Performance tests	77
E.4.1	General	77
E.4.2	Performance requirements	77
E.4.3	Preparation of the EPIRB for testing	77
E.4.4	Test signals	78
E.4.5	Modes of operation of the transmitter	78
E.5	Physical radio tests	78
E.5.1	General	78
E.5.2	On-ground plane radiated power	78
E.5.3	Off-ground plane radiated power	79
E.6	Link layer tests	79
E.7	GNSS self-test mode tests	80

E.7.1	General	80
E.7.2	Transmission with GNSS data available.....	80
E.7.3	Transmission without GNSS data available.....	80
Annex F (informative)	Symbols	81
Annex G (informative)	IEC 61162-1 RLM sentence notes.....	84
Bibliography	86
Figure 1	– Hand sizes	17
Figure 2	– AIS and 121,5 MHz signal interleaving.....	26
Figure B.1	– Test set-up	56
Figure B.2	– Calibration set-up	57
Figure D.1	– Spurious emission mask for 121,5 MHz signal	70
Figure D.2	– Typical modulation waveforms	71
Table 1	– EPIRB control functions	12
Table 2	– Effective luminous intensity	35
Table 3	– Radiant intensity	36
Table B.1	– Maritime scenarios.....	54
Table B.2	– G_{POL} values	58
Table B.3	– Maritime scenarios test results.....	61
Table B.4	– Maritime scenarios results analysis.....	61
Table B.5	– Pass/Fail analysis	62

Currently in preview, click buy full version.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –**Part 2: Cospas-Sarsat EPIRB – Emergency position
indicating radio beacon operating on 406 MHz –
Operational and performance requirements,
methods of testing and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, issue IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61097-2 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2008. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) revision of the Scope to incorporate new IMO performance standards published in 2019;
- b) addition of requirements and tests for second generation beacons designed for operation with the Cospas-Sarsat medium earth orbit (MEO) satellite constellation;
- c) addition of an AIS locating device, a night vision light and an optional return link service (RLS);

- d) reduction of the minimum duty cycle of the 121,5 MHz homing signal;
- e) addition of requirements for an internal GNSS receiver including a related range of additional GNSS tests in Annex B;
- f) inclusion of a new Clause 3 for terms, definitions and abbreviated terms;
- g) addition of a new Annex E for the AIS locating signal specification, a new Annex F for symbols and a new Annex G for IEC 61162-1 RLM sentence notes;
- h) deletion of the original Annex E which is now of historic interest.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
80/999/FDIS	80/1002/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61097 series, published under the general title *Global maritime distress and safety system (GMDSS)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition or
- amended.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 2: Cospas-Sarsat EPIRB – Emergency position indicating radio beacon operating on 406 MHz – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and type-testing requirements of the emergency position-indicating radio beacon used in the Cospas-Sarsat satellite system (EPIRB), as required by the International Convention for Safety of Life at Sea (SOLAS) as amended, and which is associated with IEC 60945. When a requirement in this document is different from the requirements in IEC 60945 or other standards, the requirement in this document takes precedence.

This document incorporates the performance standards of IMO Resolution MSC.471(101), the International Telecommunication Union (ITU) Radio Regulations as well as the technical characteristics for such transmitters contained in Recommendation ITU-R M.633, and takes account of the general requirements contained in IMO Resolution A.694(17).

This document also includes minimum performance standards for a non-float-free EPIRB without float-free release mechanism (see Annex C).

NOTE 1 Although a number of the requirements and tests can be similar, this document is not intended to be used with 406 MHz ship security alert system (SSAS) beacons.

All texts of this document, whose wording is identical to that in the IMO Resolutions A.662(16), A.694(17), and MSC.471(101) will be printed in *italics* and the Resolution/Recommendation and paragraph number indicated between brackets.

NOTE 2 Classes of EPIRBs considered in this document are:

- Class 0: Category 1 Float-free (–55 °C to +70 °C). The float-free release mechanism (A.662(16)) is capable of operating throughout the temperature range of –30 °C to +65 °C and of surviving a stowage temperature range of –55 °C to +70 °C.
- Class 1: Category 1 Float-free (–40 °C to +55 °C). The float-free release mechanism (A.662(16)) is capable of operating throughout the temperature range of –30 °C to +65 °C and of surviving a stowage temperature range of –40 °C to +65 °C.

These classes are not required by IMO Resolutions but can be applied at the discretion of each Administration.

- Class 2: Category 1 Float-free (–20 °C to +55 °C). The float-free release mechanism (A.662(16)) is capable of being stowed and of operating throughout the temperature range of –30 °C to +65 °C.

NOTE 3 Category 2 Non float-free, EPIRBs in all classes are considered in Annex C.

NOTE 4 All classes include a 121,5 MHz homing device, described in Annex D.

NOTE 5 All classes include an AIS locating signal, described in Annex E.

NOTE 6 All classes include beacon position data, obtained from a navigation device internal to the EPIRB and can also provide an external navigation input as described in Annex B.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.