

INTERNATIONAL STANDARD

**Global maritime distress and safety system (GMDSS) –
Part 7: Shipborne VHF radiotelephone transmitter and receiver – Operational and
performance requirements, test methods and required test results**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will also have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references.....	10
3 Terms, definitions and abbreviated terms	11
3.1 Terms and definitions	11
3.2 Abbreviated terms	14
4 Performance requirements	14
4.1 General.....	15
4.2 Power supply	15
4.3 Controls and indicators.....	15
4.3.1 General	15
4.3.2 DSC controls and indicators	16
4.3.3 Distress controls	16
4.3.4 Received signal strength indicator	17
4.3.5 Markings and identifications	17
4.4 Interfaces and human-machine interface.....	17
4.5 Bridge alert management	19
4.6 Manuals.....	19
4.7 Software maintenance.....	19
5 Transmitter.....	20
5.1 Frequencies and classes of emission.....	20
5.1.1 General	20
5.1.2 Frequency deviation.....	20
5.1.3 Audiofrequency band	20
5.2 Frequency accuracy and tolerance	20
5.3 Output power	20
5.4 Permissible warming-up period.....	21
5.5 Continuous operation	21
5.6 Controls and indicators.....	21
5.6.1 Channel control and switching.....	21
5.6.2 Radiotelephone facility	22
5.6.3 Loudspeaker and telephone handset (radiotelephone facility).....	22
5.7 Safety precautions	22
5.8 Antenna system	23
6 Receiver.....	23
6.1 Frequencies and classes of emission.....	23
6.2 Frequency tolerance and accuracy	23
6.3 Usable sensitivity	23
6.3.1 Radiotelephone facility	23
6.3.2 Digital selective calling facility	23
6.4 Receiver output.....	23
6.5 Permissible warming-up period.....	23
6.6 Immunity to interference	24
6.7 Controls	24
6.8 Multiple watch facilities	24
6.8.1 General	24

6.8.2	Scanning characteristics	25
7	Digital selective calling facility	25
7.1	DSC capabilities	25
7.2	Distress message storage	26
7.3	DSC characteristics	26
8	Test methods and required test results	26
8.1	Test conditions	26
8.1.1	Normal and extreme test conditions	26
8.1.2	Test power source	26
8.1.3	Procedure for tests at extreme temperatures	26
8.1.4	General requirements	26
8.1.5	Tests by inspection	27
8.2	General conditions of measurement	27
8.2.1	Arrangements for test signals applied to the receiver input	27
8.2.2	Receiver squelch facility	27
8.2.3	Normal test modulation	27
8.2.4	Artificial antenna	27
8.2.5	Arrangements for test signals applied to the transmitter input	27
8.2.6	Transmitter output power	27
8.2.7	Test of equipment with duplex filter	27
8.2.8	Test channels	27
8.2.9	Measurement uncertainty	28
8.3	Transmitter	28
8.3.1	Switching time	28
8.3.2	Frequency error	29
8.3.3	Carrier power	29
8.3.4	Frequency deviation	30
8.3.5	Limitation characteristics of the modulator	31
8.3.6	Sensitivity of modulation, including microphone	32
8.3.7	Audiofrequency response	32
8.3.8	Audiofrequency harmonic distortion of the emission	32
8.3.9	Adjacent channel power	33
8.3.10	Conducted spurious emissions conveyed to the antenna	33
8.3.11	Residual modulation of the transmitter	34
8.3.12	Transient frequency behaviour of the transmitter	34
8.3.13	Protection of the transmitter	38
8.3.14	Frequency error (demodulated signal)	39
8.3.15	Modulation index	39
8.3.16	Modulation rate	39
8.3.17	Residual modulation	40
8.3.18	Modulator attack time	40
8.4	Audio general receiver	41
8.4.1	Harmonic distortion and rated audiofrequency output power	41
8.4.2	Audiofrequency response	42
8.4.3	Maximum usable sensitivity	43
8.4.4	Co-channel rejection ratio	44
8.4.5	Adjacent channel selectivity	44
8.4.6	Spurious response rejection	45
8.4.7	Intermodulation response	46

8.4.8	Blocking.....	46
8.4.9	Conducted spurious emissions conveyed to the antenna.....	47
8.4.10	Amplitude response of the receiver limiter	47
8.4.11	Receiver hum and noise level.....	48
8.4.12	Squelch operation	48
8.4.13	Squelch hysteresis.....	49
8.4.14	Scanning characteristics of multiple watch facilities	49
8.5	DSC watch receiver.....	50
8.5.1	DSC test signal.....	50
8.5.2	Maximum usable sensitivity	51
8.5.3	Adjacent channel selectivity	51
8.5.4	Co-channel rejection ratio	52
8.5.5	Intermodulation response	52
8.5.6	Spurious response rejection	52
8.5.7	Blocking.....	54
8.5.8	Dynamic range.....	54
8.5.9	Conducted spurious emissions conveyed to the antenna.....	54
Annex A	(normative) Power measuring receiver specification.....	56
A.1	IF filter	56
A.2	Attenuation indicator	57
A.3	RMS value indicator	57
A.4	Oscillator and amplifier.....	57
Annex B	(normative) Implementation of bridge alert management	58
B.1	Classification of BAM alerts.....	58
B.1.1	Requirements	58
B.1.2	Test methods and required results.....	58
B.2	Bridge alert management	59
B.2.1	General requirements	59
B.2.2	Unacknowledged BAM warnings.....	59
B.2.3	Remote acknowledgement and silencing of BAM alerts	59
B.3	BAM alert source identification and reporting in ALF sentences.....	60
B.3.1	General requirements.....	60
B.3.2	Receipt of distress or urgency call.....	61
B.3.3	Receipt of calls other than distress or urgency.....	62
B.3.4	Automatic positioning ceased	63
B.3.5	Position older than 4 h	64
B.3.6	Antenna error or failure	65
B.3.7	Transmission power error or otherwise inhibited transmission	66
Annex C	(normative) DSC operation.....	67
C.1	General.....	67
C.2	Naming convention of DSC message types	67
C.3	Test setup.....	67
C.3.1	General	67
C.3.2	Test methods	69
C.4	Non-automated features	69
C.4.1	Non-automated feature requirements.....	69
C.4.2	Non-automated features tests.....	74
C.5	Standby	85
C.5.1	Standby requirements	85

C.5.2	Standby tests	86
C.6	Sending distress automated procedure	87
C.6.1	Sending distress automated procedure requirements	87
C.6.2	Sending distress automated procedure tests	91
C.7	Received distress automated procedure	98
C.7.1	Received distress automated procedure requirements	98
C.7.2	Received distress automated procedure tests	101
C.8	Sending non-distress automated procedure	107
C.8.1	Sending non-distress automated procedure requirements	107
C.8.2	Sending non-distress automated procedure tests	110
C.9	Received non-distress automated procedure	113
C.9.1	Received non-distress automated procedure requirements	113
C.9.2	Received non-distress automated procedure tests	116
C.10	Communications automated procedure	119
C.10.1	Communications automated procedure requirements	119
C.10.2	Communications automated procedure tests	120
C.11	Multiple automated procedures and parallel event handling	120
C.11.1	Multiple automated procedures and parallel event handling requirements	120
C.11.2	Multiple automated procedures and parallel event handling tests	121
C.12	Error handling in the automated procedures	131
C.12.1	Error handling requirements	131
C.12.2	Error handling tests	133
Annex D (normative)	DSC message composition	136
D.1	Default values	136
D.2	The default DROBOSE	137
D.3	Allowable non-distress DSC message parameters	137
Annex E (normative)	Audible annunciation and BAM alert signalling	138
E.1	Audible alert specifications	138
E.2	Alerting with critical errors	140
E.3	Default audible alert sounds	140
Annex F (normative)	Remote control operation using DSC sentence	142
F.1	General	142
F.2	Requirements	143
F.2.1	Operational requirements	143
F.2.2	Technical requirements	143
F.3	Method of test and required results	143
F.3.1	General	143
F.3.2	Test for input of DSC sentence and resulting transmission of DSC call	144
Annex G (normative)	Manufacturer's declarations and equipment manual	145
Bibliography		146
Figure 1	– Interfaces of the equipment	18
Figure 2	– Transmitter permissible frequency deviation	31
Figure 3	– Storage oscilloscope view t_1 , t_2 and t_3	36
Figure 4	– Test set-up for measuring transient frequency behavior	37
Figure 5	– Modulator attack time test configuration	41

Figure 6 – Receiver audiofrequency response	43
Figure A.1 – IF filter specification	56
Figure C.1 – Tests and error checks	72
Figure D.1 – Loading DSC defaults	136
Table 1 – Sentences input to the equipment for position information	18
Table 2 – Sentences output from the equipment	18
Table 3 – Sentences input to the equipment	19
Table 4 – Sentences output from the equipment for BNWAS	19
Table 5 – Sentences output from the equipment for CAM	19
Table 6 – Sentences input to the equipment from CAM	19
Table 7 – Transmitter transient timing (ms)	35
Table A.1 – Selectivity characteristic	56
Table A.2 – Attenuation points close to carrier	56
Table A.3 – Attenuation points distant from carrier	57
Table B.1 – Classification of GMDSS equipment alerts for BAM purpose	58
Table B.2 – BAM alert text in ALF sentence for cause distress	61
Table B.3 – BAM Alert text in ALF sentence for cause urgency	62
Table B.4 – BAM alert text in ALF sentence for received calls other than distress and urgency	63
Table B.5 – BAM alert text in ALF sentence for cause automatic positioning ceased	64
Table B.6 – BAM alert text in ALF sentence for cause position older than 4 h	64
Table B.7 – BAM alert text in ALF sentence for cause antenna or antenna tuner failure	65
Table B.8 – BAM alert text in ALF sentence for cause transmission power inhibit or failure	66
Table C.1 – Verification of DROBOSE (1) to (8)	81
Table C.2 – DSC messages to send from the EUT	81
Table C.3 – Transmission test results	82
Table C.4 – DSC messages to send from the TE	122
Table C.5 – Verification of communications procedure	123
Table C.6 – Verification required without acknowledgement	124
Table C.7 – Verification required with acknowledgement	124
Table C.8 – Verification required without acknowledgement	125
Table C.9 – Verification required with acknowledgement	125
Table C.10 – Verification required with MMSI ship station	126
Table C.11 – Verification required with MMSI coast station	126
Table C.12 – DSC messages	127
Table C.13 – DSC messages to be sent from the TE	127
Table C.14 – Verification required before activation of received distress procedure	128
Table C.15 – Verification required after activation of received distress procedure	128
Table C.16 – DSC messages to send from the TE	129
Table D.1 – Default DROBOSE	137
Table D.2 – Allowable parameter combinations	137
Table E.1 – Audible characteristics	138

Table E.2 – Non-configurable alarm sounds	141
Table E.3 – Recommended alert sounds	141

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –**Part 7: Shipborne VHF radiotelephone transmitter and receiver –
Operational and performance requirements,
test methods and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization, comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use, and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the informative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61097-7 has been prepared by IEC technical committee 80: Maritime navigation and radio communication equipment and systems. It is an International Standard.

This second edition cancels and replaces the first edition published in 1996, and Amendment 1:2018. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the text has been updated to incorporate the provisions of the new IMO performance standards given in Resolution MSC.511(105) and new ITU-R recommendations given in M.493-16;

- b) the provisions for digital selective calling which were previously in IEC 61097-3 have been incorporated;
- c) the provisions for watch keeping receivers which were previously in IEC 61097-8 have been incorporated;
- d) new requirements have been added for a received signal strength indicator in 4.3.4 and for software maintenance in 4.6 in support of IMO recommendations;
- e) new Annex B and Annex E have been added for bridge alert management;
- f) new Annex C and Annex D have been added for digital selective calling;
- g) a new Annex F has been added for remote control operation;
- h) a new Annex G has been added for equipment manuals.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1151/FDIS	80/1157/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61097 series, published under the general title *Global maritime distress and safety system (GMDSS)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 7: Shipborne VHF radiotelephone transmitter and receiver – Operational and performance requirements, test methods and required test results

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and test methods with required test results for VHF radio installations capable of voice communication and digital selective calling as required by chapter IV of the International Convention for Safety of Life at Sea (SOLAS).

This document incorporates the applicable part of the performance standards included in IMO Resolution A.524(13) and MSC.511(105), the technical characteristics included in Recommendation ITU-R M.489-2 and Recommendation ITU-R M.493-16, and takes account of IMO Resolution A.694(17) which is associated with IEC 60945, and conforms with the ITU Radio Regulations where applicable.

When a requirement in this document is different from IEC 60945, the requirement in this document shall take precedence.

This document also takes account, as appropriate, of requirements for the presentation of navigation-related information on shipborne navigational displays given in IMO Resolution MSC.191(79) and is associated with IEC 62288 and the requirements for bridge alert management given in Resolution MSC.302(87) associated with IEC 62923-1 and IEC 62923-2.

NOTE 1 All text of this document, whose wording is identical to that in IMO Resolutions and ITU-R Recommendations is printed in *italics* and the Resolution/Recommendation and clause numbers are indicated in brackets.

NOTE 2 This document introduces requirements, tests and their required results in the context of digital selective calling (DSC) as defined by ITU-R recommendations such as ITU-R M.493, and in the context of bridge alert management (BAM) as defined by IMO MSC.302(87) and IEC 62923-1. Certain terms, such as "alert", "warning" and "priority" can have different meanings depending on the context in which the term is used. The meaning of specific terms used in this document is as defined in the context of DSC unless specifically expressed otherwise. For example, the expression "BAM alert" is used to indicate that the term "alert" is used in the context of BAM in that instance. Annex E provides further specifications on mapping of signals between the context of DSC and the context of BAM.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108 (all parts), *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*