

INTERNATIONAL STANDARD

IEC
61097-9

First edition
1997-12

Global maritime distress and safety system (GMDSS) –

Part 9:

**Shipborne transmitters and receivers for use in
the MF and HF bands suitable for telephony,
digital selective calling (DSC) and narrow band
direct printing (NBDP) – Operational and
performance requirements, methods of testing
and required test results**

*Système mondial de détresse et de sécurité
en mer (SMDSM) –*

Partie 9:

*Émetteurs et récepteurs de bord de navires utilisables dans les
bandes décadiques et hectométriques pour la téléphonie,
l'appel sélectif numérique (ASN) et l'impression directe à bande
étroite (IDBE) – Exigences d'exploitation et de fonctionnement,
méthodes d'essai et résultats d'essai exigés*

© IEC 1997 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland
Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XA**

For price, see current catalogue

CONTENTS

	Page
FOREWORD	5
Clause	
1 Scope	6
2 Normative references	7
3 Performance requirements	8
3.1 Introduction	8
3.2 Power supplies	9
3.3 Control	9
3.4 Interfaces	9
3.5 Frequency indication	9
3.6 Distress controls	9
3.7 Control panel priority	10
3.8 Labels	10
3.9 Safety precautions	11
3.10 Classes of emission	11
3.11 Frequency bands	11
3.12 Warming-up period	11
4 Transmitter	11
4.1 Frequencies and classes of emission	11
4.2 Frequency accuracy and stability	12
4.3 Output power	12
4.4 Transmitter input	13
4.5 Permissible warming-up period	13
4.6 Continuous operation	13
4.7 Controls and indicators	13
4.8 Safety precautions	14
4.9 Power supply	14
4.10 Synthesizer lock	14
4.11 Channel switching	14
4.12 NB/P transmit and receive timing	14
5 Receiver	14
5.1 Frequencies and classes of emission	14
5.2 Frequency stability and accuracy	15
5.3 Usable sensitivity	15
5.4 Receiver output	15
5.5 Permissible warming-up period	15
5.6 Immunity to interference	15
5.7 Controls	15

Clause	Page
5.8 Power supply.....	16
5.9 Antenna static protection	16
5.10 Loudspeaker switching	16
5.11 Noise reducer.....	16
5.12 Audio gain control and automatic gain control (AGC).....	16
5.13 NBDP transmit and receive timing.....	16
6 Radiotelephone alarm signal generator.....	16
6.1 Introduction	16
6.2 General	16
6.3 Frequency and duration of tones.....	17
6.4 Modulation	17
6.5 Controls	17
6.6 Duration of alarm signal.....	17
6.7 Alarm signal repeat	17
6.8 Activation of the radio telephone transmitter	17
6.9 Aural monitoring	17
7 Methods of testing and required test results	17
7.1 Test conditions	18
7.2 Performance check.....	18
7.3 Environmental tests	19
7.4 Electromagnetic compatibility (EMC).....	19
7.5 Immunity	19
7.6 Acoustic noise	19
7.7 Compass safe distance	20
7.8 Safety precautions.....	20
7.9 General conditions of measurement.....	20
8 Transmitter	22
8.1 General	22
8.2 Frequency error	22
8.3 Output power and intermodulation products	23
8.4 Unwanted frequency modulation	24
8.5 Sensitivity of the microphone	25
8.6 Sensitivity of the 600 Ω line input for SSB telephony	25
8.7 Automatic level control and/or limiter for SSB telephony.....	26
8.8 Audio frequency response using SSB telephony.....	26
8.9 Power of out-of-band emissions using SSB telephony	27
8.10 Power of conducted spurious emissions of SSB telephony	28
8.11 Residual hum and noise power using telephony	28
8.12 Residual frequency modulation on DSC and NBDP	29
8.13 Carrier suppression	29
8.14 Continuous operation.....	30
8.15 Protection of the transmitter.....	30
8.16 Residual RF noise power	31
8.17 Switching time for NBDP.....	31

Clause	Page
9 Receiver	32
9.1 Audio frequency output levels	32
9.2 Frequency error	32
9.3 Unwanted frequency modulation	33
9.4 Audio frequency pass band	34
9.5 Maximum usable sensitivity	35
9.6 Harmonic content in output	36
9.7 Adjacent channel selectivity	36
9.8 Blocking	38
9.9 Cross-modulation	39
9.10 Intermodulation	39
9.11 Spurious response rejection ratio	40
9.12 Audio frequency intermodulation	42
9.13 Conducted spurious emissions into the antenna	43
9.14 Internally generated spurious signals	43
9.15 Improvement in signal-to-noise ratio with AGC	43
9.16 AGC range	44
9.17 AGC time constants (attack and recovery time)	44
9.18 Switching time for NBDP	45
9.19 Reciprocal mixing	45
9.20 Protection of input circuits	46
 Figures	
1 – Limits for unwanted emission (MF/HF transmitter)	47
2 – Limits for automatic level control	48
3 – Limits for audio frequency response	49
 Annexes	
A – Relationship between bit error rate (BER) input and symbol error rate (SER) output ...	50
B – Bibliography	54
C – Delays in equipment and its effect on narrow band direct printing communication in the GMDSS using the protocol in Recommendation ITU-R M.625	55

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –**Part 9: Shipborne transmitters and receivers for use in the MF and HF bands suitable for telephony, digital selective calling (DSC) and narrow band direct printing (NBDP) –
Operational and performance requirements, methods of testing and required test results**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subject since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61097-9 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/147/FDIS	80/164/RVD

All information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

Annexes A, B and C are for information only.

The bilingual version of this standard will be issued later.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 9: Shipborne transmitters and receivers for use in the MF and HF bands suitable for telephony, digital selective calling (DSC) and narrow band direct printing (NBDP) – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61097 specifies the minimum operational and performance requirements and methods of testing with required test results for transmitters and receivers capable of voice communication, digital selective calling and narrow band direct printing telegraphy for the GMDSS operating in either the medium frequency band only or in medium and high frequency bands allocated in the ITU Radio Regulations to the Maritime Mobile Service, as required by Chapter IV of SOLAS 1974 as amended in 1988 and which is associated with IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement of this standard shall take precedence.

This standard refers to equipment for:

- single side-band (SSB) transmission and reception for radio telephony;
- frequency shift keying or single side-band transmission and reception for digital selective calling signals (DSC) according to Recommendation ITU-R M.493-7; and
- frequency shift keying or single side-band transmission and reception for narrow band direct printing telegraphy (NBDP) according to Recommendation ITU-R M.625-3;

as applicable.

This standard refers to radio equipment, which is not integrated with DSC encoders or decoders, or NBDP modems, but defines the interfaces with, and the RF characteristics of, such equipment.

NOTE – The requirements for integrated DSC encoders or decoders may be found in IEC 61097-3 and for integrated NBDP modems in the future IEC 61097-11.

These requirements include the relevant provisions of the Radio Regulations and of the IMO Resolutions A.334(X), A.421(XI), A.694(17), A.804(19), and A.806(19) and SOLAS.

NOTE – The requirement for two-tone generators (A.421(XI)) is only applicable until 1 February 1999.

If the equipment, or parts of it, is designed in such a manner that it can be used for other categories of maritime radiocommunication services (e.g. radio data or facsimile transmission), those parts of the equipment shall fulfil the relevant requirements of the appropriate standards for the service(s) in question.

NOTE – All text of this standard the wording of which is identical to that in IMO Resolutions and to that in the relevant ITU-R Recommendations is printed in *italics* and is prefixed by references (804 etc.) in brackets. When the text is identical in A.804 and A.806 the reference A.806 will be used.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61097. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this part of IEC 61097 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60945:1996, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61097-3:1994, *Global maritime distress and safety system (GMDSS) – Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required test results*

IEC 61097-8 – *Global maritime distress and safety system (GMDSS) – Part 8: Shipborne watchkeeping receivers for reception of digital selective calling (DSC) in the maritime MF, MF/HF and UHF bands – Operational and performance requirements, methods of testing and required test results*¹⁾

IEC 61162-1:1995, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

ISO 3791:1967, *Office machines and data processing equipment – Keyboard layouts for numeric applications*

International Convention on Safety of Life at Sea (SOLAS):1974 (as amended), *Chapter IV: Radiocommunications*

IMO Resolution A.334(IX):1975, *Recommendation on operational standards for radiotelephone transmitters and receivers*

IMO Resolution A.421(XI):1979, *Operational standards for radiotelephone alarm signal generators*

IMO Resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.804(19):1995, *Performance standards for shipborne MF radio installations capable of voice communication and digital selective calling*

IMO Resolution A.806(19):1995, *Performance standards for shipborne MF/HF radio installations capable of voice communication, narrow-band direct-printing and digital selective calling*

ITU:1994, *Radio Regulations*

ITU-R M.493-7:1995, *Digital selective-calling system for use in the maritime mobile service*

ITU-R M.625-3:1995, *Direct-printing telegraph equipment in the maritime mobile service*

¹⁾ To be published.

ITU-T E.161 (formerly CCITT Recommendation E.161):1988, *Arrangement of figures, letters and symbols on telephones and other devices that can be used for access to a telephone network*

ITU-T V.11:1993, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbits/s*