



IEC 61158-3-13

Edition 1.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications –
Part 3-13: Data-link layer service definition – Type 1 elements

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

X

ICS 35.100.20; 25.040.40

ISBN 2-8318-9416-6

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
1.1 Overview.....	7
1.2 Specifications.....	7
1.3 Conformance.....	7
2 Normative references.....	8
3 Terms, definitions, symbols, abbreviations and conventions.....	8
3.1 Reference model terms and definitions.....	9
3.2 Service convention terms and definitions.....	9
3.3 Data-link service terms and definitions.....	10
3.4 Symbols and abbreviations.....	15
3.5 Common conventions.....	16
3.6 Additional Type 13 conventions.....	17
4 Data-link service and concept.....	17
4.1 Overview.....	17
4.2 Detailed description of isochronous-data services.....	25
4.3 Detailed description of asynchronous-data service.....	26
4.4 Detailed description of exception-signaling services.....	32
4.5 NMT-status services.....	33
5 Data-link management services (and concepts).....	35
5.1 General.....	35
5.2 Facilities of the DLMS.....	35
5.3 Services of the DL-management.....	35
5.4 Overview of interactions.....	36
5.5 Detail specification of service and interactions.....	37
Bibliography.....	42
Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses.....	12
Figure 2 – Type 13 communication architecture.....	17
Figure 3 – Sequence diagram of isochronous-data service.....	18
Figure 4 – Sequence diagram of service-data service.....	19
Figure 5 – Sequence diagram of an unspecified-data transfer service.....	20
Figure 6 – Sequence diagram of a status-data transfer service.....	20
Figure 7 – Sequence diagram of an ident-data transfer service.....	21
Figure 8 – Sequence diagram of an NMT-command transfer service.....	22
Figure 9 – Sequence diagram of an exception-signaling service.....	23
Figure 10 – Sequence diagram of a NMT-status transfer service.....	24
Figure 11 – Reset, Set value and Get value services.....	36
Figure 12 – Event and Frame status service.....	37
Table 1 – Type 13 node ID assignment.....	24
Table 2 – Primitives and parameters used on the isochronous data service.....	25
Table 3 – Transmit /Receive isochronous-data primitives and the parameters.....	25

Table 4 – Primitives and parameters used on service data transfer service	26
Table 5 – Transmit / Receive service-data primitives and the parameters	27
Table 6 – Primitives and parameters used on the unspecified-data service	27
Table 7 – Transmit / receive unspecified-data primitives and the parameters	28
Table 8 – Primitives and parameters used on status-data transfer service	29
Table 9 – Status data primitives and the parameters	29
Table 10 – Primitives and parameters used on ident-data transfer service	30
Table 11 – Ident data primitives and the parameters	30
Table 12 – Primitives and parameters used on the NMT-command service	31
Table 13 – NMT-command primitives and the parameters	31
Table 14 – Primitives and parameters used on the exception-signaling service	32
Table 15 – Exception-signaling initialization primitives and the parameters	32
Table 16 – Exception signaling initialization primitives and the parameters	33
Table 17 – Primitives and parameters used on the NMT-status service	33
Table 18 – NMT-status primitives and the parameters	34
Table 19 – Summary of DL-management primitives and parameters	36
Table 20 – DLM-Reset primitives and parameters	37
Table 21 – DLM-Set-value primitives and parameters	38
Table 22 – DLE-variables and permissible values (from IE : 61158-4-13)	38
Table 23 – DLM-Get-value primitives and parameters	39
Table 25 – Event primitives and parameters	39
Table 26 – Event-related state change variables	40
Table 27 – Frame status primitives and parameters	40
Table 28 – Frame parameters	41

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 3-13: Data-link layer service definition – Type 13 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as far as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission of their respective intellectual-property-right holders.

International Standard IEC 61158-3-13 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-3 subseries cancel and replace IEC 61158-3:2003. This edition of this part constitutes a technical addition. This part and its Type 13 companion parts also replace IEC/PAS 62408, published in 2005.

This edition includes the following significant technical changes with respect to the previous edition:

- a) deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data-link layer, for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) division of this part into multiple parts numbered 3-1, 3-2, ..., 3-19.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/473/FDIS	65C/484/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the data-link layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.

Currently in preview, click buy full version

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 3-13: Data-link layer service definition – Type 13 elements

1 Scope

1.1 Overview

This part of IEC 61158 provides common elements for basic time-critical messaging communications between devices in an automation environment. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the Type 13 fieldbus data-link layer in terms of

- a) the primitive actions and events of the service;
- b) the parameters associated with each primitive action and event, and the form which they take; and
- c) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the service provided to

- the Type 13 fieldbus application layer at the boundary between the application and data-link layers of the fieldbus reference model, and
- systems management at the boundary between the data-link layer and systems management of the fieldbus reference model.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual data-link layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of data-link protocols for time-critical communications. A secondary objective is to provide migration paths from previously-existing industrial communications protocols.

This specification may be used as the basis for formal DL-Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor do they constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition standard. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfills the Type 13 data-link layer services defined in this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498-1, Information technology – Open Systems Interconnection – Basic Reference Model — Basic Reference Model: The Basic Model

ISO/IEC 7498-3, Information technology – Open Systems Interconnection – Basic Reference Model — Basic Reference Model: Naming and addressing

ISO/IEC 10731, Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services