



IEC 61158-4-12

Edition 1.0 2007-12

INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –
Part 4-12: Data-link layer protocol specification – Type 12 elements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XG**

ICS 35.100.20; 25.040.40

ISBN 2-8318-9439-5

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
1.1 General.....	10
1.2 Specifications.....	10
1.3 Procedures.....	10
1.4 Applicability.....	10
1.5 Conformance.....	10
2 Normative references.....	11
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Reference model terms and definitions.....	11
3.2 Service convention terms and definitions.....	12
3.3 Common terms and definitions.....	13
3.4 Additional Type 12 definitions.....	13
3.5 Common symbols and abbreviations.....	16
3.6 Additional Type 12 symbols and abbreviations.....	17
3.7 Conventions.....	19
4 Overview of the DL-protocol.....	24
4.1 Operating principle.....	24
4.2 Topology.....	24
4.3 Frame processing principles.....	24
4.4 Data-link layer overview.....	25
4.5 Error detection overview.....	26
4.6 Node reference model.....	26
4.7 Operation overview.....	27
5 Frame structure.....	28
5.1 Frame coding principles.....	28
5.2 Data types and encoding rules.....	28
5.3 DLPDU structure.....	31
5.4 Type 12 DLPDU structure.....	33
5.5 Network variable structure.....	48
5.6 Type 12 mailbox structure.....	48
6 Attributes.....	49
6.1 Management.....	49
6.2 Statistics.....	66
6.3 Watchdogs.....	69
6.4 Slave information interface.....	72
6.5 Media independent interface (MII).....	77
6.6 Fieldbus memory management unit (FMMU).....	80
6.7 Sync manager.....	83
6.8 Distributed clock.....	90
7 DL-user memory.....	94
7.1 Overview.....	94
7.2 Mailbox access type.....	95
7.3 Buffered access type.....	98
8 Type 12: FDL protocol state machines.....	100

8.1	Overview of slave DL state machines	100
8.2	State machine description	100
Annex A (informative) – Type 12: Additional specifications on DL-Protocol state machines.....		108
A.1	DHSM	108
A.2	SYSM.....	127
A.3	RMSM	140
Bibliography.....		144
Figure 1	– Type description example	20
Figure 2	– Common structure of specific fields.....	21
Figure 3	– Frame structure.....	25
Figure 4	– Mapping of data in a frame.....	26
Figure 5	– Slave node reference model.....	27
Figure 6	– Type 12 PDUs embedded in Ethernet frame.....	28
Figure 7	– Type 12 PDUs embedded in UDP/IP	28
Figure 8	– DL information type description	51
Figure 9	– Address type description	53
Figure 10	– DL control type description.....	55
Figure 11	– DL status type description	57
Figure 12	– Successful write sequence to DL-user control register	59
Figure 13	– Successful read sequence to the DL-user status register	60
Figure 14	– RX error counter type description	67
Figure 15	– Lost link counter type description	68
Figure 16	– Additional counter type description.....	69
Figure 17	– Sync configuration type description	70
Figure 18	– Watchdog divider type description.....	70
Figure 19	– Sync manager watchdog type description.....	71
Figure 20	– Sync manager watchdog status type description	71
Figure 21	– Watchdog counter type description.....	72
Figure 22	– Slave information interface access type description	72
Figure 23	– Slave information interface control/status type description	74
Figure 24	– Slave information interface address type description	76
Figure 25	– Slave information interface data type description	77
Figure 26	– MII control/status type description	78
Figure 27	– MII address type description	79
Figure 28	– MII data type description	80
Figure 29	– FMMU mapping example.....	80
Figure 30	– FMMU entity type description	81
Figure 31	– SyncM mailbox interaction.....	84
Figure 32	– SyncM buffer allocation	84
Figure 33	– SyncM buffer interaction	85
Figure 34	– Handling of write/read toggle with read mailbox	86
Figure 35	– Sync manager channel type description	88

Figure 36 – Distributed clock local time parameter type description 92

Figure 37 – Successful write sequence to mailbox 95

Figure 38 – Bad write sequence to mailbox 96

Figure 39 – Successful read sequence to mailbox 96

Figure 40 – Bad read sequence to mailbox 97

Figure 41 – Successful write sequence to buffer 98

Figure 42 – Successful read sequence to buffer 99

Figure 43 – Structuring of the protocol machines of an slave 100

Figure 44 – Slave information interface read operation 102

Figure 45 – Slave information interface write operation 103

Figure 46 – Slave information interface reload operation 104

Figure 47 – Distributed clock 106

Figure 48 – Delay measurement sequence 107

Table 1 – PDU element description example 20

Table 2 – Example attribute description 21

Table 3 – State machine description elements 22

Table 4 – Description of state machine elements 23

Table 5 – Conventions used in state machines 23

Table 6 – Transfer Syntax for bit sequences 29

Table 7 – Transfer syntax for data type Unsignedn 29

Table 8 – Transfer syntax for data type Integern 30

Table 9 – Type 12 frame inside an Ethernet frame 31

Table 10 – Type 12 frame inside an UDP Frame 32

Table 11 – Type 12 frame structure containing Type 12 PDUs 33

Table 12 – Type 12 frame structure containing network variables 33

Table 13 – Type 12 frame structure containing mailbox 33

Table 14 – Auto Increment Physical Read (APRD) 34

Table 15 – Configured Address Physical Read (FPRD) 35

Table 16 – Broadcast Read (BRD) 36

Table 17 – Logical Read (LRD) 37

Table 18 – Auto Increment Physical Write (APWR) 38

Table 19 – Configured Address Physical Write (FPWR) 39

Table 20 – Broadcast Write (BWR) 40

Table 21 – Logical Write (LWR) 41

Table 22 – Auto Increment Physical ReadWrite (APRW) 42

Table 23 – Configured Address Physical ReadWrite (FPRW) 43

Table 24 – Broadcast ReadWrite (BRW) 44

Table 25 – Logical ReadWrite (LRW) 45

Table 26 – Auto Increment Physical Read Multiple Write (ARMW) 46

Table 27 – Configured Address Physical Read Multiple Write (FRMW) 47

Table 28 – Network variable 48

Table 29 – Mailbox 48

Table 30 – Error Reply Service Data	49
Table 31 – DL information	52
Table 32 – Configured station address	54
Table 33 – DL control	55
Table 34 – DL status	58
Table 35 – DLS-user specific registers	61
Table 36 – DLS-user event	63
Table 37 – DLS-user event mask	64
Table 38 – External event	65
Table 39 – External event mask	66
Table 40 – RX error counter	67
Table 41 – Lost link counter	68
Table 42 – Watchdog divider	70
Table 43 – PDI watchdog	70
Table 44 – Sync manager channel watchdog	71
Table 45 – Sync manager watchdog Status	71
Table 46 – Watchdog counter	72
Table 47 – Slave information interface size	73
Table 48 – Slave information interface control/status	75
Table 49 – Actual slave information interface address	76
Table 50 – Actual slave information interface data	77
Table 51 – MII control/status	78
Table 52 – Actual MII address	79
Table 53 – Actual MII data	80
Table 54 – Fieldbus memory management unit (FMMU) entity	82
Table 55 – Fieldbus memory management unit (FMMU)	83
Table 56 – Sync manager channel	88
Table 57 – Sync manager structure	90
Table 58 – Distributed clock local time parameter	93
Table 59 – Distributed clock DLS-user parameter	94
Table A.1 – Primitives issued by DHSM to PSM	108
Table A.2 – Primitives issued by PSM to DHSM	108
Table A.3 – Parameters used with primitives exchanged between DHSM and PSM	108
Table A.4 – Identifier for the octets of a Ethernet frame	109
Table A.5 – DHSM state table	111
Table A.6 – DHSM function table	127
Table A.7 – Primitives issued by SYSM to DHSM	127
Table A.8 – Primitives issued by DHSM to SYSM	128
Table A.9 – Primitives issued by DL-User to SYSM	128
Table A.10 – Primitives issued by SYSM to DL-User	128
Table A.11 – Parameters used with primitives exchanged between SYSM and DHSM	128
Table A.12 – SYSM state table	130
Table A.13 – SYSM function table	140

Table A.14 – Primitives issued by RSM to SYM	140
Table A.15 – Primitives issued by SYM to RSM	140
Table A.16 – Parameters used with primitives exchanged between RSM and SYM	140
Table A.17 – RSM state table.....	142
Table A.18 – RSM function table.....	143

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 4-12: Data-link layer protocol specification – Type 12 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as far as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment and limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International Standard IEC 61158-4-12 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-4 subseries cancel and replace IEC 61158-4:2003. This edition of this part constitutes a technical addition, which also replaces IEC/PAS 62407, published in 2005.

This edition of IEC 61158-4 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data link layer, for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) division of this part into multiple parts numbered -4-1, -4-2, ..., -4-19.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/474/FDIS	65C/485/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-12: Data-link layer protocol specification – Type 12 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities:

- a) in a synchronously-starting cyclic manner, and
- b) in a cyclic or acyclic asynchronous manner, as requested each cycle by each of those data-link entities.

Thus this protocol can be characterized as one which provides cyclic and acyclic access asynchronously but with a synchronous restart of each cycle.

1.2 Specifications

This standard specifies

- a) procedures for the transfer of data and control information from one data-link user entity to one or more user entity;
- b) the structure of the DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between DL-entities (DLEs) through the exchange of DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and the MAC services of ISO/IEC 8802-3.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI reference model and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This part of this standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-2 (Ed.4.0), *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-12, *Industrial communication networks – Fieldbus specifications – Part 3-12: Data-link layer service definition – Type 12 elements*

IEC 61588, *Precision clock synchronization protocol for networked measurement and control system*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model – Basic Reference Model: Naming and addressing*

ISO/IEC 8802-1(E), ANSI/IEEE Std 802.1 *Local and metropolitan area networks – Virtual bridged local area networks.*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and Physical Layer specifications*

ISO/IEC 9899, *Programming Languages – C.*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE 802.1Q, *IEEE Standard for Local and metropolitan area networks – Virtual Bridged Local Area Networks*; available at <<http://www.ieee.org>>

IETF RFC 768, *User PDU Protocol*; available at <<http://www.ietf.org>>

IETF RFC 791, *Internet Protocol*; available at <<http://www.ietf.org>>