

INTERNATIONAL STANDARD

IEC
61162-410

First edition
2001-11

Maritime navigation and radiocommunication equipment and systems – Digital interfaces –

Part 410: Multiple talkers and multiple listeners – Ship systems interconnection – Transport profile requirements and basic transport profile

© IEC 2001 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission 3, rue de Varembeé Geneva, Switzerland
Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XB**

For price, see current catalogue

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope and object.....	8
2 Normative references.....	9
3 Definitions.....	10
4 Transport layer service specification.....	15
4.1 General.....	15
4.2 T-profile network and host computer addressing.....	15
4.2.1 Introduction.....	15
4.2.2 Addressing scheme.....	15
4.2.3 Unique and singular hosts on the network.....	16
4.2.4 Non-segmented logical network.....	16
4.2.5 Size of network.....	16
4.3 Communication services requirements.....	16
4.3.1 Introduction.....	16
4.3.2 Connectivity and data transfer internally and externally.....	16
4.3.3 Service classes.....	16
4.4 Time services.....	19
4.4.1 General.....	19
4.4.2 Services.....	19
4.5 Management services.....	20
4.5.1 General.....	20
4.5.2 Services.....	20
4.6 Graceful degradation facility.....	21
5 Transport layer interface (TLI).....	21
5.1 Overview.....	21
5.1.1 LNAC and TLI.....	22
5.2 General principles.....	22
5.2.1 TLI, TP network service classes and connection points.....	22
5.2.2 Connection point capabilities.....	23
5.2.3 Attributes of TP network.....	25
5.2.4 Attributes of connection point.....	26
5.2.5 Connection point states.....	26
5.3 TLI service overview.....	29
5.3.1 General.....	29
5.3.2 TLI management services.....	29
5.3.3 Connection point management.....	30
5.3.4 Data management.....	33
6 T-profile for redundant Internet.....	36
6.1 Introduction.....	36
6.1.1 Rationale for the use of Internet protocols.....	36
6.1.2 Relationship to basic Internet protocols.....	36
6.1.3 Rationale for use of Ethernet.....	37

6.2	Transport profile architecture	37
6.2.1	General	37
6.2.2	Redundancy.....	38
6.2.3	Communication services	39
6.3	Message formats	39
6.3.1	General format.....	39
6.3.2	Special reliable link messages	40
6.3.3	Broadcast messages.....	40
6.4	Reliable stream protocol	41
6.4.1	Introduction	41
6.4.2	Connection management	41
6.4.3	Data transmission	45
6.4.4	Data reception	46
6.4.5	Link close	47
6.5	Reliable message service	47
6.5.1	Introduction	47
6.5.2	Data reception	47
6.5.3	Data transmission on the urgent link	47
6.6	Unreliable message service	47
6.6.1	Introduction	47
6.6.2	Connection management	47
6.6.3	Message length limitation.....	49
6.6.4	Data transmission	49
6.6.5	Data reception	49
6.7	Time services	50
6.7.1	Introduction	50
6.7.2	Time management architecture	50
6.7.3	Client interfaces.....	50
6.7.4	System integration requirements	51
6.8	Network management services	51
6.8.1	Introduction	51
6.8.2	Physical architecture.....	51
6.8.3	Required safety precautions.....	51
6.8.4	NMA requirements	51
6.8.5	Network element requirements.....	51
7	T-profile for non-redundant Internet.....	52
7.1	Introduction	52
7.2	Relationship to redundant Internet protocol	52
7.3	Redundancy	52
7.4	Reliable stream protocol	53
7.5	Reliable message service	53
7.6	Unreliable message service	53
7.7	Time services	53
7.8	Network management services	53
8	T-profile for wide area networks (MAU-LNA communication link)	53
8.1	Introduction	53
8.1.1	General architecture	53
8.1.2	TP network and NNN code definitions	54

8.2	Relationship to non-redundant Internet T-profile	54
8.3	Reliable stream service	55
8.4	Reliable message service	55
8.5	Other services	55
Annex A (informative)	Typical software library structure	56
Annex B (informative)	Channel synchronization example	57
Annex C (informative)	NTP and SNTP overview.....	58
Annex D (informative)	Overview of Internet network management services	59

Currently in preview, click buy full vers.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
DIGITAL INTERFACES –**
**Part 410: Multiple talkers and multiple listeners –
Ship systems interconnection –
Transport profile requirements and basic transport profile**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61162-410 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems

The text of this standard is based on the following documents:

FDIS	Report on voting
80/311/FDIS	80/326/RVD

For information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

The special typographical conventions and nomenclature used in this standard are defined in IEC 61162-400 annex A.

Annexes A, B, C and D are for information only.

The committee has decided that the contents of this publication will remain unchanged until June 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Currently in preview, click buy full vers.

INTRODUCTION

International Standard IEC 61162 is a four-part standard which specifies four digital interfaces for applications in marine navigation, radiocommunication and system integration.

The four parts are:

- IEC 61162-1 Single talker and multiple listeners
- IEC 61162-2 Single talker and multiple listeners, high speed transmission
- IEC 61162-3 Multiple talkers and multiple listeners – Serial data instrument network
- IEC 61162-4 Multiple talkers and multiple listeners – Ship systems interconnection.

Part 4 of the standard is subdivided into a number of individual standards with part numbers in the 400 series.

This part of the standard contains the specification of the requirements to an IEC 61162-4 transport profile (T-profile) and also the specification of one implementation, based on redundant Ethernet and Internet protocol functionality. The T-profile is the protocol transport mechanisms that offer simple message or byte stream transport services to the higher protocol layers (defined in other parts of the standard). In addition, the T-profile also offers services for time distribution and physical network management.

The use of Internet and Ethernet protocols offer low cost and high efficiency data transport in any kind of system. However, for safety related applications, certain measures have to be taken to avoid that particulars of office-quality and off-the-shelf technology create safety risks. This part of the standard specifies mechanisms by which a certain degree of quality of service can be guaranteed from these networks, including the provision of redundancy.

Other T-profile documents will be prepared with specifications of the same T-profile requirements over other transport protocols. This will be issued in the same number series as this standard (IEC 61162-41x).

Relationship with the other parts of the IEC 61162 series of standards is defined in annex B to IEC 61162-400.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 410: Multiple talkers and multiple listeners – Ship systems interconnection – Transport profile requirements and basic transport profile

1 Scope and object

This part of IEC 61162-4 defines the general requirements of the T-profile and three implementations of the T-profile over the Internet V4 (IPV4) protocol suite. Part 400 of this standard defines the relationship between the different protocol levels (T-profile, A-profile and companion standards) and part 401 defines the A-profile, the immediate use of the protocol level defined in this part.

The different components of the IEC 61162-4 standard are defined in IEC 61162-400. The T-profile is the specification of the communication services and the communication protocols used by the LNA to implement the A-profile functionality. Basically, the T-profile consists of the following components:

- a) a transport layer interface (TLI) definition that specifies the services and the semantics that will be available to the application level of the LNA (and in some cases the MAU). This includes data transport as well as time and network management services. The TLI will be general to all T-profiles and is defined in this part 400 of the standard,
- b) A T-profile protocol definition that specifies how the services provided by the TLI and additional time distribution and physical network management services are implemented on the protocol level. This part 410 contains a number of alternative T-profile protocol specifications using the Internet V4 series of standards. Additional parts of this standard will address other T-profiles based on other protocol families.

Note that the time distribution and network management functionality may or may not include specific TLI services. For some systems this functionality may be interfaced to directly by the underlying operating system. Note also that time distribution and network management are not strictly speaking transport related protocol functionality. However, the implementation of these services is normally dependent on the transport protocols in use and is, thus, placed in the T-profile part of the standard.

The purpose of this standard is to define and describe the services that will be provided at the transport layer interface in a way which is completely independent of the underlying network environment as well as defining one possible implementation of these services over the Internet V4 protocols. The separation of service and protocol definitions allows the specification of several different transport profiles, each one dedicated to a specific network environment, and to use the same transport service interface in all cases.

Clause 4 defines the transport level services and clause 5 describes the transport layer interface through which the services are offered. These clauses define the general, network independent services.

Clause 6 defines the transport profile architecture for redundant Ethernet and Internet protocols version 4 (IPV4). Clause 7 defines the architecture for a local area non-redundant Internet network. These clauses define two specific implementations of the T-profile services.

Clause 8 defines a simple MAU-LNA protocol for use over wide area network (WAN) TCP/IP links. This can be used to implement a WAN architecture for the overall system. The WAN architecture is not intended for integrated ship control systems, but can be used for remote test integration and remote maintenance and diagnostics. The WAN protocol can also be used to support MAUs that are located in other host computers than the LNA, but on one local network (conformance class 4).

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61162. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 61162 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 61162-400, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 400: Multiple talkers and multiple listeners – Ship systems interconnection – Introduction and general principles*

ISO 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

ISO/IEC 9595: *Information technology – Open Systems Interconnection – Common management information service*

ISO/IEC 9596-1: *Information technology – Open Systems Interconnection – Common management information protocol – Part 1: Specification*

RFC 768:1980, *User Datagram Protocol (UDP)*, *Internet Activities Board recommended standard*

RFC 793:1981, *Transmission Control Protocol (TCP)*, *Internet Activities Board recommended standard*

RFC 826:1982, *Address Resolution Protocol (ARP)*, *Internet Activities Board elective standard*

RFC 894:1984, *Internet Protocol on Ethernet Networks*, *Internet Activities Board elective standard*

RFC 1157:1990, *Simple Network Management Protocol (SNMP)*

RFC 180:1990, *Common Management Information Services and Protocols for the Internet (CMIS and CMIP)*

RFC 1213:1991, *Management Information Base for Network Management of TCP/IP-based Internets: MIB-II*

RFC 1305:1992, *Network Time Protocol, Version 3 – Specification and Implementation*

RFC 2030:1996, *Simple Network Time Protocol (SNTP), Version 4 for IPv4, IPv6 and OSI*

RFC 2500:1999, *Internet Official Protocol Standards – Internet Activities Board standard*

NOTE RFC (request for comments) is a document, issued by the Internet engineering task force (IETF) the International standardization body for the Internet, that describes a part of the Internet protocol. Some RFCs are accepted as official Internet standards and listed in the “Internet Official Protocol Standards” itself an RFC.