

# INTERNATIONAL STANDARD

# IEC 61285

Second edition  
2004-10

---

---

## Industrial-process control – Safety of analyser houses

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

U

*For price, see current catalogue*

## CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 Location of AHs and connection within the process plant areas .....	9
4.1 Response time .....	9
4.2 Utilities.....	9
4.3 Safety .....	9
4.4 Access .....	10
5 Design, construction and layout of AHs .....	10
5.1 General .....	10
5.2 General requirements .....	10
5.3 Dimensions and layout .....	11
5.4 Structural requirements .....	11
5.5 Equipment.....	11
5.6 Labelling/instructions/documentation .....	13
6 Explosion protection of AHs.....	14
6.1 General .....	14
6.2 General requirements.....	14
6.3 Protection of AHs against explosion hazards by means of artificial ventilation .....	14
6.4 Protection of AHs against explosion hazards by means of natural ventilation .....	17
7 Measures to prevent health hazards to personnel in AHs.....	18
7.1 General .....	18
7.2 Guidelines .....	18
7.3 General requirements.....	18
7.4 Safety measures .....	19
7.5 External hazards .....	20
7.6 Additional measures for abnormal working conditions.....	20
7.7 Labelling/instructions/documentation .....	20
Annex A (normative) Leakage risk of modules in AHs .....	22
Annex B (informative) Ventilation calculation (assumes STP conditions).....	24
Bibliography.....	27
Table A.1 – Module evaluation.....	23

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL-PROCESS CONTROL –  
SAFETY OF ANALYSER HOUSES**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61285 has been prepared by subcommittee 65D: Analysing equipment, of IEC technical committee 65: Industrial-process measurement and control.

This second edition cancels and replaces the first edition published in 1994. This edition constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- a) incorporation of previously issued corrigendum;
- b) minor updates to several sections and references

The text of this standard is based on the following documents:

FDIS	Report on voting
65D/107/FDIS	65D/110/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Currently in preview, click buy full version

## INTRODUCTION

Process analysers measure the characteristics of a process stream continuously and automatically. The process sample is introduced automatically and the system is designed for unattended operation and minimal maintenance.

This document is designed to set forth minimum safety requirements for typical analyser houses (AHs). It shall be superseded in all cases by national, local, or corporate requirements, which may be more stringent.

The measured output is transmitted continuously for process control, operator action or documentation. Process analysers are used for

- environmental analysis;
- personnel protection;
- equipment protection;
- quality measurement/control;
- process control (plant optimization);
- energy conservation.

In the simplest case, the analyser sensor is mounted directly in the material to be measured, and there is no need to extract a sample. In other cases, a sample is extracted from the main stream and transported to the analyser. The system may include many functional elements such as

- sample extraction;
- sample transport;
- sample conditioning;
- sample stream disposal and/or return to process;
- utilities and auxiliary materials supply;
- stream switching;
- automatic or manual calibration and validation system;
- signal processing;
- performance monitoring and control.

(See IEC 61115.)

Analyser elements can be arranged modularly and located separately. There are advantages in grouping analysers and systems and further advantages in enclosing them. Advantages include

- lower cost of installation of utilities and signals;
- protection of personnel and complex modules and equipment from adverse ambient conditions;
- ease of maintenance;
- safety.

Analysers are constructed to various standards: some are ex-proof, some intrinsically safe, some suitable for Zone 2 and some suitable only for a non-hazardous area. Not all analysers are available in all variants.

Process plants usually include all zones – 0, 1, 2 and non-hazardous.

The selection of the AH location, the source of ventilation air, and the classification of the house interior and its analysers is an economic exercise.

Factors include the distance from the sample point to the AH , classification of the area around the AH, distance from the AH to the source of non-hazardous air, and the cost of analysers of classification appropriate to the house interior.

Currently in preview, click buy full vers.

## INDUSTRIAL-PROCESS CONTROL – SAFETY OF ANALYSER HOUSES

### 1 Scope

This International Standard describes the physical requirements for the safe operation of the process analyser measuring system installed in an AH in order to ensure its protection against fire, explosion and health hazards. This standard extends beyond IEC 60079-16 to include houses with Zone 2 interiors and to apply to toxic hazards. (Appropriate national guidelines on toxic hazards are to be followed.)

This standard does not address facilities where dust is the hazard.

Clause 4 addresses the location of the AH and connection within the process plant areas.

Clause 5 addresses the design, construction and layout of the AH. It does not address parts of the analyser measuring system installed in other locations such as sample conditioning rooms (SCR) or switchgear rooms.

Clause 6 addresses measures for reducing the danger of explosion for AHs while permitting maintenance of equipment with the power on and the case open.

NOTE For most fluids, the major constraint is that the concentration of vapours, which are hazardous for personnel, is lower than the lower explosive (flammable) limit (LEL) (see Clause 7).

Using n-Pentane as an example, the LEL is 1,4 % or  $14\,000 \times 10^{-6}$ . The level immediately dangerous to life or health (which is the maximum level from which a worker could escape within 30 min without any escape-impairing symptoms or any irreversible health effects) is only 0,5 % or  $5\,000 \times 10^{-6}$ .

Classification of a house interior as Zone 1 may imply that no technician can enter without protective equipment such as breathing gear. Placing an AH in a Zone 1 area would usually imply that no technician could approach the house without wearing protective equipment.

Clause 7 addresses those measures for protecting personnel from materials in the atmosphere of AHs that are hazardous to health.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-16:1990, *Electrical apparatus for explosive gas atmospheres – Part 16: Artificial ventilation for the protection of analyser(s) houses*