

FINAL VERSION

VERSION FINALE



**Lamp controlgear –
Part 1: General and safety requirements**

**Appareillages de lampes –
Partie 1: Exigences générales et exigences de sécurité**

CONTENTS

FOREWORD.....	9
INTRODUCTION.....	12
1 Scope.....	13
2 Normative references	13
3 Terms and definitions	15
4 General requirements	23
5 General notes on tests	24
6 Classification.....	25
7 Marking	25
7.1 Items to be marked	25
7.2 Durability and legibility of marking.....	27
8 Terminals	28
8.1 Integral terminals	28
8.2 Terminals other than integral terminals	28
9 Earthing.....	28
9.1 Provisions for protective earthing (Symbol: IEC 60411-5019 (2006-08)).....	28
9.2 Provisions for functional earthing (Symbol: IEC 60411-5018 (2011-07)).....	29
9.3 Lamp controlgear with conductors for protective earthing by tracks on printed circuit boards	29
9.4 Earthing of built-in lamp controlgear.....	29
9.5 Earthing via independent controlgear.....	29
9.5.1 Earth connection to other equipment	29
9.5.2 Earthing of the lamp components powered via the independent lamp controlgear	29
10 Protection against accidental contact with live parts	30
11 Moisture resistance and insulation.....	31
12 Electric strength	32
13 Thermal endurance test for windings of ballasts	33
14 Fault conditions	36
15 Construction.....	40
15.1 Wood, cotton, silk, paper and similar fibrous material	40
15.2 Printed circuits.....	40
15.3 Pins and socket-outlets used in SELV or ELV circuits	41
15.4 Insulation between circuits and accessible parts	41
15.4.1 General	41
15.4.2 SELV circuits.....	41
15.4.3 FELV circuits	42
15.4.4 Other circuits.....	43
15.4.5 Insulation between circuits and accessible conductive parts	43
16 Creepage distances and clearances	44
16.1 General.....	44
16.2 Creepage distances	46
16.2.1 General	46
16.2.2 Minimum creepage distances for working voltages	47

16.2.3	Creepage distances for working voltages with frequencies above 30 kHz	48
16.2.4	Compliance with the required creepage distances	49
16.3	Clearances	50
16.3.1	General	50
16.3.2	Clearances for working voltages	51
16.3.3	Clearances for ignition voltages and working voltages with higher frequencies.....	52
16.3.4	Compliance with the required clearances.....	54
17	Screws, current-carrying parts and connections.....	55
18	Resistance to heat, fire and tracking.....	55
19	Resistance to corrosion	56
20	No-load output voltage	56
Annex A (normative) Test to establish whether a conductive part is a live part which may cause an electric shock		57
A.1	General test requirements.....	57
A.2	Limits for measured voltages	57
A.3	Limits for touch current	57
Annex B (normative) Particular requirements for thermally protected lamp controlgear		58
B.1	Introductory remark.....	58
B.2	General.....	58
B.3	Terms and definitions.....	58
B.4	General requirements for thermally protected lamp controlgear.....	59
B.5	General notes on tests.....	59
B.6	Classification	59
B.6.1	General	59
B.6.2	According to the class of protection	59
B.6.3	According to the type of protection	59
B.7	Marking.....	60
B.8	Thermal endurance of windings	60
B.9	Lamp controlgear heating	60
B.9.1	Preselection test.....	60
B.9.2	"Class P" thermally protected lamp controlgear	61
B.9.3	Temperature declared thermally protected lamp controlgear as specified in IEC 61347-2-8, with a rated maximum case temperature of 130 °C or lower	62
B.9.4	Temperature declared thermally protected lamp controlgear as specified in IEC 61347-2-8 with a rated maximum case temperature exceeding 130 °C	63
B.9.5	Temperature declared thermally protected lamp controlgear as specified in IEC 61347-2-9	64
Annex C (normative) Particular requirements for electronic lamp controlgear with means of protection against overheating.....		66
C.1	General.....	66
C.2	Terms and definitions.....	66
C.3	General requirements for electronic lamp controlgear with means of protection against overheating	66
C.4	General notes on tests.....	67
C.5	Classification	67

C.6	Marking.....	67
C.7	Limitation of heating	67
C.7.1	Pre-selection test.....	67
C.7.2	Functioning of the protection means	67
Annex D (normative)	Requirements for carrying out the heating tests of thermally protected lamp controlgear	69
D.1	Test enclosure	69
D.2	Heating of enclosure	69
D.3	Lamp controlgear operating conditions.....	69
D.4	Lamp controlgear position in the enclosure	69
D.5	Temperature measurements	70
Annex E (normative)	Use of constant S other than 4 500 in t_w tests.....	71
E.1	General.....	71
E.2	Procedure A.....	71
E.3	Procedure B.....	71
Annex F (normative)	Draught-proof enclosure.....	74
Annex G (normative)	Explanation of the derivation of the values of pulse voltages	75
G.1	Pulse voltage rise time T	75
G.2	Long-duration pulse voltages	75
G.3	Short-duration pulse voltages	75
G.4	Measurement of short-duration pulse energy	75
Annex H (normative)	Tests	81
H.1	Ambient temperature and test room	81
H.2	Supply voltage and frequency	81
H.2.1	Test voltage and frequency.....	81
H.2.2	Stability of supply and frequency	81
H.2.3	Supply voltage waveform for reference ballast only	81
H.3	Electrical characteristics of lamps	82
H.4	Magnetic effects	82
H.5	Mounting and connection of reference lamps	82
H.6	Reference lamp stability.....	82
H.7	Instrument characteristics	82
H.7.1	Potential circuits	82
H.7.2	Current circuits	82
H.7.3	RMS measurements	83
H.8	Inverter power sources	83
H.9	Reference ballast.....	83
H.10	Reference lamps.....	83
H.11	Test conditions	83
H.11.1	Resistance measurement delays	83
H.11.2	Electrical resistance of contacts and leads	83
H.12	Lamp controlgear heating	83
H.12.1	Built-in lamp controlgear	83
H.12.2	Independent lamp controlgear	84
H.12.3	Integral lamp controlgear	84
H.12.4	Test conditions	85
Annex I (normative)	Additional requirements for built-in magnetic ballasts with double or reinforced insulation	86
I.1	General.....	86

I.2	Terms and definitions.....	86
I.3	General requirements	86
I.4	General notes on tests.....	87
I.5	Classification	87
I.6	Marking.....	87
I.7	Protection against accidental contact with live parts.....	87
I.8	Terminals.....	87
I.9	Provision for earthing.....	87
I.10	Moisture resistance and insulation	87
I.11	High-voltage impulse test.....	87
I.12	Thermal endurance test for windings of ballasts.....	88
I.13	Ballast heating.....	88
I.14	Screws, current-carrying parts and connections	88
I.15	Creepage distances and clearances.....	88
I.16	Resistance to heat and fire	88
I.17	Resistance to corrosion	88
Annex J (normative)	Schedule of more onerous requirements.....	89
Annex K (informative)	Conformity testing during manufacture	90
K.1	General.....	90
K.2	Testing	90
K.3	Additional dielectric strength tests for controlgear with protection against pollution by the use of coating or potting materials	92
Annex L (normative)	Particular additional requirements for controlgears providing SELV.....	93
L.1	General.....	93
L.2	Terms and definitions.....	93
L.3	Classification	94
L.4	Marking.....	94
L.5	Protection against electric shock.....	95
L.6	Heating.....	95
L.7	Short-circuit and overload protection.....	96
L.8	Insulation resistance and electric strength	97
L.8.1	General	97
L.8.2	Insulation resistance.....	97
L.8.3	Electric strength	97
L.9	Construction	98
L.10	Components	98
L.11	Creepage distances, clearances and distances through insulation	99
Annex M (informative)	Dielectric strength test voltages for controlgear intended for the use in impulse withstand Category III.....	100
Annex N (normative)	Requirements for insulation materials used for double or reinforced insulation	101
N.1	General.....	101
N.2	Reference document.....	101
N.3	Terms and definitions.....	101
N.4	General requirements	101
N.4.1	Material requirements	101
N.4.2	Solid insulation	101
N.4.3	Thin sheet insulation.....	101

Annex O (normative) Additional requirements for built-in electronic controlgear with double or reinforced insulation	105
O.1 General.....	105
O.2 Terms and definitions.....	105
O.3 General requirements	105
O.4 General notes on tests	105
O.5 Classification	106
O.6 Marking.....	106
O.7 Protection against accidental contact with live parts.....	106
O.8 Terminals.....	106
O.9 Provision for earthing.....	106
O.10 Moisture resistance and insulation	106
O.11 Electric strength.....	106
O.12 Thermal endurance of windings	106
O.13 Fault conditions	106
O.14 Construction	107
O.15 Creepage distances and clearances.....	107
O.16 Screws, current-carrying parts and connections	107
O.17 Resistance to heat and fire	107
O.18 Resistance to corrosion	107
Annex P (normative) Creepage distances and clearances and distance through isolation (DTI) for lamp controlgear which are protected against pollution by the use of coating or potting.....	108
P.1 General.....	108
P.2 Creepage distances	108
P.2.1 General	108
P.2.2 Minimum creepage distance for working voltages and rated voltage with frequencies up to 30 kHz	108
P.2.3 Creepage distances for working voltages with frequencies above 30 kHz.....	108
P.2.4 Compliance with the required creepage distances	110
P.3 Distance through isolation.....	111
P.3.1 General	111
P.3.2 Compliance tests.....	111
P.3.3 Preconditioning of the lamp controlgear.....	111
P.3.4 Electrical tests after conditioning	112
Annex Q (informative) Example for U_p calculation	114
Annex R (informative) Concept of creepage distances and clearances.....	115
R.1 Basic concept considerations.....	115
R.1.1 Creepage distances	115
R.1.2 Clearances	115
R.2 Why setting up tables?.....	116
Annex S (informative) Examples of controlgear insulation coordination	117
Annex T (informative) Creepage distances and clearances for controlgear with a higher degree of availability (impulse withstand category III).....	118
T.1 General.....	118
T.2 Clearances for working voltages of lamp controlgear not protected against pollution by coating or potting materials	118
T.3 Clearances for working voltages of lamp controlgear protected against pollution by coating or potting	119

T.4	Distances through insulation – Particular additional requirements for controlgear providing SELV	119
	Bibliography.....	121
	Figure 1 – Relation between winding temperature and endurance test duration	34
	Figure 2 – Test circuit for controlgear	40
	Figure 3 – Example of a controlgear insulation related to Table 6	43
	Figure 4 – Application of Table 7 and Table 8	47
	Figure 5 – Application of Table 9, Table 10 and Table 11.....	50
	Figure 6 – Application of Table 10 and Table 11	51
	Figure B.1 – Test circuit for thermally protected lamp controlgear	64
	Figure D.1 – Example of heating enclosure for thermally protected ballasts	70
	Figure E.1 – Assessment of claimed value of S	73
	Figure G.1 – Circuit for measuring short-duration pulse energy.....	78
	Figure G.2 – Suitable circuit for producing and applying long-duration pulse	80
	Figure H.1 – Test arrangement for heating test	85
	Figure N.1 – Test arrangement for checking mechanical withstanding of insulating materials in thin sheet layers	104
	Figure Q.1 – Example for the calculation of U_p	114
	Figure S.1 – Example of schematic drawings, showing the different controlgear insulation coordination	117
	Table 1 – Required rated impulse withstand voltage of equipment	22
	Table 2 – Working voltage and U_{out} steps	27
	Table 3 – Electric strength test voltage	32
	Table 4 – Theoretical test temperatures for ballasts subjected to an endurance test duration of 30 days	35
	Table 5 – Minimum creepage distance on printed circuit board	38
	Table 6 – Insulation requirements between active parts and accessible conductive parts	44
	Table 7 – Minimum creepage distances for working voltage	48
	Table 8 – Minimum value of creepage distances for sinusoidal or non-sinusoidal working voltages at different frequency ranges; basic or supplementary insulation	49
	Table 9 – Minimum clearances for working voltages	51
	Table 10 – Minimum distances of clearances for sinusoidal or non-sinusoidal voltages; inhomogeneous field conditions; basic or supplementary insulation	53
	Table 11 – Minimum distances of clearances for sinusoidal or non-sinusoidal voltages; inhomogeneous field conditions; reinforced insulation.....	54
	Table B.1 – Thermal protection operation	62
	Table B.2 – Thermal protection operation	63
	Table G.1 – Component values for measurement of pulse energy.....	78
	Table K.1 – Minimum values for electrical tests	91
	Table L.1 – Symbols for marking if marking is used	95
	Table L.2 – Values of temperatures in normal use	96
	Table L.3 – Values of insulation resistances	97

Table L.4 – Table of dielectric strength test voltages for controlgears intended for use in impulse withstand Category II 98

Table L.5 – Distances through insulation (DTI) for the impulse withstand category II / material group IIIa (175 CTI < 400) 99

Table M.1 – Table of dielectric strength test voltages for controlgears intended for use in impulse withstand Category III 100

Table N.1 – Electric strength test voltage required during the mandrel test 103

Table P.1 – Minimum creepage distances for working voltages and rated voltages with frequencies up to 30 kHz 108

Table P.2 – Minimum value of creepage distances for sinusoidal or non-sinusoidal working voltages at different frequency ranges; basic or supplementary insulation 109

Table P.3 – Impulse withstand test voltage for products of impulse withstand category II 112

Table T.1 – Minimum clearances for working voltages – Impulse withstand category III 119

Table T.2 – Impulse withstand test voltages of impulse withstand category III for lamp controlgear protected against pollution by coating or potting material 119

Table T.3 – Distances through insulation (DTI) for the impulse withstand category III/material group IIIa (175 CTI < 400) 120

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LAMP CONTROLGEAR –

Part 1: General and safety requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC 61347-1 bears the edition number 3.1. It consists of the third edition (2015-02) [documents 34C/1118/FDIS and 34C/1135/RVD] and its amendment 1 (2017-09) [documents 34C/1351/FDIS and 34C/1358/RVD]. The technical content is identical to the base edition and its amendment.

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 61347-1 has been prepared by subcommittee 34C: Auxiliaries for lamps, of IEC technical committee 34: Lamps and related equipment.

This third edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) additional marking requirements;
- b) additional requirements for creepage distances and clearances:
 - for working voltages with operating frequencies up to 30 kHz;
 - for working voltages with higher operating frequencies than 30 kHz;
 - for impulse and resonance voltages ignition;
 - for basic, supplementary and reinforced insulation;
 - for insulation between circuits;
 - for coated or potted controlgear;
- c) modification of definition of ELV and FELV;
- d) modification of schematic drawing, showing the different controlgear classification and insulation requirements;
- e) scope extension;
- f) new Annex A: test to establish whether a conductive part is a live part which may cause an electric shock;
- g) new Annex M: creepage distances and clearances for controlgear where a higher degree of availability (impulse withstand category III) may be requested;
- h) new Annex Q: example for U_p calculation;
- i) new Annex P: creepage distances and clearances and distance through isolation (DTI) for lamp controlgear which are protected against pollution by the use of coating or potting;
- j) new Annex R: concept of creepage distances and clearances.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 1 is to be used in conjunction with the appropriate Part 2, which contains clauses to supplement or modify the corresponding clauses in Part 1, to provide the relevant requirements for each type of product.

NOTE In this standard, the following print types are used.

- Requirements proper: in roman type.
- *Test specifications: in italic type.*
- Explanatory matter: in smaller roman type.

A list of all parts of the IEC 61347 series, published under the general title *Lamp controlgear*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61347 provides a set of general and safety requirements and tests which are considered to be generally applicable to most types of lamp controlgear and which can be called up as required by the different parts that make up IEC 61347-2. This Part 1 is thus not to be regarded as a specification in itself for any type of lamp controlgear, and its provisions apply only to particular types of lamp controlgear, to the extent determined by the appropriate Part 2 of IEC 61347.

The parts which make up IEC 61347-2, in referring to any of the clauses of this part, specify the extent to which such a clause is applicable and the order in which the tests are to be performed; they also include additional requirements as necessary. The order in which the clauses of this part are numbered has no particular significance, as the order in which their provisions apply is determined for each type of lamp controlgear by the appropriate Part 2 of the IEC 61347-2 series. All such parts are self-contained and therefore do not contain references to each other.

Where the requirements of any of the clauses of this part of IEC 61347 are referred to in the various parts that make up IEC 61347-2 by the phrase "The requirements of clause n of IEC 61347-1 apply", this phrase will be interpreted as meaning that all requirements of the clause in question of Part 1 apply, except any which are clearly inapplicable to the particular type of lamp controlgear covered by the Part 2 concerned.

Lamp controlgear which complies with the text of this standard will not necessarily be judged to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

Lamp controlgear employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirement and, if found to be substantially equivalent, may be judged to comply with the safety principles of the standard.

Performance requirements for lamp controlgear are the subject of IEC 60921, IEC 60923, IEC 60925, IEC 60927, IEC 60929, IEC 61047 and IEC 62384 as appropriate for the type of lamp controlgear.

Safety requirements ensure that electrical equipment constructed in accordance with these requirements does not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which it was intended.

Requirements for electronic lamp controlgear for other types of lamps will be the subject of a separate standard, as the need arises.

Controlgear can consist of a printed circuit board and may incorporate the following:

- controlgear;
- lampholder(s);
- switch(es);
- supply terminals.

The lamp controlgear should comply with this standard.

The lampholders(s), switch(es) and supply terminals should comply with their own standards.

LAMP CONTROLGEAR –

Part 1: General and safety requirements

1 Scope

This part of IEC 61347 specifies general and safety requirements for lamp controlgear for use on d.c. supplies up to 1 000 V and/or a.c. supplies up to 1 000 V at 50 Hz or 60 Hz.

This standard also covers lamp controlgear for lamps which are not yet standardized.

Tests dealt with in this standard are type tests. Requirements for testing individual lamp controlgear during production are not included.

Requirements for semi-luminaires are given in IEC 60598-1:2014 (see definition 1.2.60).

Particular requirements for controlgears providing safety extra low voltage (from now on SELV) are given in Annex L.

It can be expected that lamp control gear which comply with this standard will not compromise safety between 90 % and 110 % of their rated supply voltage in independent use and when operated in luminaires complying with the safety standard IEC 60598-1 and the relevant part IEC 60598-2-xx and with lamps complying with the relevant lamp standards. Performance requirements may require tighter limits.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60065:2001¹, *Audio, video and similar electronic apparatus – Safety requirements*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60081, *Double-capped fluorescent lamps – Performance specifications*

IEC 60085:2007, *Electrical insulation – Thermal classification and designation*

IEC 60112:2003, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*
IEC 60112:2003/AMD1:2009

IEC 60216 (all parts), *Electrical insulating materials – Thermal endurance properties*

IEC 60317-0-1:2013, *Specifications for particular types of windings wires – Part 0-1: General requirements – Enamelled round copper wire*

¹ Seventh edition. This edition has been replaced in 2014 by IEC 60065:2014.