



# INTERNATIONAL STANDARD

---

**Maritime navigation and radiocommunication equipment and systems –  
Shipborne voyage data recorder (VDR) –  
Part 2: Simplified voyage data recorder (S-VDR) – Performance requirements,  
methods of testing and required test results**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE **XA**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and abbreviations .....	9
3.1 Definitions .....	9
3.2 Abbreviations .....	10
4 Performance requirements .....	11
4.1 General.....	11
4.2 Purpose .....	12
4.3 Operational requirements .....	12
4.3.1 Design and construction .....	12
4.3.2 Maintenance of sequential records .....	12
4.3.3 Co-relation in date and time.....	12
4.3.4 Protective capsule .....	12
4.3.5 Assessment of recording medium .....	13
4.3.6 Interfaces .....	14
4.4 Data selection and security .....	14
4.4.1 Selection of data items .....	14
4.4.2 Configuration data .....	14
4.4.3 Resistance to tampering .....	15
4.4.4 Recording integrity .....	15
4.5 Continuity of operation .....	15
4.5.1 Operation .....	15
4.5.2 Power source .....	16
4.5.3 Dedicated reserve power source.....	16
4.5.4 Recording period and duration.....	16
4.6 Data items to be recorded .....	16
4.6.1 Date and time .....	16
4.6.2 Ship position .....	17
4.6.3 Speed .....	17
4.6.4 Heading.....	17
4.6.5 Bridge audio .....	17
4.6.6 Communications audio .....	17
4.6.7 Radar data – post-display selection .....	17
4.6.8 AIS .....	18
4.6.9 Other items.....	18
4.6.10 Echo sounder .....	18
4.6.11 Main alarms.....	18
4.6.12 Rudder order and response .....	18
4.6.13 Engine order and response.....	18
4.6.14 Hull openings (doors) status .....	18
4.6.15 Watertight and fire door status.....	19
4.6.16 Accelerations and hull stresses .....	19
4.6.17 Wind speed and direction .....	19

5	Technical characteristics .....	19
5.1	Co-relation in date and time .....	19
5.2	Particular design requirements for the protective capsule .....	19
5.2.1	Fixed protective capsule .....	19
5.3	Location beacon(s) for the protective capsule .....	20
5.3.1	Device for the location of the fixed capsule .....	20
5.3.2	Device(s) for the location of the float-free capsule .....	20
5.4	Survivability of recorded data .....	21
5.4.1	Long-term retention under normal conditions .....	21
5.4.2	Survival following an incident .....	21
5.5	Information to be included in the manufacturer's documentation .....	22
5.5.1	Installation guidelines .....	22
5.5.2	Operation and maintenance manual .....	22
5.5.3	Information for use by an investigation authority .....	22
5.6	Bridge audio specifications .....	23
5.6.1	Input interface .....	23
5.6.2	Reference signal .....	23
5.6.3	Audio frequency response .....	23
5.6.4	Quality index .....	23
5.6.5	Audio noise level – signal to noise and distortion .....	23
5.7	Communications audio .....	24
5.7.1	Input interfaces .....	24
5.7.2	Reference signal .....	24
5.7.3	Audio frequency response .....	24
5.7.4	Quality index .....	24
5.7.5	Audio noise level – signal to noise .....	24
5.7.6	Audio noise level – signal to noise and distortion (SINAD) .....	24
5.8	Radar data – post-display selection .....	24
5.8.1	Input interface .....	24
5.8.2	Image outputs .....	25
6	Methods of testing and required test results .....	25
6.1	General .....	25
6.1.1	Definitions .....	25
6.1.2	Playback equipment .....	26
6.1.3	Sequence of tests .....	26
6.1.4	Requirements to be checked by inspection only .....	26
6.1.5	Environmental test conditions for normal operation .....	27
6.1.6	Recording duration .....	27
6.1.7	Dedicated reserve power source .....	28
6.1.8	Recharging of dedicated reserve power source .....	28
6.1.9	Brief interruption of electrical power .....	28
6.1.10	System integrity .....	28
6.1.11	Maintenance of sequential records .....	29
6.1.12	Co-relation in date and time .....	29
6.1.13	Design and construction of the protective capsule .....	29
6.1.14	Selection of data items .....	32
6.1.15	Power source .....	32
6.2	Data items to be recorded .....	32
6.2.1	Date/time, ship's position, speed and heading .....	32

6.2.2	Bridge audio .....	33
6.2.3	Communications audio .....	36
6.2.4	Radar data, post-display selection .....	39
6.2.5	AIS .....	47
6.2.6	Other items.....	48
6.2.7	Interfaces .....	48
Annex A (normative) IEC 61162 sentence formats .....		49
Annex B (informative) Cross-references between VDR and S-VDR .....		50
Annex C (normative) Download and playback equipment for investigating authorities .....		51
Annex D (informative) Mandatory alarms .....		52
Annex E (informative) Requirement/test – cross-references .....		57
Bibliography.....		59
Figure 1 – Test set-up block diagram .....		41
Figure 2 – Comparison of images .....		45
Table 1 – Bridge audio, signal to noise measurements .....		35
Table 2 – Bridge audio, signal to noise and distortion (SINAD) measurements.....		36
Table 3 – Communications audio, signal to no-signal measurements .....		38
Table 4 – Communications audio, signal to noise and distortion (SINAD) measurements .....		39
Table 5 – Intersection colours of test images 1 and 2.....		43
Table A.1 – References in this standard .....		49
Table B.1 – Subject list and subclauses .....		50
Table D.1 – IMO instrument: SOLAS Chapter II-1 .....		55
Table D.2 – IMO instrument: SOLAS Chapter II-2 .....		56
Table D.3 – IMO instrument: Resolution A.481.....		56
Table E.1 – Subject list and subclauses .....		57

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION  
EQUIPMENT AND SYSTEMS –  
SHIPBORNE VOYAGE DATA RECORDER (VDR) –****Part 2: Simplified voyage data recorder (S-VDR) –  
Performance requirements,  
methods of testing and required test results**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61996-2 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This second edition cancels and replaces the first edition published in 2006, and constitutes a technical revision. A new requirement has been added to 4.3.6 for an interface to be used for downloading the stored data to an external computer. This is defined in Annex C which replaces the Annex C of the first edition which contained an IMO Circular which recommended such an interface. An optional LAN interface for connection to radar has been added in 5.8. Some corrections to the text have also been made.

The text of this standard is based on the following documents:

CDV	Report on voting
80/471/CDV	80/500/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61996 series, under the general title *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR)*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

The S-VDR has been introduced by IMO for fitting to existing ships as a simplified alternative to the voyage data recorder (VDR) which is required for all new ships.

This part of IEC 61996 provides information on the testing requirements for S-VDR as defined in IMO performance standard MSC.163(78).

The specification for S-VDR differs significantly from that for VDR in two areas:

- a) the requirements for monitoring certain sensors are reduced when the data is not provided in IEC 61162 format, and
- b) the requirements for the protective S-VDR capsule are different from the VDR capsule, both for the fixed and float-free versions.

Annex B provides a cross-reference between this standard and IEC 61996-1 to aid test houses who may already have test results for VDRs which are being submitted as S-VDRs.

Subsequent to publishing the performance standard for S-VDR, MSC.163(78) in 2004, the IMO sub-committee on Safety of Navigation (NAV) discussed the issue of download and playback of information. Recognising that after an accident there is a need for investigators to be able to download the stored data and playback the information from VDRs/S-VDRs without delay, the sub-committee agreed on recommended means for extracting stored data for investigation authorities. This was adopted by MSC.81 in 2005 as an amendment to resolution MSC.163(78) given in resolution MSC.214(81). This edition of the standard incorporates this amendment.

**MARITIME NAVIGATION AND RADIOCOMMUNICATION  
EQUIPMENT AND SYSTEMS –  
SHIPBORNE VOYAGE DATA RECORDER (VDR) –**

**Part 2: Simplified voyage data recorder (S-VDR) –  
Performance requirements,  
methods of testing and required test results**

## **1 Scope**

This part of IEC 61996 specifies the minimum performance requirements, technical characteristics and methods of testing, and required test results, for simplified shipborne voyage data recorders (S-VDRs) as required by IMO MSC.163(78). It takes into account IMO resolution A.694(17) and is associated with IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement in this standard takes precedence.

NOTE All text of this standard, whose wording is identical to that of IMO MSC.163(78) or A.861(20) is printed in *italics*, and the Resolution and associated performance standard paragraph numbers are indicated in brackets.

## **2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-27:1987, *Environmental testing – Part 2: Tests – Test Ea and guidance: Shock*

IEC 60268-16:2003, *Sound system equipment – Part 16: Objective rating of speech intelligibility by speech transmission index*

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61097-2, *Global maritime distress and safety system (GMDSS) – Part 2: COSPAS SARSAT EPIRB – Satellite emergency position indicating radio beacon operating on 406 MHz – Operational and performance requirements, methods of testing and required test results*

IEC 61097-7:1996, *Global maritime distress and safety system (GMDSS) – Part 7: Shipborne VHF radiotelephone transmitter and receiver – Operational and performance requirements, methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61260:1995, *Electroacoustics – Octave-band and fractional-octave-band filters*

IEC 61672-1:2002, *Electroacoustics – Sound level meters – Part 1: Specifications*

IMO A.658(16): *Use and fitting of retro-reflective materials on life-saving appliances*

IMO A.662(16): *Performance standards for float-free release and activation arrangements for emergency radio equipment*

IMO A.694(17): *General requirements for shipborne radio equipment forming part of the Global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO A.810(19): *Performance standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz*

IMO A.830(19): *Code on alarms and indicators*

IMO A.861(20): *Performance standards for shipborne voyage data recorders (VDRs)*

IMO MSC.81(70): *Testing of life saving appliances*

IMO MSC.163(78): *Performance standards for shipborne simplified voyage data recorders (S-VDR)*

IMO MSC.214(81): *Annex 2: Amendments to the recommendation on performance standards for shipborne simplified voyage data recorders (VDRs) (Resolution MSC.163(78))*

IMO:1974, *International Convention for the Safety of Life at Sea (SOLAS), as amended*

ITU-R M.633-3:2004, *Transmission characteristics of a satellite emergency position-indicating radiobeacon (satellite EPIRB) system operating through a low polar-orbiting satellite system in the 406 MHz band*

Eurocae: ED56A Amendment 1 – *Minimum operational performance specification (MOPS) for cockpit voice recorder system*

VESA:1996, *Video electronics standards association – Discrete monitor timings standard 1.0, Revision 0.7 (DMT)*

SAE AS 8045:1988, *Engineering Society for advancing mobility land sea air and space – Minimum performance standard for underwater locating devices – acoustic-self-powered*