

## FINAL VERSION

## VERSION FINALE



**Metallic communication cable test methods –  
Part 4-10: Electromagnetic compatibility (EMC) – Transfer impedance and  
screening attenuation of feed-throughs and electromagnetic gaskets – Double  
coaxial test method**

**Méthodes d'essai des câbles métalliques de communication –  
Partie 4-10: Compatibilité électromagnétique (CEM) – Impédance de transfert et  
affaiblissement d'écran des traversées et des joints d'étanchéité  
électromagnétiques – Méthode d'essai coaxiale double**

## CONTENTS

FOREWORD .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 Principle of the test method .....	9
5 Procedure.....	12
5.1 Equipment .....	12
5.2 Dynamic range.....	12
5.3 Verification of the test set-up .....	12
5.4 Sample preparation.....	12
6 Measurement.....	12
6.1 General.....	12
6.2 Screening attenuation .....	12
6.3 Transfer impedance .....	12
7 Expression of results .....	13
7.1 Transfer impedance .....	13
7.2 Screening attenuation .....	13
7.3 Requirements .....	13
Annex A (informative) Background for the measurement of the shielding effectiveness of feed-throughs and electromagnetic gaskets .....	14
A.1 General.....	14
A.2 Theoretical model of the test procedure .....	15
A.3 Performing measurements .....	16
A.3.1 Characteristic impedance and uniformity of the test fixture .....	16
A.3.2 Measuring EMI-gaskets using a NWA .....	16
A.3.3 Pictures and measurement results .....	17
Annex B (informative) Reference device for verification measurement .....	23
B.1 General.....	23
B.2 Design of the reference device.....	23
B.3 Verification measurement result.....	24
Annex C (informative) Impact of ground loops on low frequency measurements .....	25
C.1 General.....	25
C.2 Analysis of the test set-up.....	25
Annex D (informative) Measurement of the transfer impedance of conductive gaskets with controlled contact pressure.....	28
D.1 General.....	28
D.2 Measuring equipment and auxiliary measuring devices .....	28
D.3 Test setup.....	28
D.4 Test specimen .....	29
D.5 Measurement procedure .....	30
D.5.1 Test method A: matched RF-generator and test receiver .....	30
D.5.2 Test method B: un-matched NWA measurement .....	30
D.5.3 Both methods .....	30
D.6 Expression of results .....	31
D.6.1 Method A: matched RF-generator and test receiver measurement .....	31

D.6.2 Method B: un-matched NWA measurement.....	31
Bibliography.....	32
Figure 1 – A two-port .....	7
Figure 2 – Equivalent circuit of the test set-up and definition of $Z_T$ .....	7
Figure 3 – Cross-section of a typical feed-through configuration .....	10
Figure 4 – Cross-section of the test fixture with a connector .....	10
Figure 5 – Cross-section of the test fixture with an electromagnetic gasket.....	11
Figure A.1 – Cross-section of a typical feed-through configuration .....	14
Figure A.2 – Cross-section of the test fixture with a connector .....	15
Figure A.3 – Equivalent circuit of the test setup with the shunt admittance $y$ of the feed-through .....	15
Figure A.4 – TDR step response at input-port of test fixture .....	16
Figure A.5 – View of the test fixture connected to a network analyzer .....	18
Figure A.6 – Top view of the test fixture .....	18
Figure A.7 – Detailed view of the contact area .....	18
Figure A.8 – Detailed view of the captivation for the conductive O-ring test.....	19
Figure A.9 – Isolation of the network analyzer.....	20
Figure A.10 – Isolation of the test fixture when characterizing an ideal short (metal plate).....	20
Figure A.11 – Measured operational screening transmission when characterizing a typical conductive O-ring.....	21
Figure A.12 – Transfer impedance $Z_T$ of a typical conductive O-ring.....	21
Figure A.13 – Screening attenuation $a_S$ of a typical conductive O-ring .....	22
Figure B.1 – Reference device, e.g. resistor soldered onto a PCB.....	23
Figure B.2 – Typical verification measurement result .....	24
Figure C.1 – Double coaxial test set-up .....	25
Figure C.2 – Equivalent circuits of the double coaxial test set-up.....	26
Figure C.3 – Results obtained with (green) and without ferrites on the test leads (blue).....	27
Figure D.1 – Test set-up .....	28
Figure D.2 – Details of the test fixture.....	29
Figure D.3 – Specimen size and shape .....	30
Table D.1 – Specimen size .....	29

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### METALLIC COMMUNICATION CABLE TEST METHODS –

#### Part 4-10: Electromagnetic compatibility (EMC) – Transfer impedance and screening attenuation of feed-throughs and electromagnetic gaskets – Double coaxial test method

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters expressed, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.**

**IEC 62153-4-10 edition 2.1 contains the second edition (2015-11) [documents 46/563/FDIS and 46/580/RVD] and its amendment 1 (2020-07) [documents 46/736/CDV and 46/769/RVC].**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

International Standard IEC 62153-4-10 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This second edition constitutes a technical revision.

The main technical changes with regard to the previous edition are as follows:

- addition of a new clause that describes a procedure for verification of the measurement set-up and further information regarding sample preparation;
- addition of a new Annex that describes how to improve measurement certainty in the very low frequency area.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62153 series, under the general title: *Metallic communication cable test methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## METALLIC COMMUNICATION CABLE TEST METHODS –

### Part 4-10: Electromagnetic compatibility (EMC) – Transfer impedance and screening attenuation of feed-throughs and electromagnetic gaskets – Double coaxial test method

#### 1 Scope

This part of IEC 62153 details a coaxial method suitable for determining the transfer impedance and/or screening attenuation of feed-throughs and electromagnetic gaskets.

The shielded screening attenuation test set-up according to IEC 62153-4-4 (triangular method) has been modified to take into account the particularities of feed-throughs and gaskets.

A wide dynamic and frequency range can be applied to test even super screened feed-throughs and gaskets with normal instrumentation from low frequencies up to the limit of defined transversal waves in the coaxial circuits at approximately 4 GHz.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Void.

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

##### 3.1

**operational (Betriebs) transfer function in the forward direction**  $H_{B21}$

**operational (Betriebs) scattering parameter**  $S_{21}$

quotient of the reflected square root of power wave fed into the reference impedance of the output of the two-port and the unreflected square root of the power wave consumed at the input of the two-port

EXAMPLE (see Figure 1)