

INTERNATIONAL STANDARD



**Metallic communication cable test methods –
Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of
transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of
connectors and assemblies up to and above 3 GHz – Triaxial tube in tube
method**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 3 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - www.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD



**Metallic communication cable test methods –
Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of
transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c
of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube
method**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.100; 33.120.10

ISBN 978-2-8322-3054-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	8
4 Physical background.....	10
5 Principle of the test methods	10
5.1 General.....	10
5.2 Transfer impedance	12
5.3 Screening attenuation	12
5.4 Coupling attenuation	12
6 Test procedure	13
6.1 General.....	13
6.2 Tube in tube procedure	13
6.3 Test equipment	14
6.4 Calibration procedure.....	15
6.5 Connection between extension tube and device under test	15
6.6 Dynamic range respectively noise floor	15
6.7 Impedance matching.....	16
6.8 Influence of Adapters	16
7 Sample preparation	17
7.1 Coaxial connector or device.....	17
7.2 Balanced or multiconductor device.....	17
7.3 Cable assembly	19
8 Measurement of transfer impedance	19
8.1 General.....	19
8.2 Principle block diagram of transfer impedance	19
8.3 Measuring procedure – Influence of connecting cables	19
8.4 Measuring.....	20
8.5 Evaluation of test results.....	20
8.6 Test report	20
9 Screening attenuation.....	21
9.1 General.....	21
9.2 Impedance matching.....	21
9.2.1 General	21
9.2.2 Evaluation of test results with matched conditions	22
9.2.3 Measuring with mismatch.....	22
9.2.4 Evaluation of test results	22
9.3 Test report	23
10 Coupling attenuation.....	23
10.1 Procedure	23
10.2 Expression of results	24
10.3 Test report.....	24
10.4 Balunless procedure	25
Annex A (normative) Determination of the impedance of the inner circuit	26

Annex B (informative) Example of a self-made impedance matching adapter	27
Annex C (informative) Measurements of the screening effectiveness of connectors and cable assemblies	29
C.1 General.....	29
C.2 Physical basics	29
C.2.1 General coupling equation	29
C.2.2 Coupling transfer function.....	31
C.3 Triaxial test set-up	33
C.3.1 General	33
C.3.2 Measurement of cable assemblies	34
C.3.3 Measurement of connectors.....	35
C.4 Conclusion.....	38
Annex D (informative) Influence of contact resistances	39
Bibliography.....	41
Figure 1 – Definition of Z_T	9
Figure 2 – Principle of the test set-up to measure transfer impedance and screening or coupling attenuation of connectors with tube in tube	11
Figure 3 – Principle of the test set-up to measure transfer impedance and screening attenuation of a cable assembly.....	14
Figure 4 – Principle set-up for verification test	16
Figure 5 – Preparation of balanced or multiconductor connectors	18
Figure 6 – Test set-up (principle) for transfer impedance measurement according to test method B of IEC 62153-4-3.....	19
Figure 7 – Measuring the screening attenuation with tube in tube with impedance matching device.....	21
Figure 8 – Measuring the coupling attenuation with tube in tube and balun	24
Figure 9 – Typical measurement of a connector of 0,04 m length with 1 m extension tube	25
Figure 10 – Measuring the coupling attenuation with multiport VNA (balunless procedure is under consideration).....	25
Figure B.1 – Attenuation and return loss of a 50 Ω to 5 Ω impedance matching adapter, log scale	27
Figure B.2 – Attenuation and return loss of a 50 Ω to 5 Ω impedance matching adapter, lin scale	28
Figure C.1 – Equivalent circuit of coupled transmission lines	30
Figure C.2 – Summing function S	31
Figure C.3 – Calculated coupling transfer function ($l = 1$ m; $\epsilon_{r1} = 2,3$; $\epsilon_{r2} = 1$; $Z_F = 0$).....	32
Figure C.4 – Triaxial set-up for the measurement of the screening attenuation a_S and the transfer impedance Z_T	33
Figure C.5 – Simulation of a cable assembly (logarithmic scale)	35
Figure C.6 – Simulation of a cable assembly (linear scale)	35
Figure C.7 – Triaxial set-up with extension tube for short cable assemblies	36
Figure C.8 – Triaxial set-up with extension tube for connectors.....	36
Figure C.9 – Simulation, logarithmic frequency scale	37
Figure C.10 – Measurement, logarithmic frequency scale	37
Figure C.11 – Simulation, linear frequency scale.....	37

Figure C.12 – Measurement, linear frequency scale.....	37
Figure C.13 – Simulation, logarithmic frequency scale	38
Figure C.14 – simulation, linear frequency scale	38
Figure D.1 – Contact resistances of the test set-up	39
Figure D.2 – Equivalent circuit of the test set-up	39
Table 1 – IEC 62153, Metallic communication cable test methods – Test procedures with triaxial test set-up	11

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

METALLIC COMMUNICATION CABLE TEST METHODS –

Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube method

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters expressed, as early as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62153-4-7 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This second edition cancels and replaces the first edition published in 2006. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

The document is revised and updated. The changes of the revised IEC 62153-4-3:2013, and IEC 62153-4-4:2015, are included.

Measurements can be achieved now with mismatch at the generator site, impedance matching devices are not necessary.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/572/FDIS	46/585/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62153 series, under the general title: *Metallic communication cable test methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The shielded screening attenuation test set-up according to IEC 62153-4-3 and IEC 62153-4-4 have been extended to take into account the particularities of electrically short elements like connectors and cable assemblies. Due to the concentric outer tube of the triaxial set-up, measurements are independent of irregularities on the circumference and outer electromagnetic fields.

With the use of an additional resonator tube (inner tube respectively tube in tube), a system is created where the screening effectiveness of an electrically short device is measured in realistic and controlled conditions. Also a lower cut off frequency for the transition between electrically short (transfer impedance Z_T) and electrically long (screening attenuation a_S) can be achieved.

A wide dynamic and frequency range can be applied to test even super screened connectors and assemblies with normal instrumentation from low frequencies up to the limit of defined transversal waves in the outer circuit at approximately 4 GHz.

METALLIC COMMUNICATION CABLE TEST METHODS –

Part 4-7: Electromagnetic compatibility (EMC) – Test method for measuring of transfer impedance Z_T and screening attenuation a_s or coupling attenuation a_c of connectors and assemblies up to and above 3 GHz – Triaxial tube in tube method

1 Scope

This triaxial method is suitable to determine the surface transfer impedance and/or screening attenuation and coupling attenuation of mated screened connectors (including the connection between cable and connector) and cable assemblies. This method could also be extended to determine the transfer impedance, coupling or screening attenuation of balanced or multipin connectors and multicore cable assemblies. For the measurement of transfer impedance and screening- or coupling attenuation, only one test set-up is needed.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 62153-4-1, *Metallic communication cable test methods – Part 4-1: Electromagnetic compatibility (EMC) – Introduction to electromagnetic screening measurements*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic Compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-4, *Metallic communication cable test methods – Part 4-4: Electromagnetic compatibility (EMC) – Shielded screening attenuation, test method for measuring of the screening attenuation as up to and above 3 GHz*

IEC 62153-4-15, *Metallic communication cable test methods – Part 4-15: Electromagnetic compatibility (EMC) – Test method for measuring transfer impedance and screening attenuation – or coupling attenuation with Triaxial Cell*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 Surface transfer impedance

Z_T
for an electrically short screen, quotient of the longitudinal voltage U_1 induced to the inner circuit by the current I_2 fed into the outer circuit or vice versa, see figure 1

Note 1 to entry: The surface transfer impedance is expressed in ohms.

Note 2 to entry: The value Z_T of an electrically short screen is expressed in ohms [Ω] or decibels in relation to 1 Ω .

Note 3 to entry: See Figure 1.