

INTERNATIONAL STANDARD

IEC
62238

First edition
2003-03

Maritime navigation and radiocommunication equipment and systems – VHF radiotelephone equipment incorporating Class "D" Digital Selective Calling (DSC) – Methods of testing and required test results

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

XB

For price, see current catalogue

CONTENTS

FOREWORD	5
INTRODUCTION	6
1 Scope	7
2 Normative references.....	7
3 Terms, definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations.....	9
4 General and operational requirements	9
4.1 General	9
4.2 Composition	9
4.3 Construction	9
4.4 Controls and indicators	10
4.5 Facilities for coding and decoding of DSC.....	11
4.6 DSC display.....	12
4.7 Handset and loudspeaker	13
4.8 Safety precautions	13
4.9 Labelling.....	13
4.10 Warm up.....	14
5 Technical requirements.....	14
5.1 Switching time	14
5.2 Class of emission and modulation characteristics	14
5.3 Facilities for DSC transmission and reception	14
5.4 Ships identity – MMSI and Group IDSI.....	15
5.5 Entry of position information	15
5.6 Alarm circuits for incoming calls.....	15
5.7 Multiple watch facilities	16
5.8 Built-in test	17
6 General conditions of measurement.....	17
6.1 Arrangements for test signals applied to the receiver input	17
6.2 Squelch	17
6.3 Normal test modulation	17
6.4 Artificial antenna.....	18
6.5 Arrangements for test signals applied to the transmitter input	18
6.6 Test channels	18
6.7 Generation and examination of the digital selective call signal	18
6.8 Standard test signals for DSC.....	18
6.9 Determination of the symbol error ratio in the output of the receiving part.....	18
6.10 Measurement uncertainty and interpretation of the measured results.....	19
6.11 Test conditions, power sources, and ambient temperatures	19
6.12 Normal test conditions	20
6.13 Extreme test conditions	20
6.14 Procedure for tests at extreme temperatures	21

7	Environmental tests	21
7.1	Introduction	21
7.2	Procedure	21
7.3	Performance check	21
7.4	Vibration test	21
7.5	Temperature tests	21
8	Transmitter	22
8.1	Frequency error	22
8.2	Carrier power	22
8.3	Frequency deviation	23
8.4	Sensitivity of the modulator, including microphone	24
8.5	Audiofrequency response	24
8.6	Audiofrequency harmonic distortion of the emission	24
8.7	Adjacent channel power	25
8.8	Conducted spurious emissions conveyed to the antenna	25
8.9	Transient frequency behaviour of the transmitter	26
8.10	Residual modulation of the transmitter	28
8.11	Frequency error (DSC signal)	28
8.12	Modulation index for DSC	29
8.13	Modulation rate for DSC	29
8.14	Testing of generated call sequences	29
9	Radiotelephone receiver	30
9.1	Harmonic distortion and rated audiofrequency output power	30
9.2	Audiofrequency response	30
9.3	Maximum usable sensitivity	31
9.4	Co-channel rejection	32
9.5	Adjacent channel selectivity	32
9.6	Spurious response rejection	33
9.7	Intermodulation response	33
9.8	Blocking or desensitization	34
9.9	Spurious emissions	34
9.10	Receiver residual noise level	35
9.11	Squelch operation	35
9.12	Squelch hysteresis	36
9.13	Multiple watch characteristic	36
10	Receiver or DSC decoder	37
10.1	Maximum usable sensitivity	37
10.2	Co-channel rejection	38
10.3	Adjacent channel selectivity	38
10.4	Spurious response and blocking immunity	39
10.5	Intermodulation response	39
10.6	Dynamic range	40
10.7	Spurious emissions	40
10.8	Verification of correct decoding of various types of DSC calls	40
10.9	Reaction to VTS and AIS channel management DSC transmissions	41
10.10	Simultaneous reception	41
11	Electromagnetic compatibility	42

Annex A (normative) DSC Calls.....	48
Annex B (normative) Power measuring receiver specification.....	49
B.1 IF filter.....	49
B.2 Attenuation indicator.....	50
B.3 RMS value indicator.....	50
B.4 Oscillator and amplifier.....	50
Annex C (informative) Summary of major differences of this standard from existing regional standards.....	51
C.1 European Standard EN 301 025.....	51
C.2 American Standard RTCM Special Committee No 101.....	51
Annex D (informative) Recommended standards for equipment operating in high level electromagnetic environments.....	52
D.1 Introduction.....	52
D.2 Method of measurement.....	52
D.3 Limits.....	53
Annex E (informative) International VHF marine radio channels and frequencies.....	54
Annex F (informative) U.S. VHF marine radio channels and frequencies.....	57
Annex G (informative) CANADIAN VHF marine radio channels and frequencies.....	59
Figure 1 – Frequency deviation.....	43
Figure 2 – Audiofrequency response.....	44
Figure 3 – Test set-up for measuring transient frequency behaviour.....	45
Figure 4 – Storage oscilloscope view t_1 , t_2 and t_3	46
Figure 5 – Receiver audiofrequency response.....	47
Figure B.1 – IF filter specification.....	49
Figure D.1 – Method of measurement.....	52

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –VHF radiotelephone equipment incorporating
Class “D” Digital Selective Calling (DSC) –
Methods of testing and required test results

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides, and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62238 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/352/FDIS	80/359/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Equipment designed to this International Standard is intended to provide compatibility with the Global Maritime Distress and Safety System (GMDSS) for fitting to vessels to which the International Convention on the Safety of Life at Sea (SOLAS) 1974 does not apply. Such vessels are typically small commercial vessels, pleasure vessels, fishing vessels, etc.

The equipment does not meet all the requirements of the International Maritime Organization (IMO) for SOLAS vessels. However, it does meet the IMO guidelines for non-SOLAS vessels in that it is capable of maintaining a listening watch on VHF channel 16 simultaneously with a watch on DSC channel 70.

The equipment is further capable of both transmitting and receiving distress alerts by DSC on channel 70, thus providing for the safety of own ship together with the ability to assist other ships in distress.

The emphasis in this standard is on simplicity of operation. The VHF equipment uses DSC controllers based on Class D, which will probably be integrated in the VHF radio equipment but in any event will have the capability to select the radio channels automatically. An input for position information in IEC 61162-1 format is a requirement and the use of automatic position updating is to be encouraged.

Distress calls may only be made by means of a protected, dedicated button. Furthermore, channel 16 is required to be selected automatically after transmission of a distress or urgency call.

Position is included in the distress call either through being entered manually or with an internal GPS or an external GPS. Moreover, a DSC expansion sentence is sent after a distress alert to enhance the position resolution to better than 1 nautical mile.

Routine calls require only the input of the called MMSI and a channel number in the case of a ship to ship call. For incoming calls, the radio should be easily configured by the operator to either select automatically or manually the channel number given in the message. Means are provided for the user to enter a temporary group MMSI to permit calling amongst a group of related vessels.

The intended aim of designers of equipment to this international standard is that it should take no longer than 10 min for an operator to learn to use the equipment. This is achieved by the provision of clear simple menus with the most frequently used functions at the top of the menu tree.

As an aid to safety, it is a requirement, in order to prevent the transmission of DSC calls from an unidentifiable ship, that DSC operation is inhibited on a new equipment until the vessel's own MMSI has been entered.

Equipment designed to this standard is fitted with a 50 Ω external antenna socket or connector for use on board vessels and operates in the bands between 156 MHz and 174 MHz allocated to the maritime mobile service.

Equipment designed to this standard will not necessarily have exposed metal work which is isolated from the power supply. Earthing exposed metal work may cause a terminal of the source of electrical energy to be earthed.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

VHF radiotelephone equipment incorporating Class “D” Digital Selective Calling (DSC) – Methods of testing and required test results

1 Scope

This International Standard covers the minimum requirements for general communication for shipborne fixed installations using a VHF radiotelephone incorporating class “D” Digital Selective Calling.

These requirements include the relevant provisions of the ITU Radio Regulations, ITU-R Recommendations M.493-10 where class D is defined, and incorporate the relevant guidelines of the IMO as detailed in MSC/Circ. 803, MSC/Circ. 862 and Resolution MSC.131(75).

This standard also specifies technical characteristics, methods of measurement and required test results.

Recommended standards for equipment intended to work in high level electromagnetic environments are described and included in annex D.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IMO Resolution MSC.131(75):2002, *Maintenance of a continuous listening watch on VHF channel 16 by SOLAS ships whilst at sea and installation of VHF DSC facilities on non-SOLAS ships*

IMO MSC/Circ.803: *Participation of non-SOLAS ships in the Global Maritime Distress and Safety System (GMDSS)*

IMO MSC/Circ.862: *Clarifications of certain requirements in IMO performance standards for GMDSS equipment*

ITU Radio Regulations, Appendix S18: 1998, *Table of transmitting frequencies in the band 156 - 174 MHz for stations in the maritime mobile service*

ITU-R Recommendation M.493-10, *Digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.821-1: 1997, *Optional expansion of the digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.825-3, *Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1084-4: 2001, *Interim solutions for improved efficiency in the use of the band 156 -174 MHz by stations in the maritime mobile service*

ITU-R Recommendation M.1371-1: 2001, *Technical characteristics for a universal shipborne automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU-R Recommendation SM.332-4, *Selectivity of receiver*

ITU-T Recommendation E.161, *Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network*

ITU-T Recommendation P.53: 1994, *Psophometer for use on telephone-type circuits*