

INTERNATIONAL STANDARD

IEC 62286

First edition
2003-05

Service diagnostic interface for consumer electronics products and networks Implementation for IEEE 1394

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

R

For price, see current catalogue

CONTENTS

FOREWORD	3
INTRODUCTION	4
1 Scope	5
2 Normative references.....	5
3 Terms, definitions and abbreviations.....	6
3.1 Terms and definitions	6
3.2 Abbreviations.....	7
4 Different types of service diagnostics.....	8
4.1 Stand-alone products.....	8
4.2 A/V or multimedia network	8
4.3 Remote diagnosis	8
5 Specification of the SDI	8
5.1 General	8
5.2 Hardware.....	8
5.2.1 Tester hardware requirements	8
5.2.2 Connection cable	8
5.2.3 Device Under Test (DUT) hardware requirements	9
5.3 Software	9
5.3.1 General.....	9
5.3.2 Tester software requirements.....	9
5.3.3 DUT software requirements for the SDI.....	10
6 Tester software requirements.....	10
6.1 Interface to manufacturer service program.....	10
6.2 Connecting the diagnostic	10
6.3 Product identification	11
6.3.1 General information (company identification)	11
6.3.2 Company specific information	11
6.3.3 Product specific information.....	11
7 Control protocol.....	11
7.1 Direct diagnosis.....	11
7.1.1 Configuration ROM directory structure	11
7.2 Remote diagnosis.....	16
Annex A (informative) User interface.....	17
Figure A.1 – Example of device list	18
Figure A.2 – Example of device properties	19
Table 1 – Root directory.....	12
Table 2 – Instance directory	14
Table 3 – EACEM unit directory	14

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SERVICE DIAGNOSTIC INTERFACE FOR CONSUMER
ELECTRONICS PRODUCTS AND NETWORKS –
Implementation for IEEE 1394**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. In this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations cooperating with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they also accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62286 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

This standard was developed by a project team of service and interface specialists within the European Association of Consumer Electronics Manufacturers (EACEM). EACEM subsequently merged with EICTA in September 2001. EICTA is the European Information, Communications and Consumer Electronics Technology Industry Association.

The text of this standard is based on the following documents:

CDV	Report on voting
100/432/CDV	100/493A/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

Consumer products are often repaired by service workshops who are servicing all kinds of products developed by different manufacturers.

For high complexity products, the fault diagnosis becomes more and more difficult and time consuming. To make diagnosis possible, manufacturers often develop some built-in diagnostic software which can be used for fault finding together with an external diagnostic unit through a Service Diagnostic Interface (SDI).

To avoid the need for a service workshop to purchase several different diagnostic units from different manufacturers for different products, a standardized SDI is proposed for use by all manufacturers and in all products in which such diagnostic interfaces are required. The result will be that only one SDI is needed in the service workshops.

The SDI should also be suitable for diagnosis in a network (A/V or multimedia network) in which different products from different manufacturers are connected together. The interface should also allow for future development.

The standard SDI which has to be specified, should:

- be usable in future products;
- be easily connectable to a product or a network;
- be cheap;
- not limit product design.

SERVICE DIAGNOSTIC INTERFACE FOR CONSUMER ELECTRONICS PRODUCTS AND NETWORKS – Implementation for IEEE 1394

1 Scope

This International Standard specifies the requirements that have to be implemented in future products that incorporate a digital interface, and service diagnostic software developed for these products. The Service Diagnostic Interface (SDI) requires the use of a PC (desktop or laptop) into which service diagnostic software can be loaded. A part of this PC software has to be standardised while another part of this PC software is manufacturer/product related.

To reach a common approach in servicing all products from all manufacturers, it is necessary to standardise specific items in the products (Device Under Test/DUT) as well as in the diagnostic software on the PC.

The Service Diagnostic Interface (SDI) is based on the IEEE 1394:1995 specification because this interface will be used in most future products. The use of this connection and existing communication protocols enable implementation in products at low costs, and gives maximum flexibility and efficiency.

The SDI consists of:

- Specific hardware and software requirements of the DUT.
- Specific requirements of the PC:
 - the Service software,
 - an IEEE 1394 interface (to be built in if not already present).
- The connection between the PC and the DUT.

This specification is a minimal specification necessary to be able to carry out computerised diagnosis and covers the standardised software of the PC as well as the standardised software and provisions in the DUT.

If an IEEE 1394 interface is present on the product, then the requirement for product identification as described in this document (see 6.3) is mandatory. In addition, all communication for any service application should go through the IEEE 1394 interface only, as described in this document (in Clause 7).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61883-1:2003, *Consumer audio/video equipment – Digital Interface – Part 1: General*

IEEE 1212:2001, *Microprocessor Systems – Control and Status Registers (CSR): Architecture for microcomputer buses*

IEEE 1394:1995, *IEEE Standard for a High Performance Serial Bus – Firewire*

IEEE 1394a:2000, *IEEE Standard for a High Performance Serial Bus – Amendment 1*