

INTERNATIONAL STANDARD

IEC
62287-1

First edition
2006-03

Maritime navigation and radiocommunication equipment and systems – Class B shipborne equipment of the automatic identification system (AIS) –

Part 1: Carrier-sense time division multiple access (CSTDMA) techniques

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

XC

For price, see current catalogue

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references.....	8
3 Abbreviations.....	9
4 General requirements.....	10
4.1 General.....	10
4.2 Manuals.....	12
4.3 Marking and identification.....	12
5 Environmental, power supply, interference and safety requirements.....	12
6 Performance requirements.....	13
6.1 Composition.....	13
6.2 Operating frequency channels.....	13
6.3 GNSS receiver for position reporting.....	13
6.4 Identification.....	14
6.5 AIS information.....	14
6.6 Alarms and indications, fall-back arrangements.....	15
6.7 User interface.....	17
7 Technical requirements.....	17
7.1 General.....	17
7.2 Physical layer.....	18
7.3 Link layer.....	21
7.4 Network layer.....	36
7.5 Transport layer.....	38
7.6 Digital Selective Calling (DSC).....	38
8 Test conditions.....	38
8.1 General.....	38
8.2 Normal and extreme test conditions.....	38
8.3 Test signals.....	39
8.4 Test arrangements.....	40
9 Power supply, environmental and EMC tests.....	42
9.1 Test summary.....	42
9.2 Vibration/shock.....	43
9.3 Performance tests/checks.....	44
9.4 Undervoltage test (brown out).....	44
10 Operational tests.....	45
10.1 General.....	45
10.2 Modes of operation.....	45
10.3 Messages extending one time period.....	48
10.4 Channel selection.....	48
10.5 Internal GNSS receiver.....	49
10.6 AIS information.....	49
10.7 Initialisation period.....	52
10.8 Alarms and indications, fall-back arrangements.....	52
10.9 User interface.....	53

11	Physical tests	55
11.1	TDMA transmitter	55
11.2	TDMA receivers	59
11.3	Conducted spurious emissions	66
12	Specific tests of link layer	67
12.1	TDMA synchronisation	67
12.2	Carrier-sense tests	68
12.3	VDL state/reservations	70
12.4	Data encoding (bit stuffing)	70
12.5	Frame check sequence	71
12.6	Slot allocation (channel access protocol)	71
12.7	Assigned operation	72
12.8	Message formats	73
13	Specific tests of network layer	74
13.1	Regional area designation by VDL message	74
13.2	Regional area designation by serial message or manually	75
13.3	Management of received regional operating settings	75
	Annex A (informative) Results of computer simulations and testing of CSTDMA technology ..	78
	Annex B (informative) Description of the system	81
	Annex C (normative) DSC channel management	82
	Annex D (informative) Channel management regions	89
	Figure 1 – OSI layer model	18
	Figure 2 – Carrier-Sense timing	22
	Figure 3 – Power versus time mask	23
	Figure 4 – Transmission packet	24
	Figure 5 – Training sequence	26
	Figure 6 – Transmission timing	28
	Figure 7 – Example for CS/TDMA access	29
	Figure 8 – Format for repeating four-packet cluster	40
	Figure 9 – Measurement arrangement for carrier power	55
	Figure 10 – Emission mask	56
	Figure 11 – Measurement arrangement for modulation accuracy	57
	Figure 12 – Measurement arrangement	59
	Figure 13 – Measurement arrangement with two generators	60
	Figure 14 – SINAD or PER/BER Measuring Equipment	62
	Figure 15 – Measurement arrangement for intermodulation	64
	Figure 16 – Configuration for Carrier-Sense threshold test	69
	Figure 17 – Regional area scenario	74
	Figure A.1 – Effect on Class A AIS messages of Class B messages	78
	Figure A.2 – Reception of messages by Class A AIS	79
	Figure A.3 – Reception of messages by Class B AIS	79
	Figure A.4 – Range achieved by a Class A AIS from Class B AIS	80
	Figure D.1 – Channel management regions used for test given in 13.3.1	89

Table 1 – Position sensor fallback conditions.....	16
Table 2 – Use of accuracy (PA) flag.....	16
Table 3 – Transceiver characteristics.....	19
Table 4 – Transmitter parameters.....	20
Table 5 – Receiver parameters.....	21
Table 6 – Definition of timings for Figure 3.....	23
Table 7 – Start-buffer.....	25
Table 8 – Summary of the transmission packet.....	27
Table 9 – Transmission timing.....	27
Table 10 – Access parameters.....	29
Table 11 – Use of VDL messages by a Class B"CS" AIS.....	32
Table 12 – Number of data bits for use with Message 14.....	33
Table 13 – Contents of Message 18.....	33
Table 14 – Message 24 Part A:.....	34
Table 15 – Message 24 Part B:.....	35
Table 16 – Contents of Message 23.....	35
Table 17 – Reporting Interval Settings for use with Message 23.....	36
Table 18 – Channel management.....	37
Table 19 – Content of first two packets.....	40
Table 20 – Fixed PRS data derived from ITU-T.O.153.....	40
Table 21 – Test summary.....	42
Table 22 – Peak frequency deviation versus time.....	58
Table 23 – Frequencies for inter-modulation test.....	65
Table 24 – Required threshold test results.....	69
Table 25 – Required carrier sense timing results.....	70
Table 26 – Required channels in use.....	75
Table C.1 – DSC monitoring tones.....	83

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
CLASS B SHIPBORNE EQUIPMENT OF THE
AUTOMATIC IDENTIFICATION SYSTEM (AIS) –**

**Part 1: Carrier-sense time division multiple access
(CSTDMA) techniques**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62287-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/426/FDIS	80/434/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 62287 consists of the following parts, under the general title *Maritime navigation and radiocommunication and systems – Class B shipborne equipment of the automatic identification system (AIS)*

Part 1: Carrier-sense time division multiple access (CSTDMA) techniques

Part 2: Self-organising time division multiple access (SOTDMA) techniques

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Currently in preview, click buy full vers.

INTRODUCTION

In the ITU Radiocommunications Sector Recommendation ITU-R M.1371-1 "Technical characteristics for a universal shipborne Automatic Identification System (AIS) using SOTDMA (Self-Organising Time Division Multiple Access) in the VHF maritime mobile band", provision is made for a Class B AIS for use on craft not covered by a mandatory carriage requirement under SOLAS Chapter V, Regulation 19. This part of IEC 62287 sets out the requirements, methods of test and required test results for such a Class B AIS.

The International Maritime Organization (IMO), in its Resolution MSC.140(76), recognised that the radio channels used by AIS, particularly AIS 1 (161,975 MHz) and AIS 2 (162,025 MHz), are regarded as an AIS network, and any disruption to those channels by any one AIS device could affect the operation of all AIS devices on that network. IMO also recognised that Administrations should take steps necessary to ensure the integrity of the radio channels used for AIS in their waters.

IEC Technical Committee 80 (TC 80) allocated a new work item 80/287/NP to Working Group 8a (WG 8a), tasking them with producing a test standard for Class B AIS equipment. During the development of this test standard, Administrations expressed concern that large numbers of Class B AIS equipped vessels could have a detrimental effect on the safe operation of the AIS network by SOLAS Class A vessels, Base Stations and AIS on board to Navigation (AtoN AIS). As a result, a new network access technology was developed, which allows large numbers of Class B fitted vessels to coexist with Class A with a negligible detrimental effect on AIS network.

The new technology, hereinafter referred to as "Carrier Sense TDMA (CSTDMA)", requires that the Class B "CS" AIS listens to the AIS network to determine if the network is free of activity and, only if the network is free, can it transmit its information. This Class B AIS is also required to listen for reservations from base stations and comply with these reservations. This polite operation ensures that this Class B AIS minimises the probability of interference with Class A, Base Station or AtoN AIS operations. Extensive computer models simulation and practical laboratory testing and sea trials were undertaken to validate CSTDMA during its development (see Annex A).

WG8a recognised that the primary function of a Class B AIS is for fitted vessels to be visible and participate in the AIS network. CSTDMA was designed to fulfil these requirements.

This Class B AIS is backward compatible with ITU-R Recommendation M.1371-1 (see Annex B).

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
CLASS B SHIPBORNE EQUIPMENT OF THE
AUTOMATIC IDENTIFICATION SYSTEM (AIS) –**

**Part 1: Carrier-sense time division multiple access
(CSTDMA) techniques**

1 Scope

This part of IEC 62287 specifies the minimum operational and performance requirements, methods of testing and required test results for Class B shipborne AIS equipment using CSTDMA techniques. This standard takes into account other associated IEC International Standards and existing national standards, as applicable.

It is applicable for AIS equipment used on craft that are not covered by the mandatory carriage requirement of AIS under SOLAS Chapter V.

An AIS station intended to operate in receive-only mode shall not be considered a Class B shipborne mobile AIS station.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108-1, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 1: Global positioning system (GPS) – Receiver equipment – Performance standards, methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61993-1, *Maritime navigation and radiocommunication equipment and systems – Part 1: Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques – Operational and performance requirements, methods of testing and required test results*

IEC 61993-2, *Maritime navigation and radiocommunication equipment and systems – Automatic identification systems (AIS) – Part 2: Class A shipborne equipment of the universal automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results*

ISO/IEC 3309:1993, *Information technology – Telecommunications and information exchange between systems – High-level data link control (HDLC) procedures – Frame structure*

IMO MSC.140(76), *Recommendation for the protection of the AIS VHF data link*

ITU-R Recommendation M.493-11, *Digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.825-3, *Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1084-4, *Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service*

ITU-R Recommendation M.1371-1, *Technical characteristics for a universal shipborne automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU-T Recommendation O.153, *Basic parameters for the measurement of error performance at bit rates below the primary rate*

Currently in preview, click buy full version