

INTERNATIONAL STANDARD

IEC
62447-1

First edition
2007-06

**Helical-scan compressed digital video cassette
system using 6,35 mm magnetic tape –
Format D-12 –**

**Part 1:
VTR specifications**



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XC**

For price, see current catalogue

CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references	9
3 Abbreviations and acronyms.....	10
4 Environment and test conditions	10
4.1 Environment.....	10
4.2 Reference tape.....	11
4.3 Calibration tapes	11
4.3.1 Tape.....	11
4.3.2 Record locations and dimensions	11
4.3.3 Calibration signals	11
5 Tape.....	11
5.1 Base.....	11
5.2 Width	11
5.3 Width fluctuation	11
5.4 Reference edge straightness.....	11
5.5 Tape thickness	12
5.6 Transmissivity	12
5.7 Offset yield strength	12
5.8 Magnetic coating	12
5.9 Coating coercivity.....	12
6 Helical recordings.....	12
6.1 Tape speed	12
6.2 Sectors.....	12
6.3 Record location and dimension	12
6.4 Helical track record tolerance zones.....	13
6.5 Relative positions of recorded information	13
6.5.1 Relative positions of longitudinal tracks	13
6.5.2 Programme area reference point	13
6.6 Gap azimuth.....	18
6.6.1 Cue and control track	18
6.6.2 Helical track	18
6.7 Transport and scanner	18
7 Programme track data	22
7.1 General.....	22
7.1.1 Introduction	22
7.1.2 Labeling convention.....	22
7.1.3 Signal processing	23
7.1.4 Magnetization.....	32
7.2 Insert and track information (ITI) sector.....	32
7.2.1 Structure	32
7.2.2 ITI preamble	32
7.2.3 Start sync area (SSA).....	32
7.2.4 Track information area (TIA).....	39
7.2.5 ITI postamble	40

7.3	Audio sector	41
7.3.1	Structure	41
7.3.2	Audio pre and post-amble	41
7.3.3	Audio sync block	41
7.4	Video sector	45
7.4.1	Structure	45
7.4.2	Video pre and post-amble	46
7.4.3	Video sync block	46
7.5	Subcode sector	48
7.5.1	Structure	48
7.5.2	Subcode preamble and postamble	49
7.5.3	Subcode sync block	49
7.6	Edit gap	51
8	Audio processing	51
8.1	Introduction	51
8.2	Encoding mode	52
8.2.1	Source coding	52
8.2.2	Emphasis	52
8.2.3	Audio error code	52
8.2.4	Relative audio-video timing	52
8.2.5	Audio frame processing	52
8.3	Audio shuffling	54
8.4	Audio auxiliary data (AAUX)	55
8.4.1	AAUX source pack (AS)	56
8.4.2	AAUX source control pack (ASC)	57
8.5	Error correction code addition	58
8.5.1	Inner error correction code	58
8.5.2	Outer error correction code	58
9	Video processing	60
9.1	Introduction	60
9.2	Compressed macro block and data-sync block	60
9.3	Video auxiliary data (VAUX)	62
9.3.1	VAUX source pack (VS)	63
9.3.2	VAUX source control pack (VSC)	64
9.4	Error correction code addition	66
9.4.1	Inner error correction code	66
9.4.2	Outer error correction code	66
10	Subcode processing	67
10.1	Introduction	67
10.2	Subcode data	67
10.2.1	Time code pack (TC)	69
10.2.2	Binary group pack (BG)	69
10.3	Error correction code addition	70
11	Longitudinal tracks	71
11.1	Control track	71
11.1.1	Method of recording	71
11.1.2	Servo reference pulse	71
11.1.3	Flux polarity	71

11.1.4 Flux level.....	71
11.1.5 Pulse width.....	71
11.1.6 Servo reference pulse timing.....	71
11.1.7 Colour frame indication.....	71
11.2 Cue track.....	72
11.2.1 Method of recording.....	72
11.2.2 Flux level.....	72
11.2.3 Relative timing.....	72
Annex A (normative) Tape tension.....	73
Annex B (normative) Track pattern during insert editing.....	74
Annex C (normative) Cross-tape track measurement technique.....	75
Annex D (informative) Relationship between tape length and recording time.....	78
Annex E (informative) Interface.....	79
Bibliography.....	81
Figure 1 – Location and dimensions of recorded tracks.....	14
Figure 2 – Location of recorded cue and control track.....	15
Figure 3 – Location and dimensions of tolerance zone of recorded helical tracks.....	18
Figure 4 – Possible scanner configuration and tape wrap for four-head construction.....	20
Figure 5 – Possible scanner configuration and tape wrap for eight-head construction.....	21
Figure 6 – Possible recording system configuration (informative).....	23
Figure 7 – Sector arrangement on helical track.....	23
Figure 8 – Modulation for audio sector.....	24
Figure 9 – Modulation for video sector.....	25
Figure 10 – Modulation for subcode sector.....	26
Figure 11 – Possible block diagram for signal processing.....	27
Figure 12 – Bit stream before interleaved NRZI modulation.....	29
Figure 13 – Frequency characteristics of tracks.....	29
Figure 14 – Frequency characteristics of tracks (detail).....	30
Figure 15 – Pre-coding.....	31
Figure 16 – Structure of ITI sector.....	33
Figure 17 – Structure of audio sector.....	41
Figure 18 – Structure of sync blocks in audio sector.....	42
Figure 19 – Structure of video sector.....	46
Figure 20 – Structure of sync blocks in video sector.....	47
Figure 21 – Structure of subcode sector.....	48
Figure 22 – Structure of sync blocks in subcode sector.....	50
Figure 23 – Video and audio frame for the 1080/60i system.....	53
Figure 24 – Video and audio frame for the 1080/50i system.....	53
Figure 25 – Video and audio frame for the 720/60p system.....	54
Figure 26 – Sample to audio data bytes conversion.....	55
Figure 27 – Arrangement of AAUX packs in audio auxiliary data.....	55

Figure 28 – Data and inner parity of a data sync block.....	59
Figure 29 – Data and outer parity of a data sync block for audio sector	59
Figure 30 – Arrangement	63
Figure 31 – Data and outer parity of a data sync block for video sector.....	67
Figure 32 – Arrangement of subcode data	68
Figure 33 – Bit assignment for subcode data and parity	70
Figure 34 – Recorded control code waveform timing for the 60-Hz system.....	71
Figure 35 – Recorded control code waveform timing for the 50 Hz system	72
Figure B.1 – Typical track pattern during insert editing	74
Figure C.1 – Correction factors (actual tape speed, tension).....	7
Figure C.2 – Track location error plot (example)	77
Figure C.3 – Cross-tape measurement technique.....	77
Figure E.1 – Block diagram of HD recorder	80
Table 1 – Record location and dimensions for the 60-Hz system.....	16
Table 2 – Record location and dimensions for the 50-Hz system.....	17
Table 3 – Parameters for a possible scanner design.....	19
Table 4 – Servo information	31
Table 5 – Bit stream of ITI preamble for servo information F_0	33
Table 6 – Bit stream of ITI preamble for servo information F_1	34
Table 7 – Bit stream of ITI preamble for servo information F_2	35
Table 8 – Bit stream of SSA for servo information F_0	36
Table 9 – Bit stream of SSA for servo information F_1	37
Table 10 – Bit stream of SSA for servo information F_2	38
Table 11 – Bit stream of TIA for servo information F_0	39
Table 12 – Bit stream of TIA for servo information F_1	39
Table 13 – Bit stream of TIA for servo information F_2	39
Table 14 – Bit stream of ITI post-amble for servo information F_0	40
Table 15 – Bit stream of ITI post-amble for servo information F_1	40
Table 16 – Bit stream of ITI post-amble for servo information F_2	40
Table 17 – ID data in audio sector	43
Table 18 – Audio application ID	43
Table 19 – Track pair number	44
Table 20 – Bit assignment of ID codewords	45
Table 21 – ID data in video sector	47
Table 22 – Video application ID	48
Table 23 – ID data in subcode sector	50
Table 24 – Subcode application ID.....	51
Table 25 – AAUX data	56
Table 26 – Mapping of AAUX source pack	56
Table 27 – Mapping of AAUX source control pack.....	57
Table 28 – Relation between the compressed macro block number and the data-sync block for the 60 Hz system.....	61

Table 29 – Relation between the compressed macro block number and the data-sync block for the 50 Hz system.....	62
Table 30 – VAUX data	63
Table 31 – Mapping of VAUX source pack	63
Table 32 – Mapping of VAUX source control pack.....	64
Table 33 – FF/FS for the 1080-line system.....	65
Table 34 – FF/FS for the 720-line system	65
Table 35 – Mapping of subcode pack.....	68
Table 36 – Mapping of time code pack.....	69
Table 37 – Mapping of a binary group pack.....	70
Table C.1 – Nomenclature and calculation of track location error.....	76
Table D.1 – Tape length, thickness, and recording time	78

Currently in preview, click buy full version.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HELICAL-SCAN COMPRESSED DIGITAL VIDEO CASSETTE
SYSTEM USING 6,35 mm MAGNETIC TAPE –
FORMAT D-12 –**

Part 1: VTR specifications

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62447-1 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
100/1091/CDV	100/1186/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 62447-1 series, under the general title *Helical-scan compressed digital video cassette system using 6,35 mm magnetic tape – Format D-12*, can be found on the IEC website.

This Part 1 describes the VTR specifications which are tape, magnetization, helical recording, modulation method and basic system data for video compressed data.

Part 2 describes the specifications for encoding process and data format for 1080i, 1080p and 720p systems.

Part 3 describes the specifications for transmission of DV-based compressed video and audio data stream over 360 Mb/s serial digital interface.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

HELICAL-SCAN COMPRESSED DIGITAL VIDEO CASSETTE SYSTEM USING 6,35 mm MAGNETIC TAPE – FORMAT D-12 –

Part 1: VTR specifications

1 Scope

This part of IEC 62447 specifies the content, format, and recording method of the data blocks containing video, audio, and associated data which form the helical records on 6,35-mm tape in cassettes as specified in SMPTE 307M.

In addition, this standard specifies the content, format, and recording method for longitudinal cue and control tracks.

One compressed video channel, eight independent audio channels and subcode data are recorded on tape in the digital form. Each of these channels is capable of independent editing.

On the following digital video formats, the helical recordings are synchronized to:

- 1080 line/59,94 Hz field frequency;
- 1080 line/50 Hz field frequency;
- 720 line/59,94 Hz frame frequency.

These are hereafter referred to as the 1080/60i, 1080/50i, and 720/60p systems, respectively. Similarly, in this standard, the 60 Hz system nomenclature refers to both 1080/60i and 720/60p systems, whereas, the 50 Hz system refers only to the 1080/50i system. Nomenclature 1080 line system refers to both 1080/60i and 1080/50i systems, while the 720 line system refers only to the 720/60p system.

The recorded digital video signal shall be compressed according to the DV-based 100 Mb/s specification.

The recorded digital video signal, eight audio channels and subcode data shall be defined by the data structure according to the DV-based 100 Mb/s specification.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62447-2, *Helical-scan compressed digital videocassette system using 6,35 mm magnetic tape – Format D-12 – Part 2: Compression format*

SMPTE 12M:1999, Television, Audio and Film – Time and Control Code

SMPTE 276M:1995, Television – Transmission of AES-EBU Digital Audio Signals Over Coaxial Cable

SMPTE 292M:1998, Television – Bit-Serial Digital Interface for High-Definition Television Systems

AES3-1992(R1997), Serial transmission format for two-channel linearly represented digital audio data