

# FINAL VERSION

# VERSION FINALE



**Household refrigerating appliances – Characteristics and test methods –  
Part 3: Energy consumption and volume**

**Appareils de réfrigération à usage ménager – Caractéristiques et méthodes  
d'essai –  
Partie 3: Consommation d'énergie et volume**

## CONTENTS

FOREWORD.....	8
INTRODUCTION.....	11
1 Scope.....	12
2 Normative references .....	12
3 Terms, definitions and symbols.....	12
3.1 Terms and definitions.....	12
3.2 Symbols.....	13
4 Applicable test steps for determination of energy and volume.....	13
4.1 Setup for energy testing.....	13
4.2 Steady state power consumption.....	13
4.3 Defrost and recovery energy and temperature change .....	13
4.4 Defrost frequency .....	13
4.5 Number of test points and interpolation.....	13
4.6 Load processing efficiency.....	14
4.7 Specified auxiliaries.....	14
4.8 Volume determination .....	14
5 Target temperatures for energy determination .....	14
5.1 General.....	14
5.2 Temperature control settings for energy consumption test .....	15
6 Determination of energy consumption.....	15
6.1 General.....	15
6.2 Objective .....	16
6.3 Number of test runs .....	17
6.4 Steady state power consumption.....	17
6.5 Defrost and recovery energy and temperature change .....	17
6.6 Defrost interval .....	18
6.7 Specified auxiliaries.....	18
6.8 Calculation of energy consumption .....	18
6.8.1 General.....	18
6.8.2 Daily energy consumption.....	18
6.8.3 Interpolation .....	19
6.8.4 Specified auxiliaries.....	19
6.8.5 Total energy consumption.....	20
7 Circumvention devices.....	20
8 Uncertainty of measurement.....	21
9 Test report.....	21
Annex A (normative) Set up for energy testing.....	22
A.1 General.....	22
A.2 Additional set up requirements for energy testing.....	22
A.2.1 Ice making trays .....	22
A.2.2 User adjustable controls .....	22
A.2.3 Ambient temperature .....	22
A.2.4 Accessories and shelves .....	22
A.2.5 Anti-condensation heaters .....	23
A.2.6 Automatic icemakers – ice storage bins .....	23

Annex B (normative) Determination of steady state power and temperature .....	26
B.1 General.....	26
B.2 Setup for testing and data collection .....	26
B.3 Case SS1: no defrost control cycle or where stability is established for a period between defrosts .....	26
B.3.1 Case SS1 approach.....	26
B.3.2 Case SS1 acceptance criteria.....	29
B.3.3 Case SS1 calculation of values.....	30
B.4 Case SS2: steady state determined between defrosts .....	30
B.4.1 Case SS2 approach.....	30
B.4.2 Case SS2 acceptance criteria.....	32
B.4.3 Case SS2 calculation of values.....	33
B.5 Correction of steady state power.....	34
Annex C (normative) Defrost and recovery energy and temperature change .....	36
C.1 General.....	36
C.2 Setup for testing and data collection .....	36
C.3 Case DF1: where steady state operation can normally be established before and after defrosts.....	37
C.3.1 Case DF1 approach.....	37
C.3.2 Case DF1 acceptance criteria.....	39
C.3.3 Case DF1 calculation of values.....	40
C.4 Number of valid defrost and recovery periods .....	42
C.5 Calculation of representative defrost energy and temperature.....	42
Annex D (normative) Defrost interval .....	44
D.1 General.....	44
D.2 Elapsed time defrost controllers.....	44
D.3 Compressor run time defrost controllers.....	45
D.4 Variable defrost controllers.....	47
D.4.1 General .....	47
D.4.2 Variable defrost controllers – declared defrost intervals.....	47
D.4.3 Variable defrost controllers – no declared defrost intervals (demand defrost).....	48
D.4.4 Variable defrost controllers – non compliant .....	48
Annex E (normative) Interpolation of results.....	50
E.1 General.....	50
E.2 Temperature adjustment prior to interpolation .....	51
E.3 Case 1: linear interpolation – two test points.....	51
E.3.1 General .....	51
E.3.2 Requirements .....	51
E.3.3 Calculations.....	51
E.4 Case 2: triangulation – three (or more) test points.....	55
E.4.1 General .....	55
E.4.2 Requirements for two (or more) compartment triangulation .....	56
E.4.3 Calculations for two compartment triangulation – manual interpolation .....	59
E.4.4 Calculations for two compartment triangulation – matrices.....	60
E.4.5 Checking temperature validity where there are more than two compartments for triangulation.....	62
E.4.6 Calculations for three compartment triangulation – matrices .....	63
Annex F (normative) Energy consumption of specified auxiliaries .....	67

F.1	Purpose .....	67
F.2	Ambient controlled anti-condensation heaters .....	67
F.2.1	Outline of the method .....	67
F.2.2	Measurement procedure .....	67
F.2.3	Data requirements .....	68
F.2.4	Regional weather data .....	68
F.2.5	Calculation of power consumption .....	68
F.2.6	Where anti-condensation heater(s) cannot be disabled but their power consumption can be measured directly .....	69
F.2.7	Where anti-condensation heater(s) cannot be disabled and their power consumption cannot be measured directly .....	70
F.2.8	Where anti-condensation heater(s) has a user-adjustable setting .....	70
F.3	Automatic icemakers – energy to make ice .....	70
F.3.1	General .....	70
F.3.2	Tank type automatic icemakers .....	70
Annex G (normative)	Determination of load processing efficiency .....	77
G.1	Purpose .....	77
G.2	General description .....	77
G.3	Setup, equipment and preparation .....	78
G.3.1	General .....	78
G.3.2	Equipment .....	79
G.3.3	Quantity of water to be processed .....	79
G.3.4	Position of the water load in compartment .....	80
G.3.5	Temperature of the water to be processed .....	83
G.4	Load processing efficiency test method .....	84
G.4.1	Commencement of the load processing efficiency test .....	84
G.4.2	Placement of the load .....	84
G.4.3	Measurements to be taken .....	85
G.4.4	Conclusion of load processing efficiency test .....	85
G.5	Determination of load processing efficiency .....	86
G.5.1	General .....	86
G.5.2	Quantification of input energy .....	87
G.5.3	Quantification of additional energy used to process the load .....	88
G.5.4	Load processing efficiency .....	90
G.5.5	Load processing multiplier .....	90
G.5.6	Addition of user related loads into daily energy .....	91
Annex H (normative)	Determination of volume .....	94
H.1	Scope .....	94
H.2	Total volume .....	94
H.2.1	Volume measurements .....	94
H.2.2	Determination of volume .....	94
H.2.3	Volume of evaporator space .....	95
H.2.4	Two-star sections and/or compartments .....	95
H.3	Key for Figures H.1 through H.5 .....	95
H.4	Calculation of the volume of the section or sub-compartment in the compartment whose target temperatures are different from each other .....	98
Annex I (informative)	Worked examples of energy consumption calculations .....	101
I.1	Example calculation of daily energy consumption .....	101
I.2	Variable defrost – calculation of defrost intervals .....	102

I.3	Examples of Interpolation.....	103
I.3.1	General .....	103
I.3.2	Linear interpolation.....	103
I.3.3	Two compartments – manual triangulation.....	112
I.3.4	Two compartments – triangulation using matrices.....	116
I.3.5	Three compartments – triangulation using matrices.....	118
I.4	Calculating the energy impact of internal temperature changes.....	120
I.4.1	General .....	120
I.4.2	One compartment.....	120
I.4.3	Triangulation .....	121
I.5	Automatically controlled anti-condensation heater(s).....	122
I.6	Calculation of load processing efficiency.....	124
I.7	Determination of annual energy consumption.....	126
I.8	Examples of determination of power and temperature from raw data.....	127
I.8.1	Manual review of data.....	127
I.8.2	Review of data and selection of minimum spread using bespoke software.....	147
Annex J (informative)	Development of the IEC global test method for refrigerating appliances.....	149
J.1	Purpose.....	149
J.2	Overview.....	149
J.3	Test method objective.....	149
J.4	Description of key components of energy consumption.....	150
Annex K (normative)	Analysis of a refrigerating appliance without steady state between defrosts.....	152
K.1	Purpose.....	152
K.2	Products with regular characteristics but without steady state operation.....	152
K.2.1	General.....	152
K.2.2	Special case DF2 approach.....	152
K.2.3	Case DF2 acceptance criteria.....	153
K.2.4	Case DF2 calculation of values.....	153
Annex L (informative)	Derivation of ambient temperature correction formula.....	155
L.1	Purpose.....	155
L.2	Background.....	155
L.3	Approach.....	156
Figure B.1	Illustration of a test period made of blocks of 5 temperature control cycles – temperature for Case SS1.....	27
Figure B.2	Illustration of a test period made of blocks of 5 temperature control cycles – power for Case SS1.....	28
Figure B.3	Case SS2 – typical operation of a refrigerating appliance with a defrost control cycle.....	31
Figure C.1	Conceptual illustration of the additional energy associated with a defrost and recovery period.....	37
Figure C.2	Case DF1 with steady state operation before and after a defrost.....	38
Figure E.1	Interpolation where temperatures change in multiple compartments (compartment D critical).....	54
Figure E.2	Interpolation with valid results in both Compartment A and B.....	54
Figure E.3	Interpolation with no valid results.....	55

Figure E.4 – Schematic representation of interpolation by triangulation .....	57
Figure G.1 – Conceptual illustration of the load processing efficiency test .....	78
Figure G.2 – Shelf locations and loading sequence (example showing 10 PET bottles).....	81
Figure G.3 – Ice cube tray locations and clearances .....	83
Figure G.4 – Representation of the additional energy to process the added load .....	87
Figure G.5 – Case where a defrost and recovery period occurs during load processing .....	89
Figure H.1 – Basic view of top mounted freezer appliance .....	96
Figure H.2 – Automatic ice-maker dispenser and chute.....	97
Figure H.3 – Automatic ice-making compartment .....	97
Figure H.4 – Rail of drawer type shelves or baskets.....	98
Figure H.5 – Rotary divider of fresh food compartment for French Doors .....	98
Figure H.6 – Part with partition in the freezer is a two-star compartment (or a chill compartment next to a fresh food compartment) .....	99
Figure H.7 – Part without partition next to the freezer or fresh food compartment is a two-star compartment or a chill compartment, respectively .....	99
Figure H.8 – Freezer door shelves are a two-star section .....	99
Figure H.9 – Drawer in the freezer is a two-star section (or a chill section compartment in a fresh food compartment) .....	100
Figure H.10 – Space between a door shelf and drawer-type two star section .....	100
Figure I.1 – Example linear interpolation two compartment (Compartment B critical) .....	105
Figure I.2 – Example linear interpolation two compartment (Compartment B critical) .....	106
Figure I.3 – Example Interpolation where both test points have both compartments below target (two valid results) .....	107
Figure I.4 – Example Interpolation where both test points have both compartments below target (two valid results) .....	108
Figure I.5 – Example Interpolation where neither test point has both compartments below target (no valid results).....	109
Figure I.6 – Example Interpolation where neither test point has both compartments below target (no valid results) .....	110
Figure I.7 – Example Interpolation for 4 compartments .....	112
Figure I.8 – Example of triangulation (temperatures).....	114
Figure I.9 – Example of triangulation (temperature and energy) .....	115
Figure I.10 – An example of power and temperature data .....	128
Figure I.11 – Example of finding a test period with minimum spread in power .....	148
Figure K.1 – Special Case SS2 – where steady state operation is never reached between defrost and recovery periods and Annex C stability may not be established .....	152
Table A.1 – Target temperatures for energy determination by compartment type.....	15
Table B.1 – Assumed $\Delta COP$ adjustment.....	35
Table F.1 – Format for temperature and humidity data – ambient controlled anti-condensation heaters.....	69
Table I.1 – Example of linear interpolation, single compartment.....	103
Table I.2 – Example 1 of linear interpolation, two compartments .....	104
Table I.3 – Example 2 of linear interpolation, two compartments .....	106
Table I.4 – Example 3 of linear interpolation, two compartments .....	108
Table I.5 – Example of linear interpolation, test data for four compartments.....	110

Table I.6 – Example of linear interpolation, results for four compartments.....	112
Table I.7 – Example of triangulation, two compartments.....	113
Table I.8 – Example of triangulation, three compartments.....	118
Table I.9 – Example of population-weighted humidity probabilities and heater wattages at 16 °C, 22 °C and 32 °C.....	123
Table I.10 – An example of calculation of energy, power and temperature for each temperature control cycle (TCC).....	129
Table I.11 – An example of calculation of energy, power and temperature for all possible blocks (size = 3 TCC).....	131
Table I.12 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 3 TCC).....	133
Table I.13 – An example of calculation of energy, power and temperature for all possible blocks (size = 5 TCC).....	136
Table I.14 – An example of calculation of energy, power and temperature for all possible blocks (size = 9 TCC).....	138
Table I.15 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 5 TCC).....	140
Table I.16 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 9 TCC).....	142
Table I.17 – Determination of defrost validity DF1.....	144
Table I.18 – Determination of steady state values using SS.....	146
Table L.1 – Assumed relative insulation value for multi-compartment products.....	158

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOUSEHOLD REFRIGERATING APPLIANCES –  
CHARACTERISTICS AND TEST METHODS –****Part 3: Energy consumption and volume**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.**

**IEC 62552-3 edition 1.1 contains the first edition (2015-02) [documents 59M/63/FDIS and 59M/66/RVD] and its amendment 1 (2020-11) [documents 59M/128/FDIS and 59M/134/RVD].**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

Standard IEC 62552-3 has been prepared by subcommittee 59M: Performance of electrical household and similar cooling and freezing appliances, of IEC technical committee 59: Performance of household and similar electrical appliances

IEC 62552-1, IEC 62552-2 and IEC 62552-3 together constitute a technical revision and include the following significant technical changes with respect to IEC 62552:2007:

- a) All parts of the standard have been largely rewritten and updated to cope with new testing requirements, new product configurations, the advent of electronic product controls and computer based test-room data collection and processing equipment.
- b) In Part 1 there are some changes to test room equipment specifications and the setup for testing to provide additional flexibility especially when testing multiple appliances in a single test room.
- c) For more efficient analysis and to better characterise the key product characteristics under different operating conditions, the test data from many of the energy tests in Part 3 (this part) is now split into components (such as **steady state** operation and defrost and recovery). The approach to determination of energy consumption has been completely revised, with many internal checks now included to ensure that data complying with the requirements of the standard is as accurate as possible and of high quality.
- d) Part 3 (this part) now provides a method to quantify each of the relevant energy components and approaches on how these can be combined to estimate energy under different conditions on the expectation that different regions will select components and weightings that are most applicable when setting both their local performance and energy efficiency criteria while using a single set of global test measurements.
- e) For energy consumption measurements in Part 3 (this part), no thermal mass (test packages) is included in any compartment and compartment temperatures are based on the average of air temperature sensors (compared to the temperature in the warmest test package). There are also significant differences in the position of temperature sensors in unfrozen compartments.
- f) The energy consumption test in Part 3 (this part) now has two specified ambient temperatures (16°C and 32°C).
- g) While, in Part 2 test packages are still used for the storage test to confirm performance in different operating conditions, in Part 1 they have been standardised to one size (100 mm × 100 mm × 50 mm) to simplify loading and reduce test variability. A clearance of at least 15 mm is now specified between test packages and the compartment liner.
- h) A load processing energy efficiency test has been added in Part 3 (this part).
- i) A tank-type ice making energy efficiency test has been added in Part 3 (this part).
- j) A cooling capacity test has been added in Part 2.
- k) A pull-down test has been added in Part 2.
- l) Shelf area and storage volume measurement methods are no longer included. In Part 3 the volume measurement has been revised to be the total internal volume with only components necessary for the satisfactory operation of the refrigeration system considered as being in place.
- m) Tests (both performance (Part 2) and energy (Part 3 – this part)) have been added for wine storage appliances.

The following print types are used in this international standard:

- requirements: in roman type;
- test specifications: in *italic type*;
- notes: in small roman type.
- Words in **bold** are defined in IEC 62552-1:2015, Clause 3 or in this part.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62252 series, published under the general title *Household refrigerating appliances – characteristics and test methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

IEC 62552 is split into 3 parts as follows:

- IEC 62552-1: Scope, definitions, instrumentation, test room and set up of refrigerating products;
- IEC 62552-2: General performance requirements for **refrigerating appliances** and methods for testing them;
- IEC 62552-3: **Energy consumption** and **volume** determination (this part).

# HOUSEHOLD REFRIGERATING APPLIANCES – CHARACTERISTICS AND TEST METHODS –

## Part 3: Energy consumption and volume

### 1 Scope

This part of IEC 62552 specifies the essential characteristics of household and similar **refrigerating appliances** cooled by internal natural convection or forced air circulation, and establishes test methods for checking these characteristics.

This part of IEC 62552 describes the methods for the determination of **energy consumption** characteristics and defines how these can be assembled to estimate **energy consumption** under different usage and climate conditions. This part of IEC 62552 also defines the determination of **volume**.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62552-1:2015, *Household refrigerating appliances – Characteristics and test methods – Part 1: General requirements*

IEC 62552-2:2015, *Household refrigerating appliances – Characteristics and test methods – Part 2: Performance requirements*

### 3 Terms, definitions and symbols

#### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62552-1, as well as the following apply.

##### 3.1.1 specified auxiliaries

functions or features that affect the **energy consumption** of a **refrigerating appliance** and where their actual **energy consumption** depends on the conditions of use or operation

Note 1 to entry: This standard makes optional provision for determining the **energy consumption** impacts of these functions or features in accordance with regional requirements.

Note 2 to entry: Test requirements for specified auxiliaries, where applicable, are set out in Annex F and their application specified in 6.8.4. The only specified auxiliaries in this edition of the standard are ambient controlled anti-condensation heaters and tank type automatic icemakers.

##### 3.1.2 defrost interval

the measured or estimated length of a **defrost control cycle**, starting from the point of initiation of one **defrost control cycle** to the point of initiation of the subsequent **defrost control cycle**, expressed in hours of elapsed (clock) time