

# INTERNATIONAL STANDARD

---

**3D display devices –  
Part 22-1: Measuring methods for autostereoscopic displays – Optical**





## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [www.iec.ch/glossary](http://www.iec.ch/glossary)

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

# INTERNATIONAL STANDARD

---

**3D display devices –  
Part 22-1: Measuring methods for autostereoscopic displays – Optical**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 31.120; 31.260

ISBN 978-2-8322-3688-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions and abbreviated terms .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 Standard measuring conditions.....	8
4.1 Standard environmental conditions .....	8
4.1.1 Temperature, humidity and pressure conditions.....	8
4.1.2 Illumination conditions .....	8
4.2 Light measuring device .....	8
4.2.1 General .....	8
4.2.2 Aperture size .....	9
4.3 Measuring setup .....	9
4.3.1 Designed viewing distance .....	9
4.3.2 Measurement area.....	10
4.3.3 Measuring layout .....	10
4.4 Test signal.....	12
4.5 Standard measuring points .....	13
5 Measuring method for two-view and multi-view displays .....	14
5.1 Maximum luminance direction .....	14
5.1.1 General .....	14
5.1.2 Measuring equipment .....	14
5.1.3 Measuring conditions.....	15
5.1.4 Measuring procedure .....	15
5.1.5 Measurement report .....	15
5.2 Lobe angle and lobe angle variation on screen .....	16
5.2.1 General .....	16
5.2.2 Measuring equipment .....	16
5.2.3 Measuring conditions.....	16
5.2.4 Measuring procedure .....	17
5.2.5 Measurement report .....	17
5.3 Luminance, screen luminance uniformity, and angular luminance variation .....	18
5.3.1 Luminance and screen luminance uniformity.....	18
5.3.2 Angular luminance variation.....	19
5.4 White chromaticity, white chromaticity uniformity on screen, and white chromaticity variation in angle.....	20
5.4.1 White chromaticity and white chromaticity uniformity on screen .....	20
5.4.2 White chromaticity angular variation .....	22
6 Standard measuring method for integral imaging displays (1D/2D) .....	23
6.1 General.....	23
6.2 Lobe angle and lobe angle variation on screen .....	24
6.3 Luminance, screen luminance uniformity, and angular luminance variation .....	24
6.3.1 Luminance and screen luminance uniformity.....	24
6.3.2 Angular luminance variation.....	24

6.4	White chromaticity, white chromaticity uniformity on screen, and white chromaticity variation in angle.....	24
6.4.1	White chromaticity and white chromaticity uniformity on screen .....	24
6.4.2	White chromaticity variation in angle.....	24
7	Measuring method for 3D crosstalk related property .....	24
7.1	3D crosstalk (luminance components ratio), 3D crosstalk variation on screen, and 3D crosstalk variation in angle for two-view and multi-view displays.....	24
7.1.1	3D crosstalk (luminance components ratio) and 3D crosstalk variation on screen .....	24
7.1.2	3D crosstalk angular variation.....	27
7.2	3D crosstalk related property for multi-view display.....	28
7.2.1	General .....	28
7.2.2	Offset crosstalk .....	28
7.2.3	3D pixel crosstalk .....	30
Annex A (informative)	Principle of autostereoscopic display.....	35
A.1	General.....	35
A.2	Two-view display .....	35
A.3	Multi-view display .....	36
A.4	Integral imaging display .....	37
Annex B (informative)	Angular profile of luminance.....	39
Annex C (informative)	3D crosstalk based on one inter-pupil distance .....	40
C.1	General.....	40
C.2	Measuring equipment.....	41
C.3	Measuring conditions .....	41
C.4	Measuring procedure .....	41
C.5	Measuring report.....	41
Annex D (informative)	View density for multi-view parallax smoothness .....	44
D.1	General.....	44
D.2	Measuring equipment.....	44
D.3	Measuring conditions .....	44
D.4	Measuring procedure .....	44
D.5	Measuring report .....	44
Bibliography	.....	46
Figure 1	– Measuring system .....	9
Figure 2	– Measuring layout for centre point measurement .....	10
Figure 3	– Measuring layout for multi-point measurement (side view).....	11
Figure 4	– Other measuring layout for multi-point measurement (side view).....	11
Figure 5	– Measuring layout for horizontal viewing direction dependency.....	12
Figure 6	– Measuring layout for vertical viewing direction dependency.....	12
Figure 7	– Two examples of the relation between pixel and lenslet in multi-view display .....	13
Figure 8	– Measuring points for the centre and multi-point measurement.....	14
Figure 9	– Example of $n$ by $m$ measuring points .....	14
Figure 10	– Example of measurement results for angular luminance profile .....	16
Figure 11	– Example of lobe angle measurement.....	17
Figure 12	– Example of 3D crosstalk variation on screen .....	25
Figure 13	– Example of acquired images in multi-view display .....	25

Figure 14 – Spatial luminance data acquisition (left) and example of calculated spatial crosstalk graph (right) .....	26
Figure 15 – Example of minimum luminance and maximum luminance for offset crosstalk .....	29
Figure 16 – Example of adjacent overlap .....	30
Figure 17 – Example of slanted lens configuration where 4,688 sub-pixels in a row are covered in one lens pitch .....	31
Figure 18 – Measuring layout example for 3D pixel crosstalk for multi-view displays having dozens of perspective output images .....	32
Figure 19 – Example of luminance angular profile for a multi-view display having 28 views (perspective images) .....	33
Figure A.1 – Structure of two-view display .....	35
Figure A.2 – Basic principle of two-view display .....	36
Figure A.3 – Structure of multi-view display .....	36
Figure A.4 – Basic principle of multi-view display .....	37
Figure A.5 – Basic principle of integral imaging display .....	37
Figure B.1 – Example of angular profile of luminance .....	39
Figure C.1 – Example image of a traditional multi-view display .....	40
Figure C.2 – Example image of the multi-view display having at least one view within one IPD .....	40
Figure C.3 – Example of luminance angular profile for a multi-view display having at least one view within one IPD (at designed viewing distance = 3,878 m) .....	42
Table 1 – Example of reported specification of two-dimensional LMD .....	9
Table 2 – Example of measurement results for maximum luminance direction .....	16
Table 3 – Example of measurement results for lobe angle variation on screen .....	18
Table 4 – Example of measurement results for luminance and screen luminance non-uniformity .....	19
Table 5 – Example of measurement results for angular luminance variation .....	20
Table 6 – Example of measurement results for white chromaticity and white chromaticity uniformity on screen .....	22
Table 7 – Example of measurement results for white chromaticity variation in angle .....	23
Table 8 – Example of measurement results for 3D crosstalk variation on screen .....	27
Table 9 – Example of measurement results for 3D crosstalk angular variation .....	28
Table 10 – Example of measurement results for offset crosstalk .....	30
Table 11 – Example of 3D pixel crosstalk calculation results .....	34
Table B.1 – Example of measurement results .....	39
Table C.1 – Example of measurement results for 3D crosstalk based on one IPD .....	43
Table D.1 – Example of measurement results for motion parallax smoothness .....	45

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## 3D DISPLAY DEVICES –

## Part 22-1: Measuring methods for autostereoscopic displays – Optical

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62629-22-1 has been prepared by IEC technical committee 110: Electronic display devices.

This second edition cancels and replaces the first edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of offset crosstalk and 3D pixel crosstalk as 3D crosstalk related property.

The text of this standard is based on the following documents:

FDIS	Report on voting
110/784/FDIS	110/797/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62629 series, under the general title *3D display devices*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## 3D DISPLAY DEVICES –

### Part 22-1: Measuring methods for autostereoscopic displays – Optical

#### 1 Scope

This part of IEC 62629-22 specifies optical measuring methods for autostereoscopic display devices. It defines general measuring procedures for optical characteristics of two-view and multi-view displays and integral imaging displays.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62629-1-2, *3D display devices – Part 1-2: Generic – Terminology and letter symbols*

ISO/CIE 19476, *Characterization of the performance of luminance meters and luminance meters*

CIE 15:2004, *Colorimetry*

#### 3 Terms, definitions and abbreviated terms

##### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62629-1-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

##### 3.1.1

##### **3D pixel crosstalk**

pixel crosstalk by horizontal pixels for one lens pitch

##### 3.2 Abbreviated terms

For the purposes of this document, the following abbreviated terms apply.

CCD	charge-coupled device
DVD	designed viewing distance
FPD	flat panel display
FWHM	full width half maximum
FWTQM	full width at three-quarter maximum
IPD	inter pupil distance