

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation électrique
Partie 1-2: Composants communs – Spécification de l'alimentation électrique
par port USB**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2018 USB-IF

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from IEC, or USB-IF at the respective address given below. Any questions about USB-IF copyright should be addressed to the USB-IF. Enquiries about obtaining additional rights to this publication and other information requests should be addressed to the IEC or your local IEC member National Committee.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

USB Implementers Forum, Inc.
3855 S.W. 153rd Drive
Beaverton, OR 97003
United States of America
Tel. +1 503-619-0426
Admin@usb.org
www.usb.org

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CIPR.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation électrique
Partie 1-2: Composants communs – Spécification de l'alimentation électrique
par port USB**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.220; 33.120; 35.200

ISBN 978-2-8322-7646-4

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER

Part 1-2: Common components – USB Power Delivery specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising a national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-1-2 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/3189/CDV	100/3251/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB-IF.

This standard is the USB-IF publication Universal Serial Bus Power Delivery Specification Revision 3.0, Version 1.2.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS", WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATIVE TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICATION.

THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY INTELLECTUAL PROPERTY RIGHTS.

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, RAND-Z licensing arrangement for compliant products. For more information, please see:

<https://www.usb.org/documents>

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM."

**Universal Serial Bus
Power Delivery Specification**

Revision: 3.0
Version: 1.2
Release date: 21 June 2018

Currently in preview, click buy full version

LIMITED COPYRIGHT LICENSE

THE USB 3.0 PROMOTERS GRANT A CONDITIONAL COPYRIGHT LICENSE UNDER THE COPYRIGHTS EMBODIED IN THE USB POWER DELIVERY SPECIFICATION TO USE AND REPRODUCE THE SPECIFICATION FOR THE SOLE PURPOSE OF, AND SOLELY TO THE EXTENT NECESSARY FOR, EVALUATING WHETHER TO IMPLEMENT THE SPECIFICATION IN PRODUCTS THAT WOULD COMPLY WITH THE SPECIFICATION. WITHOUT LIMITING THE FOREGOING, USE OF THE SPECIFICATION FOR THE PURPOSE OF FILING OR MODIFYING ANY PATENT APPLICATION TO TARGET THE SPECIFICATION OR USB COMPLIANT PRODUCTS IS NOT AUTHORIZED. EXCEPT FOR THIS EXPRESS COPYRIGHT LICENSE, NO OTHER RIGHTS OR LICENSES ARE GRANTED, INCLUDING WITHOUT LIMITATION ANY PATENT LICENSES. IN ORDER TO OBTAIN ANY ADDITIONAL INTELLECTUAL PROPERTY LICENSES OR LICENSING COMMITMENTS ASSOCIATED WITH THE SPECIFICATION A PARTY MUST EXECUTE THE USB 3.0 ADOPTERS AGREEMENT. NOTE: BY USING THE SPECIFICATION, YOU ACCEPT THESE LICENSE TERMS ON YOUR OWN BEHALF AND, IN THE CASE WHERE YOU ARE DOING THIS AS AN EMPLOYEE, ON BEHALF OF YOUR EMPLOYER.

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Please send comments via electronic mail to techsup@usb.org

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Copyright © 2010-2018, USB 3.0 Promoter Group: Apple Inc., Hewlett-Packard Inc., Intel Corporation, Microsoft Corporation, Renesas, STMicroelectronics, and Texas Instruments.

All rights reserved.

Chairs

Alvin Cox	Cabling Sub-Chair
Bob Dunstan	Specification Chair/Protocol Subgroup Chair
Deric Waters	PHY Chair
Ed Berrios	Power Supply Chair
Rahman Ismail	System Policy Chair
Richard Petrie	Specification Chair/Device Policy Chair

Editors

Bob Dunstan
Richard Petrie

Contributors

Currently in preview, click buy full version

Charles Wang	ACON, Advanced-Connectek, Inc.	Sathish Kumar	Cadence Design Systems, Inc.
Conrad Choy	ACON, Advanced-Connectek, Inc.	Ganesan	
Dennis Chuang	ACON, Advanced-Connectek, Inc.	Alessandro Ingrassia	Canova Tech
Steve Sedio	ACON, Advanced-Connectek, Inc.	Andrea Colognese	Canova Tech
Sunney Yang	ACON, Advanced-Connectek, Inc.	Antonio Orzelli	Canova Tech
Vicky Chuang	ACON, Advanced-Connectek, Inc.	Davide Ghedin	Canova Tech
Joseph Scanlon	Advanced Micro Devices	Matteo Casalin	Canova Tech
Caspar Lin	Allion Labs, Inc.	Michael Marioli	Canova Tech
Casper Lee	Allion Labs, Inc.	Nicola Scantamburlo	Canova Tech
Danny Shih	Allion Labs, Inc.	Paolo Pilla	Canova Tech
Howard Chang	Allion Labs, Inc.	Yi-Feng Lin	Canyon Semiconductor
Greg Stewart	Analogix Semiconductor, Inc.	YuHung Lin	Canyon Semiconductor
Mehran Badii	Analogix Semiconductor, Inc.	David Tsai	Chrontel, Inc.
Alexei Kosut	Apple	Anshul Gulati	Cypress Semiconductor
Bill Cornelius	Apple	Anup Nayak	Cypress Semiconductor
Carlos Colderon	Apple	Benjamin Kropf	Cypress Semiconductor
Chris Uiterwijk	Apple	Dhanraj Rajput	Cypress Semiconductor
Colin Whitby-Strevens	Apple	Ganesh Subramaniam	Cypress Semiconductor
Corey Axelowitz	Apple	Jagadeesan Raj	Cypress Semiconductor
Corey Lange	Apple	Junjie cui	Cypress Semiconductor
Dave Conroy	Apple	Manu Kumar	Cypress Semiconductor
David Sekowski	Apple	Muthu M	Cypress Semiconductor
Girault Jones	Apple	Nicholas Bodnar	Cypress Semiconductor
James Orr	Apple	Pradeep Bajpai	Cypress Semiconductor
Jason Chung	Apple	Rajaram R	Cypress Semiconductor
Jay Kim	Apple	Rama Vakkari	Cypress Semiconductor
Jeff Wilcox	Apple	Rushil Madan	Cypress Semiconductor
Jennifer Tsai	Apple	Simon Nguyen	Cypress Semiconductor
Karl Bowers	Apple	Steven Vong	Cypress Semiconductor
Keith Porthouse	Apple	Subu Sankaran	Cypress Semiconductor
Kevin Hsiue	Apple	Sumeet Gupta	Cypress Semiconductor
Matt Mora	Apple	Tejender Sheoran	Cypress Semiconductor
Paul Baker	Apple	Venkat Mandagulathar	Cypress Semiconductor
Reese Schreiber	Apple	Xiaofeng Shen	Cypress Semiconductor
Ruchi Chaturvedi	Apple	Zeng Wei	Cypress Semiconductor
Sameer Kelkar	Apple	Adolfo Montero	Dell Inc.
Sasha Tietz	Apple	Bruce Montag	Dell Inc.
Scott Jackson	Apple	Gary Verdun	Dell Inc.
Sree Raman	Apple	Merle Wood	Dell Inc.
William Ferry	Apple	Mohammed Hijazi	Dell Inc.
Zaki Moussaoui	Apple	Siddhartha Reddy	Dell Inc.
Jeff Liu	ASMedia Technology Inc.	Bindhu Vasu	Dialog Semiconductor (UK) Ltd
Kuo Lung Li	ASMedia Technology Inc.	Chanchal Gupta	Dialog Semiconductor (UK) Ltd
Ming-Wei Hsu	ASMedia Technology Inc.	Dipti Baheti	Dialog Semiconductor (UK) Ltd
PS Tseng	ASMedia Technology Inc.	Duc Doan	Dialog Semiconductor (UK) Ltd
Sam Tzeng	ASMedia Technology Inc.	Holger Petersen	Dialog Semiconductor (UK) Ltd
Thomas Hsu	ASMedia Technology Inc.	Jianming Yao	Dialog Semiconductor (UK) Ltd
Weikao Chang	ASMedia Technology Inc.	John Shi	Dialog Semiconductor (UK) Ltd
Yang Cheng	ASMedia Technology Inc.	KE Hong	Dialog Semiconductor (UK) Ltd
Shan Mehta	Bizlink Technology Inc.	Kevin Mori	Dialog Semiconductor (UK) Ltd
Benar Shukla	Bizlink Technology, Inc.	Larry Ping	Dialog Semiconductor (UK) Ltd
Eric Liu	Bizlink Technology, Inc.	Mengfei Liu	Dialog Semiconductor (UK) Ltd
Murphy Hsieh	Bizlink Technology, Inc.	Scott Brown	Dialog Semiconductor (UK) Ltd
Sean O'Neal	Bizlink Technology, Inc.	Yimin Chen	Dialog Semiconductor (UK) Ltd
Tiffany Hsiao	Bizlink Technology, Inc.	Yong Li	Dialog Semiconductor (UK) Ltd
Weichung Ooi	Bizlink Technology, Inc.	Dan Ellis	DisplayLink (UK) Ltd.
Rahul Bhushan	Broadcom Corp.	Jason Young	DisplayLink (UK) Ltd.
Asila nahas	Cadence Design Systems, Inc.	Kevin Jacobs	DisplayLink (UK) Ltd.
Claire Ying	Cadence Design Systems, Inc.	Paulo Alcobia	DisplayLink (UK) Ltd.
Jie min	Cadence Design Systems, Inc.	Peter Burgers	DisplayLink (UK) Ltd.
Mark Summers	Cadence Design Systems, Inc.		
Michal Staworko	Cadence Design Systems, Inc.		

Richard Petrie	DisplayLink (UK) Ltd.	Rahul Lakdawala	Hewlett Packard
Abel Astley	Ellisys	Robin Castell	Hewlett Packard
Chuck Trefts	Ellisys	Roger Benson	Hewlett Packard
Emmanuel Durin	Ellisys	Ron Schooley	Hewlett Packard
Mario Pasquali	Ellisys	Hideyuki HAYAFUJI	Hosiden Corporation
Tim Wei	Ellisys	Keiji Mine	Hosiden Corporation
Chien-Cheng Kuo	Etron Technology, Inc.	Masaki YAMAOKA	Hosiden Corporation
Jack Yang	Etron Technology, Inc.	Takashi MUTO	Hosiden Corporation
Richard Crisp	Etron Technology, Inc.	Yasunori NISHIKAWA	Hosiden Corporation
Shyanjia Chen	Etron Technology, Inc.	Kenneth Chan	HP Inc.
TsungTa Lu	Etron Technology, Inc.	Lee Atkinson	HP Inc.
Christian Klein	Fairchild Semiconductor	Steve Chen	HP Inc.
Oscar Freitas	Fairchild Semiconductor	Suketu Partiwala	HP Inc.
Souhib Harb	Fairchild Semiconductor	Suketu Partiwala	HP Inc.
Amanda Ying	Feature Integration Technology Inc.	Vaibhav Malik	HP Inc.
Jacky Chan	Feature Integration Technology Inc.	Walter Fry	HP Inc.
Kenny Hsieh	Feature Integration Technology Inc.	Bai Sean	Huawei Technologies Co., Ltd.
KungAn Lin	Feature Integration Technology Inc.	Chunjiang Zhao	Huawei Technologies Co., Ltd.
Paul Yang	Feature Integration Technology Inc.	JianQuan Wu	Huawei Technologies Co., Ltd.
su Jaden	Feature Integration Technology Inc.	Li Zongjian	Huawei Technologies Co., Ltd.
Yu-Lin Chu	Feature Integration Technology Inc.	Lihua Duan	Huawei Technologies Co., Ltd.
Yulin Lan	Feature Integration Technology Inc.	Min Chen	Huawei Technologies Co., Ltd.
AJ Yang	Foxconn / Hon Hai	Wang Feng	Huawei Technologies Co., Ltd.
Fred Fons	Foxconn / Hon Hai	Wei Haihong	Huawei Technologies Co., Ltd.
Jie zheng	Foxconn / Hon Hai	Robert Heaton	Indie Semiconductor
Steve Sedio	Foxconn / Hon Hai	Vincent Wang	Indie Semiconductor
Terry Little	Foxconn / Hon Hai	Sie Boo Chiang	Infineon Technologies
Bob McVay	Fresco Logic Inc.	Tue Fatt David Wee	Infineon Technologies
Christopher Meyers	Fresco Logic Inc.	Wee Tar Richard Ng	Infineon Technologies
Dian Kurniawan	Fresco Logic Inc.	Wolfgang Furtner	Infineon Technologies
Tom Burton	Fresco Logic Inc.	Bob Dunstan	Intel Corporation
Adam Rodriguez	Google Inc.	Brad Saunders	Intel Corporation
Alec Berg	Google Inc.	Chee Lim Nge	Intel Corporation
Dave Bernard	Google Inc.	Christine Krause	Intel Corporation
David Schneider	Google Inc.	Dan Froelich	Intel Corporation
Jim Guerin	Google Inc.	David Harriman	Intel Corporation
Juan Fantin	Google Inc.	David Hines	Intel Corporation
Ken Wu	Google Inc.	David Thompson	Intel Corporation
Mark Hayter	Google Inc.	Guobin Liu	Intel Corporation
Nithya Jagannathan	Google Inc.	Harry Skinner	Intel Corporation
Srikanth Lakshmikanthan	Google Inc.	Henrik Leegaard	Intel Corporation
Todd Broch	Google Inc.	Jenn Chuan Cheng	Intel Corporation
Toshak Singhal	Google Inc.	Jervis Lin	Intel Corporation
Vincent Palatin	Google Inc.	John Howard	Intel Corporation
Xuelin Wu	Google Inc.	Karthi Vadivelu	Intel Corporation
Alan Kinningham	Granite River Labs	Leo Heiland	Intel Corporation
Balamurugan Manialagan	Granite River Labs	Maarit Harkonen	Intel Corporation
Mike Engbretson	Granite River Labs	Nge Chee Lim	Intel Corporation
Mike Wu	Granite River Labs	Paul Durley	Intel Corporation
Mukesh Tatiya	Granite River Labs	Rahman Ismail	Intel Corporation
Rajaraman V	Granite River Labs	Rajaram Regupathy	Intel Corporation
Tim Lin	Granite River Labs	Ronald Swartz	Intel Corporation
Alan Berkema	Hewlett Packard	Sarah Sharp	Intel Corporation
Lee Atkinson	Hewlett Packard	Scott Brenden	Intel Corporation
		Sridharan Ranganathan	Intel Corporation
		Steve McGowan	Intel Corporation
		Tim McKee	Intel Corporation
		Toby Opferman	Intel Corporation

Jia Wei	Intersil Corporation	Thomas Farkas	Microchip Technology Inc.
Al Hsiao	ITE Tech. Inc.	Andrew Yang	Microsoft Corporation
Greg Song	ITE Tech. Inc.	Anthony Chen	Microsoft Corporation
Richard Guo	ITE Tech. Inc.	Arvind Murching	Microsoft Corporation
Victor Lin	ITE Tech. Inc.	Dave Perchlik	Microsoft Corporation
Y.C. Chou	ITE Tech. Inc.	David Voth	Microsoft Corporation
Kenta Minejima	Japan Aviation Electronics Industry Ltd. (JAE)	Geoff Shew	Microsoft Corporation
Mark Saubert	Japan Aviation Electronics Industry Ltd. (JAE)	Jayson Kastens	Microsoft Corporation
Toshio Shimoyama	Japan Aviation Electronics Industry Ltd. (JAE)	Kai Inha	Microsoft Corporation
Brian Fetz	Keysight Technologies Inc.	Marwan Kadado	Microsoft Corporation
Babu Mailachalam	Lattice Semiconductor Corp	Michelle Bergeron	Microsoft Corporation
Gianluca Mariani	Lattice Semiconductor Corp	Rahul Ramadas	Microsoft Corporation
Joel Coplen	Lattice Semiconductor Corp	Randy Aull	Microsoft Corporation
Thomas Watza	Lattice Semiconductor Corp	Shiu Ng	Microsoft Corporation
Vesa Lauri	Lattice Semiconductor Corp	Timo Toivola	Microsoft Corporation
Bruce Chuang	Leadtrend	Toby Nixon	Microsoft Corporation
Eilian Liu	Leadtrend	Vivek Gupta	Microsoft Corporation
Daniel H Jacobs	LeCroy Corporation	Yang You	Microsoft Corporation
Jake Jacobs	LeCroy Corporation	Aaron Xu	Monolithic Power Systems Inc.
Kimberley McKay	LeCroy Corporation	Bo Zhou	Monolithic Power Systems Inc.
Mike Micheletti	LeCroy Corporation	Christian Sporck	Monolithic Power Systems Inc.
Roy Chestnut	LeCroy Corporation	Di Han	Monolithic Power Systems Inc.
Tyler Joe	LeCroy Corporation	Zhihong Yu	Monolithic Power Systems Inc.
Phil Jakes	Lenovo	Dan Wagner	Motorola Mobility Inc.
Aaron Melgar	Lion Semiconductor	Ben Crowe	MQP Electronics Ltd.
Chris Zhou	Lion Semiconductor	Pat Crowe	MQP Electronics Ltd.
Sehyung Jeon	Lion Semiconductor	Sten Carlsen	MQP Electronics Ltd.
Wonyoung Kim	Lion Semiconductor	Kenji Oguma	NEC Corporation
Yongho Kim	Lion Semiconductor	Frank Borngläber	Nokia Corporation
Dave Thompson	LSI Corporation	Kai Inha	Nokia Corporation
Alan Kinningham	Luxshare-ICT	Pekka Leinonen	Nokia Corporation
Daniel Chen	Luxshare-ICT	Richard Petrie	Nokia Corporation
James Stevens	Luxshare-ICT	Sten Carlsen	Nokia Corporation
Josue Castillo	Luxshare-ICT	Abhijeet Kulkarni	NXP Semiconductors
Scott Shuey	Luxshare-ICT	Ahmad Yazdi	NXP Semiconductors
Chikara Kakizawa	Maxim Integrated Products	Bart Vertenten	NXP Semiconductors
Jacob Scott	Maxim Integrated Products	Dennis Ha	NXP Semiconductors
Ken Helfrich	Maxim Integrated Products	Dong Nguyen	NXP Semiconductors
Michael Miskho	Maxim Integrated Products	Guru Prasad	NXP Semiconductors
Chris Yokum	MCCI Corporation	Ken Jaramillo	NXP Semiconductors
Geert Knapen	MCCI Corporation	Krishnan TN	NXP Semiconductors
Terry Moore	MCCI Corporation	Michael Joehren	NXP Semiconductors
Velmurugan Selvaraj	MCCI Corporation	Robert de Nie	NXP Semiconductors
Satoru Kumashiro	MegaChips Corporation	Rod Whitby	NXP Semiconductors
Brian Marley	Microchip Technology Inc.	Vijendra Kuroodi	NXP Semiconductors
Dave Perchlik	Microchip Technology Inc.	Winston Langeslag	NXP Semiconductors
Don Perkins	Microchip Technology Inc.	Robert Heaton	Obsidian Technology
Fernando Gonzalez	Microchip Technology Inc.	Andrew Yoo	ON Semiconductor
John Sisto	Microchip Technology Inc.	Brady Maasen	ON Semiconductor
Josh Averyt	Microchip Technology Inc.	Bryan McCoy	ON Semiconductor
Kiet Tran	Microchip Technology Inc.	Christian Klein	ON Semiconductor
Mark Bohm	Microchip Technology Inc.	Cor Voorwinden	ON Semiconductor
Matthew Kalibat	Microchip Technology Inc.	Edward Berrios	ON Semiconductor
Mick Davis	Microchip Technology Inc.	Michael Smith	ON Semiconductor
Prasanna Vengateshan	Microchip Technology Inc.	Oscar Freitas	ON Semiconductor
Rich Wahler	Microchip Technology Inc.	Tom Duffy	ON Semiconductor
Richard Petrie	Microchip Technology Inc.	Craig Wiley	Parade Technologies Inc.
Ronald Kunin	Microchip Technology Inc.	Aditya Kulkarni	Power Integrations
Shannon Cash	Microchip Technology Inc.	Amruta Patra	Power Integrations
		Rahul Joshi	Power Integrations
		Ricardo Pregiteer	Power Integrations
		Shruti Anand	Power Integrations
		Amit gupta	Qualcomm, Inc

George Paparrizos	Qualcomm, Inc	Steven Ghang	Silicon Laboratories, Inc.
Giovanni Garcea	Qualcomm, Inc	Abhishek Sardeshpande	SiliConch Systems Private Limited
Jack Pham	Qualcomm, Inc	Aniket Mathad	SiliConch Systems Private Limited
James Goel	Qualcomm, Inc	Chandana N	SiliConch Systems Private Limited
Joshua Warner	Qualcomm, Inc	Jaswanth Ammineni	SiliConch Systems Private Limited
Karyn Vuong	Qualcomm, Inc	Jinisha Patel	SiliConch Systems Private Limited
Vamsi Samavedam	Qualcomm, Inc	Kaustubh Kumar	SiliConch Systems Private Limited
Vatsal Patel	Qualcomm, Inc	Nitish Nitish	SiliConch Systems Private Limited
Chris Sporck	Qualcomm, Inc.	Pavitra Balasubramanian	SiliConch Systems Private Limited
Craig Aiken	Qualcomm, Inc.	Rakesh Polasa	SiliConch Systems Private Limited
Narendra Mehta	Qualcomm, Inc.	Shubham Paliwal	SiliConch Systems Private Limited
Terry Remple	Qualcomm, Inc.	Vishnu Pusuluri	SiliConch Systems Private Limited
Will Kun	Qualcomm, Inc.	John Sisto	SMSC
Yoram Rimoni	Qualcomm, Inc.	Ken Gay	SMSC
Tsung-Peng Chuang	Realtek Semiconductor Corp.	Mark Bohm	SMSC
Atsushi Mitamura	Renesas Electronics Corp.	Richard Wahler	SMSC
Bob Dunstan	Renesas Electronics Corp.	Shannon Cash	SMSC
Brian Allen	Renesas Electronics Corp.	Tim Knowlton	SMSC
Dan Aoki	Renesas Electronics Corp.	William Chiechi	SMSC
Hajime Nozaki	Renesas Electronics Corp.	Shigenori Tagami	Sony Corporation
John Carpenter	Renesas Electronics Corp.	Shinichi Hirata	Sony Corporation
Kiichi Muto	Renesas Electronics Corp.	Amanda Hosler	Specwerkz
Masami Katagiri	Renesas Electronics Corp.	Bob Dunstan	Specwerkz
Nobuo Furuya	Renesas Electronics Corp.	Diane Lenox	Specwerkz
Patrick Yu	Renesas Electronics Corp.	Michael Munn	StarTech.com Ltd.
Peter Teng	Renesas Electronics Corp.	Fabien Friess	ST-Ericsson
Philip Leung	Renesas Electronics Corp.	Giuseppe Platania	ST-Ericsson
Steve Roux	Renesas Electronics Corp.	Jean-Francois Gatto	ST-Ericsson
Tetsu Sato	Renesas Electronics Corp.	Milan Stamenkovic	ST-Ericsson
Toshifumi Yamaoka	Renesas Electronics Corp.	Nicolas Florenchie	ST-Ericsson
Chunan Kuo	Richtek Technology Corporation	Patrizia Milazzo	ST-Ericsson
Heinz Wei	Richtek Technology Corporation	Christophe Cochard	STMicroelectronics
TZUHSIEN CHUANG	Richtek Technology Corporation	Christophe Lorin	STMicroelectronics
Tatsuya Irisawa	Ricoh Company Ltd.	Jessy Guilbot	STMicroelectronics
Akihiro Ono	Rohm Co. Ltd.	Joel Huloux	STMicroelectronics
Chris Lin	Rohm Co. Ltd.	John Bloomfield	STMicroelectronics
Hidenori Nishimoto	Rohm Co. Ltd.	Massimo Panzica	STMicroelectronics
Kris Bahar	Rohm Co. Ltd.	Meriem Mersel	STMicroelectronics
Manabu Miyata	Rohm Co. Ltd.	Nathalie Ballot	STMicroelectronics
Ruben Balbuena	Rohm Co. Ltd.	Pascal Legrand	STMicroelectronics
Takashi Sato	Rohm Co. Ltd.	Patrizia Milazzo	STMicroelectronics
Vijendra Kuroodi	Rohm Co. Ltd.	Richard O'Connor	STMicroelectronics
Yusuke Kondo	Rohm Co. Ltd.	Morten Christiansen	Synopsys, Inc.
Kazuomi Nagai	ROHM Co., Ltd.	Nivin George	Synopsys, Inc.
Matti Kulmala	Salcomp Plc	Zongyao Wen	Synopsys, Inc.
Toni Lehimo	Salcomp Plc	Joan Marrinan	Tektronix
Tong Kim	Samsung Electronics Co. Ltd.	Kimberley McKay	Teledyne-LeCroy
Alvin Cox	Seagate Technology LLC	Matthew Dunn	Teledyne-LeCroy
Emmanuel Lemay	Seagate Technology LLC	Tony Minchell	Teledyne-LeCroy
John Hein	Seagate Technology LLC	Anand Dabak	Texas Instruments
Marc Noblitt	Seagate Technology LLC	Bill Waters	Texas Instruments
Michael Morgan	Seagate Technology LLC	Bing Lu	Texas Instruments
Ronald Rueckert	Seagate Technology LLC	Deric Waters	Texas Instruments
Tony Priborsky	Seagate Technology LLC	Grant Ley	Texas Instruments
Chin Chang	Semtech Corporation	Gregory Watkins	Texas Instruments
Tom Farkas	Semtech Corporation	Ingolf Frank	Texas Instruments
Ning Dai	Silergy Corp.	Ivo Huber	Texas Instruments
Wanfeng Zhang	Silergy Corp.	Javed Ahmad	Texas Instruments
Kafai Leung	Silicon Laboratories, Inc.		
Kok Hong Soh	Silicon Laboratories, Inc.		
Sorin Badiu	Silicon Laboratories, Inc.		

Jean Picard	Texas Instruments
John Perry	Texas Instruments
Martin Patoka	Texas Instruments
Mike Campbell	Texas Instruments
Scott Jackson	Texas Instruments
Shafiuddin Mohammed	Texas Instruments
Srinath Hosur	Texas Instruments
Steven Tom	Texas Instruments
Yoon Lee	Texas Instruments
Tod Wolf	The Silanna Group Pty. Ltd.
Chris Yokum	Total Phase
Brad Cox	Ventev Mobile
Colin Vose	Ventev Mobile
Dydron Lin	VIA Technologies, Inc.
Fong-Jim Wang	VIA Technologies, Inc.
Jay Tseng	VIA Technologies, Inc.
Rex Chang	VIA Technologies, Inc.
Terrance Shih	VIA Technologies, Inc.
Ho Wen Tsai	Weltrend Semiconductor
Hung Chiang	Weltrend Semiconductor
Jeng Cheng Liu	Weltrend Semiconductor
Priscilla Lee	Weltrend Semiconductor
Wayne Lo	Weltrend Semiconductor
Charles Neumann	Western Digital Technologies, Inc.
Curtis Stevens	Western Digital Technologies, Inc.
John Maroney	Western Digital Technologies, Inc.
Joe O'Brien	Wilder Technologies
Will Miller	Wilder Technologies
Juejia Zhou	Xiaomi Communications Co., Ltd.
Xiaoxing Yang	Xiaomi Communications Co., Ltd.

Revision History

Revision	Version	Comments	Issue Date
1.0	1.0	Initial release Revision 1.0	5 July 2012
1.0	1.1	Including errata through 31-October-2012	31 October 2012
1.0	1.2	Including errata through 26-June-2013	26 June 2013
1.0	1.3	Including errata through 11-March-2014	11 March 2014
2.0	1.0	Initial release Revision 2.0	11 August 2014
2.0	1.1	Including errata through 7-May 2015	7 May 2015
2.0	1.2	Including errata through 25-March-2016	25 March 2016
2.0	1.3	Including errata through 11-January-2017	11 January 2017
3.0	1.0	Initial release Revision 3.0	11 December 2015
3.0	1.0a	Including errata through 25-March-2016	25 March 2016
3.0	1.1	Including errata through 12-January-2016	12 January 2017
3.0	1.2	Including errata through 21-June-2018:	21 June 2018

Table of Contents

INTELLECTUAL PROPERTY DISCLAIMER	6
Chairs	7
Editors	7
Contributors	7
Revision History	13
Table of Contents	14
List of Tables	20
List of Figures	26
1. Introduction	34
1.1 Overview	34
1.2 Purpose	35
1.3 Scope	35
1.4 Conventions	35
1.4.1 Precedence	35
1.4.2 Keywords	36
1.4.3 Numbering	37
1.5 Related Documents	37
1.6 Terms and Abbreviations	38
1.7 Parameter Values	45
1.8 Changes from Revision 2.0	46
1.9 Compatibility with Revision 2.0	46
2. Overview	46
2.1 Introduction	46
2.2 Section Overview	47
2.3 Revision 2.0 Changes and Compatibility	48
2.3.1 Changes from Revision 2.0	48
2.3.2 Compatibility with Revision 2.0	48
2.4 USB Power Delivery Capable Devices	49
2.5 SOP* Communication	50
2.5.1 Introduction	50
2.5.2 SOP* Collision Avoidance	50
2.5.3 SOP Communication	50
2.5.4 SOP*/SOP'' Communication with Cable Plugs	50
2.6 Operational Overview	52
2.6.1 Source Operation	52
2.6.2 Sink Operation	55
2.6.3 Cable Plugs	57
2.7 Architectural Overview	58
2.7.1 Policy	60
2.7.2 Message Formation and Transmission	61
2.7.3 Collision Avoidance	61
2.7.4 Power supply	61
2.7.5 DFP/UFP	62

2.7.6	Cable and Connectors	62
2.7.7	Interactions between Non-PD, BC and PD devices	62
2.7.8	Power Rules	63
3.	USB Type-A and USB Type-B Cable Assemblies and Connectors	63
4.	Electrical Requirements	63
4.1	Interoperability with other USB Specifications	63
4.2	Dead Battery Detection / Unpowered Port Detection	63
4.3	Cable IR Ground Drop (IR Drop)	63
4.4	Cable Type Detection	63
5.	Physical Layer	64
5.1	Physical Layer Overview	64
5.2	Physical Layer Functions	64
5.3	Symbol Encoding	65
5.4	Ordered Sets	66
5.5	Transmitted Bit Ordering	66
5.6	Packet Format	68
5.6.1	Packet Framing	68
5.6.2	CRC	70
5.6.3	Packet Detection Errors	72
5.6.4	Hard Reset	72
5.6.5	Cable Reset	72
5.7	Collision Avoidance	73
5.8	Biphase Mark Coding (BMC) Signaling Scheme	73
5.8.1	Encoding and signaling	74
5.8.2	Transmit and Receive Masks	76
5.8.3	Transmitter Load Model	82
5.8.4	BMC Common specifications	83
5.8.5	BMC Transmitter Specifications	84
5.8.6	BMC Receiver Specifications	86
5.9	Built in Self-Test (BIST)	89
5.9.1	BIST Carrier Mode	89
5.9.2	BIST Test Data	89
6.	Protocol Layer	89
6.1	Overview	89
6.2	Messages	89
6.2.1	Message Construction	90
6.3	Control Message	98
6.3.1	GoodCRC Message	99
6.3.2	GotoMin Message	100
6.3.3	Accept Message	100
6.3.4	Reject Message	100
6.3.5	Ping Message	101
6.3.6	PS_RDY Message	101
6.3.7	Get_Source_Cap Message	101
6.3.8	Get_Sink_Cap Message	101
6.3.9	DR_Swap Message	101
6.3.10	PR_Swap Message	102
6.3.11	VCONN_Swap Message	102

6.3.12	Wait Message	103
6.3.13	Soft Reset Message	104
6.3.14	Not_Supported Message	104
6.3.15	Get_Source_Cap_Extended Message	104
6.3.16	Get_Status Message	104
6.3.17	FR_Swap Message	104
6.3.18	Get_PPS_Status	105
6.3.19	Get_Country_Codes	105
6.3.20	Get_Sink_Cap_Extended Message	105
6.4	Data Message	105
6.4.1	Capabilities Message	106
6.4.2	Request Message	115
6.4.3	BIST Message	119
6.4.4	Vendor Defined Message	120
6.4.5	Battery_Status Message	143
6.4.6	Alert Message	144
6.4.7	Get_Country_Info Message	145
6.5	Extended Message	145
6.5.1	Source_Capabilities_Extended Message	146
6.5.2	Status Message	150
6.5.3	Get_Battery_Cap Message	153
6.5.4	Get_Battery_Status Message	153
6.5.5	Battery_Capabilities Message	154
6.5.6	Get_Manufacturer_Info Message	154
6.5.7	Manufacturer_Info Message	155
6.5.8	Security Messages	156
6.5.9	Firmware Update Messages	156
6.5.10	PPS_Status Message	157
6.5.11	Country_Codes Message	158
6.5.12	Country_Info Message	158
6.5.13	Sink_Capabilities_Extended Message	159
6.6	Timers	162
6.6.1	CRCReceiveTimer	162
6.6.2	SenderResponseTimer	163
6.6.3	Capability Timers	163
6.6.4	Wait Timers and Times	164
6.6.5	Power Supply Timers	164
6.6.6	NoResponseTimer	165
6.6.7	BIST Timers	166
6.6.8	Power Role Swap Timers	166
6.6.9	Soft Reset Timers	166
6.6.10	Hard Reset Timers	166
6.6.11	Structured VDM Timers	167
6.6.12	Vconn Timers	168
6.6.13	tCableMessage	168
6.6.14	DiscoverIdentityTimer	168
6.6.15	Collision Avoidance Timers	168
6.6.16	Fast Role Swap Timers	169
6.6.17	Chunking Timers	169

6.6.18	Programmable Power Supply Timers	170
6.6.19	Time Values and Timers	170
6.7	Counters	173
6.7.1	MessageID Counter	173
6.7.2	Retry Counter	173
6.7.3	Hard Reset Counter	174
6.7.4	Capabilities Counter	174
6.7.5	Discover Identity Counter	174
6.7.6	VDMBusyCounter	174
6.7.7	Counter Values and Counters	174
6.8	Reset	175
6.8.1	Soft Reset and Protocol Error	175
6.8.2	Hard Reset	177
6.8.3	Cable Reset	177
6.9	Collision Avoidance	178
6.10	Message Discarding	178
6.11	State behavior	179
6.11.1	Introduction to state diagrams used in Chapter 6	179
6.11.2	State Operation	179
6.11.3	List of Protocol Layer States	197
6.12	Message Applicability	198
6.12.1	Applicability of Control Messages	199
6.12.2	Applicability of Data Messages	200
6.12.3	Applicability of Extended Messages	201
6.12.4	Applicability of Structured VDM Commands	202
6.12.5	Applicability of Reset Signaling	203
6.12.6	Applicability of Fast Role Swap signal	203
6.13	Value Parameters	203
7.	Power Supply	203
7.1	Source Requirements	203
7.1.1	Behavioral Aspects	203
7.1.2	Source Bulk Capacitance	204
7.1.3	Types of Sources	204
7.1.4	Source Transitions	204
7.1.5	Response to Hard Resets	210
7.1.6	Changing the Output Power Capability	211
7.1.7	Robust Source Operation	211
7.1.8	Output Voltage Tolerance and Range	212
7.1.9	Charging and Discharging the Bulk Capacitance on V_{BUS}	213
7.1.10	Swap Standby for Sources	213
7.1.11	Source Peak Current Operation	214
7.1.12	Source Capabilities Extended Parameters	214
7.1.13	Fast Role Swap	216
7.1.14	Non-application of V_{BUS} Slew Rate Limits	218
7.2	Sink Requirements	218
7.2.1	Behavioral Aspects	218
7.2.2	Sink Bulk Capacitance	218
7.2.3	Sink Standby	218

- 7.2.4 Suspend Power Consumption 219
- 7.2.5 Zero Negotiated Current 219
- 7.2.6 Transient Load Behavior 219
- 7.2.7 Swap Standby for Sinks 219
- 7.2.8 Sink Peak Current Operation 219
- 7.2.9 Robust Sink Operation 220
- 7.2.10 Fast Role Swap 221
- 7.3 Transitions 221
 - 7.3.1 Increasing the Current 222
 - 7.3.2 Increasing the Voltage 224
 - 7.3.3 Increasing the Voltage and Current 226
 - 7.3.4 Increasing the Voltage and Decreasing the Current 228
 - 7.3.5 Decreasing the Voltage and Increasing the Current 230
 - 7.3.6 Decreasing the Current 232
 - 7.3.7 Decreasing the Voltage 234
 - 7.3.8 Decreasing the Voltage and the Current 236
 - 7.3.9 Sink Requested Power Role Swap 238
 - 7.3.10 Source Requested Power Role Swap 241
 - 7.3.11 GotoMin Current Decrease 244
 - 7.3.12 Source Initiated Hard Reset 246
 - 7.3.13 Sink Initiated Hard Reset 248
 - 7.3.14 No change in Current or Voltage 250
 - 7.3.15 Fast Role Swap 252
 - 7.3.16 Increasing the Programmable Power Supply Voltage 254
 - 7.3.17 Decreasing the Programmable Power Supply Voltage 256
 - 7.3.18 Changing the Source PDO or APDO 258
 - 7.3.19 Increasing the Programmable Power Supply Current 260
 - 7.3.20 Decreasing the Programmable Power Supply Current 262
 - 7.3.21 Same Request Programmable Power Supply 264
- 7.4 Electrical Parameters 265
 - 7.4.1 Source Electrical Parameters 265
 - 7.4.2 Sink Electrical Parameters 269
 - 7.4.3 Common Electrical Parameters 270
- 8. Device Policy 271
 - 8.1 Overview 271
 - 8.2 Device Policy Manager 271
 - 8.2.1 Capabilities 272
 - 8.2.2 System Policy 272
 - 8.2.3 Control of Source/Sink 272
 - 8.2.4 Cable Detection 273
 - 8.2.5 Managing Power Requirements 273
 - 8.2.6 Use of “Unconstrained Power” bit with Batteries and AC supplies 275
 - 8.2.7 Interface to the Policy Engine 277
 - 8.3 Policy Engine 277
 - 8.3.1 Introduction 277
 - 8.3.2 Atomic Message Sequence Diagrams 278
 - 8.3.3 State Diagrams 410
- 9. States and Status Reporting 476

9.1	Overview	476
9.1.1	PDUSB Device and Hub Requirements	478
9.1.2	Mapping to USB Device States	478
9.1.3	PD Software Stack	481
9.1.4	PDUSB Device Enumeration	481
9.2	PD Specific Descriptors	483
9.2.1	USB Power Delivery Capability Descriptor	483
9.2.2	Battery Info Capability Descriptor	484
9.2.3	PD Consumer Port Capability Descriptor	485
9.2.4	PD Provider Port Capability Descriptor	485
9.3	PD Specific Requests and Events	486
9.3.1	PD Specific Requests	486
9.4	PDUSB Hub and PDUSB Peripheral Device Requests	487
9.4.1	GetBatteryStatus	487
9.4.2	SetPDFeature	488
10.	Power Rules	490
10.1	Introduction	490
10.2	Source Power Rules	490
10.2.1	Source Power Rule Considerations	490
10.2.2	Normative Voltages and Currents	491
10.2.3	Optional Voltages/Currents	493
10.2.4	Power sharing between ports	495
10.3	Sink Power Rules	495
10.3.1	Sink Power Rule Considerations	495
10.3.2	Normative Sink Rules	495
A.	CRC calculation	496
A.1	C code example	496
A.2	Table showing the full calculation over one Message	498
B.	PD Message Sequence Examples	499
B.1	External power is supplied downstream	499
B.2	External power is supplied upstream	502
B.3	Giving back power	508
C.	VDM Command Examples	518
C.1	Discover Identity Example	518
C.1.1	Discover Identity Command request	518
C.1.2	Discover Identity Command response – Active Cable	518
C.1.3	Discover Identity Command response – Hub	520
C.2	Discover SVIDs Example	521
C.2.1	Discover SVIDs Command request	521
C.2.1	Discover SVIDs Command response	521
C.3	Discover Modes Example	522
C.3.1	Discover Modes Command request	522
C.3.2	Discover Modes Command response	522
C.4	Enter Mode Example	523
C.4.1	Enter Mode Command request	523
C.4.2	Enter Mode Command response	523
C.4.1	Enter Mode Command request with additional VDO	524
C.5	Exit Mode Example	525

- C.5.1 Exit Mode Command request 525
- C.5.2 Exit Mode Command response 525
- C.6 Attention Example 526
 - C.6.1 Attention Command request 526
 - C.6.2 Attention Command request with additional VDO 526
- D. BMC Receiver Design Examples 527
 - D.1 Finite Difference Scheme 527
 - D.1.1 Sample Circuitry 527
 - D.1.2 Theory 527
 - D.1.3 Data Recovery 529
 - D.1.4 Noise Zone and Detection Zone 530
 - D.2 Subtraction Scheme 530
 - D.2.1 Sample Circuitry 530
 - D.2.2 Output of Each Circuit Block 531
 - D.2.3 Subtractor Output at Power Source and Power Sink 531
 - D.2.4 Noise Zone and Detection Zone 532
- E. FRS System Level Example 532
 - E.1 Overview 532
 - E.2 FRS Initial Setup 534
 - E.3 FRS Process 536

List of Tables

- Table 1-1 Terms and Abbreviations 38
- Table 5-1 4b5b Symbol Encoding Table 65
- Table 5-2 Ordered Sets 66
- Table 5-3 Validation of Ordered Sets 66
- Table 5-4 Data Size 67
- Table 5-5 SOP ordered set 68
- Table 5-6 SOP' ordered set 69
- Table 5-7 SOP'' ordered set 69
- Table 5-8 SOP'_Debug ordered set 69
- Table 5-9 SOP''_Debug ordered set 70
- Table 5-10 CRC-32 Mapping 71
- Table 5-11 Hard Reset ordered set 72
- Table 5-12 Cable Reset ordered set 72
- Table 5-13 Rp values used for Collision Avoidance 73
- Table 5-14 BMC Tx Mask Definition, X Values 77
- Table 5-15 BMC Tx Mask Definition, Y Values 78
- Table 5-16 BMC Rx Mask Definition 82
- Table 5-17 BMC Common Normative Requirements 83
- Table 5-18 BMC Transmitter Normative Requirements 84
- Table 5-19 BMC Receiver Normative Requirements 86
- Table 6-1 Message Header 90
- Table 6-2 Revision Interoperability during an Explicit Contract 93

Table 6-3 Extended Message Header	94
Table 6-4 Use of Unchunked Message Supported bit	95
Table 6-5 Control Message Types	99
Table 6-6 Data Message Types	106
Table 6-7 Power Data Object	107
Table 6-8 Augmented Power Data Object	107
Table 6-9 Fixed Supply PDO - Source	109
Table 6-10 Fixed Power Source Peak Current Capability	111
Table 6-11 Variable Supply (non-Battery) PDO - Source	111
Table 6-12 Battery Supply PDO - Source	111
Table 6-13 Programmable Power Supply APDO - Source	112
Table 6-14 Fixed Supply PDO - Sink	113
Table 6-15 Variable Supply (non-Battery) PDO - Sink	114
Table 6-16 Battery Supply PDO - Sink	114
Table 6-17 Programmable Power Supply APDO - Sink	114
Table 6-18 Fixed and Variable Request Data Object	115
Table 6-19 Fixed and Variable Request Data Object with GiveBack Support	115
Table 6-20 Battery Request Data Object	115
Table 6-21 Battery Request Data Object with GiveBack Support	116
Table 6-22 Programmable Request Data Object	116
Table 6-23 BIST Data Object	119
Table 6-24 Unstructured VDM Header	121
Table 6-25 Structured VDM Header	121
Table 6-26 Structured VDM Commands	122
Table 6-27 SVID Values	122
Table 6-28 Commands and Responses	124
Table 6-29 ID Header VDO	125
Table 6-30 Product Types (UFP)	126
Table 6-31 Product Types (Cable Plug)	127
Table 6-32 Product Types (DFP)	127
Table 6-33 Cert Stat VDO	127
Table 6-34 Product VDO	128
Table 6-35 Passive Cable VDO	128
Table 6-36 Active Cable VDO 1	130
Table 6-37 Active Cable VDO 2	132
Table 6-38 AMA VDO	133
Table 6-39 VPD VDO	134
Table 6-40 Discover SVIDs Responder VDO	135
Table 6-41 Battery Status Data Object (BSDO)	143
Table 6-42 Alert Data Object	144
Table 6-43 Country Code Data Object	145
Table 6-44 Extended Message Types	146
Table 6-45 Source Capabilities Extended Data Block (SCEDB)	147

Table 6-46 SOP Status Data Block (SDB)	151
Table 6-47 SOP'/SOP'' Status Data Block (SDB)	153
Table 6-48 Get Battery Cap Data Block (GBCDB)	153
Table 6-49 Get Battery Status Data Block (GBSDB).....	154
Table 6-50 Battery Capability Data Block (BCDB)	154
Table 6-51 Get Manufacturer Info Data Block (GMIDB)	155
Table 6-52 Manufacturer Info Data Block (MIDB)	155
Table 6-53 PPS Status Data Block (PPSSDB)	157
Table 6-54 Country Codes Data Block (CCDB)	158
Table 6-55 Country Info Data Block (CIDB).....	159
Table 6-56 Sink Capabilities Extended Data Block (SKEDB)	159
Table 6-57 Time Values	171
Table 6-58 Timers.....	172
Table 6-59 Counter parameters	174
Table 6-60 Counters	174
Table 6-61 Response to an incoming Message (except VDM)	176
Table 6-62 Response to an incoming VDM.....	176
Table 6-63 Message discarding	178
Table 6-64 Protocol Layer States	197
Table 6-65 Applicability of Control Messages.....	199
Table 6-66 Applicability of Data Messages.....	200
Table 6-67 Applicability of Extended Messages	201
Table 6-68 Applicability of Structured VDM Commands.....	202
Table 6-69 Applicability of Reset Signaling	203
Table 6-70 Applicability of Fast Role Swap signal	203
Table 6-71 Value Parameters	203
Table 7-1 Sequence Description for Increasing the Current	223
Table 7-2 Sequence Description for Increasing the Voltage	225
Table 7-3 Sequence Diagram for Increasing the Voltage and Current	227
Table 7-4 Sequence Description for Increasing the Voltage and Decreasing the Current.....	229
Table 7-5 Sequence Description for Decreasing the Voltage and Increasing the Current.....	231
Table 7-6 Sequence Description for Decreasing the Current	233
Table 7-7 Sequence Description for Decreasing the Voltage	235
Table 7-8 Sequence Description for Decreasing the Voltage and the Current.....	237
Table 7-9 Sequence Description for a Sink Requested Power Role Swap	239
Table 7-10 Sequence Description for a Source Requested Power Role Swap	242
Table 7-11 Sequence Description for a GotoMin Current Decrease	245
Table 7-12 Sequence Description for a Source Initiated Hard Reset	247
Table 7-13 Sequence Description for a Sink Initiated Hard Reset	249
Table 7-14 Sequence Description for no change in Current or Voltage.....	251
Table 7-15 Sequence Description for Fast Role Swap.....	252
Table 7-16 Sequence Description for Increasing the Programmable Power Supply Voltage	254

Table 7-17 Sequence Description for Decreasing the Programmable Power Supply Voltage	256
Table 7-18 Sequence Description for Changing the Source PDO or APDO	258
Table 7-19 Sequence Description for increasing the Current in PPS mode.....	260
Table 7-20 Sequence Description for decreasing the Current in PPS mode	262
Table 7-21 Sequence Description for increasing the Current in PPS mode.....	264
Table 7-22 Source Electrical Parameters	265
Table 7-23 Sink Electrical Parameters	269
Table 7-24 Common Source/Sink Electrical Parameters.....	270
Table 8-1 Basic Message Flow	278
Table 8-2 Potential issues in Basic Message Flow	279
Table 8-3 Basic Message Flow with CRC failure	280
Table 8-4 Interruptible and Non-interruptible AMS	282
Table 8-5 Steps for a successful Power Negotiation.....	284
Table 8-6 Steps for a GotoMin Negotiation	287
Table 8-7 Steps for a successful Power Negotiation.....	289
Table 8-8 Steps for a Soft Reset.....	292
Table 8-9 Steps for Source initiated Hard Reset	295
Table 8-10 Steps for Sink initiated Hard Reset.....	298
Table 8-11 Steps for Source initiated Hard Reset – Sink long reset	301
Table 8-12 Steps for a Successful Source Initiated Power Role Swap Sequence	304
Table 8-13 Steps for a Successful Sink Initiated Power Role Swap Sequence	307
Table 8-14 Steps for a Successful Fast Role Swap Sequence.....	312
Table 8-15 Steps for Data Role Swap, UFP operating as Sink initiates	315
Table 8-16 Steps for Data Role Swap, UFP operating as Source initiates	317
Table 8-17 Steps for Data Role Swap, DFP operating as Source initiates	319
Table 8-18 Steps for Data Role Swap, DFP operating as Sink initiates	321
Table 8-19 Steps for Source to Sink Vconn Source Swap	323
Table 8-20 Steps for Sink to Source Vconn Source Swap	326
Table 8-21 Steps for Source Alert to Sink	329
Table 8-22 Steps for Sink Alert to Source	330
Table 8-23 Steps for a Sink getting Source Status Sequence.....	331
Table 8-24 Steps for a Source getting Sink Status Sequence.....	333
Table 8-25 Steps for a Sink getting Source PPS status Sequence	335
Table 8-26 Steps for a Sink getting Source Capabilities Sequence	337
Table 8-27 Steps for a Dual-Role Source getting Dual-Role Sink's capabilities as a Source Sequence	339
Table 8-28 Steps for a Source getting Sink Capabilities Sequence	341
Table 8-29 Steps for a Dual-Role Sink getting Dual-Role Source capabilities as a Sink Sequence	343
Table 8-30 Steps for a Sink getting Source extended capabilities Sequence.....	345
Table 8-31 Steps for a Dual-Role Source getting Dual-Role Sink extended capabilities Sequence	347
Table 8-32 Steps for a Sink getting Source Battery capabilities Sequence	349

Table 8-33 Steps for a Source getting Sink Battery capabilities Sequence	351
Table 8-34 Steps for a Sink getting Source Battery status Sequence	353
Table 8-35 Steps for a Source getting Sink Battery status Sequence	355
Table 8-36 Steps for a Source getting Sink's Port Manufacturer Information Sequence.....	357
Table 8-37 Steps for a Source getting Sink's Port Manufacturer Information Sequence.....	359
Table 8-38 Steps for a Source getting Sink's Battery Manufacturer Information Sequence	361
Table 8-39 Steps for a Source getting Sink's Battery Manufacturer Information Sequence	363
Table 8-40 Steps for a Vconn Source getting Sink's Port Manufacturer Information Sequence	365
Table 8-41 Steps for a Source getting Country Codes Sequence	367
Table 8-42 Steps for a Source getting Sink's Country Codes Sequence	369
Table 8-43 Steps for a Vconn Source getting Sink's Country Codes Sequence	371
Table 8-44 Steps for a Source getting Country Information Sequence.....	373
Table 8-45 Steps for a Source getting Sink's Country Information Sequence	375
Table 8-46 Steps for a Vconn Source getting Sink's Country Information Sequence.....	377
Table 8-47 Steps for a Source requesting a security exchange with a Sink Sequence.....	379
Table 8-48 Steps for a Sink requesting a security exchange with a Source Sequence.....	381
Table 8-49 Steps for a Vconn Source requesting a security exchange with a Cable Plug Sequence	383
Table 8-50 Steps for a Source requesting a firmware update exchange with a Sink Sequence	385
Table 8-51 Steps for a Sink requesting a firmware update exchange with a Source Sequence	387
Table 8-52 Steps for a Vconn Source requesting a firmware update exchange with a Cable Plug Sequence	389
Table 8-53 Steps for DFP to UFP Discover Identity.....	391
Table 8-54 Steps for Source Port to Cable Plug Discover Identity	393
Table 8-55 Steps for DFP to Cable Plug Discover Identity.....	395
Table 8-56 Steps for DFP to UFP Enter Mode.....	397
Table 8-57 Steps for DFP to UFP Exit Mode	399
Table 8-58 Steps for DFP to Cable Plug Enter Mode.....	401
Table 8-59 Steps for DFP to Cable Plug Exit Mode	403
Table 8-60 Steps for UFP to DFP Attention.....	405
Table 8-61 Steps for BIST Carrier Mode Test	407
Table 8-62 Steps for BIST Test Data Test.....	409
Table 8-63 Policy Engine States	471
Table 9-1 USB Power Delivery Type Codes	483
Table 9-2 USB Power Delivery Capability Descriptor	483
Table 9-3 Battery Info Capability Descriptor.....	484
Table 9-4 PD Consumer Port Descriptor	485
Table 9-5 PD Provider Port Descriptor	485
Table 9-6 PD Requests.....	486
Table 9-7 PD Request Codes.....	486

Table 9-8 PD Feature Selectors	486
Table 9-9 Battery Status Structure	487
Table 9-10 Battery Wake Mask	488
Table 9-11 Charging Policy Encoding	489
Table 10-1 Considerations for Sources	490
Table 10-2 Normative Voltages and Minimum Currents	491
Table 10-3 Fixed Supply PDO – Source 5V	492
Table 10-4 Fixed Supply PDO – Source 9V	493
Table 10-5 Fixed Supply PDO – Source 15V	493
Table 10-6 Fixed Supply PDO – Source 20V	493
Table 10-7 Programmable Power Supply PDOs and APDOs based on the PDP	494
Table 10-8 Programmable Power Supply Voltage Ranges	494
Table B-1 External power is supplied downstream	500
Table B-2 External power is supplied upstream	503
Table B-3 Giving back power	508
Table C-1 Discover Identity Command request from Initiator Example	518
Table C-2 Discover Identity Command response from Active Cable Responder Example	519
Table C-3 Discover Identity Command response from Hub Responder Example	520
Table C-4 Discover SVIDs Command request from Initiator Example	521
Table C-5 Discover SVIDs Command response from Responder Example	521
Table C-6 Discover Modes Command request from Initiator Example	522
Table C-7 Discover Modes Command response from Responder Example	522
Table C-8 Enter Mode Command request from Initiator Example	523
Table C-9 Enter Mode Command response from Responder Example	524
Table C-10 Enter Mode Command request from Initiator Example	524
Table C-11 Exit Mode Command request from Initiator Example	525
Table C-12 Exit Mode Command response from Responder Example	525
Table C-13 Attention Command request from Initiator Example	526
Table C-14 Attention Command request from Initiator with additional VDO Example	526
Table E-1: Sequence Table for setup of a Fast Role Swap (Hub connected to Power Adapter first)	534
Table E-2 Sequence Table for setup of a Fast Role Swap (Hub connected to Notebook before Power Adapter)	535
Table E-3 Sequence Table for slow Vbus discharge (it discharges after FR_Swap message is sent)	537
Table E-4 Vbus discharges quickly after adapter disconnected.	538

List of Figures

Figure 2-1 Logical Structure of USB Power Delivery Capable Devices	49
Figure 2-2 Example SOP' Communication between VCONN Source and Cable Plug(s)	51
Figure 2-3 USB Power Delivery Communications Stack	58
Figure 2-4 USB Power Delivery Communication Over USB	59
Figure 2-5 High Level Architecture View	60
Figure 5-1 Interpretation of ordered sets	66
Figure 5-2 Transmit Order for Various Sizes of Data	67
Figure 5-3 USB Power Delivery Packet Format	68
Figure 5-4 CRC 32 generation	71
Figure 5-5 Line format of Hard Reset	72
Figure 5-6 Line format of Cable Reset	73
Figure 5-7 BMC Example	74
Figure 5-8 BMC Transmitter Block Diagram	74
Figure 5-9 BMC Receiver Block Diagram	74
Figure 5-10 BMC Encoded Start of Preamble	75
Figure 5-11 Transmitting or Receiving BMC Encoded Frame Terminated by Zero with High-to-Low Last Transition	75
Figure 5-12 Transmitting or Receiving BMC Encoded Frame Terminated by One with High-to-Low Last Transition	75
Figure 5-13 Transmitting or Receiving BMC Encoded Frame Terminated by Zero with Low to High Last Transition	76
Figure 5-14 Transmitting or Receiving BMC Encoded Frame Terminated by One with Low to High Last Transition	76
Figure 5-15 BMC Tx 'ONE' Mask	77
Figure 5-16 BMC Tx 'ZERO' Mask	77
Figure 5-17 BMC Rx 'ONE' Mask when Sourcing Power	79
Figure 5-18 BMC Rx 'ZERO' Mask when Sourcing Power	80
Figure 5-19 BMC Rx 'ONE' Mask when Power neutral	80
Figure 5-20 BMC Rx 'ZERO' Mask when Power neutral	81
Figure 5-21 BMC Rx 'ONE' Mask when Sinking Power	81
Figure 5-22 BMC Rx 'ZERO' Mask when Sinking Power	82
Figure 5-23 Transmitter Load Model for BMC Tx from a Source	83
Figure 5-24 Transmitter Load Model for BMC Tx from a Sink	83
Figure 5-25 Transmitter diagram illustrating zDriver	85
Figure 5-26 Inter-Frame Gap Timings	85
Figure 5-27 Example Multi-Drop Configuration showing two DRPs	87
Figure 5-28 Example Multi-Drop Configuration showing a DFP and UFP	88
Figure 5-29 Test Data Frame	89
Figure 6-1 USB Power Delivery Packet Format including Control Message Payload	90
Figure 6-2 USB Power Delivery Packet Format including Data Message Payload	90
Figure 6-3 USB Power Delivery Packet Format including an Extended Message Header and Payload	90
Figure 6-4 Example Security_Request sequence Unchunked (Chunked bit = 0)	96

Figure 6-5 Example byte transmission for Security_Request Message of Data Size 7 (Chunked bit is set to 0).....	96
Figure 6-6 Example byte transmission for Security_Response Message of Data Size 7 (Chunked bit is set to 0).....	96
Figure 6-7 Example Security_Request sequence Chunked (Chunked bit = 1).....	97
Figure 6-8 Example Security_Request Message of Data Size 7 (Chunked bit set to 1).....	97
Figure 6-9 Example Chunk 0 of Security_Response Message of Data Size 30 (Chunked bit set to 1)	98
Figure 6-10 Example byte transmission for a Security_Request Message Chunk request (Chunked bit is set to 1)	98
Figure 6-11 Example Chunk 1 of Security_Response Message of Data Size 30 (Chunked bit set to 1)	98
Figure 6-12 Example Capabilities Message with 2 Power Data Objects.....	106
Figure 6-13 BIST Message	119
Figure 6-14 Vendor Defined Message	120
Figure 6-15 Discover Identity Command response	125
Figure 6-16 Example Discover SVIDs response with 3 SVIDs	135
Figure 6-17 Example Discover SVIDs response with 4 SVIDs	136
Figure 6-18 Example Discover SVIDs response with 12 SVIDs followed by an empty response.....	136
Figure 6-19 Example Discover Modes response for a given SVID with 3 Modes.....	136
Figure 6-20 Successful Enter Mode sequence	137
Figure 6-21 Enter Mode sequence Interrupted by Source Capabilities and then Re-run	138
Figure 6-22 Unsuccessful Enter Mode sequence due to NAK.....	138
Figure 6-23 Exit Mode sequence.....	139
Figure 6-24 Attention Command request/response sequence.....	140
Figure 6-25 Command request/response sequence.....	140
Figure 6-26 Enter/Exit Mode Process.....	142
Figure 6-27 Battery_Status Message	143
Figure 6-28 Alert Message.....	144
Figure 6-29 Get_Country_Info Message.....	145
Figure 6-30 Source_Capabilities_Extended Message.....	146
Figure 6-31 SOP Status Message	150
Figure 6-32 SOP'/SOP'' Status Message	152
Figure 6-33 Get_Battery_Cap Message	153
Figure 6-34 Get_Battery_Status Message.....	153
Figure 6-35 Battery_Capabilities Message	154
Figure 6-36 Get_Manufacturer_Info Message	155
Figure 6-37 Manufacturer_Info Message	155
Figure 6-38 Security_Request Message.....	156
Figure 6-39 Security_Response Message	156
Figure 6-40 Firmware_Update_Request Message	157
Figure 6-41 Firmware_Update_Response Message	157
Figure 6-42 PPS_Status Message	157
Figure 6-43 Country_Codes Message	158

Figure 6-44 Country_Info Message	158
Figure 6-45 Sink_Capabilities_Extended Message	159
Figure 6-46 Outline of States	179
Figure 6-47 References to states	179
Figure 6-48 Chunking architecture Showing Message and Control Flow.....	180
Figure 6-49 Chunked Rx State Diagram	181
Figure 6-50 Chunked Tx State Diagram	183
Figure 6-51 Chunked Message Router State Diagram.....	186
Figure 6-52 Common Protocol Layer Message transmission State Diagram	187
Figure 6-53 Source Protocol Layer Message transmission State Diagram	190
Figure 6-54 Sink Protocol Layer Message transmission State Diagram	191
Figure 6-55 Protocol layer Message reception	192
Figure 6-56 Hard/Cable Reset	194
Figure 7-1 Placement of Source Bulk Capacitance.....	204
Figure 7-2 Transition Envelope for Positive Voltage Transitions	205
Figure 7-3 Transition Envelope for Negative Voltage Transitions	205
Figure 7-4 PPS Positive Voltage Transitions.....	207
Figure 7-5 PPS Negative Voltage Transitions.....	207
Figure 7-6 Expected PPS Ripple Relative to an LSB.....	208
Figure 7-7 PPS Programmable Voltage and Current Limit.....	209
Figure 7-8 PPS Programmable Voltage and Current Limit.....	210
Figure 7-9 Source V _{BUS} and V _{CONN} Response to Hard Reset	211
Figure 7-10 Application of vSrcNew and vSrcValid limits after tSrcReady	213
Figure 7-11 Source Peak Current Overload.....	214
Figure 7-12 Holdup Time Measurement	215
Figure 7-13 V _{BUS} Power during Fast Role Swap	216
Figure 7-14 V _{BUS} detection and timing during Fast Role Swap, initial V _{BUS} (at new source) > vSafe5V (min).	217
Figure 7-15 V _{BUS} detection and timing during Fast Role Swap, initial V _{BUS} (at new source) < vSafe5V (min).	217
Figure 7-16 Placement of Sink Bulk Capacitance	218
Figure 7-17 Transition Diagram for Increasing the Current.....	222
Figure 7-18 Transition Diagram for Increasing the Voltage.....	224
Figure 7-19 Transition Diagram for Increasing the Voltage and Current	226
Figure 7-20 Transition Diagram for Increasing the Voltage and Decreasing the Current	228
Figure 7-21 Transition Diagram for Decreasing the Voltage and Increasing the Current	230
Figure 7-22 Transition Diagram for Decreasing the Current	232
Figure 7-23 Transition Diagram for Decreasing the Voltage	234
Figure 7-24 Transition Diagram for Decreasing the Voltage and the Current	236
Figure 7-25 Transition Diagram for a Sink Requested Power Role Swap.....	238
Figure 7-26 Transition Diagram for a Source Requested Power Role Swap.....	241
Figure 7-27 Transition Diagram for a GotoMin Current Decrease	244
Figure 7-28 Transition Diagram for a Source Initiated Hard Reset.....	246

Figure 7-29 Transition Diagram for a Sink Initiated Hard Reset	248
Figure 7-30 Transition Diagram for no change in Current or Voltage	250
Figure 7-31 Transition Diagram for Fast Role Swap	252
Figure 7-32 Transition Diagram for Increasing the Programmable Power Supply Voltage	254
Figure 7-33 Transition Diagram for Decreasing the Programmable Power Supply Voltage	256
Figure 7-34 Transition Diagram for Changing the Source PDO or APDO	258
Figure 7-35 Transition Diagram for increasing the Current in PPS mode	260
Figure 7-36 Transition Diagram for decreasing the Current in PPS mode	262
Figure 7-37 Transition Diagram for no change in Current or Voltage in PPS mode	264
Figure 8-1 Example of daisy chained displays	276
Figure 8-2 Basic Message Exchange (Successful)	278
Figure 8-3 Basic Message flow indicating possible errors	279
Figure 8-4 Basic Message Flow with Bad CRC followed by a Retry	280
Figure 8-5 Successful Fixed, Variable or Battery Power Negotiation	283
Figure 8-6 Successful GotoMin operation	287
Figure 8-7 PPS Keep Alive	289
Figure 8-8 Soft Reset	292
Figure 8-9 Source initiated Hard Reset	294
Figure 8-10 Sink Initiated Hard Reset	297
Figure 8-11 Source initiated reset - Sink long reset	300
Figure 8-12 Successful Power Role Swap Sequence Initiated by the Source	303
Figure 8-13 Successful Power Role Swap Sequence Initiated by the Sink	307
Figure 8-14 Successful Fast Role Swap Sequence	311
Figure 8-15 Data Role Swap, UFP operating as Sink initiates	315
Figure 8-16 Data Role Swap, UFP operating as Source initiates	317
Figure 8-17 Data Role Swap, DFP operating as Source initiates	319
Figure 8-18 Data Role Swap, DFP operating as Sink initiates	321
Figure 8-19 Source to Sink VCONN Source Swap	323
Figure 8-20 Sink to Source VCONN Source Swap	326
Figure 8-21 Source Alert to Sink	328
Figure 8-22 Sink Alert to Source	330
Figure 8-23 Sink Gets Source Status	331
Figure 8-24 Source Gets Sink Status	333
Figure 8-25 Sink Gets Source PPS Status	335
Figure 8-26 Sink Gets Source's Capabilities	337
Figure 8-27 Dual-Role Source Gets Dual-Role Sink's Capabilities as a Source	339
Figure 8-28 Source Gets Sink's Capabilities	341
Figure 8-29 Dual-Role Sink Gets Dual-Role Source's Capabilities as a Sink	343
Figure 8-30 Sink Gets Source's Extended Capabilities	345
Figure 8-31 Dual-Role Source Gets Dual-Role Sink's Extended Capabilities	347
Figure 8-32 Sink Gets Source's Battery Capabilities	349

Figure 8-33 Source Gets Sink's Battery Capabilities 351

Figure 8-34 Sink Gets Source's Battery Status 353

Figure 8-35 Source Gets Sink's Battery Status 355

Figure 8-36 Source Gets Sink's Port Manufacturer Information 357

Figure 8-37 Sink Gets Source's Port Manufacturer Information 359

Figure 8-38 Source Gets Sink's Battery Manufacturer Information 361

Figure 8-39 Sink Gets Source's Battery Manufacturer Information 363

Figure 8-40 VCONN Source Gets Cable Plug's Manufacturer Information 365

Figure 8-41 Source Gets Sink's Country Codes 367

Figure 8-42 Sink Gets Source's Country Codes 369

Figure 8-43 VCONN Source Gets Cable Plug's Country Codes 371

Figure 8-44 Source Gets Sink's Country Information 373

Figure 8-45 Sink Gets Source's Country Information 375

Figure 8-46 VCONN Source Gets Cable Plug's Country Information 377

Figure 8-47 Source requests security exchange with Sink 379

Figure 8-48 Sink requests security exchange with Source 381

Figure 8-49 Vconn Source requests security exchange with Cable Plug 383

Figure 8-50 Source requests firmware update exchange with Sink 385

Figure 8-51 Sink requests firmware update exchange with Source 387

Figure 8-52 Vconn Source requests firmware update exchange with Cable Plug 389

Figure 8-53 DFP to UFP Discover Identity 391

Figure 8-54 Source Port to Cable Plug Discover Identity 393

Figure 8-55 DFP to Cable Plug Discover Identity 395

Figure 8-56 DFP to UFP Enter Mode 397

Figure 8-57 DFP to UFP Exit Mode 399

Figure 8-58 DFP to Cable Plug Enter Mode 401

Figure 8-59 DFP to Cable Plug Exit Mode 403

Figure 8-60 UFP to DFP Attention 405

Figure 8-61 BIST Carrier Mode Test 406

Figure 8-62 BIST Test Data Test 408

Figure 8-63 Outline of States 410

Figure 8-64 References to states 410

Figure 8-65 Example of state reference with conditions 411

Figure 8-66 Example of state reference with the same entry and exit 411

Figure 8-67 Source Port Policy Engine State Diagram 412

Figure 8-68 Sink Port State Diagram 417

Figure 8-69 Source Port Soft Reset and Protocol Error State Diagram 421

Figure 8-70 Sink Port Soft Reset and Protocol Error Diagram 422

Figure 8-71 Source Port Not Supported Message State Diagram 423

Figure 8-72 Sink Port Not Supported Message State Diagram 424

Figure 8-73 Source Port Ping State Diagram 425

Figure 8-74 Source Port Source Alert State Diagram 425

Figure 8-75 Sink Port Source Alert State Diagram 425

Figure 8-76 Sink Port Sink Alert State Diagram.....	426
Figure 8-77 Source Port Sink Alert State Diagram	426
Figure 8-78 Sink Port Get Source Capabilities Extended State Diagram	426
Figure 8-79 Source Give Source Capabilities Extended State Diagram	427
Figure 8-80 Sink Port Get Source Status State Diagram	427
Figure 8-81 Source Give Source Status State Diagram	428
Figure 8-82 Source Port Get Sink Status State Diagram	428
Figure 8-83 Sink Give Sink Status State Diagram	428
Figure 8-84 Sink Port Get Source PPS Status State Diagram	429
Figure 8-85 Source Give Source PPS Status State Diagram	429
Figure 8-86 Get Battery Capabilities State Diagram	430
Figure 8-87 Give Battery Capabilities State Diagram	430
Figure 8-88 Get Battery Status State Diagram	430
Figure 8-89 Give Battery Status State Diagram.....	431
Figure 8-90 Get Manufacturer Information State Diagram	431
Figure 8-91 Give Manufacturer Information State Diagram.....	432
Figure 8-92 Get Country Codes State Diagram	432
Figure 8-93 Give Country Codes State Diagram.....	433
Figure 8-94 Get Country Information State Diagram.....	433
Figure 8-95 Give Country Information State Diagram	433
Figure 8-96 Send security request State Diagram	434
Figure 8-97 Send security response State Diagram	434
Figure 8-98 Security response received State Diagram.....	435
Figure 8-99 Send firmware update request State Diagram	435
Figure 8-100 Send firmware update response State Diagram.....	435
Figure 8-101 Firmware update response received State Diagram.....	436
Figure 8-102: DFP to UFP Data Role Swap State Diagram	437
Figure 8-103: UFP to DFP Data Role Swap State Diagram	439
Figure 8-104: Dual-Role Port in Source to Sink Power Role Swap State Diagram	441
Figure 8-105: Dual-role Port in Sink to Source Power Role Swap State Diagram	443
Figure 8-106: Dual-Role Port in Source to Sink Fast Role Swap State Diagram	445
Figure 8-107: Dual-role Port in Sink to Source Fast Role Swap State Diagram	447
Figure 8-108 Dual-Role (Source) Get Source Capabilities diagram	449
Figure 8-109 Dual-Role (Source) Give Sink Capabilities diagram.....	449
Figure 8-110 Dual-Role (Sink) Get Sink Capabilities State Diagram.....	449
Figure 8-111 Dual-Role (Sink) Give Source Capabilities State Diagram	450
Figure 8-112 Dual-Role (Source) Get Source Capabilities Extended State Diagram	450
Figure 8-113 Dual-Role (Source) Give Sink Capabilities diagram.....	451
Figure 8-114 VCONN Swap State Diagram	451
Figure 8-115 Initiator to Port VDM Discover Identity State Diagram	454
Figure 8-116 Initiator VDM Discover SVIDs State Diagram	455
Figure 8-117 Initiator VDM Discover Modes State Diagram.....	456
Figure 8-118 Initiator VDM Attention State Diagram.....	457

Figure 8-119 Responder Structured VDM Discover Identity State Diagram..... 457

Figure 8-120 Responder Structured VDM Discover SVIDs State Diagram 458

Figure 8-121 Responder Structured VDM Discover Modes State Diagram..... 459

Figure 8-122 Receiving a Structured VDM Attention State Diagram 460

Figure 8-123 DFP VDM Mode Entry State Diagram 460

Figure 8-124 DFP VDM Mode Exit State Diagram 461

Figure 8-125 UFP Structured VDM Enter Mode State Diagram..... 462

Figure 8-126 UFP Structured VDM Exit Mode State Diagram 463

Figure 8-127 Cable Ready VDM State Diagram 464

Figure 8-128 Cable Plug Soft Reset State Diagram..... 464

Figure 8-129 Cable Plug Hard Reset State Diagram 465

Figure 8-130 VCONN Source Soft Reset or Cable Reset of a Cable Plug State Diagram 465

Figure 8-131 Source Startup Structured VDM Discover Identity State Diagram 466

Figure 8-132 Cable Plug Structured VDM Enter Mode State Diagram 468

Figure 8-133 Cable Plug Structured VDM Exit Mode State Diagram..... 469

Figure 8-134 BIST Carrier Mode State Diagram 470

Figure 9-1 Example PD Topology..... 477

Figure 9-2 Mapping of PD Topology to USB..... 478

Figure 9-3 USB Attached to USB Powered State Transition 479

Figure 9-4 Any USB State to USB Attached State Transition (When operating as a Consumer)..... 479

Figure 9-5 Any USB State to USB Attached State Transition (When operating as a Provider)..... 480

Figure 9-6 Any USB State to USB Attached State Transition (After a USB Type-C Data Role Swap)..... 480

Figure 9-7 Software stack on a PD aware OS 481

Figure 9-8 Enumeration of a PDUSB Device 482

Figure 10-1 Source Power Rule Illustration 491

Figure 10-2 Source Power Rule Example..... 492

Figure B-1 External Power supplied downstream 499

Figure B-2 External Power supplied upstream..... 502

Figure B-3 Giving Back Power 508

Figure D-1 Circuit Block of BMC Finite Difference Receiver 527

Figure D-2 BMC AC and DC noise from VBUS at Power Sink 528

Figure D-3 Sample BMC Signals (a) without [USB 2.0] SE0 Noise (b) with [USB 2.0] SE0 Noise 528

Figure D-4 Scaled BMC Signal Derivative with 50ns Sampling Rate..... 529

Figure D-5 BMC Signal and Finite Difference Output with Various Time Steps 529

Figure D-6 Output of Finite Difference in dash line and Edge Detector in solid line 530

Figure D-7 Noise Zone and Detect Zone of BMC Receiver 530

Figure D-8 Circuit Block of BMC Subtraction Receiver 531

Figure D-9 (a) Output of LPF1 and LPF2 (b) Subtraction of LPF1 and LPF2 Output 531

Figure D-10 Output of the BMC LPF1 in blue dash curve and the Subtractor in red solid curve 531

Figure E-1 Example FRS Capable System	532
Figure E-2 Slow V_{BUS} Discharge.....	533
Figure E-3 Fast V_{BUS} Discharge	534
Figure E-4 Sequence Diagram for slow V_{BUS} discharge (it discharges after FR_Swap message is sent).....	537

1 Introduction

USB has evolved from a data interface capable of supplying limited power to a primary provider of power with a data interface. Today many devices charge or get their power from USB ports contained in laptops, cars, aircraft or even wall sockets. USB has become a ubiquitous power socket for many small devices such as cell phones, MP3 players and other hand-held devices. Users need USB to fulfill their requirements not only in terms of data but also to provide power to, or charge, their devices simply, often without the need to load a driver, in order to carry out “traditional” USB functions.

There are however, still many devices which either require an additional power connection to the wall, or exceed the USB rated current in order to operate. Increasingly, international regulations require better energy management due to ecological and practical concerns relating to the availability of power. Regulations limit the amount of power available from the wall which has led to a pressing need to optimize power usage. The USB Power Delivery Specification has the potential to minimize waste as it becomes a standard for charging devices that are not satisfied by [\[USBBC 1.2\]](#).

Wider usage of wireless solutions is an attempt to remove data cabling but the need for “tethered” charging remains. In addition, industrial design requirements drive wired connectivity to do much more over the same connector.

USB Power Delivery is designed to enable the maximum functionality of USB by providing more flexible power delivery along with data over a single cable. Its aim is to operate with and build on the existing USB ecosystem; increasing power levels from existing USB standards, for example Battery Charging, enabling new higher power use cases such as USB powered Hard Disk Drives (HDDs) and printers.

With USB Power Delivery the power direction is no longer fixed. This enables the product with the power (Host or Peripheral) to provide the power. For example, a display with a supply from the wall can power, or charge, a laptop. Alternatively, USB power bricks or chargers are able to supply power to laptops and other battery powered devices through their, traditionally power providing, USB ports.

USB Power Delivery enables hubs to become the means to optimize power management across multiple peripherals by allowing each device to take only the power it requires, and to get more power when required for a given application. For example, battery powered devices can get increased charging current and then give it back temporarily when the user’s HDD requires spinning up. **Optionally** the hubs can communicate with the PC to enable even more intelligent and flexible management of power either automatically or with some level of user intervention.

USB Power Delivery allows Low Power cases such as headsets to negotiate for only the power they require. This provides a simple solution that enables USB devices to operate at their optimal power levels.

The Power Delivery Specification, in addition to providing mechanisms to negotiate power also can be used as a side-band channel for standard and vendor defined messaging. Power Delivery enables alternative modes of operation by providing the mechanisms to discover, enter and exit Alternate Modes. The specification also enables discovery of cable capabilities such as supported speeds and current levels.

1.1 Overview

This specification defines how USB Devices can negotiate for more current and/or higher or lower voltages over the USB cable (using the USB Type-C CC wire as the communications channel) than are defined in the [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 1.3\]](#) or [\[USBBC 1.2\]](#) specifications. It allows Devices with greater power requirements than can be met with today’s specification to get the power they require to operate from V_{BUS} and negotiate with external power sources (e.g. Wall Warts). In addition, it allows a Source and Sink to swap power roles such that a Device could supply power to the Host. For example, a display could supply power to a notebook to charge its battery.

The USB Power Delivery Specification is guided by the following principles:

- Works seamlessly with legacy USB Devices
- Compatible with existing spec-compliant USB cables
- Minimizes potential damage from non-compliant cables (e.g. ‘Y’ cables etc.)
- Optimized for low-cost implementations

This specification defines mechanisms to discover, enter and exit Modes defined either by a standard or by a particular vendor. These Modes can be supported either by the Port Partner or by a cable connecting the two Port Partners.

The specification defines mechanisms to discover the capabilities of cables which can communicate using Power Delivery.

This specification adds a mechanism to swap the data roles such that the upstream facing Port becomes the downstream facing Port and vice versa. It also enables a swap of the end supplying V_{CONN} to a powered cable.

To facilitate optimum charging, the specification defines two mechanisms a USB Charger can advertise for the Device to use:

1. A list of fixed voltages each with a maximum current. The Device selects a voltage and current from the list. This is the traditional model used by Devices that use internal electronics to manage the charging of their battery including modifying the voltage and current actually supplied to the battery. The side-effect of this model is that the charging circuitry generates heat that may be problematic for small form factor devices.
2. A list of programmable voltage ranges each with a maximum current (PPS). The Device requests a voltage (in 20 mV increments) that is within the advertised range and a maximum current. The USB Charger delivers the requested voltage until the maximum current is reached at which time the USB charger reduces its output voltage so as not to supply more than the requested maximum current. During the high current portion of the charge cycle, the USB Charger can be directly connected (through an appropriate safety device) to the battery. This model is used by Devices that want to minimize the thermal impact of their internal charging circuitry.

1.2 Purpose

The USB Power Delivery specification defines a power delivery system covering all elements of a USB system including: Hosts, Devices, Hubs, Chargers and cable assemblies. This specification describes the architecture, protocols, power supply behavior, connectors and cabling necessary for managing power delivery over USB at up to 100W. This specification is intended to be fully compatible and extend the existing USB infrastructure. It is intended that this specification will allow system OEMs, power supply and peripheral developers adequate flexibility for product versatility and market differentiation without losing backwards compatibility.

USB Power Delivery is designed to operate independently of the existing USB bus defined mechanisms used to negotiate power which are:

- [\[USB 2.0\]](#), [\[USB 3.2\]](#) in band requests for high power interfaces.
- [\[USBBC 1.2\]](#) mechanisms for supplying higher power (not mandated by this specification).
- [\[USB Type-C 1.3\]](#) mechanisms for supplying higher power

Initial operating conditions remain the USB Default Operation as defined in [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 1.3\]](#) or [\[USBBC 1.2\]](#).

- The DFP sources *vSafe5V* over V_{BUS} .
- The UFP consumes power from V_{BUS} .

1.3 Scope

This specification is intended as an extension to the existing [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 1.3\]](#) and [\[USBBC 1.2\]](#) specifications. It addresses only the elements required to implement USB Power Delivery. It is targeted at power supply vendors, manufacturers of [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 1.3\]](#) and [\[USBBC 1.2\]](#) Platforms, Devices and cable assemblies.

Normative information is provided to allow interoperability of components designed to this specification. Informative information, when provided, illustrates possible design implementation.

1.4 Conventions

1.4.1 Precedence

If there is a conflict between text, figures, and tables, the precedence **shall** be tables, figures, and then text.