

INTERNATIONAL STANDARD



Transmitting and receiving equipment for radiocommunication – Frequency response of optical-to-electric conversion device in high-frequency radio-over-fibre systems –
Part 2: Measurement method of common-mode rejection ratio of optical coherent detection device for radio-over-fibre transmitter



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

INTERNATIONAL STANDARD



**Transmitting and receiving equipment for radio communication – Frequency response of optical-to-electric conversion device in high-frequency radio-over-fibre systems –
Part 2: Measurement method of common-mode rejection ratio of optical coherent detection device for radio-over-fibre transmitter**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.20

ISBN 978-2-8322-9567-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and abbreviated terms	6
3.1 Terms and definitions.....	6
3.2 Abbreviated terms.....	7
4 Optical coherent detection device	7
4.1 General.....	7
4.1.1 Configuration.....	7
4.1.2 Component parts	7
4.1.3 Structure	7
4.2 Optical coherent detection device	8
4.2.1 General	8
4.2.2 Material of 90° optical hybrid	8
4.2.3 Material of balanced photodiode	8
5 Sampling for quality control	8
5.1 Sampling.....	8
5.2 Sampling frequency	8
6 Measurement method of common-mode rejection ratio	8
6.1 Circuit diagram	8
6.2 Circuit description and requirements	9
6.3 Measurement conditions	10
6.3.1 Temperature and environment	10
6.3.2 Warming-up of measurement equipment.....	10
6.4 Principle of measurement method	10
6.4.1 General	10
6.4.2 Mathematical expressions of basic measurement principle	10
6.4.3 Principle of measurement of common-mode rejection ratio	12
6.5 Measurement procedure	13
Annex A (informative) Application of optical coherent detection device to RF signal transmission	14
A.1 Purpose.....	14
A.2 Diagrams	14
Bibliography.....	15
Figure 1 – Optical coherent detection device	8
Figure 2 – Circuit diagram.....	9
Figure 3 – Schematic illustration of the electric power spectra of the signal measured by the electrical spectrum analyser	13
Figure A.1 – Example of block diagram of a radar radio frontend using a coherent receiver	14

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**TRANSMITTING AND RECEIVING EQUIPMENT FOR
RADIOCOMMUNICATION – FREQUENCY RESPONSE OF
OPTICAL-TO-ELECTRIC CONVERSION DEVICE IN
HIGH-FREQUENCY RADIO-OVER-FIBRE SYSTEMS –****Part 2: Measurement method of common-mode rejection ratio of optical
coherent detection device for radio-over-fibre transmitter**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62803-2 has been prepared by IEC technical committee 103: Transmitting and receiving equipment for radiocommunication. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
103/269/FDIS	103/274/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62803 series, published under the general title *Transmitting and receiving equipment for radiocommunication – Frequency response of optical-to-electric conversion device in high-frequency radio-over-fibre systems* can be found on the IEC website.

Future documents in this series will carry the new general title as cited above. Titles of existing documents in this series will be updated at the time of the next edition.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour in use" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

A variety of photonic devices operated in microwave and millimetre-wave bands are useful for an optical fibre transport system as well as wireless communication and broadcasting systems. An optical-to-electric conversion device including an optical receiver plays as an interface, which converts an optical signal into an electrical signal directly.

Microwave and millimetre-wave radio-over-fibre (RoF) systems are comprised mainly of two parts: an RF to photonic converter (E/O) and a photonic to RF converter (O/E). Radio waves are converted into an optical signal at the E/O, and the signal is transferred through the optical fibre, and then the radio waves are regenerated at the O/E.

A variety of photonic devices which carry microwave and millimeter-wave signals at sub-THz frequencies are used for high-frequency RoF systems. In high-frequency RoF systems such as millimetre-wave band radio signal transfer systems, the specifications of conversion efficiency and its frequency response have been important technical parameters, and therefore, the IEC 62803 series has been developed. Nowadays, the coherent optical fibre network system is used widely, namely in core and metro networks with a capacity greater than 100 Gbit/s/ch. Finally, cost and performance have improved. In this coherent optical fibre network system, an optical coherent detection device, which is comprised of an optical 90° hybrid coupler and balanced photodetectors, provides an IQ separation in an optical domain for easy digital signal processing. This detection device can be useful not only for the coherent optical signal transport but also for a millimeter-wave RoF system with high signal quality. To achieve a high signal quality, which means a good suppression of noises, a common-mode rejection ratio is a key parameter of the optical coherent detection. This document has been developed to provide to the industry a measurement method of a coherent optical detection device for evaluating the specifications to be used in high-frequency RoF systems, as well as in an optical coherent transport system. This document defines the measurement method of a common-mode rejection ratio, which has a significant impact on the performance of RoF systems.

TRANSMITTING AND RECEIVING EQUIPMENT FOR RADIOCOMMUNICATION – FREQUENCY RESPONSE OF OPTICAL-TO-ELECTRIC CONVERSION DEVICE IN HIGH-FREQUENCY RADIO-OVER-FIBRE SYSTEMS –

Part 2: Measurement method of common-mode rejection ratio of optical coherent detection device for radio-over-fibre transmitter

1 Scope

This part of IEC 62803 provides the measurement method of the common-mode rejection ratio of optical coherent detection devices in high-speed RoF systems, as well as in high-speed optical signal transmission systems. In addition, the method is also effective for the estimation of the detailed frequency response of the common-mode rejection ratios and O/E conversion efficiency. The method applies for the following:

- frequency range: 1 GHz to 110 GHz;
- wavelength band: 0,8 μm to 2,0 μm .

The use of optical coherent detection devices for high-speed RoF system is shown in Annex A as an example.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

common-mode rejection ratio

ratio between the signal powers of differential signals and common-mode signals

3.1.2

two-tone lightwave

lightwave that contains two dominant spectral components whose power difference is relatively small and frequency separation is stable

3.1.3

carrier-suppressed

situation when an MZM is biased at its minimum transmission point, the non-modulated carrier lightwave transmitted through and the two arms of the MZM are cancelled with each other at the output coupler