

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Measurement of internal electric field in insulating materials – Pressure wave propagation method

Mesurage du champ électrique interne dans les matériaux isolants – Méthode de l'onde de pression



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications provided, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Measurement of internal electric field in insulating materials – Pressure wave propagation method

Mesurage du champ électrique interne dans les matériaux isolants – Méthode de l'onde de pression

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 17.220.99, 29.035.01

ISBN 978-2-8322-8338-7

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	8
4 Principle of the method.....	9
5 Samples.....	11
6 Electrode materials.....	12
7 Pressure pulse wave generation.....	12
8 Set-up of the measurement.....	13
9 Calibrating the electric field.....	14
10 Measurement procedure.....	14
11 Data processing for experimental measurement.....	15
12 Space charge distribution measurement.....	16
13 Impact of coaxial geometry.....	16
13.1 Measuring set-up of pressure wave propagation method for the coaxial geometry sample.....	16
13.2 Physical model in coaxial geometry.....	17
13.3 Measuring conditions.....	18
13.4 Calibration of electric field for a coaxial sample.....	19
13.4.1 Summary.....	19
13.4.2 Linearity verification.....	19
13.4.3 Validity verification of the ratio between two current peaks.....	19
13.4.4 Method for retrieving internal electric field from the measured current signal.....	20
Annex A (informative) Precise additional method of the original signal for the PWP method on a planar sample.....	22
A.1 Simple integration limitation.....	22
A.2 Analysis of the resiliency effect and correction procedure.....	23
A.3 Example of the correction procedure on a PE sample.....	24
A.4 Estimation of the correction coefficients.....	25
A.5 M. TLAB® code.....	27
Annex B (informative) Linearity verification of the measuring system.....	29
B.1 Linearity verification.....	29
B.2 Sample conditions.....	29
B.3 Linearity verification procedure.....	29
B.4 Example of linearity verification.....	29
Annex C (informative) Measurement examples for planar plaque samples.....	32
C.1 Samples.....	32
C.2 Pressure pulse generation.....	32
C.3 Calibration of sample and signal.....	32
C.4 Testing sample and experimental results.....	33
C.4.1 Measurement results.....	33

C.4.2	Internal electric field distribution in the testing sample	34
C.4.3	Distribution of space charge density in the testing sample	36
Annex D (informative)	Measurement examples for coaxial geometry samples	38
D.1	Example of linearity verification of coaxial geometry	38
D.1.1	Sample conditions	38
D.1.2	Linearity verification procedure	38
D.1.3	Example of linearity verification	38
D.2	Verification of the current peak area ratio between the outer and inner electrodes	39
D.2.1	Verification principle	39
D.2.2	Example of verification of the current peak area ratio	40
D.3	Testing sample and experimental results	40
D.3.1	Raw results of measurements	40
D.3.2	Electric field distribution in the coaxial sample	42
D.3.3	Space charge distribution in the coaxial sample	44
Bibliography	46
Figure 1	– Principle of the PWP method	11
Figure 2	– Measurement set-up for the PWP method	13
Figure 3	– Sample of circuit to protect the amplifier from damage by a small discharge on the sample	13
Figure 4	– Diagram of the pressure wave propagation method set-up for a coaxial sample	17
Figure 5	– Diagram of wave propagation of PWP for a coaxial geometry sample	17
Figure 6	– Diagram of the propagation of pressure wave on the section of a cylinder	19
Figure 7	– Flowchart for the computation of the electric field in a coaxial sample from PWP measured currents	21
Figure A.1	– Comparison between practical and ideal pressure pulses	22
Figure A.2	– Original signal of the sample free of charge under moderate voltage	23
Figure A.3	– Comparison between original and corrected reference signals with a sample free of charge under moderate voltage	24
Figure A.4	– Electric field in a sample under voltage with space charge calculated from original and corrected signals	25
Figure A.5	– Geometrical characteristics of the reference signal for the correction coefficient estimation	26
Figure A.6	– Reference signal corrected with coefficients graphically obtained and adjusted	26
Figure A.7	– Electric field in a sample under voltage with space charge calculated with graphically obtained coefficient and adjusted coefficient	27
Figure B.1	– Voltage signals obtained from the oscilloscope by the amplifier with different amplifications	30
Figure B.2	– Current signals induced by the sample, considering the input impedance and the amplification of the amplifier	30
Figure B.3	– Relationship between the measured current peak of the first electrode and applied voltage	31
Figure C.1	– Measured current signal under –5,8 kV	32
Figure C.2	– First measured current signal (< 1 min)	33
Figure C.3	– Measured current signal after 1,5 h under –46,4 kV	33

Figure C.4 – Measured current signal without applied voltage after 1,5 h under –46,4 kV	34
Figure C.5 – Internal electric field distribution under –5,8 kV	34
Figure C.6 – Internal electric field distribution under –46,4 kV, at the initial state	35
Figure C.7 – Internal electric field distribution after 1,5 h under –46,4 kV	35
Figure C.8 – Internal electric field distribution without applied voltage after 1,5 h under –46,4 kV	36
Figure C.9 – Space charge distribution after 1,5 h under –46,4 kV	37
Figure C.10 – Space charge distribution without applied voltage after 1,5 h under –46,4 kV	37
Figure D.1 – Measured currents from the LDPE coaxial sample under different applied voltages in a few minutes	39
Figure D.2 – Relationships between the peak amplitude of the measured current at outer and inner electrodes and applied voltage	39
Figure D.3 – First measured current signal (< 1 min) for the coaxial sample	40
Figure D.4 – Measured current signals for the coaxial sample at beginning and after 2 h under –90,0 kV	41
Figure D.5 – Measured current signals for the coaxial sample after 2 h under –90,0 kV, and without applied voltage after 2 h under high voltage	41
Figure D.6 – Internal electric field distribution under –22,5 kV for the coaxial sample	42
Figure D.7 – Internal electric field distribution under –90,0 kV for the coaxial sample, at the initial state	43
Figure D.8 – Internal electric field distribution after 2 h under –90,0 kV	43
Figure D.9 – Internal electric field distribution without applied voltage after 2 h under –90,0 kV	44
Figure D.10 – Space charge distribution with and without applied voltage after 2 h under –90,0 kV	45
Table A.1 – Variants of symbols used in the text	27
Table D.2 – Analysis of ratio between theoretical and measured peak area for measured current signal	40

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MEASUREMENT OF INTERNAL ELECTRIC FIELD IN INSULATING MATERIALS – PRESSURE WAVE PROPAGATION METHOD

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62836 has been prepared by IEC technical committee 112: Evaluation and qualification of electrical insulating materials and systems. It is an International Standard.

This first edition cancels and replaces IEC TS 62836 published in 2020.

This edition includes the following significant technical changes with respect to IEC TS 62836:

- a) addition of Clause 12 for the measurement of space charge distribution in a planar sample;
- b) addition of Clause 13 for coaxial geometry samples;
- c) addition of Annex D with measurement examples for coaxial geometry samples;
- d) addition of a Bibliography;
- e) measurement examples for a planar sample have been moved from Clause 12 in IEC TS 62836 to Annex C.

The text of this International Standard is based on the following documents:

Draft	Report on voting
112/627/FDIS	112/632/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

High-voltage insulating structures, especially high-voltage DC cables and capacitors etc., are subjected to charge accumulation and this can lead to electrical breakdown if the electric field produced by the charges exceeds the electrical breakdown threshold. With the trend to multiply power plants, especially green power plants such as wind or solar generators, more cables will be used for connecting these power plants to the grid and share the electric energy between countries. Therefore, a standardized procedure for testing how the internal electric field can be characterized has become essential for the materials used for the cables, and even the structure of these cables when considering electrodes or the junction between cables. The measurement of the internal electric field provides a tool for comparing materials and helps to establish thresholds on the internal electric field for high-voltage applications in order to avoid risks of breakdown as much as possible. The pressure wave propagation (PWP) method has been used by many researchers to measure the space charge distribution and the internal electric field distribution in insulators. However, since experimental equipment, with slight differences, is developed independently by researchers throughout the world, it is difficult to compare the measurement results between the different equipment.

The procedure outlined in this document provides a reliable point of comparison between different test results carried out by different laboratories in order to avoid interpretation errors. The method is suitable for a planar plaque sample as well as for a coaxial sample, with homogeneous insulating materials of thickness from 0,5 mm to 5 mm.

MEASUREMENT OF INTERNAL ELECTRIC FIELD IN INSULATING MATERIALS – PRESSURE WAVE PROPAGATION METHOD

1 Scope

This document provides an efficient and reliable procedure to test the internal electric field in the insulating materials used for high-voltage applications, by using the pressure wave propagation (PWP) method. It is suitable for a planar and coaxial geometry sample with homogeneous insulating materials of thickness larger or equal to 0,5 mm and an electric field higher than 1 kV/mm, but it is also dependent on the thickness of the sample and the pressure wave generator.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

pressure wave propagation

procedure where a pressure wave is propagated in a material containing electric charges and the induced electric signal from electrodes is measured.

3.1.2

interface charge

net layer of charges between two different materials, either two different insulators or a conductor and an insulator.

3.1.3

space charge

net charge inside an insulating dielectric material

3.2 Abbreviated terms

CB	carbon black
EV	ethylene vinyl acetate
LDPE	low density polyethylene
LIPP	laser induced pressure pulse
PE	polyethylene
PIPP	piezoelectric induced pressure pulse
PMMA	poly methyl methacrylate
PWP	pressure wave propagation
S/N	signal to noise ratio