

INTERNATIONAL STANDARD



**Semiconductor devices – Stress migration test standard –
Part 1: Copper stress migration test standard**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - www.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD



**Semiconductor devices – Stress migration test standard –
Part 1: Copper stress migration test standard**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.080.01

ISBN 978-2-8322-4732-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	5
4 Test method	7
4.1 Test structures.....	7
4.2 Test equipment.....	11
4.3 Test temperatures.....	11
4.4 Test conditions, sample size and measurements.....	11
4.5 Failure criteria.....	11
4.6 Passing criteria.....	11
5 Data to be reported.....	12
Annex A (informative) Explanation for stress migration, stress induced voiding Temperature, geometry dependence	13
A.1 Stress-induced voids.....	13
A.2 Stress temperature	13
A.3 Geometry linewidth dependence of SIV risk	14
A.4 VIA size dependence of SIV risk	16
A.5 SIV under multiple VIAs	17
A.6 Metal thickness dependence of SIV risk.....	17
A.7 SM lifetime model	18
A.8 Sensitivity for test structure.....	19
Annex B (informative) Example of geometry dependence for nose pattern	21
B.1 General.....	21
B.2 Geometry factor	21
Bibliography.....	23
Figure 1 – SM test structure sketches	8
Figure 2 – SM test structure sketches – Illustrative sketches of proposed optional SM test structures.....	10
Figure A.1 – Temperature dependent behaviour of SM MTF values of 5 µm VIA chains in the range of 125 °C – 275 °C	14
Figure A.2 – Power-law relation of MTF vs linewidth	15
Figure A.3 – Median time-to-fail SM data as a function of VIA sizes.....	16
Figure A.4 – Hydrostatic stress gradient at near room temperatures vs VIA size (area).....	16
Figure A.5 – FA images of two VIA case and MTF vs multiple VIA of SM	17
Figure A.6 – Metal thickness versus resistance increase under SM tests	18
Figure A.7 – Stress profile of conventional and VIM VIA chains	19
Figure A.8 – SM data of conventional and VIM VIA chains	20
Figure B.1 – Representation of real product interconnect.....	21
Figure B.2 – Representation of SM nose pattern.....	21
Figure B.3 – Failure rate – Body area dependence with nose pattern.....	22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SEMICONDUCTOR DEVICES – STRESS MIGRATION TEST STANDARD –

Part 1: Copper stress migration test standard

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62880-1 has been prepared by IEC technical committee 47: Semiconductor devices.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
47/2407/FDIS	47/2416/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62880 series, published under the general title *Semiconductor devices – Stress migration test standard*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SEMICONDUCTOR DEVICES – STRESS MIGRATION TEST STANDARD –

Part 1: Copper stress migration test standard

1 Scope

This part of IEC 62880 describes a constant temperature (isothermal) aging method for testing copper (Cu) metallization test structures on microelectronics wafers for susceptibility to stress-induced voiding (SIV). This method is to be conducted primarily at the wafer level or production during technology development, and the results are to be used for lifetime prediction and failure analysis. Under some conditions, the method can be applied to package-level testing. This method is not intended to check production lots for shipment, because of the long test time.

Dual damascene Cu metallization systems usually have liners, such as tantalum (Ta) or tantalum nitride (Ta₂N₅) on the bottom and sides of trenches etched into dielectric layers. Hence, for structures in which a single via contacts a wide line below it, a void under the via can cause an open circuit at almost the same time as any percentage resistance shift that would satisfy a failure criterion.

2 Normative references

There are no normative references in this document.

NOTE Related documents are listed in the Bibliography.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia is available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

stress migration

SM

critical failure phenomenon of the semiconductor device interconnects

3.2

stress induced voiding

SIV

voiding generated in the semiconductor device interconnects which is caused by thermal stress

Note 1 to entry: In copper interconnect, voiding occurs under VIA or inside VIA, and causes resistance increase or open failure.

Note 2 to entry: See Annex B for mechanism.