

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Determination of inrush current characteristics of lighting products

Détermination des caractéristiques du courant d'appel des produits d'éclairage



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or for further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Determination of inrush current characteristics of lighting products

Détermination des caractéristiques du courant d'appel des produits d'éclairage

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.140.01; 29.140.99

ISBN 978-2-8322-8205-2

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Symbols and abbreviated terms.....	8
5 General notes on measurements	8
6 Inrush current measurements	8
7 DC method (default method).....	10
7.1 Measurement setup	10
7.2 Determining the value of the adjustment resistance	11
7.2.1 Determining the value of $R_{adj,1}$	11
7.2.2 Determining the value of $R_{adj,k}$	12
7.3 Measurement and calculation of the inrush current characteristics	13
7.3.1 Inrush current characteristics for a single DUT ($k = 1$).....	13
7.3.2 Inrush current characteristics for multiple DUTs.....	14
8 Alternative AC method.....	14
8.1 General.....	14
8.2 Determining the value of the adjustment resistance	15
8.2.1 Determining the value of $R_{adj,1}$	15
8.2.2 Determining the value of $R_{adj,k}$	16
8.3 Measurement and calculation of the inrush current characteristics	16
8.3.1 Measuring and calculating the inrush current for a single DUT.....	16
8.3.2 Measuring and calculating the inrush current for multiple DUTs.....	16
9 Additional alternative methods.....	17
Annex A (informative) Application of inrush current characteristics	18
A.1 General.....	18
A.2 Matching of DUT inrush current characteristics with switch or MCB specifications	18
Bibliography.....	19
Figure 1 – Determination of the inrush current pulse durations t_{H10} and t_{H50}	9
Figure 2 – Measurement setup for the DC method (default method).....	10
Figure 3 – Switching unit.....	11
Figure 4 – Typical current rise and voltage decrease as a function of time after loading C_p (step c)) followed by turning on the switching unit (step e)) as described under step f).....	12
Figure 5 – Determination of I_{max} (ignoring the current peaks for $t < 100 \mu s$).....	14
Figure 6 – Measurement setup for the AC method (alternative method).....	15
Figure 7 – Addition of m DUTs to the measurement circuit (both DC and AC methods).....	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DETERMINATION OF INRUSH CURRENT CHARACTERISTICS OF LIGHTING PRODUCTS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"); the preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations cooperating with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 63129 has been prepared by IEC technical committee 34: Lamps and related equipment.

The text of this International Standard is based on the following documents:

CDV	Report on voting
34/636/CDV	34/679/RVC

For information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Inrush current is the transient current drawn by an electrical device after it is switched on via an independent mains switch, the maximum amplitude of which is often much higher than in steady state during normal operation. Inrush current occurs because of charging capacitances during power up of a device.

Quantities such as peak inrush current and inrush current pulse duration are key parameters to characterize the inrush current, which are important to consider when selecting the switchgear of a lighting installation. This information is indispensable for electric installation planners, lighting designers and installers to be able to guarantee compatibility of a lighting system with other installation components like switches and overcurrent protection devices.

Careful selection of overcurrent protection devices, like circuit breakers, is important when dealing with high inrush currents. The overcurrent protection should react quickly to overload or short circuit but should not interrupt the circuit when an inrush current flows (i.e. false tripping). Another unwanted adverse effect that could occur when inrush current is not considered is welding of contacts of mechanical or electromechanical switches (manual or automatic).

The aim of this document is to determine the peak inrush current and the inrush current pulse duration of one or multiple lighting products of the same type.

This can serve as valuable information for installers in making the correct selection of components like switches and overcurrent protection devices in an installation or conversely for determination of the maximum number of lighting products of the same type that can be applied in an installation with switches and overcurrent protection devices (see Annex A).

The resulting functional compatibility between switchgear and lighting products in an installation is the main rationale for this document.

The rated voltage of lighting products which can be tested with this document is limited to 230 V AC only. Future inclusion of other voltages (for example 100 V AC, 120 V AC, 200 V AC, 277 V AC, 347 V AC) is not excluded.

DETERMINATION OF INRUSH CURRENT CHARACTERISTICS OF LIGHTING PRODUCTS

1 Scope

This document describes a method, based on measurements combined with calculations, to determine specific characteristics of the inrush current of single and/or multiple lighting products of the same type. Lighting products include the following:

- light sources with integrated controlgear,
- controlgear,
- luminaires.

The inrush current characteristics that are determined are

- the peak inrush current,
- the inrush current pulse duration.

This document applies to lighting products connected to low-voltage 230 V AC 50/60 Hz electrical supply networks.

NOTE In Clause 6 it is stated that the methodology applies reference values for the reference (line) inductance and the reference (short circuit) peak current which reflect the typical situation in a 230 V AC installation.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia, available at <http://www.electropedia.org/>
- ISO Online browsing platform, available at <http://www.iso.org/obp>

3.1

bidirectional diode thyristor

DIAC

two-terminal thyristor having substantially the same switching behaviour in the first and third quadrants of the current-voltage characteristic

[SOURCE: IEC 60050-521:2002, 521-04-66]

3.2

bidirectional triode thyristor

TRIAC

three-terminal thyristor having substantially the same switching behaviour in the first and third quadrants of the current-voltage characteristic

[SOURCE: IEC 60050-521:2002, 521-04-67]