



**IEEE**

**IEC/IEEE 62209-1528**

Edition 1.0 2020-10

# **INTERNATIONAL STANDARD**



**Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –  
Part 1528: Human models, instrumentation, and procedures  
(Frequency range of 4 MHz to 10 GHz)**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**

**Copyright © 2020 IEC, Geneva, Switzerland**

**Copyright © 2020 IEEE**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing being secured. Requests for permission to reproduce should be addressed to either IEC at the address below or IEC's member National Committee in the country of the requester or from IEEE.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue  
New York, NY 10016-5997  
United States of America  
[stds.ipr@ieee.org](mailto:stds.ipr@ieee.org)  
[www.ieee.org](http://www.ieee.org)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About the IEEE**

IEEE is the world's largest professional association dedicated to advancing technological innovation and excellence for the benefit of humanity. IEEE and its members inspire a global community through its highly cited publications, conferences, technology standards, and professional and educational activities.

**About IEC/IEEE publications**

The technical content of IEC/IEEE publications is kept under constant review by the IEC and IEEE. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

67 000 electrotechnical terminology entries in English and French extracted from the Terms and definitions clause of IEC publications issued between 2002 and 2015. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



**IEEE**

**IEC/IEEE 62209-1528**

Edition 1.0 2020-10

# **INTERNATIONAL STANDARD**



---

**Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –  
Part 1528: Human models, instrumentation, and procedures  
(Frequency range of 4 MHz to 10 GHz)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 17.220.20

ISBN 978-2-8322-8533-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	14
INTRODUCTION.....	17
1 Scope.....	18
2 Normative references .....	18
3 Terms and definitions .....	18
4 Symbols and abbreviated terms.....	26
4.1 Physical quantities .....	26
4.2 Constants .....	26
4.3 Abbreviated terms.....	26
5 Quick start guide and evaluation plan checklist.....	28
6 Measurement system specifications.....	30
6.1 General requirements for full SAR testing .....	30
6.2 Phantom specifications .....	31
6.2.1 General .....	31
6.2.2 Basic phantom parameters .....	31
6.2.3 Head phantom .....	33
6.2.4 Flat phantom .....	34
6.2.5 Device-specific phantoms .....	35
6.3 Influence of hand on SAR in head.....	35
6.4 Scanning system requirements .....	36
6.5 Device holder specifications.....	36
6.6 Characteristics of the readout electronics.....	37
7 Protocol for SAR assessment .....	37
7.1 General.....	37
7.2 Measurement preparation .....	37
7.2.1 Preparation of tissue-equivalent medium and system check.....	37
7.2.2 Preparation of the wireless communication DUT .....	38
7.2.3 DUT operating mode requirements .....	38
7.2.4 Positioning of the DUT relative to the phantom .....	40
7.2.5 Antenna configurations .....	57
7.2.6 Optics and accessories.....	57
7.2.7 DUTs with an alternative form factor.....	57
7.2.8 Test frequencies for DUTs .....	58
7.3 Tests to be performed for DUTs .....	58
7.3.1 General .....	58
7.3.2 Basic approach for DUT testing .....	59
7.4 Measurement procedure .....	60
7.4.1 General .....	60
7.4.2 Full SAR testing procedure .....	60
7.4.3 Drift .....	64
7.4.4 SAR measurements of DUTs with multiple antennas or multiple transmitters .....	66
7.5 Post-processing of SAR measurement data .....	72
7.5.1 Interpolation .....	72
7.5.2 Extrapolation .....	72
7.5.3 Definition of the averaging volume.....	72

7.5.4	Searching for the maxima .....	73
7.6	Time-period averaged SAR considerations.....	73
7.6.1	General .....	73
7.6.2	RF conducted power.....	73
7.6.3	Time-period averaged SAR measurement settings for SAR measurement methods .....	73
7.6.4	Exposure condition and test position considerations .....	74
7.6.5	Time-period averaged SAR for simultaneous transmission.....	74
7.6.6	TX factor assessment .....	74
7.6.7	SAR measurements .....	75
7.6.8	Uncertainty in TPAS evaluations.....	75
7.7	Proximity sensors considerations .....	76
7.7.1	General .....	76
7.7.2	Procedures for determining proximity sensor triggering distances .....	77
7.7.3	Procedure for determining proximity sensor coverage area .....	80
7.7.4	SAR measurement procedure involving proximity sensors .....	81
7.8	SAR correction for deviations of complex permittivity from targets .....	81
7.8.1	General .....	81
7.8.2	SAR correction formula.....	82
7.8.3	Uncertainty of the correction formula .....	83
7.9	Minimization of testing time.....	83
7.9.1	General .....	83
7.9.2	Fast SAR testing.....	84
7.9.3	SAR test reductions .....	89
8	Measurement uncertainty estimation.....	100
8.1	General.....	100
8.2	Requirements on the uncertainty evaluation.....	101
8.3	Description of uncertainty models .....	102
8.3.1	General .....	102
8.3.2	SAR measurement on a DUT.....	102
8.3.3	System validation and system check measurement.....	102
8.3.4	System check repeatability and reproducibility .....	102
8.3.5	Fast SAR testing (relative measurement).....	102
8.4	Parameters contributing to uncertainty .....	104
8.4.1	Measurement system errors.....	104
8.4.2	Phantom and device (DUT or validation antenna) errors .....	105
8.4.3	Corrections to the SAR result (if applied).....	107
9	Measurement report .....	108
9.1	General.....	108
9.2	Items to be recorded in the measurement report .....	108
Annex A (normative)	SAR measurement system verification .....	112
A.1	Overview.....	112
A.2	System check .....	112
A.2.1	Purpose.....	112
A.2.2	Phantom set-up .....	113
A.2.3	System check antenna.....	113
A.2.4	System check antenna input power measurement.....	114
A.2.5	System check procedure.....	115
A.2.6	System check acceptance criteria.....	116

A.3	System validation.....	116
A.3.1	Purpose.....	116
A.3.2	Phantom set-up.....	116
A.3.3	System validation antennas.....	116
A.3.4	Input power measurement.....	117
A.3.5	System validation procedure.....	117
A.4	Fast SAR testing system validation and system check.....	119
A.4.1	General.....	119
A.4.2	Fast SAR testing system validation.....	119
A.4.3	Fast SAR testing system check.....	120
Annex B	(informative) SAR test reduction supporting information.....	122
B.1	General.....	122
B.2	Test reduction based on characteristics of DUT design.....	122
B.2.1	General.....	122
B.2.2	Statistical analysis overview.....	122
B.2.3	Analysis results.....	123
B.2.4	Conclusions.....	126
B.2.5	Expansion to multi-transmission antennas.....	126
B.3	Test reduction based on analysis of SAR results on other signal modulations.....	126
B.3.1	General.....	126
B.3.2	Analysis results.....	127
B.4	Test reduction based on SAR level analysis.....	128
B.4.1	General.....	128
B.4.2	Statistical analysis.....	129
B.4.3	Test reduction applicability example.....	132
B.5	Other statistical approaches to search for the high SAR test configurations.....	134
B.5.1	General.....	134
B.5.2	Test reductions based on a DOE.....	134
B.5.3	One factor at a time (OFAT) search.....	134
B.5.4	Analysis of unstructured data.....	134
Annex C	(informative) Measurement uncertainty of results obtained from specific fast SAR testing methods.....	135
C.1	General.....	135
C.2	Measurement uncertainty evaluation – contributing parameters.....	135
C.2.1	General.....	135
C.2.2	Probe calibration and system calibration drift.....	136
C.2.3	Isotropy.....	136
C.2.4	Probe positioning.....	137
C.2.5	Mutual sensor coupling.....	138
C.2.6	Scattering within the probe array.....	139
C.2.7	Sampling error.....	139
C.2.8	Array boundaries.....	139
C.2.9	Probe or probe array coupling with the DUT.....	139
C.2.10	Measurement system immunity / secondary reception.....	139
C.2.11	Deviations in phantom shape.....	140
C.2.12	Spatial variation in dielectric properties.....	140
C.2.13	Reconstruction.....	140
C.3	Uncertainty budget.....	140
Annex D	(normative) SAR system validation antennas.....	143

D.1	General antenna requirements	143
D.2	Standard dipole antenna	143
D.2.1	Mechanical description	143
D.2.2	Numerical target SAR values	146
D.3	Standard waveguide	148
D.3.1	Mechanical description	148
D.3.2	Numerical target SAR values	149
D.4	System validation antennas for below 150 MHz	149
D.4.1	General	149
D.4.2	Confined loop antenna	150
D.4.3	Meander dipole antenna	152
D.5	Orthogonal E-field source – VPIFA	153
D.5.1	Mechanical description	153
D.5.2	Numerical target SAR values	156
Annex E (normative)	Calibration and characterization of dosimetric (SAR) probes	157
E.1	Introductory remarks	157
E.2	Linearity	158
E.3	Assessment of the sensitivity of the dipole sensors	158
E.3.1	General	158
E.3.2	Two-step calibration procedures	158
E.3.3	One-step calibration procedure – reference antenna method	164
E.3.4	One-step calibration procedure – coaxial balun method	168
E.4	Isotropy	170
E.4.1	Axial isotropy	170
E.4.2	Hemispherical isotropy	170
E.5	Lower detection limit	175
E.6	Boundary effect	176
E.7	Response time	176
Annex F (informative)	Example recipe for phantom tissue-equivalent media	177
F.1	General	177
F.2	Ingredients	177
F.3	Tissue-equivalent medium liquid formulas (permittivity/conductivity)	178
Annex G (normative)	Phantom specifications	180
G.1	Rationale for the phantom characteristics	180
G.1.1	General	180
G.1.2	Rationale for the SAM phantom	180
G.1.3	Rationale for the flat phantom	180
G.2	SAM phantom specifications	181
G.2.1	General SAM phantom specifications	181
G.2.2	SAM phantom shell specification	185
G.3	Flat phantom specifications	187
G.4	Justification of flat phantom dimensions	188
G.5	Rationale for tissue-equivalent media	191
G.6	Definition of a phantom coordinate system and a DUT coordinate system	193
Annex H (informative)	Measurement of the dielectric properties of tissue-equivalent media and uncertainty estimation	195
H.1	Overview	195
H.2	Measurement techniques	195
H.2.1	General	195

H.2.2	Instrumentation.....	195
H.2.3	General principles .....	195
H.3	Slotted coaxial transmission line .....	196
H.3.1	General .....	196
H.3.2	Equipment set-up .....	196
H.3.3	Measurement procedure .....	197
H.4	Contact coaxial probe .....	197
H.4.1	General .....	197
H.4.2	Equipment set-up .....	198
H.4.3	Measurement procedure .....	199
H.5	TEM transmission line.....	199
H.5.1	General .....	199
H.5.2	Equipment set-up .....	200
H.5.3	Measurement procedure .....	200
H.6	Dielectric properties of reference liquids .....	201
Annex I (informative)	Studies for potential hand effects on head SAR.....	204
I.1	Overview.....	204
I.2	Background.....	204
I.2.1	General .....	204
I.2.2	Hand phantoms .....	205
I.3	Summary of experimental studies .....	205
I.3.1	Experimental studies using fully compliant SAM measurement systems .....	205
I.3.2	Experimental studies using other SAR measurement systems .....	205
I.4	Summary of computational studies.....	206
I.5	Conclusions .....	206
Annex J (informative)	Skin enhancement factor .....	207
J.1	Background.....	207
J.2	Rationale .....	208
J.3	Simulations .....	208
J.4	Recommendation .....	209
Annex K (normative)	Application-specific phantoms .....	211
K.1	General.....	211
K.2	Phantom basic requirements.....	211
K.3	Examples of specific alternative phantoms.....	211
K.3.1	Face-down SAM phantom.....	211
K.3.2	Head-stand SAM phantom .....	212
K.3.3	Wrist phantom .....	212
K.4	Scanning and evaluation requirements.....	213
K.5	Uncertainty assessment.....	213
K.6	Reporting .....	213
Annex L (normative)	Fast compliance evaluations using a flat-bottom phantom with a curved corner (Uniphantom).....	214
L.1	General.....	214
L.2	Uniphantom .....	214
L.3	Device positions for compliance testing and definitions of handset shapes .....	214
L.3.1	General .....	214
L.3.2	Handsets with a straight form factor.....	215
L.3.3	Handsets with a clamshell form factor.....	215
L.4	Testing procedure .....	215

L.4.1	General .....	215
L.4.2	Handsets with straight form factors .....	215
L.4.3	Handsets with clamshell form factors .....	216
L.5	Uncertainty of SAR measurement results using Uniphantom .....	217
Annex M (informative)	Wired hands-free headset testing .....	218
M.1	Concept .....	218
M.2	Example results .....	219
M.3	Discussion .....	220
Annex N (informative)	Applying the head SAR test procedures .....	221
Annex O (normative)	Uncertainty analysis for measurement system manufacturers and calibration laboratories .....	224
O.1	Probe linearity and detection limits .....	224
O.2	Broadband signal uncertainty .....	225
O.3	Boundary effect .....	225
O.4	Field-probe readout electronics uncertainty .....	226
O.5	Signal step-response time uncertainty .....	226
O.6	Probe integration-time uncertainty .....	227
O.6.1	General .....	227
O.6.2	Probe integration-time uncertainty for periodic pulsed signals .....	227
O.6.3	Probe integration-time uncertainty for non-periodic signals .....	228
O.7	Contribution of mechanical constraints .....	228
O.7.1	Mechanical tolerances of the probe position (directions parallel to phantom surface) .....	228
O.7.2	Probe positioning with respect to phantom shell surface .....	228
O.7.3	First-order approximation of exponential decay .....	229
O.8	Contribution of post-processing .....	229
O.8.1	General .....	229
O.8.2	Evaluation test function .....	230
O.8.3	Data-processing algorithm uncertainty evaluations .....	232
O.9	Tissue-equivalent medium properties uncertainty .....	235
O.9.1	General .....	235
O.9.2	Medium density .....	235
O.9.3	Medium conductivity uncertainty .....	235
O.9.4	Medium permittivity uncertainty .....	235
O.9.5	Assessment of dielectric properties measurement uncertainties .....	235
O.9.6	Medium temperature uncertainty .....	237
Annex P (normative)	Post-processing techniques .....	239
P.1	Extrapolation and interpolation schemes .....	239
P.1.1	General .....	239
P.1.2	Extrapolation schemes .....	239
P.1.3	Interpolation schemes .....	239
P.2	Averaging scheme and maximum finding .....	239
P.2.1	Volume average schemes .....	239
P.2.2	Finding the psSAR and estimating the uncertainty .....	240
Annex Q (informative)	Rationale for time-period averaged SAR test procedure .....	241
Annex R (normative)	Measurement uncertainty analysis for testing laboratories .....	242
R.1	RF ambient conditions .....	242
R.2	Device positioning and holder uncertainties .....	242
R.2.1	General .....	242

R.2.2	Device holder perturbation uncertainty.....	243
R.2.3	DUT positioning uncertainty with a specific test device holder: Type A .....	244
R.3	Probe modulation response .....	244
R.4	Time-period averaged SAR .....	245
R.4.1	General .....	245
R.4.2	TX factor uncertainty .....	245
R.5	Measured SAR drift.....	246
R.5.1	General .....	246
R.5.2	Accounting for drift .....	246
R.6	SAR scaling uncertainty .....	247
Annex S (normative)	Validation antenna SAR measurement uncertainty .....	248
S.1	Deviation of experimental antennas .....	248
S.2	Other uncertainty contributions when using system validation antennas .....	248
Annex T (normative)	Interlaboratory comparisons .....	250
T.1	Purpose .....	250
T.2	Phantom set-up .....	250
T.3	Reference devices .....	250
T.4	Power set-up .....	250
T.5	Interlaboratory comparison – procedure .....	251
Annex U (informative)	Determination of the margin for compliance evaluation using the Uniphantom .....	252
U.1	General.....	252
U.2	Deviation of the psSAR measured using the Uniphantom from the psSAR measured using the SAM phantom.....	252
U.3	Determination of margin based on 95 % confidence interval.....	253
U.4	Examples of the determination of the margin factor.....	253
U.4.1	Margin for handsets with straight form factors at flat-bottom position .....	253
U.4.2	Margin for handsets with straight form factors (except smart phones at flat-bottom position).....	255
U.4.3	Margin for smart phones at flat-bottom position .....	257
U.4.4	Margin for smart phones at corner position .....	259
U.4.5	Margin for handsets with clamshell form factors at corner position.....	261
Annex V (informative)	Automatic input power level control for system validation .....	264
V.1	General.....	264
V.2	Operational mechanism of AIPLC .....	264
Annex W (informative)	LTE test configurations supporting information .....	266
W.1	General.....	266
W.2	Study 1 .....	266
W.3	Study 2 .....	268
W.4	Justifications of relative standard deviations .....	269
Bibliography	.....	271
Figure 1	– Quick start guide .....	29
Figure 2	– Dimensions of the elliptical phantom .....	35
Figure 3	– Mounting of the DUT in the device holder using low-permittivity and low-loss foam to avoid changes of DUT performance by the holder material.....	37
Figure 4	– Designation of DUT reference points.....	41

Figure 5 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: six tests performed .....	42
Figure 6 – Test positions for body-worn devices .....	43
Figure 7 – Device with swivel antenna .....	44
Figure 8 – Test positions for body supported devices.....	45
Figure 9 – Test positions for desktop devices .....	47
Figure 10 – Test positions for front-of-face devices.....	48
Figure 11 – Test position for hand-held devices, not used at the head or torso .....	49
Figure 12 – Test position for limb-worn devices .....	49
Figure 13 – Test position for clothing-integrated wireless communication devices.....	50
Figure 14 – Possible test positions for a generic device .....	51
Figure 15 – Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right) .....	53
Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up.....	56
Figure 17 – Tilt position of the DUT on the left side of SAM .....	56
Figure 18 – An alternative form factor DUT with reference points and reference lines .....	57
Figure 19 – Block diagram of the tests to be performed .....	60
Figure 20 – Orientation of the probe with respect to the line normal to the phantom surface, for head and flat phantoms, shown at two different locations .....	64
Figure 21 – Measurement procedure for different types of correlated signals .....	72
Figure 22 – Positioning of the surfaces and edges of the DUT for determining the proximity sensor triggering distance.....	79
Figure 23 – Positioning of the edges of the DUT to determine proximity sensor triggering distance variations with the edge positioned at different angles from the perpendicular position.....	80
Figure 24 – Fast SAR Procedure A .....	87
Figure 25 – Fast SAR Procedure B .....	89
Figure 26 – Modified chart of Figure 19.....	93
Figure 27 – Use of conducted power for LTE mode selection, for Band 1 (1 920 MHz to 1 980 MHz) (MPR values are in dB).....	97
Figure 28 – Use of conducted power for LTE mode selection, for Band 17 (704 MHz to 716 MHz) (MPR values are in dB).....	98
Figure A.1 – Test set-up for the system check .....	114
Figure B.1 – Distribution of Tilt/Cheek.....	124
Figure B.2 – SAR relative to SAR in position with maximum SAR in GSM mode.....	128
Figure B.3 – Two points identifying the minimum distance between the position of the interpolated maximum SAR and the points at $0,6 \times SAR_{max}$ .....	130
Figure B.4 – Histogram for $D_{min}$ in the case of GSM 900 and iso-level at $0,6 \times SAR_{max}$ .....	130
Figure B.5 – Histogram for random variable $Factor_{1g,1800}$ .....	132
Figure D.1 – Mechanical details of the standard dipoles.....	145
Figure D.2 – Standard waveguide (dimensions are according to Table D.3) .....	148
Figure D.3 – Drawing of the CLA that corresponds to a resonant loop integrated in a metallic structure to isolate the resonant structure from the environment .....	150
Figure D.4 – Mechanical details of the meander dipoles for 150 MHz.....	152

Figure D.5 – VPIFA validation antenna .....	155
Figure D.6 – Mask for positioning VPIFAs .....	155
Figure E.1 – Experimental set-up for assessment of the sensitivity (conversion factor) using a vertically-oriented rectangular waveguide .....	162
Figure E.2 – Illustration of the antenna gain evaluation set-up .....	165
Figure E.3 – Schematic of the coaxial calorimeter system.....	169
Figure E.4 – Set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	171
Figure E.5 – Alternative set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	172
Figure E.6 – Experimental set-up for the hemispherical isotropy assessment.....	173
Figure E.7 – Conventions for dipole position ( $\xi$ ) and polarization ( $\theta$ ) .....	174
Figure E.8 – Measurement of hemispherical isotropy with reference antenna.....	175
Figure G.1 – Illustration of dimensions in Table G.1 and Table G.2.....	182
Figure G.2 – Close up side view of phantom showing the ear region.....	184
Figure G.3 – Side view of the phantom showing relevant markings .....	185
Figure G.4 – Sagittally bisected phantom with extended perimeter (shown placed on its side as used for device SAR tests) .....	186
Figure G.5 – Picture of the phantom showing the central strip.....	186
Figure G.6 – Cross-sectional view of SAM at the reference plane .....	187
Figure G.7 – Dimensions of the flat phantom set-up used for deriving the minimal phantom dimensions for $W$ and $L$ for a given phantom depth $D$ .....	189
Figure G.8 – FDTD predicted error in the 10 g psSAR as a function of the dimensions of the flat phantom compared with an infinite flat phantom at 800 MHz .....	190
Figure G.9 – Complex permittivity of human tissues compared to the phantom target properties .....	193
Figure G.10 – Example reference coordinate system for the left-ear ERP of the SAM phantom .....	194
Figure G.11 – Example coordinate system on a DUT .....	194
Figure H.1 – Slotted line set-up.....	196
Figure H.2 – An open-ended coaxial probe with inner and outer radii $a$ and $b$ , respectively .....	198
Figure H.3 – TEM line dielectric properties test set-up [85] .....	200
Figure J.1 – SAR and temperature increase ( $\Delta T$ ) distributions simulated for a three-layer (skin, fat, muscle) planar torso model.....	207
Figure J.2 – Statistical approach to protect 90 % of the population .....	209
Figure J.3 – psSAR skin enhancement factors .....	210
Figure K.1 – SAM face-down phantom .....	212
Figure K.2 – SAM head-stand phantom.....	212
Figure K.3 – Wrist phantom .....	213
Figure L.1 – Cross section of the unified phantom (Uniphantom) with its dimensions .....	214
Figure L.2 – Measurement positions of handsets with straight and clamshell form factors .....	215
Figure L.3 – Flow chart of testing procedure for handsets with straight form factors.....	216
Figure L.4 – Flow chart of testing procedure for handsets with clamshell form factors.....	217
Figure M.1 – Configuration of a personal wired hands-free headset.....	218

Figure M.2 – Configuration without a personal wired hands-free headset.....	219
Figure O.1 – Orientation and surface of averaging volume relative to phantom surface.....	235
Figure U.1 – Categories (classes) for comparison of the measured psSAR between the Uniphantom ( $SAR_{uni}$ ) and the SAM phantom ( $SAR_{SAM}$ ) .....	252
Figure U.2 – Histogram of the deviation of the 10 g psSAR of 45 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	254
Figure U.3 – Histogram of the deviation of the 1 g psSAR of 40 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	255
Figure U.4 – Histogram of the deviation of the 10 g psSAR of 25 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	256
Figure U.5 – Histogram of the deviation of the 1 g psSAR from 20 handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	257
Figure U.6 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	258
Figure U.7 – Histogram of the deviation of the 1 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	259
Figure U.8 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom .....	260
Figure U.9 – Histogram of the deviation of the 1 g psSAR of 19 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom .....	261
Figure U.10 – Histogram of the deviation of the 10 g psSAR of 20 handsets with clamshell form factors at the corner of the Uniphantom.....	262
Figure U.11 – Histogram of the deviation of the 1 g psSAR of 19 handsets with clamshell form factors at the corner of the Uniphantom.....	263
Figure V.1 – Generated RF input power variations to operation time without and with application of AIPLC .....	264
Figure V.2 – The system block diagram of the AIPLC.....	265
Figure V.3 – Power variation characteristics by adjusting the amplifier or signal generator outputs.....	265
Figure W.1 – Low, middle, and high channels at 2 GHz band (Band 1) .....	267
Figure W.2 – RF conducted power versus 10 g psSAR .....	268
Figure W.3 – 1 g SAR as a function of RF conducted power in various test conditions .....	269
Table 1 – Evaluation plan checklist.....	28
Table 2 – Dielectric properties of the tissue-equivalent medium .....	32
Table 3 – Area scan parameters .....	63
Table 4 – Zoom scan parameters.....	63
Table 5 – Example method to determine the combined SAR value using Alternative 1 .....	70
Table 6 – Root-mean-squared error SAR correction formula as a function of the maximum change in permittivity or conductivity [28].....	83
Table 7 – Threshold values $TH(f)$ used in this proposed test reduction protocol .....	93
Table 8 – Divisors for common probability density functions (PDFs).....	101
Table 9 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g or 10 g psSAR from a DUT or validation antenna (N = normal, R = rectangular) .....	103
Table 10 – Uncertainty of Formula (8) (see 7.8.2) as a function of the maximum change in permittivity or conductivity .....	107
Table B.1 – The number of DUTs used for the statistical study .....	123

Table B.2 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various $x$ values .....	124
Table B.3 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for 1 g and 10 g psSAR .....	124
Table B.4 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various antenna locations .....	125
Table B.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various frequency bands .....	125
Table B.6 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types .....	126
Table B.7 – Distance $D_{\min}^*$ for various “iso-level” values .....	130
Table B.8 – Experimental thresholds to have a 95 % probability that the maximum measured SAR value from the area scan will also have a psSAR.....	132
Table B.9 – SAR values from the area scan (GSM 900 band): Example 1 .....	133
Table B.10 – SAR values from the area scan (GSM 900 band): Example 2 .....	133
Table C.1 – Measurement uncertainty budget for relative SAR measurements using Class 2 fast SAR testing, for tests performed within one frequency band and modulation.....	141
Table C.2 – Measurement uncertainty budget for system check using Class 2 fast SAR testing .....	142
Table D.1 – Mechanical dimensions of the reference dipoles .....	146
Table D.2 – Numerical target SAR values (W/kg) for standard dipole and flat phantom .....	147
Table D.3 – Mechanical dimensions of the standard waveguide .....	148
Table D.4 – Numerical target SAR values for waveguides.....	149
Table D.5 – Numerical target SAR values for CLAs.....	151
Table D.6 – Mechanical dimensions of the reference meander dipole .....	152
Table D.7 – Numerical target SAR value (W/kg) for meander dipole.....	153
Table D.8 – Dimensions for VPIFA antennas at different frequencies.....	154
Table D.9 – Electric properties for the dielectric layers for VPIFA antennas .....	155
Table D.10 – Numerical target SAR values for VPIFAs on the flat phantom.....	156
Table E.1 – Uncertainty analysis for transfer calibration using temperature probes .....	160
Table E.2 – Guidelines for designing calibration waveguides .....	163
Table E.3 – Uncertainty analysis of the probe calibration in waveguide.....	164
Table E.4 – Uncertainty template for evaluation of reference antenna gain .....	166
Table E.5 – Uncertainty template for calibration using reference antenna .....	167
Table E.6 – Uncertainty components for probe calibration using thermal methods .....	170
Table F.1 – Suggested recipes for achieving target dielectric properties, 30 MHz to 900 MHz .....	178
Table F.2 – Suggested recipes for achieving target dielectric properties, 1 800 MHz to 10 000 MHz .....	179
Table G.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al. [61]) .....	183
Table G.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th percentile male head data (Gordon et al. [61])—specialist head measurement section.....	183
Table G.3 – Parameters used for calculation of reference SAR values in Table D.2 .....	190
Table H.1 – Parameters for calculating the dielectric properties of various reference liquids.....	202
Table H.2 – Dielectric properties of reference liquids at 20 °C .....	203
Table J.1 –psSAR correction factors .....	209

Table N.1 – SAR results tables for example test results in GSM 850 band .....	221
Table N.2 – SAR results tables for example test results in GSM 900 band .....	222
Table N.3 – SAR results tables for example test results in GSM 1800 band .....	222
Table N.4 – SAR results tables for example test results in GSM 1900 band .....	223
Table O.1 – Parameters for the reference function $f_1$ in Formula (O.12).....	231
Table O.2 – Reference SAR values from the distribution functions $f_1$ , $f_2$ , and $f_3$ .....	232
Table O.3 – Example uncertainty template and example numerical values for permittivity ( $\epsilon_r'$ ) and conductivity ( $\sigma$ ) measurement.....	237
Table S.1 – Uncertainties relating to the deviations of the parameters of the standard waveguide from theory.....	248
Table S.2 – Other uncertainty contributions relating to the dipole antennas specified in Annex D.....	249
Table S.3 – Other uncertainty contributions relating to the standard waveguides specified in Annex D .....	249
Table U.1 – Summary of information to determine the margin for handsets with straight form factors positioned at the flat bottom of the Uniphantom .....	254
Table U.2 – Summary of information to determine the margin for handsets with straight form factors, including slide-type and bar handsets (except smart phones), positioned at the flat bottom of the Uniphantom .....	256
Table U.3 – Summary of information to determine the margin for the smart phones positioned at the flat bottom of the Uniphantom .....	258
Table U.4 – Summary of information to determine the margin for smart phones positioned at the corner of the Uniphantom .....	260
Table U.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types .....	261
Table U.6 – Summary of information to determine the margin for handsets with clamshell form factors positioned at the corner of the Uniphantom.....	262
Table W.1 – Relative standard deviation of $\alpha$ found in Study 1 (without MPR) .....	267
Table W.2 – Maximum relative standard deviation of $\alpha$ found in Study 2 (with MPR) .....	269

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC  
ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY  
FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS  
COMMUNICATION DEVICES –****Part 1528: Human models, instrumentation, and procedures  
(Frequency range of 4 MHz to 10 GHz)**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation.

IEEE Standards documents are developed within IEEE Societies and Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of IEEE and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards. Use of IEEE Standards documents is wholly voluntary. *IEEE documents are made available for use subject to important notices and legal disclaimers (see <http://standards.ieee.org/IPR/disclaimers.html> for more information).*

IEC collaborates closely with IEEE in accordance with conditions determined by agreement between the two organizations. This Dual Logo International Standard was jointly developed by the IEC and IEEE under the terms of that agreement.

- 2) The formal decisions of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees. The formal decisions of IEEE on technical matters, once consensus within IEEE Societies and Standards Coordinating Committees has been reached, is determined by a balanced ballot of materially interested parties who indicate interest in reviewing the proposed standard. Final approval of the IEEE standards document is given by the IEEE Standards Association (IEEE SA) Standards Board.
- 3) IEC/IEEE Publications have the form of recommendations for international use and are accepted by IEC National Committees/IEEE Societies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC/IEEE Publications is accurate, IEC or IEEE cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications (including IEC/IEEE Publications) transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC/IEEE Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and IEEE do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC and IEEE are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or IEEE or their directors, employees, servants or agents including individual experts and members of technical committees and IEC National Committees, or volunteers of IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board, for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC/IEEE Publication or any other IEC or IEEE Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that implementation of this IEC/IEEE Publication may require use of material covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. IEC or IEEE shall not be held responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

International Standard IEC/IEEE 62209-1528 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure, in cooperation with the International Committee on Electromagnetic Safety of the IEEE Standards Association, under the IEC/IEEE Dual Logo Agreement.

This first edition of IEC/IEEE 62209-1528 cancels and replaces IEC 62209-1:2016, IEC 62209-2:2010, IEC 62209-2:2010/AMD1:2019 and IEEE Std 1528-2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) extension of the frequency range down to 4 MHz and up to 10 GHz;
- b) testing of devices with proximity sensors;
- c) application specific phantoms;
- d) device holder specifications;
- e) fast SAR testing procedures;
- f) test reduction procedures;
- g) LTE assessment procedure;
- h) revision of validation clause, including validation antennas;
- i) revision of SAR assessment procedure;
- j) time-average SAR measurement procedure;
- k) uncertainty analysis;

This publication is published as an IEC/IEEE Dual Logo standard.

This publication contains attached files in the form of the Fast SAR Wizard described in 7.9.2.2 as well as CAD files for the SAM phantom. These files are available at:

[http://www.iec.ch/dyn/www/f?p=103:227:0:::FSP\\_ORG\\_ID,FSP\\_LANG\\_ID:1303,25](http://www.iec.ch/dyn/www/f?p=103:227:0:::FSP_ORG_ID,FSP_LANG_ID:1303,25).

These files are intended to be used as a complement and do not form an integral part of the publication.

The text of this standard is based on the following IEC documents:

FDIS	Report on voting
106/514/FDIS	106/520/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The IEC Technical Committee and IEEE Technical Committee have decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The objective of this document is to provide procedures for measuring the human exposure from devices intended to be used at a position near the human head or body. It was developed to provide procedures to evaluate electromagnetic field (EMF) exposures due to radio frequency (RF) transmitting devices used next to the ear, in front of the face, mounted on the body, operating in conjunction with other RF-transmitting and non-transmitting devices or accessories (e.g. belt-clips), or embedded in garments. The types of devices dealt with include but are not limited to mobile telephones, cordless telephones, cordless microphones, and radio transmitters in personal computers. The applicable frequency range is from 4 MHz to 10 GHz. The document defines:

- measurement system requirements (Clause 6),
- SAR measurement protocols (Clause 7),
- SAR measurement uncertainty evaluation (Clause 8), and
- reporting requirements (Clause 9).

At the time this document was developed, two computational and measurement joint IEC/IEEE projects dealing with millimetre-wave power density assessment were under development, covering the frequency range from 6 GHz to 300 GHz. Hence there is an overlap of frequency between this document, which deals with SAR, and the other joint IEC/IEEE projects dealing with power density from 6 GHz to 10 GHz. The IEC/IEEE joint working group was aware of this fact and believed that it would give the flexibility of using whatever metrics suitable for the considered case of compliance assessment.

# MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

## Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

### 1 Scope

This document specifies protocols and test procedures for the reproducible and repeatable measurement of the conservative exposure peak spatial average SAR (psSAR) induced inside a simplified model of the head and the body by radio-frequency (RF) transmitting devices, with a defined measurement uncertainty. These protocols and procedures apply to a significant majority of the population, including children, during the use of hand-held and body-worn wireless communication devices. These devices include single or multiple transmitters or antennas, and are operated with their radiating structure(s) at distances up to 200 mm from a human head or body. This document is employed to evaluate SAR compliance of different types of wireless communication devices used next to the ear, in front of the face, mounted on the body, operating in conjunction with other RF-transmitting, non-transmitting devices or accessories (e.g. belt-clips), or embedded in garments. The applicable frequency range is from 4 MHz to 10 GHz. Devices operating in the applicable frequency range can be tested using the phantoms and other requirements defined in this document.

The device categories covered include, but are not limited to, mobile telephones, cordless microphones, and radio transmitters in personal, desktop and laptop computers, for multi-band operations using single or multiple antennas, including push-to-talk devices. This document can also be applied for wireless power transfer devices operating above 4 MHz.

This document does not apply to implanted medical devices.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62209-3:2019, *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)*.

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO, IEC, and IEEE maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>