

IEEE Recommended Practice for Cable Installation in Generating Stations and Industrial Facilities

IEEE Power and Energy Society

Developed by the
Insulated Conductors Committee

IEEE Std 1185™-2019
(Revision of IEEE Std 1185-2010)

Currently in preview, click buy full version

IEEE Recommended Practice for Cable Installation in Generating Stations and Industrial Facilities

Developed by the

Insulated Conductors Committee
of the
IEEE Power and Energy Society

Approved 7 November 2019

IEEE SA Standards Board

Currently in preview, click buy full version

Abstract: Guidance for the proper installation of cable in generating stations and industrial facilities is provided in this recommended practice.

Keywords: American wire gauge, AWG, basket grip, bend radius, cable, cable cleats, cable jamming, cable testing, cable ties, cable tray, cmil, conduit, duct bank, ducts, English units, figure 8, galloping, IEEE 1185™, installation, jam ratio, kcmil, luff, metric units, OD, outside diameter, overall diameter, pull back, pull tension, pullby, pulling bend radius, ropes, sidewall bearing pressure, sidewall pressure, slack puller, sleeve, swivel, training bend radius, trench, wire, wire way

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 15 May 2020. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

National Electrical Code, NEC, NFPA 70 are registered trademarks of the National Fire Protection Association, Inc.

National Electrical Safety Code and NESC are both registered trademarks and service marks of the Institute of Electrical and Electronics Engineers, Inc.

PDF: ISBN 978-1-5044-6280-8 STD23961
Print: ISBN 978-1-5044-6281-5 STDPD23961

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <https://www.ieee.org/about/corporate/governance/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change from time to time about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, and educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit IEEE Xplore at <http://ieeexplore.ieee.org/> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for IEEE standards can be accessed via <https://standards.ieee.org/standard/index.html>. Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore: <https://ieeexplore.ieee.org/browse/standards/collection/ieee/>. Users are encouraged to periodically check for errata.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this IEEE recommended practice was completed, the D5W Station Cable Insulation Working Group had the following membership:

John E. Merando Jr., *Chair*
William G. Bloethe, *Vice Chair*

Keith Bagwell
John R. Barker
Ettore J. Bartolucci
Michael G. Bayer
Kent W. Brown
James Conrad
Lawrence Cunningham
Charles A. Darnell
Doug DePriest
(Deceased)
Tim Fallesen
Robert E. Fleming
Steven Graham

Ajit K. Gwal
Charles W. Hills
Raihan K. Khondker
Robert Konnik
Benjamin Lanz
Philip T. Laudicina
Michael K. Lauxman
Elliot B. Lee
Gerald Liskom
Arturo Maldonado
Andrew J. Mantey
Nader Moubed
Ross A. Murphy

David Needham
James S. Parham
Jan S. Pirrong
Eric J. Rasmussen
David Rouison
Fanta Sacko
Robert Schmidt
Albert Spear
Herbert W. Stansberry
Gabriel J. Taylor
Wayne T. Walters
Robert F. Wobick
Chris Wright

The following members of the individual Standards Association balloting group voted on this recommended practice. Balloters may have voted for approval, disapproval, or abstention.

Saleman Alibhay
Keith Bagwell
John Barker
Thomas Barnes
Ettore Bartolucci
Earle Bascom III
Manfred Bawart
Michael Bayer
W. J. (Bill) Bergman
Thomas Blair
William G. Bloethe
Kenneth Bow
Derek Brown
Kent Brown
Gustavo Brunello
Demetrio Bucaneg
Nissen Burstein
William Byrd
Thomas Campbell
Robert Cerutti
Suresh Channarasappa
Arvind Chaudhary
William Chen
Michael Chirico
Robert Christman
Randy Clelland
James Conrad
Lawrence Cunningham
Charles Darnell
Glenn Davis
Gary Donner
Michael Dood

Ernest Duckworth
Donald Dunn
Tim Fallesen
Leonard Fifield
Rostyslaw Fostiak
Carl Fredericks
Craig Goodwin
Steven Graham
Jonathan Groves
Lee Herron
Lauri Hiivala
Charles Hills
Ajit Hiranandani
Werner Hoelzl
Robert Hoerauf
Richard Jackson
Laszlo Kadar
John Kay
Yuri Khersonsky
Delavar Khomarlou
Boris Kogan
Robert Konnik
Thomas Koshy
Edwin Kramer
Jim Kulchisky
Mikhail Lagoda
Chung-Yiu Lam
Benjamin Lanz
Philip Laudicina
Michael Lauxman
Elliot Lee
Gerald Liskom

William Lockley
Lawrenc Long
Daniel Mainstruck
Arturo Maldonado
Reginaldo Maniego
Andrew Mantey
William McBride
William McDermid
John E. Merando Jr.
James Michalec
Daleep Mohla
Rachel Mosier
Nader Moubed
Ross Murphy
Michael Nadeau
Arthur Neubauer
Michael Newman
Joe Nims
Lorraine Padden
James Parello
James Parham
Howard Penrose
Christopher Petrola
Jan S. Pirrong
Percy Pool
Craig Preuss
Julian Profir
Eric Rasmussen
Lakshman Raut
Gary Savage
Bartien Sayogo
Robert Schmidt

Devki Sharma
Gilad Shoshani
Jerry Smith
Gary Smullin
Albert Spear
Gregory Steinman
John Stevens
Gary Stoedter

David Tepen
Wayne Timm
Peter Tirinzoni
Nijam Uddin
James Van De Ligt
Gerald Vaughn
John Vergis

Jane Verner
Wayne Walters
Keith Waters
Jared Weitzel
Lee Welch
Kenneth White
Robert Wobick
Iain Wright

When the IEEE SA Standards Board approved this recommended practice on 7 November 2019, it had the following membership:

Gary Hoffman, *Chair*
Ted Burse, *Vice Chair*
Jean-Philippe Faure, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
Stephen D. Dukes
J. Travis Griffith
Guido Hiertz
Christel Hunter
Joseph L. Koepfinger*
Thomas Koshy
John D. Kulick

David J. Law
Joseph Levy
Howard Li
Xiaohui Liu
Kevin Lu
Daleep Mohla
Andrew Myles

Annette Kelly
Dorothy Stanley
Shaohui
Erik Wennblom
Philip Winston
Howard Wolfman
Feng Wu
Jingyi Zhou

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 1185-2019, IEEE Recommended Practice for Cable Installation in Generating Stations and Industrial Facilities.

Construction of generating stations and industrial facilities involve the installation of a large number of cables in various raceway types such as conduits, trays, duct banks, trenches, wire ways, direct burial, etc. Cable failures can lead to power outages and equipment downtime, resulting in inconvenience at best, lost production, or worse, a safety issue. This document provides information to help engineers, technicians, and trades/crafts people avoid potential wire or cable damage during installation, testing, and modification of cable systems at generating stations and industrial facilities. The majority of these cables are unshielded, and except in duct banks or direct burial, where water may be present, there is usually no uniform continuous ground plane on the outside of the cable to allow effective post-installation voltage testing of the cable. Without a continuous ground plane, effective cable post-installation testing, as well as the ability to detect cable damage prior to placing the cable in service, is limited. Therefore, greater emphasis needs to be placed on wire and cable installation methods and practices to assure proper cable installation and long life.

It should be noted that other documents such as cable manufacturer's cable installation manuals, IEEE/IEC/AEIC standards, National Electrical Code® (NEC®) (NFPA 70), Canadian Electrical Code (CEC) Parts I, II, and III, or other local codes, are available that provide cable system design and installation information. It is not the intent of this recommended practice to replace or supersede the other information but to compliment it and, as needed, provide more detail, or alternate methods and techniques for proper cable installation. It is also not the intent of this document to override the installation requirements contained in governing documents such as NEC, CEC, cable manufacturer's installation manuals or permitting documents, etc. Even though utilities in certain situations may be exempt from requirements of NEC, the utility is not exempt from following good cable installation practices in an effort to help maximize cable life and help minimize in-service cable failures.

This revision is a complete rewrite to re-organize the information into a more logical sequence. An attempt has been made to not delete any technical data from the previous edition.

Selected sections have been combined into a comprehensive section (8.2, Securing cable to raceway) that classifies the forces acting on cables, addresses cable design considerations, and provides in-depth information on cable supports and restraints, including a discussion on thermal expansion, a list of cable restraint devices and new calculations. While prior revisions were primarily based on securing vertical cables, this revision greatly expands on protecting cables from the electrodynamic forces that occur during short circuits.

Improved installation methods are also expected to increase confidence in the ability of the installed cable to function in the accident environments for nuclear power generating stations, and increase confidence in cables that improve safety and reliable operation of industrial facilities and cogeneration/fossil plants.

Monitoring pulling tensions is an effective approach to ensuring that the cable pulling limits, such as minimum bend radius, sheath bearing pressure (SWBP), and conductor strength, is not exceeded. Since most cable pulls are manual pulls and the setup time to monitor pulling tension is significant, pulling tensions are typically only quantitatively monitored when performing long, high tension pulls requiring the use of motorized pulling equipment. When a cable pull into conduit is made manually, the dynamometer reading has to be adjusted after measuring various angles. Due to the complexity of this process, manual cable pulls are seldom quantitatively monitored. This document introduces the use of conduit-cable pulling charts and other methods as alternatives to direct monitoring of the pulling tensions. This document also provides cable lubrication methods, pull rope selection criteria, pulling attachment methods, and alternative methods to traditional cable pull tension monitoring, etc.

Cable pullbys (i.e., pulling cables into conduits that already contain cables) are a common practice in the utility industry and often not thoroughly addressed in either cable manufacturer literature or existing industry

standards. Some utilities have reported damage to the existing cables in the conduits when executing pullbys. Measuring the pulling tensions may help but may not prevent cable damage due to pullbys, because the damage can occur from the pull rope or pulled by cable as the pull rope or cable passes over or under existing cables. Instead of prohibiting the practice of cable pullbys, the cable installation process should be more carefully controlled by evaluating the pullby conditions prior to starting the pullby and by placing restrictions on the process to avoid cable damage. However, it should be recognized that this is a risky procedure, and damaged cables or questionable conditions can result from cable pullby practices.

AEIC CG5 [B3] compliments this document for long power cable pulls through duct bank systems and should be considered as additional reference source. Cable installation information can also be found in IEEE Std 576™-2000 [B67] and may also be consulted as an additional reference source.

Due to the IEEE Policy 9.18 requirement to show metric units as the primary measurement unit, the English units are shown for convenience in parentheses after the metric units. The user of this document is cautioned to pay close attention to the units of the equations (metric versus English) and select units accordingly. Conformance to this standard can be achieved using either metric or English units provided the user is consistent when selecting and applying the units. The user is strongly cautioned not to mix units as mixing units can and will result in installation issues. The user is encouraged to select units that are most familiar to the installers so as to reduce the potential for creating installation problems that could go undetected until wire and cable failures occur, which is often years after installation. An attempt was made to keep the significant figures of the metric and English units comparable. However, due to the application of rounding principles, the mathematical conversion from English numbers to metric numbers may not be exact.

Acknowledgments

Figure 1 through Figure 6, the proper and improper handling of cable reels, are reprinted with permission from Dekoron Wire and Cable Company, LLC.

Figure 10, Payoff reel positioning, and Figure 14, Example of measuring sidewall pressure are reprinted with permission from RSCC.

Equation (8) through Equation (12) are derived with permission from General Cable Technology Corporation

Figure 13, Cable configuration for three cables in conduit or duct, is reprinted with permission from The Okonite Company.

Table 8, Pull rope/tape characteristics, and Table 9, Rope and tape fiber selection guide (typical characteristics), are reprinted with permission from US. Rope and Cable. This material does not have a copyright and was obtained from Rope and Fiber Selection Guide section from the website of US. Rope and Cable at www.us-rope-cable.com.

Figure 11, Example measuring bend radius, Figure 15, Swivel, Figure 19, Compression-type pulling eye, and Figure 20, Wedge-type pulling eye, are reprinted with permission from Anixter, Canada.

Figure 21, Cable cleat, is reprinted with permission from Talon Products LLC.

Figure G.1, Short circuit current waveform, is reprinted with permission from Talon Products LLC.

Contents

1. Overview	14
1.1 Scope	14
1.2 Purpose	14
1.3 Units of measure	14
1.4 Word usage	15
2. Normative references	15
3. Definitions, acronyms, and abbreviations	16
3.1 Definitions	16
3.2 Acronyms and abbreviations	16
4. Planning the pull	17
4.1 Cable storage, handling, and re-reeling	17
4.2 Cable cold temperature limits	21
4.3 Raceway types and fill recommendations	22
4.4 Planning activities	25
4.5 Pre-installation activities for duct banks	26
4.6 Distance limitations	30
4.7 Reel position and reel back tension	30
4.8 Bend location	31
4.9 Minimum bend radius	32
4.10 Maximum allowable pulling tension (MAPT)	35
4.11 Expected pulling tension	38
4.12 Cable configurations and cable jamming	40
4.13 Weight correction factor	41
4.14 Maximum allowable sidewall pressure	43
4.15 Expected SWBP	44
5. Accessories required for the pull	44
5.1 Rope and tapes	44
5.2 Swivels and sheaves	47
5.3 Rollers	49
5.4 Pulling eyes	50
5.5 Mare's tails	51
5.6 Woven mesh pulling grips and basket grips	51
5.7 Tension limiting devices	52
5.8 Lubrication	54
6. Pulling activities	57
6.1 Pre-pulling considerations	57
6.2 Set-up considerations	58
6.3 Installation considerations	58
6.4 Pulling	59
6.5 Pullbacks	60
6.6 Pushbys	61
6.7 Pullbys	62
6.8 Pulling in the jam ratio	64
6.9 Staggered or gang pulls	66
6.10 Overfill conditions	66
6.11 Figure-eight cable configurations	66

7. Conduit-cable pulling charts	67
7.1 General and methodology.....	67
7.2 Cable types and raceway configurations.....	67
7.3 Use of conduit-cable pulling charts	68
7.4 Pulling tensions and bend correction factors	69
8. Post cable pulling activities	70
8.1 Post installation considerations	70
8.2 Securing cable to raceway	71
8.3 Support and restraint devices.....	77
9. Cable testing.....	79
9.1 General.....	79
9.2 Low voltage power, control, and instrumentation cables.....	80
9.3 Medium voltage power cables.....	81
9.4 Additional diagnostic testing	82
Annex A (normative) Conduit-cable pulling charts	83
Annex B (informative) Use of conduit-cable pulling chart examples.....	95
Annex C (informative) Conduit-cable pulling chart methodology.....	100
Annex D (informative) Conduit-cable pulling chart bend correction factor.....	104
Annex E (informative) Glossary	106
Annex F (informative) Example of a cable pulling calculation	109
Annex G (informative) Example of electrodynamic force calculation	118
Annex H (informative) Bibliography	120

List of Figures

Figure 1—Lift reel with both flanges.....	18
Figure 2—Lift reel using pallet	19
Figure 3—Lift reel under bottom flange	19
Figure 4—Do not nail into reel flanges.....	19
Figure 5—Do not stack material on the top of the reel.....	20
Figure 6—Do not lift reels by the top flange.....	20
Figure 7—Wheel setup comparisons.....	28
Figure 8—Duct bank pull setup—Example 1	29
Figure 9—Duct bank pull setup—Example 2.....	29
Figure 10—Payoff reel positioning	31
Figure 11—Example measuring bend radius.....	32
Figure 12—(a) Expected pulling tension around bends for conduit or duct runs containing horizontal bends (b) concave bend (c) convex bend	39
Figure 13—Cable configuration for three cables in conduit or duct	41
Figure 14—Example of measuring sidewall pressure	43
Figure 15—Swivel	47
Figure 16—Conveyor sheave arrangement	48
Figure 17—Three-wheeled pulley.....	48
Figure 18—Example of cable tray with cable supported by rollers during pull.....	50
Figure 19—Compression-type pulling eye	50
Figure 20—Wedge-type pulling eye.....	51
Figure 21—Cable pusher.....	53
Figure 22—Cable cleat.....	79
Figure B.1—Isometric of conduit-layout—Example #1	95
Figure B.2—Isometric of conduit layout—Example #2.....	96
Figure B.3—Isometric of conduit layout—Example #3.....	98
Figure C.1—Conduit layout—chart developmenet.....	100
Figure D.1—Conduit layout—BendCorr factor	104
Figure F.1—Example for calculating cable pulling tensions	109
Figure G.1—Short circuit current waveform.....	118

List of Tables

Table 1—Minimum bend radius multipliers for non-shielded or non-armored cable	32
Table 2—Minimum bend radius multipliers for shielded or armored cable.....	33
Table 3—Instrumentation and specialty cable minimum bend radius multipliers	34
Table 4—Jacket material tensile stress values	35
Table 5—Typical maximum allowable pulling tensions using basket-weave grip	36
Table 6—Typical maximum values of allowable SWBP.....	37
Table 7—Guidelines for maximum sidewall pressure values for various cable types	43
Table 8—Pull rope/tape characteristics	45
Table 9—Rope and tape fiber selection guide (typical characteristics).....	46
Table 10—Development of effective conduit-length—chart comparison	68
Table 11—Slope adjustment factor	69
Table 12—Category wire termination	71
Table 13—Typical cable support distances per NEC, Section 300.19	73
Table A.1—Conduit-cable pulling chart for control cable.....	83
Table A.2—Conduit-cable pulling chart for control cable.....	84
Table A.3—Conduit-cable pulling chart for control cable.....	85
Table A.4—Conduit-cable pulling chart for control cable.....	86
Table A.5—Conduit-cable pulling chart for power cable	87
Table A.6—Conduit-cable pulling chart for power cable.....	88
Table A.7—Conduit-cable pulling chart for power cable	89
Table A.8—Conduit-cable pulling chart for power cable.....	90
Table A.9—Conduit-cable pulling chart for instrument cable	91
Table A.10—Conduit-cable pulling chart for instrument cable	92
Table A.11—Conduit-cable pulling chart for instrument cable	93
Table A.12—Conduit-cable pulling chart for instrument cable	94
Table B.1—Effective conduit length and degrees of bend—Example #1	95
Table B.2—Effective conduit length and degrees of bend—Example #2.....	97
Table B.3—Effective conduit length and degrees of bend—Example #3.....	99
Table C.1—Maximum cable mass (weight) in conduit	103
Table D.1—BendCorr adjustment factor— $K' = 0.5$	105
Table D.2—BendCorr adjustment factor— $K' = 0.3$	105

IEEE Recommended Practice for Cable Installation in Generating Stations and Industrial Facilities

1. Overview

1.1 Scope

This recommended practice provides guidance for wire and cable installation practices in generating stations and industrial facilities. It covers installation of cable in trays, conduit, duct banks, wire ways, gutters, and other raceway systems. It covers medium voltage power cable, low voltage power cable, control cable, instrumentation cable, coax/triax cable, fiber optic cable, data communications cable, and other specialty cables used in power plant and industrial environments. This document may also be of benefit for the proper installation of wire and cable systems in commercial, governmental, and public facilities when the same or similar wire or cable types and raceways are used.

1.2 Purpose

The purpose of this recommended practice is to provide guidance on how to help prevent installation damage, which is the single greatest cause of wire and cable failures. Cable failures can lead to power outages and equipment downtime, resulting in inconvenience at best, lost production, or worse, a safety issue. This document provides information for engineers, technicians, and trades/crafts people to avoid potential wire or cable damage during installation, testing, and modification of cable systems at generating stations and industrial facilities.

1.3 Units of measure

The requirement to show metric units first and, if desired, English units second in parentheses after the metric units is dictated by IEEE Policy 9.18, and has been implemented in this document even though the customary practice when installing American Wire Gauge (AWG) wire and cable is to use the English units. The user of this document may choose to use the English units, since cables made to AWG sizes are typically installed using English units of measure, even though the metric units are shown first and English units second in parentheses. Conformance to this recommended practice can be achieved using either metric or English units provided the user is consistent when selecting and applying the units. The user is strongly cautioned not to mix units as mixing units can and will result in installation issues. The user is encouraged to select units that are most familiar to the installers so as to reduce the potential for creating installation problems that could go undetected until wire and cable failures occur, which is often years after installation. It should also be noted that due to the reversal of the order of metric and English units, an attempt was made to keep the significant