



IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems

IEEE Instrumentation and Measurement Society

Sponsored by the
Technical Committee on Sensor Technology (TC-9)

IEEE
3 Park Avenue
New York, NY 10016-5997, USA

24 July 2008

IEEE Std 1588™-2008

(Revision of
IEEE Std 1588-2002)

Currently in preview, click buy full version

IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems

Sponsor

Technical Committee on Sensor Technology (TC-9)
of the
IEEE Instrumentation and Measurement Society

Approved 27 March 2008

IEEE-SA Standards Board

Abstract: A protocol is provided in this standard that enables precise synchronization of clocks in measurement and control systems implemented with technologies such as network communication, local computing, and distributed objects. The protocol is applicable to systems communicating via packet networks. Heterogeneous systems are enabled that include clocks of various inherent precision, resolution, and stability to synchronize. System-wide synchronization accuracy and precision in the sub-microsecond range are supported with minimal network and local clock computing resources. Simple systems are installed and operated without requiring the management attention of users because the default behavior of the protocol allows for it.

Keywords: boundary clock, clock, distributed system, master clock, measurement and control system, real-time clock, synchronized clock, transparent clock

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-3997, USA

Copyright © 2008 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 24 July 2008. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

DeviceNet is a trademark in the U.S. Patent & Trademark Office, owned by the Open DeviceNet Vendor Association, Incorporated.

ControlNet is a trademark in the U.S. Patent & Trademark Office, owned by the ControlNet International, Ltd.

PROFIBUS and PROFINET are trademarks in the U.S. Patent & Trademark Office, owned by PROFIBUS Nutzerorganisation e.V. (PNO).

PDF: ISBN 978-0-7381-5400-8 STD95773
Print: ISBN 978-0-7381-5401-5 STDPD95773

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied **“AS IS.”**

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or recommending professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standard document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board
45 Hoes Lane
Piscataway, NJ 08854
USA

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Introduction

This introduction is not part of IEEE Std 1588-2008, IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems.

This standard defines a protocol enabling precise synchronization of clocks in measurement and control systems implemented with technologies such as network communication, local computing, and distributed objects. The clocks communicate with each other over a communication network. The protocol generates a master–slave relationship among the clocks in the system. All clocks ultimately derive their time from a clock known as the grandmaster clock. In its basic form, this protocol is intended to be administration free.

History

Measurement and control applications are increasingly using distributed system technologies such as network communication, local computing, and distributed objects. Without a standardized protocol for synchronizing the clocks in these devices, it is unlikely that the benefits will be realized in the multivendor system component market. Existing protocols for clock synchronization are not optimum for these applications. For example, Network Time Protocol (NTP) targets large distributed computing systems with millisecond synchronization requirements. The protocol proposed in this standard specifically addresses the following needs of measurement and control systems:

- Spatially localized
- Microsecond to sub-microsecond accuracy and precision
- Administration free
- Accessible for both high-end devices and low-cost, low-end devices

Notice to users

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyright

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association Web site at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously.

For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA Web site at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/>. Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/>.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection herewith. A patent holder or patent applicant has filed a statement of assurance that it will grant licenses under these rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses. Other Essential Patent Claims may exist for which a statement of assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims, or determining whether any licensing terms or conditions are reasonable or non-discriminatory. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was completed, the Precise Networked Clock Synchronization Working Group had the following membership:

John C. Eidson, *Chair*
Hans Weibel, *Vice Chair*
Silvana Rodrigues, *Secretary*
John D. MacKay, *Editor*

Galina Antonova
Doug Arnold
Sivaram Balasubramanian
P. Stephan Bedrosian
Stewart Bryant
Chris Calley
George Claseman
Ron Cohen
Robert Cabbage
Ian Dobson
Tom Farley
John Fischer
John Fleck
Georg Gaderer
Geoffrey M. Garner

Michael Gerstenberger
Franz-Josef Götz
Bruce Hamilton
Kenneth Hann
Ken Harris
Jim Innis
Joel Keller
Jacob Kornerup
Kang Lee
Dirk S. Mohl
Anatoly Moldovansky
Laurent Montini
Paul Myers
Karen F. O'Donoghue
Jonathon D. Paul
Stephen Peterson

Antti Pietilainen
William E. Powell
Markus Renz
David Roe
David Rosselot
Stephan Schül
Markus Seifert
Mark Sheard
Veselin Stojanovic
Dimitar Todorov
Chang Tse
Aleksa Vrancic
Ludwig Winkel
Taylor Wray
Gabriel Zigelboim

Acknowledgments

The working group would like to acknowledge Sam Bilen, William Burr, Ray Perner, Albert Treytl, Steve Singer, and Yahel Shlomi for their contributions to the security experimental extension.

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Ali Al Awazi
Danila Chernetsov
Ryon Coleman
Wael Diab
David Droste
Lee Eccles
John C. Eidson
Georg Gaderer
Geoffrey M. Garner
Robert Graham
Randall Groves
Bruce Hamilton
Werner Hoelzl
C. Huntley
James Innis
David V. James
Anthony Jeffree
Piotr Karocki

Yongbum Kim
Kang Lee
Arthur Marris
Jon Martens
Jonathon Mclendon
Tremont Miao
Gary Michel
Anatoly Moldovansky
Bruce Muschlit
Jay Nemeth-Johannes
Michael S. Newman
Nick S. A. Nikjoo
Karen F. O'Donoghue
David B. Perrussel
Subburajan Ponnuswamy
William E. Powell
Jose Puthenkulam
Gordon Robinson
Robert Robinson

Silvana Rodrigues
David Roe
Charles Rogers
Peter Saunderson
Michael Seaman
Veselin Skendzic
Joseph Stanco
Kevin B. Stanton
Walter Struppler
Alourdes Sully
Michael Johas Teener
Patricia Thaler
Geoffrey Thompsc
John Vergis
Stephen Webb
Fang Xu
Oren Yue
Janusz Zalewski

When the IEEE-SA Standards Board approved this standard on 27 March 2008, it had the following membership:

Robert M. Grow, *Chair*
Thomas Prevost, *Vice Chair*
Steve M. Mills, *Past Chair*
Judith Gorman, *Secretary*

Victor Berman
Richard DeBlasio
Andrew Drozd
Mark Epstein
Alexander Gelman
William R. Goldbach
Arnold M. Greenspan
Kenneth S. Hanus

James Huggins
Richard H. Lett
Youngjun Kim
Joseph L. Koepfinger*
Jon Kulick
David J. Law
Glen Parsons

Ronald C. Petersen
Chuck Powers
Narayanan Ramachandran
Jon Walter Rosdahl
Anne-Marie Sahazizian
Malcolm V. Thaden
Howard L. Wolfman
Don Wright

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, *NRC Representative*
Michael H. Kelley, *NIST Representative*

Lorraine Patsco
IEEE Standards Program Manager, Document Development

Patricia A. Gerdon
IEEE Standards Program Manager, Technical Program Development

CONTENTS

1. Overview	1
1.1 Scope	1
1.2 Purpose	2
1.3 Layout of the document	2
2. Normative references	3
3. Definitions, acronyms, and abbreviations	4
3.1 Definitions	4
3.2 Acronyms and abbreviations	7
4. Conventions	8
4.1 Descriptive lexical form syntax	8
4.2 Word usage	9
4.3 Behavioral specification notation	10
5. Data types and on-the-wire formats in a PTP system	11
5.1 General	11
5.2 Primitive data type specifications	11
5.3 Derived data type specifications	12
5.4 On-the-wire formats	15
6. Clock synchronization model	16
6.1 General	16
6.2 Principle assumptions about the network and implementation recommendations	16
6.3 PTP systems	17
6.4 PTP message classes	17
6.5 PTP device types	18
6.6 Synchronization overview	29
6.7 PTP communications overview	37
7. Characterization of PTP entities	41
7.1 Domains	41
7.2 PTP timescale	41
7.3 PTP communications	42
7.4 PTP communication media	46
7.5 PTP ports	47
7.6 PTP device characterization	53
7.7 PTP timing characterization	61
8. PTP data sets	63
8.1 General specifications for data set members	63
8.2 Data sets for ordinary and boundary clocks	65
8.3 Data sets for transparent clocks	74
9. PTP for ordinary and boundary clocks	76
9.1 General protocol requirements for PTP ordinary and boundary clocks	76
9.2 State protocol	76
9.3 Best master clock algorithm	83
9.4 Grandmaster clocks	92
9.5 Message processing semantics	93
9.6 Changes in the local clock	107
10. PTP for transparent clocks	107
10.1 General requirements for both end-to-end and peer-to-peer transparent clocks	107
10.2 End-to-end transparent clock requirements	108

10.3 Peer-to-peer transparent clock requirements.....	108
11. Clock offset, path delay, residence time, and asymmetry corrections.....	108
11.1 General specifications.....	108
11.2 Computation of clock offset in ordinary and boundary clocks.....	109
11.3 Delay request-response mechanism.....	110
11.4 Peer delay mechanism.....	112
11.5 Transparent clock residence time correction for PTP version 2 events.....	117
11.6 Asymmetry correction for PTP version 2 event messages.....	120
12. Synchronization and syntonization of clocks.....	122
12.1 Syntonization.....	122
12.2 Synchronization.....	123
13. PTP message formats.....	124
13.1 General.....	124
13.2 General message format requirements.....	124
13.3 Header.....	124
13.4 Suffix.....	128
13.5 Announce message.....	128
13.6 Sync and Delay_Req messages.....	130
13.7 Follow_Up message.....	130
13.8 Delay_Resp message.....	130
13.9 Pdelay_Req message.....	131
13.10 Pdelay_Resp message.....	131
13.11 Pdelay_Resp_Follow_Up message.....	132
13.12 Signaling message.....	132
13.13 Management message.....	133
14. TLV entity specifications.....	133
14.1 General requirements.....	133
14.2 Experimental TLVs.....	134
14.3 Vendor and standard organization extension TLVs.....	135
15. Management.....	135
15.1 General.....	135
15.2 PTP management mechanism.....	136
15.3 Processing of management messages.....	136
15.4 Management message format.....	137
15.5 Management TLVs.....	138
16. General optional features.....	158
16.1 Unicast message negotiation (optional).....	158
16.2 Path trace (optional).....	163
16.3 Alternate timescales (optional).....	165
17. State configuration options.....	169
17.1 General.....	169
17.2 Data types for options.....	169
17.3 Grandmaster clusters (optional).....	170
17.4 Alternate master (optional).....	172
17.5 Unicast discovery (optional).....	173
17.6 Acceptable master table (optional).....	175
18. Compatibility requirements.....	177
18.1 Compatibility between version 2 and future versions.....	177
18.2 Compatibility between version 1 and version 2.....	177
18.3 Message formats and data types.....	178
18.4 Naming changes.....	183
18.5 Restrictions on mixed version 1 and version 2 systems.....	183

19. Conformance	184
19.1 Conformance objective.....	184
19.2 PTP conformance requirements.....	184
19.3 PTP profiles	185
Annex A (informative) Using PTP	187
Annex B (informative) Timescales and epochs in PTP	197
Annex C (informative) Examples of residence and asymmetry corrections.....	200
Annex D (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 4 .	219
Annex E (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 6..	221
Annex F (normative) Transport of PTP over IEEE 802.3 /Ethernet.....	223
Annex G (normative) Transport of PTP over DeviceNET	225
Annex H (normative) Transport of PTP over ControlNET	228
Annex I (normative) Transport of PTP over IEC 61158 Type 10	230
Annex J (normative) Default PTP profiles	237
Annex K (informative) Security protocol (experimental)	241
Annex L (informative) Transport of cumulative frequency scale factor offset (experimental).....	264
Annex M (informative) Bibliography.....	268

TABLES

Table 1	—Primitive PTP data types	12
Table 2	—domainNumber	41
Table 3	—networkProtocol enumeration	46
Table 4	—Non-EUI-64 addressTechnology enumeration	51
Table 5	—clockClass specifications	55
Table 6	—clockAccuracy enumeration	56
Table 7	—timeSource enumeration	57
Table 8	—PTP state enumeration	73
Table 9	—Delay mechanism enumeration	74
Table 10	—PTP portState definition	77
Table 11	—Event applicability in boundary clocks	83
Table 12	—Information sources for data set comparison algorithm	88
Table 13	—Updates for state decision code M1 and M2	91
Table 14	—Updates for state decision code M3	91
Table 15	—Updates for state decision code P1, and P2	91
Table 16	—Updates for state decision code S1	92
Table 17	—Source identity comparisons	95
Table 18	—Common message header	124
Table 19	—Values of messageType field	125
Table 20	—Values of flagField	126
Table 21	—correctionField semantics	127
Table 22	—References for sequenceId value exceptions	127
Table 23	—controlField enumeration	128
Table 24	—Values of logMessageInterval field	128
Table 25	—Announce message fields	129
Table 26	—Sync and Delay_Req message fields	130
Table 27	—Follow_Up message fields	130
Table 28	—Delay_Resp message fields	130
Table 29	—Pdelay_Req message fields	131
Table 30	—Pdelay_Resp message fields	131
Table 31	—Pdelay_Resp_Follow_Up message fields	132
Table 32	—Acceptance of signaling messages	132
Table 33	—Signaling message fields	133

Table 34	—tlvType values	134
Table 35	—Organization specific TLV fields	135
Table 36	—Acceptance of management messages	136
Table 37	—Management message fields	137
Table 38	—Values of the actionField	138
Table 39	—Management TLV fields	139
Table 40	—managementId values	140
Table 41	—CLOCK_DESCRIPTION management TLV data field	141
Table 42	—clockType specification	142
Table 43	—USER_DESCRIPTION management TLV data field	144
Table 44	—INITIALIZE management TLV data field	145
Table 45	—INITIALIZATION_KEY enumeration	145
Table 46	—Fault log severityCode enumeration	145
Table 47	—FAULT_LOG management TLV data field	146
Table 48	—TIME management TLV data field	147
Table 49	—CLOCK_ACCURACY management TLV data field	147
Table 50	—DEFAULT_DATA_SET management TLV data field	148
Table 51	—PRIORITY1 management TLV data field	148
Table 52	—PRIORITY2 management TLV data field	149
Table 53	—DOMAIN management TLV data field	149
Table 54	—SLAVE_ONLY management TLV data field	149
Table 55	—CURRENT_DATA_SET management TLV data field	149
Table 56	—PARENT_DATA_SET management TLV data field	150
Table 57	—TIME_PROPERTIES_DATA_SET management TLV data field	151
Table 58	—UTC_PROPERTIES management TLV data field	152
Table 59	—TRACEABILITY_PROPERTIES management TLV data field	152
Table 60	—TIMESCALE_PROPERTIES management TLV data field	152
Table 61	—PORT_DATA_SET management TLV data field	153
Table 62	—LOG_ANNOUNCE_INTERVAL management TLV data field	154
Table 63	—ANNOUNCE_RECEIPT_TIMEOUT management TLV data field	154
Table 64	—LOG_SYNC_INTERVAL management TLV data field	154
Table 65	—DELAY_MECHANISM management TLV data field	155
Table 66	—LOG_MIN_PDELAY_REQ_INTERVAL management TLV data field	155
Table 67	—VERSION_NUMBER management TLV data field	155
Table 68	—TRANSPARENT_CLOCK_DEFAULT_DATA_SET management TLV data field	156

Table 69	—PRIMARY_DOMAIN management TLV data field.....	156
Table 70	—TRANSPARENT_CLOCK_PORT_DATA_SET management TLV data field.....	157
Table 71	—MANAGEMENT_ERROR_STATUS TLV format.....	157
Table 72	—managementErrorId enumeration.....	158
Table 73	—REQUEST_UNICAST_TRANSMISSION TLV format.....	160
Table 74	—GRANT_UNICAST_TRANSMISSION TLV format.....	161
Table 75	—CANCEL_UNICAST_TRANSMISSION TLV format.....	161
Table 76	—ACKNOWLEDGE_CANCEL_UNICAST_TRANSMISSION TLV format.....	162
Table 77	—UNICAST_NEGOTIATION_ENABLE management TLV data field.....	162
Table 78	—PATH_TRACE TLV format.....	164
Table 79	—PATH_TRACE_LIST management TLV data field.....	164
Table 80	—PATH_TRACE_ENABLE management TLV data field.....	164
Table 81	—ALTERNATE_TIME_OFFSET_INDICATOR TLV format.....	166
Table 82	—ALTERNATE_TIME_OFFSET_ENABLE management TLV data field.....	167
Table 83	—ALTERNATE_TIME_OFFSET_NAME management TLV data field.....	167
Table 84	—ALTERNATE_TIME_OFFSET_MAX_KEY management TLV data field.....	168
Table 85	—ALTERNATE_TIME_OFFSET_PROPERTIES management TLV data field.....	168
Table 86	—GRANDMASTER_CLUSTER_TABLE management TLV data field.....	171
Table 87	—Alternate master attributes.....	173
Table 88	—ALTERNATE_MASTER management TLV data field.....	173
Table 89	—UNICAST_MASTER_TABLE management TLV data field.....	174
Table 90	—UNICAST_MASTER_MAX_TABLE_SIZE management TLV data field.....	175
Table 91	—Operation of acceptable master table option.....	176
Table 92	—ACCEPTABLE_MASTER_TABLE management TLV data field.....	176
Table 93	—ACCEPTABLE_MASTER_MAX_TABLE_SIZE management TLV data field.....	177
Table 94	—ACCEPTABLE_MASTER_TABLE_ENABLED management TLV data field.....	177
Table 95	—Version 1 stratum to version 2 class.....	178
Table 96	—Version 2 clockClass to version 1 stratum.....	178
Table 97	—Version 1 to version 2 translation of grandmasterIsPreferred field.....	179
Table 98	—Version 2 to version 1 translation of the priority1 field.....	179
Table 99	—Version 1 clock identifier to version 2 clockAccuracy.....	179
Table 100	—Version 2 clockAccuracy to version 1 clock identifier.....	179
Table 101	—Version 1 to version 2 translation of grandmasterIsBoundaryClock field.....	180
Table 102	—Version 2 to version 1 translation of the priority2 field.....	180
Table 103	—Version 1 control field and version 2 messageType field mappings.....	180
Table 104	—Translation of flagField from version 1 to version 2.....	181

Table 105	—Translation of flagField from version 2 to version 1	181
Table 106	—Version 2 fields with no version 1 counterpart.....	182
Table 107	—Version 1 fields with no version 2 counterpart.....	183
Table 108	—Name correspondence.....	183
Table 109	—Mixed system restrictions	184
Table B.1	—Relationships between timescales.....	199
Table C.1	—Interpretation of Figure C.1 key values	202
Table C.2	—Interpretation of Figure C.2 key values	203
Table C.3	—Interpretation of Figure C.3 key values	205
Table C.4	—Interpretation of Figure C.4 key values	207
Table C.5	—Interpretation of Figure C.5 key values	209
Table C.6	—Interpretation of Figure C.6 key values	210
Table C.7	—Interpretation of Figure C.7 key values	211
Table C.8	—Interpretation of Figure C.8 key values	213
Table C.9	—Interpretation of Figure C.9 key values	215
Table C.10	—Interpretation of Figure C.10 key values.....	217
Table C.11	—Interpretation of Figure C.11 key values.....	218
Table D.1	—IPv4 multicast addresses.....	219
Table D.2	—transportSpecific field values	220
Table E.1	—IPv6 multicast addresses	222
Table F.1	—Multicast MAC addresses	223
Table F.2	—Ethernet transport specific field.....	224
Table G.1	—DeviceNet clockIdentity octets 0 through 7.....	226
Table G.2	—DeviceNet headers for all PTP message packets	226
Table H.1	—ControlNet clockIdentity octets 2 through 7.....	228
Table I.1	—Mapping of messages.....	231
Table I.2	—IEEE 802.3 DLPDU syntax	232
Table I.3	—Multicast MAC address.....	233
Table I.4	—LT (Length/Type).....	234
Table I.6	—Mapping of the parameter and attribute names	235
Table I.7	—Translation of flagField from PTP version 2 to PROFINET.....	236
Table K.1	—flagField.SECURE flag	242
Table K.2	—AUTHENTICATION TLV	260
Table K.3	—algorithmId values	261
Table K.4	—ICV and pad length.....	261
Table K.5	—AUTHENTICATION_CHALLENGE TLV	262

Table K.6—challengeType values	262
Table K.7—SECURITY_ASSOCIATION_UPDATE TLV	263
Table K.8—addressType values	263
Table L.1—CUM_FREQ_SCALE_FACTOR_OFFSET TLV format	266

FIGURES

Figure 1	—Mealy state transition diagram	10
Figure 2	—Model of an ordinary clock	19
Figure 3	—Model of a boundary clock.....	21
Figure 4	—Model of an end-to-end transparent clock.....	22
Figure 5	—End-to-end residence time correction model.....	23
Figure 6	—Combined ordinary and end-to-end transparent clock.....	25
Figure 7	—Model of a peer-to-peer transparent clock.....	27
Figure 8	—Peer-to-peer residence time and link delay correction model.....	28
Figure 9	—Combined ordinary and peer-to-peer transparent clock	30
Figure 10	—Simple master–slave clock hierarchy	32
Figure 11	—Pruned mesh topology	33
Figure 12	—Basic synchronization message exchange	34
Figure 13	—Link delay measurement.....	35
Figure 14	—Timestamp generation model.....	36
Figure 15	—Hierarchical topology	37
Figure 16	—Linear topology.....	38
Figure 17	—Multiply connected topology.....	39
Figure 18	—Bridging disparate technologies.....	40
Figure 19	—Definition of latency constants	45
Figure 20	—Propagation asymmetry	47
Figure 21	—Port model	48
Figure 22	—Scaled log variance hysteresis	60
Figure 23	—State machine for a full implementation.....	78
Figure 24	—State machine for a slave-only implementation.....	79
Figure 25	—STATE_DECISION_EVENT logic	81
Figure 26	—State decision algorithm	87
Figure 27	—Data set comparison algorithm, part 1	89
Figure 28	—Data set comparison algorithm, part 2	90
Figure 29	—Receipt of Announce message logic.....	96
Figure 30	—Receipt of Sync message logic	98
Figure 31	—Receipt of Follow_Up message logic	100
Figure 32	—Receipt of Delay_Req message logic	101
Figure 33	—Receipt of Delay_Resp message logic.....	103
Figure 34	—Delay request-response path length measurement	110

Figure 35	—Peer delay link measurement	113
Figure 36	—Permitted mixed system configuration	183
Figure 37	—Profile print form	186
Figure C.1	—Master, end-to-end, and slave one-step clocks; no asymmetry correction	201
Figure C.2	—Master, end-to-end, and slave one-step clocks; with asymmetry correction	202
Figure C.3	—Master two-step and end-to-end transparent and slave one-step clocks; with asymmetry correction.....	204
Figure C.4	—Master and end-to-end transparent, two-step, and one-step, slave clocks; with asymmetry correction.....	206
Figure C.5	—One-step master, two-step end-to-end transparent, and one-step slave clocks; with asymmetry correction.....	208
Figure C.6	—One-step peer responder, end-to-end transparent, and peer requestor clocks; with asymmetry correction.....	210
Figure C.7	—One-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks; with asymmetry correction.....	211
Figure C.8	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 1; with asymmetry correction.....	212
Figure C.9	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction.....	214
Figure C.10	—Two-step peer responder, one-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction.....	216
Figure C.11	—One-step peer master, two-step peer-to-peer transparent, and one-step peer slave clocks; time computation	217
Figure G.1	—Event message timestamp point	225
Figure I.1	—PROFINET region combined with domains	231
Figure K.1	—PTP secure message processing	252
Figure K.2	—Challenge processing.....	254
Figure K.3	—Secure transmit processing.....	256
Figure K.4	—Secure event processing	258

IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems

IMPORTANT NOTICE: This standard is not intended to assure safety, security, health, or environmental protection in all circumstances. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1. Overview

1.1 Scope

This standard defines a protocol enabling precise synchronization of clocks in measurement and control systems implemented with technologies such as network communication, local computing, and distributed objects. The protocol is applicable to systems communicating by local area networks supporting multicast messaging including, but not limited to, Ethernet. The protocol enables heterogeneous systems that include clocks of various inherent precision, resolution, and stability to synchronize to a grandmaster clock. The protocol supports system-wide synchronization accuracy in the sub-microsecond range with minimal network and local clock computing resources. The default behavior of the protocol allows simple systems to be installed and operated without requiring the administrative attention of users. The standard includes mappings to User Datagram Protocol (UDP)/Internet Protocol (IP), DeviceNet, and a layer-2 Ethernet implementation. It includes formal mechanisms for message extensions, higher sampling rates, correction for asymmetry, a clock type to reduce error accumulation in large topologies, and specifications on how to incorporate the resulting additional data into the synchronization protocol. The standard permits synchronization accuracies better than 1 ns. The protocol has features to address applications where redundancy and security are a requirement. The standard defines conformance and management capability. There is provision to support unicast as well as multicast messaging. The standard includes an annex on recommended practices. Annexes defining communication-medium-specific implementation details for additional network implementations are expected to be provided in future versions of this standard.