



**IEEE Standard for
Local and metropolitan area networks—**

**Virtual Bridged Local Area Networks
Amendment 7: Provider Backbone Bridges**

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997, USA
14 August 2008

IEEE Std 802.1ah™-2008
(Amendment to
IEEE Std 802.1Q™-2005)

Currently in preview, click buy full version

IEEE Std 802.1ah™-2008

(Amendment to
IEEE Std 802.1Q™-2005)

**IEEE Standard for
Local and metropolitan area networks—**

Virtual Bridged Local Area Networks

Amendment 7: Provider Backbone Bridges

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 12 June 2008

IEEE-SA Standards Board

Abstract: This amendment defines an architecture and bridge protocols for interconnection of multiple Provider Bridged Networks, allowing a Provider to support up to 2^{24} service instances.

Keywords: Bridged Local Area Networks, LANs, local area networks, MAC Bridges, MANs, metropolitan area networks, MRP, MSTP, Multiple Registration Protocol, Multiple Spanning Tree Protocol, Multiple VLAN Registration Protocol, MVRP, Provider Bridged Local Area Networks, Virtual Bridged Local Area Networks, virtual LANs

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2008 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 14 August 2008. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 973-07381-5762-7 STD95803
Print: ISBN 973-07381-5763-4 STDPD95803

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standard documents are supplied **“AS IS.”**

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its content, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon his or her independent judgement in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to information requests except in those cases where the matter has previously received formal consideration. A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual will not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal interpretation of the IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Introduction

This introduction is not part of IEEE Std 802.1ah-2008, IEEE Standards for Local and Metropolitan Area Networks—Virtual Bridged Local Area Networks—Amendment 7: Provider Backbone Bridges.

Notice to users

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association website at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously.

For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA website at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/index.html>.

Patents

Attention is called to the possibility that implementation of this amendment may require use of subject matter covered by patent rights. By publication of this amendment, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this amendment are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this amendment was submitted, the IEEE 802.1 Working Group had the following membership:

Tony Jeffree, Chair

Paul Congdon, Vice Chair

Stephen Haddock, Chair, Interworking Task Group

Paul Bortorff, Stephen Haddock, and Muneyoshi Mizuki, Editors

Osama Aboul-Magd	Michael Johas Tenner	Dan Romascanu
Zehavit Alon	Prakash Kashyap	Moran Roth
Caitlin Bestler	Hal Keen	Jessy V. Rouyer
Jan Bialkowski	Keti Kilcreas	Ali Sajassi
Rob Boatright	Yongbum Kim	Joseph Salowey
Jean-Michel Bonnamy	Philippe Klein	Panagiotis Saltsidis
Rudolf Brandner	Mike Ko	Satish Sathe
Craig W. Carlson	Rajhu Kondepalli	John Sauer
Frank Chao	Bruce Swan	Mick Seaman
Rao Cherukuri	Kari Laihonen	Koichiro Seto
Taesik Cheung	Yannick Le Goff	Himanshu Shah
Alex Conta	Gael Mace	Ravi Shenoy
Diego Crupnicoff	Ben Mack-Crane	Nurit Sprecher
Claudio Desanti	David Martin	Kevin B. Stanton
Linda Dunbar	Riccardo Martinotti	Bob Sultan
Hesham Elbakoury	Marco Mascitto	George Swallow
David Elie-Dit-Cosaque	Alan McGuire	Attila Takacs
Janos Farkas	Menucher Menuchery	Francois Tallet
Don Fedyk	John Messenger	John Terry
Felix Feifei Feng	Dinesh Mohan	Pat Thaler
Norm Fierstein	Kevin Nolish	Oliver Thorp
Bob Frazier	Hiroshi Ohta	Fred Tuck
John Fuller	David Olsen	Maarten Vissers
Geoffrey Garner	Shlomo Ovdia	Manoj Wadekar
Anoop Ghanwani	Don Pannell	Yan Wang
Manz Goetz	Glenn Parsons	Brian Weis
Eric Gray	Ken Patton	Bert Wijnen
Ken Grewal	Joe Pelissier	Ludwig Winkel
Craig Gunther	Hayim Porat	Michael D. Wright
Mitch Gusat	Max Pritikin	Chien-Hsien Wu
Brian Hassink	Ananda Rajagopal	Ken Young
Brian Hausauer	Karen Randall	
Asif Hazarika	Robert Roden	
Romain Insler	Guenter Roeck	
Paul Hongkyu Jeong	Josef Roesch	

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Osama Aboul-Magd	John Hawkins	Maximilian Riegel
Toru Aihara	Atsushi Ito	Jessy V. Rouyer
Butch Anton	Raj Jain	Randall Safier
Danilo Antonelli	Tony Jeffrey	John Sargent
Hugh Barrass	Piotr Karocki	John Sauer
Parag Bhatt	Stuart J. Kerry	Veselin Skendzic
Tomo Bogataj	Yongbum Kim	Kapil Sood
Paul Bottorff	Thomas Kurihara	Amjad Soomro
Michael Bouchet	John Lemon	Nurit Sprecher
James Carlo	William Lumpkins	Manikantan Srinivasan
Juan Carreon	Thomas Mack-Crane	Thomas Starai
Keith Chow	David Martin	Marian Stasney
Charles Cook	Jonathon Mclendon	Alourdes Sully
Arjan De Heer	John Messenger	Bob Sultan
Russell Dietz	Gary Michel	Michael Johnson, Technical
Sourav Dutta	Dinesh Mohan	Pat Thaler
Don Fedyk	Jose Morales	Oliver Thorp
Prince Francis	Michael S. Newman	Thomas Tullia
Yukihiro Fujimoto	Nick S. A. Nikjoo	Mark-Rene Uchida
Devon Gayle	Glenn Parsons	Rudolf Wankel
Sergiu Goma	Haim Porat	Deok Woo
C. Guy	Venkatesha Prasad	Ben Young
Stephen Haddock		Oren Yuen

When the IEEE-SA Standards Board approved this standard on 12 June 2008, it had the following membership:

Robert M. Grow, *Chair*
Thomas Prevost, *Vice Chair*
Steve M. Mills, *Public Chair*
Judith Gorman, *Secretary*

Victor Berman	Jim Hunt	Chuck Powers
Richard DeBlasio	Richard J. Hulett	Narayanan Ramachandran
Andy Drozd	Yung Kyun Kim	Jon Walter Rosdahl
Mark Epstein	Joseph L. Koepfinger*	Robby Robson
Alexander Gelman	John Kulick	Anne-Marie Sahazizia
William R. Goldbach	David J. Law	Malcolm V. Thaden
Arnold M. Greenspan	Glenn Parsons	Howard L. Wolfman
Kenneth S. Hanus	Ronald C. Petersen	Don Wright

*Member Emeritus

Also included in the following nonvoting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, *NRC Representative*
Michael H. Kelly, *NIST Representative*

Don Messina
IEEE Standards Program Manager, Document Development

Michael D. Kipness
IEEE Standards Program Manager, Technical Program Development

Contents

1. Overview.....	2
1.1 Scope.....	2
2. Normative references.....	3
3. Definitions.....	5
4. Abbreviations.....	7
5. Conformance.....	9
5.2 Conformant components and equipment.....	9
5.3 Protocol Implementation Conformance Statement (PICS).....	9
5.7 I-component conformance.....	9
5.8 B-component conformance.....	10
5.11 Backbone Edge Bridge conformance.....	11
6. Support of the MAC Service in VLANs.....	13
6.6 Internal Sublayer Service.....	13
6.8 Enhanced Internal Sublayer Service.....	15
6.9 Support of the EISS.....	17
6.10 Support of the EISS by Provider Instance Ports.....	17
6.11 Support of the EISS by Customer Backbone Port.....	20
6.18 Backbone Service Instance Multiplex Entity.....	24
7. Principles of network operation.....	29
7.4 Locating end stations.....	29
8. Principles of bridge operation.....	31
8.8 The Filtering Database.....	31
9. Tagged frame format.....	33
9.5 Tag Protocol Identification.....	33
9.8 Backbone Service Instance Tag Control Information.....	34
12. Bridge management.....	37
12.2 Managed objects VLAN-aware bridge objects.....	37
12.3 Data types.....	37
12.7 Filtering Database.....	37
12.8 Bridge Protocol Entity.....	38
12.14 CFM entities.....	39
12.15 Backbone Core Bridge management.....	43
12.16 Backbone Edge Bridge management.....	43
13. The Multiple Spanning Tree Protocol (MSTP).....	59
13.12 Port Role assignments.....	59
13.19 Multiple Spanning Tree state machines.....	59
13.21 State machine timers.....	61
13.25 State machine conditions and parameters.....	61

13.26	State machine procedures	62
13.27	The Port Timers state machine	63
13.28	Port Receive state machine	63
13.31	Port Transmit state machine	63
13.32	Port Information state machine	64
13.37	Port Receive Pseudo Information state machine	65
13.40	Virtual Instance Port Spanning Tree operation.....	67
18.	Principles of Connectivity Fault Management operation	68
19.	CFM Entity operation	71
19.4	Maintenance Point addressing	71
20.	Connectivity Fault Management protocols.....	73
25.	Support of the MAC Service by Provider Backbone Bridged Networks	75
25.1	Service transparency	77
25.2	Customer service interface.....	77
25.3	Port-based service interface	77
25.4	S-tagged service interface	79
25.5	I-tagged service interface	82
25.6	Service instance segregation	84
25.7	Service instance selection and identification	84
25.8	Service priority and drop capability selection.....	84
25.9	Service access protection	85
26.	Principles of Provider Backbone Bridged Network operation	89
26.1	Provider Backbone Bridged Network overview	89
26.2	Provider Backbone Bridged Network example	90
26.3	Backbone VLAN connectivity.....	92
26.4	Backbone addressing	93
26.5	Detection of connectivity loops through attached networks.....	95
26.6	Scaling of Provider Backbone Bridges	96
26.7	Network Management.....	96
26.8	Connectivity Fault Management in Provider Backbone Bridges	97
Annex A	(normative) PICS proforma.....	105
Annex B	(informative) Shared and independent VLAN learning	109

Figures

Figure 6-2	I-Component Provider Instance Port.....	18
Figure 6-3	B-Component Customer Backbone Port.....	21
Figure 6-6	Two back-to-back Backbone Service Instance Multiplex Entities	24
Figure 6-7	Backbone Service Instance Multiplex Entities with example CFM shims	25
Figure 9-3	I-TAG TCI Format.....	34
Figure 12-1	Relationship among BEB managed objects	44
Figure 13-9	MSTP state machines—overview and relationships.....	60
Figure 13-11	Port Timers state machine.....	63
Figure 13-13	Port Transmit state machine.....	64
Figure 13-14	Port Information state machine	65
Figure 13-23	Port Receive Pseudo Information state machine.....	66
Figure 25-1	Internal organization of the MAC sublayer in a PBBN	75
Figure 25-2	Provider Backbone Bridge terminology	76
Figure 25-3	Customer service interface types	77
Figure 25-4	Port-based service interface	78
Figure 25-5	Port-based interface equipment.....	79
Figure 25-6	Encapsulated service frames at ISS	80
Figure 25-7	S-tagged service interface	81
Figure 25-8	S-tagged service interface equipment	81
Figure 25-9	I-tagged service interface	83
Figure 25-10	I-tagged service interface equipment	83
Figure 25-11	S-tagged and Port-based service interface access classifications	86
Figure 25-12	I-tagged service interface access protection classifications	87
Figure 26-1	PBBN example.....	91
Figure 26-2	CFM Shim Model	98
Figure 26-3	CFM example applied to a Port-based and S-tagged Service Interface.....	100
Figure 26-4	CFM example applied to an I-tagged Service Interface	101
Figure 26-5	CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc.....	103
Figure 26-6	CFM example applied to a peer E-NNI, CBP-PIP.....	104

Tables

Table 6-7	Encapsulated Addresses type.....	25
Table 9-1	IEEE 802.1Q Ethernet Type allocations.....	34
Table 9-3	Reserved I-SID values	35
Table 26-1	Backbone Service Instance Group address OUI.....	93

IEEE Standard for Local and metropolitan area networks—

Virtual Bridged Local Area Networks

Amendment 7: Provider Backbone Bridges

IMPORTANT NOTICE: This standard is not intended to assure safety, security, health, or environmental protection in all circumstances. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

[This amendment is based on IEEE Std 802.1Q™-2005.]

Editorial Note

This amendment specifies changes to IEEE Std 802.1Q-2005, as amended by IEEE Std 802.1ad™-2005, IEEE Std 802.1ak™-2007 and IEEE Std 802.1ag™-2007, that enable a provider to scale a Provider Bridged Network by interconnecting many Provider Bridged Networks over a Provider Backbone Bridged Network. The resulting backbone network can support interconnection of up to 2²⁴ equivalent of separate LANs, Bridged Local Area Networks, or Virtual Bridged Local Area Networks. Changes are applied to the base text of IEEE Std 802.1Q-2005 as amended by IEEE Std 802.1ad-2005, IEEE Std 802.1ak-2007, and IEEE Std 802.1ag-2007. Text shown in bold italics in this amendment defines the editing instructions for changes to this base text. Three editing instructions are used: ***change***, ***delete***, and ***insert***. ***Change*** is used to make a change to existing material. The editing instruction specifies the location of the change and describes what is being changed. Changes to existing text may be clarified using ~~strikeout~~ markings to indicate removal of old material, and underline markings to indicate addition of new material). ***Delete*** removes existing material. ***Insert*** adds new material without changing the existing material. Insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. Editorial notes will not be carried over into future editions of IEEE Std 802.1Q.

1. Overview

1.1 Scope

Insert the following text and bullets immediately after bullet z:

To allow scaling of Provider Networks to at least 2^{24} Service Virtual LANs, this standard further specifies the operation of Provider Backbone Bridges (PBBs) by means of an architecture and bridge protocols compatible and interoperable with Provider Bridged Network protocols and equipment, allowing interconnection of multiple Provider Bridged Networks. To this end, it

- aa) Introduces Backbone Edge Bridges that, by exchanging backbone frames that encapsulate the addresses, VLAN tags, and data of customer frames, support the virtual, media independent, equivalent of a number of independent instances of the service provided by media dependent frame transmission procedures.
- ab) Extends the parameters of the Internal Sublayer Service (ISS) and Enhanced Internal Sublayer Service (EISS) to include a connection identifier, capable of referencing the backbone addresses and other parameters, used to convey customer frames from one Backbone Edge Bridge (BEB) to all, or one of, the other BEBs supporting a particular backbone service instance.
- ac) Specifies the format of the Backbone Service Instance tag (I-TAG) that encapsulates the customer addresses, and introduces a Backbone Service Instance Identifier (I-SID) that allows each BEB to support a number of backbone service instances and permits the unambiguous identification of up to 2^{24} backbone service instances within a single Provider Backbone Bridged Network (PBBN).
- ad) Provides a model of Backbone Edge Bridge operation in terms of VLAN-aware bridge components that allows the use of Provider Bridges as Backbone Core Bridges, with PBBN traffic carried as frames containing I-TAGs on particular Backbone VLANs (B-VLANs) potentially coexisting with PBN traffic carried as frames without I-TAGs on other Backbone VLANs.
- ae) Specifies the interfaces that a Provider Backbone Bridged Network can provide to transport service frames. These comprise a Port-based service interface that assigns all received untagged and priority-tagged frames to a single S-VLAN transported over a single backbone service instance, an S-tagged service interface capable of mapping individual S-VLANs to different backbone service instances, and an I-tagged service interface capable of mapping frames from one set of backbone service instances to another.
- af) Describes the use of redundant bridges and access LANs to protect backbone service access against failure of any of those systems or components.
- ag) Specifies the management of Backbone Edge Bridges in terms of the model of operation [item ad) above], making use of defined management objects for the individual VLAN-aware bridge components, and adding managed objects to facilitate service creation.
- ah) Describes the use of connectivity fault management (CFM) to detect and isolate faults in the connectivity provided to individual S-VLANs across the PBBN, in the connectivity provided to the group of S-VLANs supported by a single backbone service instance (identified by an I-SID), and in the connectivity provided to individual B-VLANs within the backbone itself.
- ai) Specifies extensions to the Multiple Spanning Tree Protocol (MSTP) to allow network administrators to protect against loops through peered PBBNs without requiring coupling of spanning trees that operate independently for each PBBN.