

IEEE Standard for Information Technology—  
Telecommunications and information exchange  
between systems  
Wireless Regional Area Networks (WRAN)—  
Specific requirements

# Part 22: Cognitive Wireless RAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications. Policies and Procedures for Operation in the TV Bands

## Amendment 2: Enhancement for Broadband Services and Monitoring Applications

IEEE Computer Society

Sponsored by the  
LAN/MAN Standards Committee

---

IEEE  
3 Park Avenue  
New York, NY 10016-5997  
USA

IEEE Std 802.22b™-2015  
(Amendment to  
IEEE Std 802.22™-2011  
as amended by IEEE Std 802.22a™-2014)

Currently in preview, click buy full version

**IEEE Std 802.22b™-2015**  
(Amendment to  
IEEE Std 802.22™-2011  
as amended by IEEE Std 802.22a™-2014)

**IEEE Standard for Information Technology—  
Telecommunications and information exchange  
between systems  
Wireless Regional Area Networks (WRAN)—  
Specific requirements**

**Part 22: Cognitive Wireless RAN  
Medium Access Control (MAC) and  
Physical Layer (PHY) Specifications:  
Policies and Procedures for  
Operation in the TV Bands**

**Amendment 2: Enhancement for Broadband  
Services and Monitoring Applications**

Sponsor

**LAN/MAN Standards Committee  
of the  
IEEE Computer Society**

Approved 3 September 2015

**IEEE-SA Standards Board**

**Abstract:** Alternate physical layer (PHY) and necessary medium access control layer (MAC) enhancements to IEEE Std 802.22-2011 are specified in this amendment for operation in very high frequency/ultra-high frequency (VHF/UHF) television broadcast bands between 54 MHz and 862 MHz to support enhanced broadband services and monitoring applications. The amendment supports aggregate data rates greater than the maximum data rate supported by the IEEE Std 802.22-2011. This amendment defines new classes of IEEE 802.22™ devices to address these applications and supports more than 512 devices in a network. This amendment also specifies techniques to enhance communications among the devices and makes necessary amendments to the cognitive, security, and parameters and connection management clauses. This amendment supports mechanisms to enable coexistence with other IEEE 802® systems in the same band.

**Keywords:** broadband wireless access network, enhanced broadband services, high capacity, high throughput, IEEE 802.22™, IEEE 802.22b™, monitoring applications, WRAN standard

---

The Institute of Electrical and Electronics Engineers, Inc.  
515 Alexander Avenue, New York, NY 10016-5997, USA

Copyright © 2015 by The Institute of Electrical and Electronics Engineers, Inc.  
All rights reserved. Published 30 October 2015. Printed in the United States of America.

IEEE and IEEE 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-0-7381-9838-5 STD20318  
Print: ISBN 978-0-7381-9839-2 STDPD20318

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

## Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

### Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

### Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

## Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied on as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

## Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in discussions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board  
445 Hoes Lane  
Piscataway, NJ 08854 USA

## Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standards are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, with publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

## Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

## Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

## Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/xpl/standards.jsp> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

## Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

## Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patent/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

## Participants

When this amendment went to sponsor ballot, the IEEE 802.22 Working Group had the following officers:

**Apurva Mody, Chair**  
**Chang-woo Pyo, Vice Chair**

When this amendment was sent to sponsor ballot, the Task Group b had the following membership:

**Chang-woo Pyo, Chair and Editor**  
**Sung Hyun Hwang, Vice Chair**  
**Gabriel Villardi, Secretary**

Gregory Buchwald  
Winston Caldwell  
Gerald Chouinard  
Subir Das  
Peter Flynn  
Thomas Gurley  
Hiroshi Harada  
Bob Heile  
Dien Hoang  
Byung Jang Jeong

Jerome J. Kalke  
Hynduk Kang  
Gwangzeen Ko  
Bruce Kraemer  
Donghun Lee  
PinHsun Lin  
Liru Lu  
Michael Lynch  
Apurva Mody  
Paul Nikolich

Masayuki Oodo  
Ranga K. Reddy  
Ivan Reede  
Shigenobu Sasaki  
Steve Shellhammer  
Chunyi Song  
Keat-Beng Toh  
Xin (Amy) Zhang  
Bing Xuan Zhao  
Lei Zhongding

Major contributions were received from the following individuals:

Sung Hyun Hwang  
Masayuki Oodo  
Chang-woo Pyo  
Aziz Rahman

Ranga K. Reddy  
Shigenobu Sasaki  
Chunyi Song

Keat-Beng Toh  
Gabriel Villardi  
Xin (Amy) Zhang  
Bing Xuan Zhao

The following members of the individual balloting committee voted on this amendment. Balloters may have voted for approval, disapproval, or abstention.

Iwan Adhicandra  
Nobumitsu Amachi  
Butch Anton  
Madhusudan Banavara  
Tuncer Baykas  
Harry Bims  
Nancy Bravin  
William Byrd  
Edgar Callaway  
Juan Carreon  
Keith Chow  
Charles Cook  
Carlo Donati  
Sourav Datta  
Richard Edgar  
Charles Einolf  
Stanislav Filin  
Devon Gayle  
Alexander Gelman  
Tim Godfrey  
Randall Groves  
Michael Gundlach  
Thomas Gurley  
Chris Guy

Werner Hoelzl  
Sung Hyun Hwang  
Noriyuki Ikeuchi  
Akio Iso  
Atsushi Ito  
Raj Jain  
Shinkyō Kaku  
Jerome J. Kalke  
Piotr Karocki  
Stuart Kerry  
Adrian Kliks  
Bruce Kraemer  
Yasushi Kudoh  
Paul Lambert  
Arthur H. Light  
Daniel Lubar  
William Lumpkins  
Elvis Maculuba  
James Marin  
Jeffery Masters  
Michael McInnis  
Apurva Mody  
Nabil Nasser  
Michael Newman  
Nick S. A. Nikjoo

Paul Nikolich  
Masayuki Oodo  
Satoshi Oyama  
Subburajan Ponnuswamy  
Venkatesha Prasad  
Chang-woo Pyo  
Verotiana Rabarijaona  
Robert Robinson  
William Rose  
John Santhoff  
Shigenobu Sasaki  
Naotaka Sato  
Chunyi Song  
Kapil Sood  
Thomas Starai  
Walter Struppler  
Keat-Beng Toh  
Ha-Nguyen Tran  
David Trejo Pizzo  
Mark-Rene Uchida  
Gabriel Villardi  
Hung-Yu Wei  
Oren Yuen  
Mingtuo Zhou

When the IEEE-SA Standards Board approved this amendment on 3 September 2015, it had the following membership:

**John Kulick, *Chair***  
**Jon Walter Rosdahl, *Vice Chair***  
**Richard H. Hulett, *Past Chair***  
**Konstantinos Karachalios, *Secretary***

Masayuki Ariyoshi  
Ted Burse  
Stephen Dukes  
Jean-Phillippe Faure  
J. Travis Griffith  
Gary Hoffman  
Michael Janezic

Joseph L. Koepfinger\*  
David J. Law  
Hung Ling  
Andrew Myles  
T. W. Olsen  
Glenn Parsons  
Ronald C. Peterson  
Annette D. Reilly

Stephen J. Shellhammer  
Adrian P. Stephens  
Yatin Trivedi  
Phillip Winston  
Don Wright  
Yu Yuan  
Daidi Zhong

\*Member Emeritus

## Introduction

This introduction is not part of IEEE Std 802.22b™-2015, IEEE Standard for Information Technology—Telecommunications and information exchange between systems—Wireless Regional Area Networks (WRAN)—Specific requirements—Part 22: Cognitive Wireless RAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications: Policies and Procedures for Operation in the TV Bands—Amendment 2: Enhancement for Broadband Services and Monitoring Applications.

This amendment specifies alternate physical layer (PHY) and necessary medium access control layer (MAC) enhancements to IEEE Std 802.22-2011 for operation in very high frequency/ultra high frequency (VHF/UHF) television broadcast bands between 54 MHz and 862 MHz to support enhanced broadband services and monitoring applications. PHY specifications (i.e., Operation Mode 1 and Operation Mode 2) in Clause 9 and Clause 9a are designed to meet the needs required by channel models. A multi-channel operation (7.24), high modulation and coding (9.2 and 9a.2), and multiple-input, multiple-output (MIMO) (9.15 and 9a.15) provide higher throughput (compared to the IEEE Std 802.22-2011), which may be achieved by individual use or combinational use. Point-to-multipoint connections and relay connections are specified in Clause 7.

## Contents

1. Overview .....	2
1.3 Reference application .....	2
3. Definitions .....	2
4. Abbreviations and acronyms .....	4
7. MAC Common Part sublayer .....	5
7.1 General.....	5
7.2 Addressing and connections .....	6
7.3 General superframe structure.....	7
7.4 General frame structure (on PHY-OM1).....	7
7.4a General frame structure (on PHY-OM2).....	8
7.4a.1 General frame structure for normal mode.....	8
7.4a.2 General frame structure for self-coexistence mode .....	8
7.4a.3 Frame format.....	8
7.4b General frame structure for a relay network.....	12
7.4b.1 General frame structure for a centralized scheduling mode .....	12
7.4b.2 General frame structure for a distributed scheduling mode.....	13
7.4b.3 Detail of zones .....	15
7.4b.3.1 Access zone (AZ).....	15
7.4b.3.2 Centralized relay zone (CRZ).....	16
7.4b.3.3 Distributed relay zone (DRZ) .....	17
7.4b.3.4 Application of PHY Operation Mode to Zone Type .....	18
7.5 Control header .....	18
7.5.1 Superframe Control header .....	18
7.5.2 Frame Control header.....	18
7.5.2a Frame control header for PHY-OM2.....	19
7.5.2a.1 General.....	19
7.5.2a.2 Extended frame control header (Ex-FCH).....	20
7.5.2b Distributed relay zone (DRZ) Frame Control header (DRZ-FCH).....	23
7.6 MAC PDU formats.....	24
7.6.1 MAC headers .....	24
7.6.1.1 Generic MAC header .....	24
7.6.1.2 MAC subheaders and special payloads .....	25
7.6.1.2.5 Extended subheader types .....	26
7.6.1.3 CBP MAC PDU format.....	27
7.6.1.3.1 CBP information elements .....	28
7.7 Management messages .....	30
7.7.1 Downstream Channel Descriptor (DCD).....	30
7.7.1.1 DCD Channel information elements.....	32
7.7.2 Downstream MAP (DS-MAP).....	34
7.7.2.1 DS-MAP IE.....	35
7.7.2.1.1 DIUC allocations .....	35
7.7.2.1.2 DS-MAP Extended DIUC IE .....	37
7.7.3 Upstream Channel Descriptor (UCD).....	42
7.7.3.1 UCD Channel IEs .....	44
7.7.4 Upstream MAP (US-MAP).....	45
7.7.4.1 US-MAP IE.....	46
7.7.4.1.1 UIUC allocations .....	49
7.7.4.1.4 US-MAP Extended UIUC IE .....	50

7.7.7	REG-REQ/RSP .....	60
7.7.7.3	REG-REQ/RSP information elements .....	60
7.7.7.3.4	CPE capability .....	60
7.7.7.3.6	Local SID Group .....	61
7.7.8.9	Service Flow encodings .....	61
7.7.8.9.19	Per-RS QoS .....	61
7.7.11	CPE Basic Capability Request/Response (CBC-REQ/RSP) .....	62
7.7.11.3	CBC-REQ/RSP information elements .....	62
7.7.11.3.2	Physical parameters supported .....	62
7.7.11.3.4	Relay CPE Mode .....	63
7.7.11.3.5	Multi-channel operation supported .....	64
7.7.24	Confirmation codes .....	64
7.7.25	Local Cell Update messages .....	64
7.7.25.1	Local Cell Update Indication (LCU-IND) message .....	64
7.7.25.2	Local Cell Update Acknowledgment (LCU-ACK) message .....	65
7.7.26	Container message .....	66
7.7.26.1	Message format .....	66
7.7.26.2	Container ACK message .....	66
7.7.27	Downstream Transmit Test (DTT) messages .....	67
7.7.27.1	DTT Request (DTT-REQ) message .....	67
7.7.27.1.1	Message format .....	67
7.7.27.1.2	DTT-REQ information element .....	67
7.7.27.2	DTT Response (DTT-RSP) message .....	67
7.7.27.2.1	Message format .....	67
7.7.27.2.2	DTT-RSP information element .....	68
7.7.27.3	DTT Report (DTT-RPT) message .....	68
7.7.27.3.1	Message format .....	68
7.7.27.3.2	DTT-RPT information element .....	68
7.7.27.4	DTT Confirmation (DTT-CFM) message .....	69
7.7.27.4.1	Message format .....	69
7.7.27.4.2	DTT-CFM information element .....	69
7.7.28	Relay-Schedule (Relay-SCHE) message .....	69
7.7.29	Channel Allocation Manager management messages .....	70
7.7.29.1	Overview .....	70
7.7.29.2	Add new operating channel (CAM-ADD) message .....	70
7.7.29.3	Stop operating channel (CAM-STP) message .....	71
7.7.29.4	Stop operating channel acknowledgment (CAM-STP-ACK) message .....	71
7.7.29.5	Switch operating channel (CAM-SWH) message .....	71
7.7.29.6	Switch operating channel acknowledgment (CAM-SWH-ACK) message .....	72
7.7.30	Group Resource Allocation management messages .....	72
7.7.30.1	Group Resource Allocation Configuration (GRA-CFG) message .....	72
7.7.30.2	Group Resource Allocation Update (GRA-UPD) message .....	73
7.7.31	Ranging Report (RNG-RPT) message .....	75
7.8	Management of MAC PDUs .....	75
7.8.4	Packing .....	75
7.8.4.3	ARQ Feedback IEs .....	75
7.8.7	MAC PDU construction for relay .....	76
7.8.7.1	General .....	76
7.8.7.2	MAC PDU construction for distributed scheduling A-CPE on non-ARQ connections .....	76
7.8.7.2.1	Overview .....	76
7.8.7.2.2	Procedure 1 on non-ARQ connections .....	76
7.8.7.2.3	Procedure 2 on non-ARQ connections .....	77
7.8.7.2.4	Procedure 3 on non-ARQ connections .....	78

7.8.7.2.5	Procedure 4 on non-ARQ connections .....	78
7.8.7.3	MAC PDU construction for distributed scheduling A-CPE on ARQ connections .....	79
7.8.7.3.1	Overview .....	79
7.8.7.3.2	Procedure 1 for ARQ connections .....	79
7.8.7.3.3	Procedure 2 for ARQ connections .....	80
7.8.7.3.4	Procedure 3 on ARQ connections .....	83
7.8.7.3.5	Procedure 4 on ARQ connections .....	84
7.8.8	MAC PDU transmission for relay .....	87
7.8.8.1	Overview .....	87
7.8.8.2	US through a distributed scheduling A-CPE .....	87
7.8.8.3	US through a centralized scheduling A-CPE .....	87
7.8.8.4	DS through a distributed scheduling A-CPE .....	88
7.8.8.5	DS through a centralized scheduling A-CPE .....	88
7.9	ARQ mechanism .....	89
7.9.6	ARQ operation .....	89
7.9.6.4	ARQ for a relay network .....	89
7.9.6.4.1	Overview .....	89
7.9.6.4.2	Two-link ARQ mode .....	89
7.9.6.4.3	ARQ state machine .....	91
7.10	Scheduling services .....	91
7.10.2	Upstream request/grant scheduling .....	91
7.10.2.1	UGS .....	91
7.10.2.2	rtPS .....	92
7.11	Bandwidth management .....	92
7.11.1	Bandwidth Requests .....	92
7.11.1.3	Bandwidth Request for a relay network .....	92
7.11.1.3.1	Overview .....	92
7.11.1.3.2	Bandwidth Request by a distributed scheduling A-CPE .....	92
7.11.1.3.3	Bandwidth Request by a centralized scheduling A-CPE .....	93
7.11.2	Grants .....	93
7.11.2.1	Grants for a relay network .....	93
7.11.2.1.1	Bandwidth grant for relay with a distributed scheduling A-CPE .....	93
7.11.2.1.2	Bandwidth grant for relay with a centralized scheduling A-CPE .....	94
7.11.3	Polling .....	94
7.11.3.4	Polling for a relay network .....	94
7.13	Contention resolution .....	96
7.13.1	Transmission opportunities .....	96
7.14	Initialization and network association .....	97
7.14.3	A-BS initialization .....	97
7.14.3.1	General .....	97
7.14.3.2	Professional installation .....	97
7.14.3.3	A-BS antenna gain information acquisition .....	97
7.14.3.4	Determine geographic location .....	99
7.14.3.5	Access TV bands database service and receive list of available channels .....	99
7.14.3.6	Operator disallows channels .....	99
7.14.3.7	Perform incumbent detection and synchronize network with neighboring networks ..	99
7.14.3.8	Present the available channel list to the higher layers .....	99
7.14.3.9	Commence single channel operation or multi-channel operation .....	100
7.14.4	CPE initialization for relay .....	100
7.14.4.1	General .....	100
7.14.4.2	CPE performs self test .....	103
7.14.4.3	CPE antenna gain information acquisition .....	103
7.14.4.4	CPE senses for and identifies A-WRAN services and incumbents .....	103
7.14.4.5	Present sensing results to the higher layers .....	103

7.14.4.6 CPE chooses an A-WRAN service for single channel operation or for multi-channel operation .....	103
7.14.4.7 CPE performs satellite-based geolocation .....	103
7.14.4.8 Acquire DS and US parameters .....	104
7.14.4.8.1 Overview .....	104
7.14.4.8.2 Obtaining DS parameters from an A-BS .....	104
7.14.4.8.3 Obtaining DS parameters from a distributed scheduling A-CPE .....	104
7.14.4.8.4 Obtaining US parameters from an A-BS .....	106
7.14.4.8.5 Obtaining US parameters from a distributed scheduling A-CPE .....	107
7.14.4.9 CPE transmits ranging/CDMA burst .....	108
7.14.4.9.1 General .....	108
7.14.4.9.2 CDMA initial ranging and automatic adjustments to an A-BS .....	109
7.14.4.9.3 CDMA initial ranging and automatic adjustments to a distributed scheduling A-CPE (Local initial ranging) .....	110
7.14.4.9.4 CDMA initial ranging and automatic adjustments by relaying on a centralized scheduling A-CPE (Relay initial ranging) .....	112
7.14.4.9.5 Ranging parameter adjustment .....	114
7.14.4.10 CPE transmit basic capabilities for a relay network .....	114
7.14.4.10.1 CPE transmit basic capabilities to a distributed scheduling A-CPE .....	114
7.14.4.10.2 CPE transmit basic capabilities relaying on a centralized scheduling A-CPE .....	115
7.14.4.11 CPE authentication and key exchange .....	116
7.14.4.12 Registration for a relay network .....	117
7.14.4.12.1 Overview .....	117
7.14.4.12.2 Local cell management on relay .....	117
7.14.4.13 A-BS transmits channel sets to CPE .....	119
7.14.4.14 Establish IP connectivity .....	120
7.14.4.15 Establish time of day .....	120
7.14.4.16 Transfer operational parameters .....	120
7.14.4.17 Establish dynamic service flows .....	120
7.14.4.18 Neighboring network discovery .....	120
7.15 Ranging .....	121
7.15.1 DS management .....	121
7.15.1.1 DS management (A-BS and CPE) .....	121
7.15.1.2 Local DS management (distributed scheduling A-CPE and S-CPE) .....	121
7.15.1.3 Relay DS management (A-BS and S-CPE via centralized scheduling A-CPE) .....	123
7.15.2 US management .....	126
7.15.2.3 CDMA initial ranging and automatic adjustments for a relay network .....	127
7.15.2.3.1 CDMA initial ranging and automatic adjustments (A-BS and CPE) .....	127
7.15.2.3.2 CDMA local initial ranging and automatic adjustments (distributed scheduling A-CPE and S-CPE) .....	127
7.15.2.3.3 CDMA relay initial ranging and automatic adjustments (centralized scheduling A-CPE and S-CPE) .....	128
7.15.2.4 CDMA Periodic ranging and automatic adjustments for a relay network .....	129
7.15.2.4.1 CDMA periodic ranging and automatic adjustments (A-BS and CPE) .....	129
7.15.2.4.2 CDMA local periodic ranging and automatic adjustments (distributed scheduling A-CPE and CPE) .....	129
7.15.2.4.3 CDMA relay periodic ranging and automatic adjustments (centralized scheduling A-CPE and CPE) .....	130
7.16 Channel descriptor management .....	131
7.18 QoS .....	131
7.18.9 Service Flow Management .....	131
7.18.9.3 Dynamic Service Addition .....	131
7.18.9.3.1 CPE-initiated DSA .....	131

7.18.9.3.2	BS-initiated DSA .....	132
7.18.9.4	Dynamic Service Change.....	132
7.18.9.4.1	CPE-initiated DSC .....	132
7.18.9.4.2	BS-initiated DSC .....	133
7.18.9.5	Dynamic Service Deletion .....	133
7.18.9.5.1	CPE-initiated DSD .....	133
7.18.9.5.2	BS-initiated DSD .....	134
7.19	Incumbent protection .....	134
7.19.2	Measurements management.....	134
7.19.2.1	Measurements management for a relay network .....	134
7.19.4	Measurement report and notification .....	135
7.19.4.2	Measurement report and notification for a relay network .....	135
7.20	Self-coexistence.....	136
7.20.1	Coexistence Beacon Protocol (CBP) .....	136
7.20.1.1	CBP packet structure .....	136
7.20.4	Self-coexistence for a relay network.....	137
7.20.4.1	General.....	137
7.20.4.2	Mechanism for inter-A-BS self-coexistence on a relay network.....	138
7.20.4.3	CBP-based neighboring network discovery .....	139
7.20.4.3.1	Overview .....	139
7.20.4.3.2	Discovery with SCW .....	139
7.21	Quiet periods and sensing.....	140
7.21.2	Synchronization of overlapping quiet periods .....	140
7.21.2.1	Intra-frame quiet period synchronization .....	140
7.21.2.2	Inter-frame Quiet Period Synchronization.....	141
7.21.4	Quiet periods and sensing for a relay network.....	141
7.21.4.1	Quiet period synchronization for an A-BS's cell.....	141
7.21.4.2	Quiet period synchronization for a local network .....	141
7.22	Channel management .....	142
7.22.3	Channel management on a relay network .....	142
7.22.3.1	Overview.....	142
7.22.3.2	Initialization and channel sets updating.....	143
7.22.3.3	Scheduling of channel switching time.....	144
7.23	Synchronization of the IEEE 802.22 base stations and IEEE 802.22b base stations .....	145
7.24	Multi-channel operation .....	145
7.24.1	General .....	145
7.24.2	Channel allocation manager.....	147
7.24.2.1	General.....	147
7.24.2.2	Add new operating channel operation .....	148
7.24.2.2.1	General .....	148
7.24.2.2.2	BS-CAM selects a specific BS-CHU .....	149
7.24.2.2.3	BS-CAM commences operation request .....	149
7.24.2.2.4	BS-CHU commences operation acknowledgment .....	149
7.24.2.2.5	BS-CAM sends management information notification to BS-CHU .....	150
7.24.2.2.6	BS-CHU memorizes management information .....	150
7.24.2.2.7	BS-CHU performs frequency setting .....	150
7.24.2.2.8	BS-CHU performs synchronization .....	150
7.24.2.2.9	BS-CHU sends operation preparation completed notification to BS-CAM ....	150
7.24.2.2.10	BS-CHU broadcasts SCH on PHY-OM1 or FCH on PHY-OM2 .....	150
7.24.2.2.11	BS-CAM checks unused BS-CHU .....	150
7.24.2.2.12	CPE-CAM selects a specific CPE-CHU .....	150
7.24.2.2.13	CPE-CAM sends BS search command (All or specific channel) to the specific CPE-CHU .....	151
7.24.2.2.14	CPE-CHU performs BS search .....	151

7.24.2.2.15	CPE-CHU sends BS detected notification to CPE-CAM .....	151
7.24.2.2.16	CPE-CAM determines other operating CPE-CHU .....	151
7.24.2.2.17	CPE-CAM performs BSID matching .....	151
7.24.2.2.18	CPE-CAM sends BSID mismatch notification to CPE-CHU .....	151
7.24.2.2.19	CPE-CAM sends proceed notification to CPE-CHU .....	151
7.24.2.2.20	CPE-CHU performs synchronization .....	152
7.24.2.2.21	CPE-CHU sends synchronization completed notification to CPE-CAM .....	152
7.24.2.2.22	CPE-CAM checks unused CPE-CHU .....	152
7.24.2.2.23	CPE-CAM sends registration request to CPE management unit .....	152
7.24.2.2.24	CPE management unit sends registration completed notification to CPE-CAM .....	152
7.24.2.3	Add new operating channel operation by using BS search command (specific channel).....	152
7.24.2.3.1	General .....	152
7.24.2.3.2	BS-CAM sends aggregation information to BS-CHU1 .....	153
7.24.2.3.3	BS-CHU1 forwards aggregation information to CPE-CHU1 .....	153
7.24.2.3.4	CPE-CHU1 forwards aggregation information to CPE-CAM .....	153
7.24.2.3.5	BS-CAM selects a specific BS-CHU .....	153
7.24.2.3.6	BS-CAM commences operation request .....	154
7.24.2.3.7	BS-CHUn commences operation acknowledgment .....	154
7.24.2.3.8	BS-CAM sends management information notification to BS-CHUn .....	154
7.24.2.3.9	BS-CHUn memorizes management information .....	155
7.24.2.3.10	BS-CHUn performs frequency setting .....	155
7.24.2.3.11	BS-CHUn performs synchronization .....	155
7.24.2.3.12	BS-CHUn sends operation preparation completed notification to BS-CAM ..	155
7.24.2.3.13	BS-CHUn broadcasts SCH on PHY-OM1 or FCH on PHY-OM2 .....	155
7.24.2.3.14	BS-CAM checks unused BS-CHU .....	155
7.24.2.3.15	CPE-CAM selects a specific CPE-CHU .....	155
7.24.2.3.16	CPE-CAM sends BS search command (specific channel) to the specific CPE-CHUn .....	155
7.24.2.3.17	CPE-CHUn performs BS search .....	156
7.24.2.3.18	CPE-CHUn sends BS detected notification to CPE-CAM .....	156
7.24.2.3.19	CPE-CAM determines other operating CPE-CHU .....	156
7.24.2.3.20	CPE-CAM performs BSID matching .....	156
7.24.2.3.21	CPE-CAM sends BSID mismatch notification to CPE-CHUn .....	156
7.24.2.3.22	CPE-CAM sends proceed notification to CPE-CHUn .....	156
7.24.2.3.23	CPE-CHUn performs synchronization .....	156
7.24.2.3.24	CPE-CHUn sends synchronization completed notification to CPE-CAM .....	156
7.24.2.3.25	CPE-CAM checks unused CPE-CHU .....	157
7.24.2.3.26	CPE-CAM sends registration request to CPE management unit .....	157
7.24.2.3.27	CPE management unit sends registration completed notification to CPE-CAM .....	157
7.24.2.4	Stop operating channel operation .....	157
7.24.2.4.1	General .....	157
7.24.2.4.2	BS-CAM sends stop operation request to BS-CHU .....	157
7.24.2.4.3	BS-CHU starts stop operation timer .....	157
7.24.2.4.4	BS-CHU sends stop operation request acknowledgment to BS-CAM .....	158
7.24.2.4.5	BS-CHU sends stop operation request to CPE-CHU .....	158
7.24.2.4.6	CPE-CHU starts stop operation timer .....	158
7.24.2.4.7	CPE-CHU sends stop operation notification to CPE-CAM .....	158
7.24.2.4.8	CPE-CAM sends stop operation approval/command to CPE-CHU .....	158
7.24.2.4.9	CPE-CHU sends stop operation request acknowledgment to BS-CHU .....	159
7.24.2.4.10	CPE-CHU checks stop operation timer expired and stops operation .....	159
7.24.2.4.11	CPE-CHU sends stop operation completed notification to CPE-CAM .....	159

7.24.2.4.12	BS-CHU checks stop operation timer expired and stops operation .....	159
7.24.2.4.13	BS-CHU sends stop operation completed notification to CPE management unit .....	159
7.24.2.5	Switch operating channel operation.....	159
7.24.2.5.1	General .....	159
7.24.2.5.2	BS-CAM sends channel switch request to BS-CHU .....	160
7.24.2.5.3	BS-CHU starts channel switch timer .....	160
7.24.2.5.4	BS-CHU sends channel switch request acknowledgment to BS-CAM .....	161
7.24.2.5.5	BS-CHU sends channel switch request to CPE-CHU .....	161
7.24.2.5.6	CPE-CHU starts channel switch timer .....	161
7.24.2.5.7	CPE-CHU sends channel switch notification to CPE-CAM .....	161
7.24.2.5.8	CPE-CAM sends channel switch approval/command to CPE-CHU .....	161
7.24.2.5.9	CPE-CHU sends channel switch request acknowledgment to BS-CHU .....	161
7.24.2.5.10	BS-CHU checks channel switch timer expired and performs channel switch .....	161
7.24.2.5.11	CPE-CHU checks channel switch timer expired and performs channel switch .....	161
7.24.2.5.12	BS-CHU sends channel switch completed notification to BS-CAM .....	162
7.24.2.5.13	BS-CHU broadcasts SCH on PHY-OM1 or FCH on PHY-OM2 .....	162
7.24.2.5.14	BS-CHU sends DS-MAP/DCD/US-MAP/UCD to CPE-CHU .....	162
7.24.2.5.15	CPE-CHU sends channel switch completed notification to CPE-CAM .....	162
7.24.2.5.16	CPE-CHU sends channel switch completed notification to CPE management unit .....	162
7.24.3	Multi-channel operation at A-BS .....	162
7.24.4	Multi-channel operation at A-CPE .....	163
7.25	Group Resource Allocation .....	164
8.	Security mechanism in IEEE 802.22 .....	166
8.1	Security Architecture for the Data/Control and Management Planes .....	167
8.1.2	Key management and authentication overview .....	167
8.2	SCM protocol .....	167
8.2.2	Authentication state machine .....	167
8.2.2.7	Security capabilities negotiation .....	167
8.2.3	TEK exchange overview .....	168
8.2.3.1	TEK exchange overview for PMP topology .....	168
8.2.3.2	TEK state machine .....	168
8.3	Key usage .....	168
8.3.1	BS key usage .....	168
8.3.1.5	BS usage of TEX and GTEK .....	168
8.4	Cryptographic methods.....	169
8.4.1	Selection of Data Encryption and Authentication methods .....	169
8.4.2	Data Encryption and Authentication with AES GCM .....	170
8.4.2.1	PDU format.....	170
8.4.2.1.1	Packet number (PN) .....	170
8.4.2.1.2	PDU format—Authentication only .....	172
8.4.2.1.3	PDU format—Authentication and encryption .....	173
8.4.2.1.4	PDU format—Encryption only .....	174
8.4.2.2	GCM algorithm constraints .....	175
8.4.2.3	Receive processing rules .....	176
8.6	Security sublayer 2—Security mechanisms for the cognitive functions .....	176
8.6.2	CBP Authentication mechanisms.....	176
8.6.2.4	ECQV implicit certificate generation, processing, and validation requirements .....	177
8.6.2.4.1	ECQV certificate generation requirements .....	177
8.6.2.5	Signature generation, processing, and validation requirements .....	177

8.6.2.5.1	Signature generation requirements .....	177
8.6.2.6	BS Implicit Certificate Exchange .....	178
9.	PHY Operation Mode 1 (PHY-OM1) .....	178
9.2	Data rates .....	179
9.4	Superframe and frame structure.....	192
9.4.1	Preamble.....	192
9.4.1.5	Local frame preamble .....	192
9.4.1.6	Local CBP preamble.....	193
9.7	Channel coding.....	194
9.7.2	Forward Error Correction (FEC).....	194
9.7.2.1	Binary Convolutional code (BCC) mode (mandatory).....	194
9.7.2.1.2	Puncturing .....	194
9.7.2.1.3	OFDM slot concatenation .....	195
9.7.2.5	Multidimensional trellis coded modulation (MD-TCM) mode (optional) .....	196
9.7.2.5.1	Overview of multidimensional trellis coded modulation (MD-TCM) .....	196
9.7.2.5.2	Coset selection .....	197
9.7.2.5.3	Region pair selection .....	198
9.7.2.5.4	Symbol selection .....	200
9.8	Constellation mapping and modulation.....	200
9.8.1	Data modulation.....	200
9.9	Control mechanisms .....	203
9.9.4	Power control .....	203
9.9.4.2	Transmit Power Control mechanism .....	203
9.14	Receiver requirements .....	205
9.14.1	Receiver minimum sensitivity .....	205
9.15	Multiple-input, multiple-output (MIMO).....	205
9.15.1	Overview.....	205
9.15.2	MIMO pilot allocation .....	205
9.15.2.1	Overview.....	205
9.15.2.2	Pilot allocation for two antennas .....	205
9.15.2.3	Pilot allocation for four antennas.....	206
9.15.3	Space time coding (STC).....	207
9.15.3.1	Overview.....	207
9.15.3.2	Transmit diversity using two antennas (Alamouti O-STBC) .....	208
9.15.3.3	Transmit diversity with array-interference gain .....	208
9.15.3.3.1	Overview .....	208
9.15.3.3.2	Transmit diversity with array-interference gain for two antennas .....	209
9.15.3.3.3	Transmit diversity with array-interference gain for four antennas .....	210
9.15.4	Spatial multiplexing.....	212
9.15.4.1	Overview.....	212
9.15.4.2	Spatial multiplexing using two antennas .....	212
9.15.4.3	Spatial multiplexing using four antennas.....	213
9a.	PHY Operation Mode 2 (PHY-OM2) .....	213
9a.1	Symbol description .....	214
9a.1.1	OFDM symbol mathematical representation .....	214
9a.1.1.1	Time domain description .....	215
9a.1.1.2	Frequency domain description.....	215
9a.1.2	Symbol parameters.....	215
9a.1.2.1	Subcarrier spacing.....	215
9a.1.2.2	Symbol duration for different cyclic prefix modes.....	216
9a.1.2.3	Transmission parameters .....	216
9a.1.3	OFDMA basic terms definition.....	217

9a.1.3.1	Tile, slot, and data region.....	217
9a.1.3.2	Data mapping.....	219
9a.2	Data rates.....	221
9a.3	Functional block diagram applicable to the PHY.....	233
9a.4	Frame structure.....	234
9a.4.1	Preamble.....	235
9a.4.1.1	Frame preamble and local frame preamble.....	235
9a.4.1.2	CBP preamble.....	237
9a.4.2	Control header and MAP definitions.....	237
9a.4.2.1	Frame control header (FCH).....	237
9a.4.2.2	DS-MAP, US-MAP, DCD, and UCD.....	238
9a.5	CBP packet format.....	238
9a.6	OFDM subcarrier allocation.....	238
9a.6.1	Pilot pattern.....	238
9a.6.1.1	Downstream (DS).....	238
9a.6.1.2	Upstream (US).....	239
9a.6.2	DS subcarrier allocation.....	239
9a.6.2.1	Symbol structure for subchannel in the DS.....	239
9a.6.2.2	Subcarrier allocation and data mapping onto subcarriers.....	240
9a.6.3	Upstream subcarrier allocation.....	242
9a.6.3.1	Symbol structure for subchannel in the upstream.....	242
9a.6.3.2	Subcarrier allocation and data mapping onto subcarriers.....	243
9a.6.3.3	Data subchannel rotation scheme.....	245
9a.6.4	Bit interleaving.....	246
9a.7	Channel coding.....	246
9a.7.1	Data scrambling.....	246
9a.7.2	Forward error correction (FEC).....	246
9a.7.2.1	BCC mode (mandatory).....	247
9a.7.2.1.1	Binary convolutional coding.....	247
9a.7.2.1.2	Puncturing.....	247
9a.7.2.1.3	OFDM slot concatenation.....	247
9a.7.2.2	Multidimensional trellis coded modulation (MD-TCM) mode (optional).....	249
9a.8	Constellation mapping and modulation.....	249
9a.8.1	Data modulation.....	249
9a.8.2	Pilot modulation.....	250
9a.9	Control mechanisms.....	250
9a.9.1	DS synchronization.....	250
9a.9.2	US synchronization.....	250
9a.9.3	Opportunistic US bursts.....	250
9a.9.3.1	CDMA bursts.....	250
9a.9.3.1.1	CDMA codes.....	251
9a.9.3.1.2	Initial-ranging transmission.....	251
9a.9.3.1.3	CDMA periodic-ranging, BW-request, and UCS notification transmission.....	252
9a.9.3.1.4	Ranging, BW request, and UCS notification opportunity windows.....	253
9a.9.4	Power control.....	254
9a.9.4.1	Transmit power control boundaries and EIRP limits.....	254
9a.9.4.2	Transmit power control mechanism.....	254
9a.10	Network synchronization.....	255
9a.11	Frequency control requirements.....	255
9a.12	Antenna.....	255
9a.13	RF mask.....	255
9a.14	Receiver requirements.....	255
9a.15	MIMO pilot allocation.....	256
9a.15.1	Overview.....	256

9a.15.2 Pilot allocation for two antennas.....	256
9a.15.3 Pilot allocation for four antennas.....	257
9a.15.4 Space time coding (STC).....	257
10. Cognitive radio capability .....	257
10.1 General.....	257
12. Parameters and connection management .....	258
12.1 Parameters, timers, message IEs.....	258
12.1.1 MAC (dynamic service flow, multicast, ARQ, capability, and bandwidth management).....	258
12.1.1.1 MAC (Relay, Multi-channel).....	258
12.1.2 PHY (initialization, operation, and DS/US synchronization).....	258
14. Management plane interfaces and procedures .....	263
14.2 Primitive definitions .....	263
14.2.1 Management SAP (M-SAP).....	263
14.2.1.4 BS configuration and monitoring primitives .....	263
14.2.1.4.1 M-AVAIL-TV-CH-REPORT REQUEST .....	263
14.2.1.4.2 M-AVAIL-TV-CH-REPORT-INDICATION .....	264
14.2.1.4.5 M-OPERATING-TV-CHS-CONFIRMATION .....	264
14.2.1.5 CPE reports the resulting available WRAN services list.....	266
14.2.1.5.4 M-WRAN-SERVICES-INDICATION .....	266
Annex G (informative) Bibliography .....	268
Annex H (informative) Multiple-input, multiple-output (MIMO)—Receiver side implementation .....	269

**IEEE Standard for Information Technology—  
Telecommunications and information exchange  
between systems  
Wireless Regional Area Networks (WRAN)—  
Specific requirements**

**Part 22: Cognitive Wireless RAN  
Medium Access Control (MAC) and  
Physical Layer (PHY) Specifications:  
Policies and Procedures for  
Operation in the TV Bands**

**Amendment 2: Enhancement for Broadband  
Services and Monitoring Applications**

*IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.*

*This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.*

(This amendment is based on IEEE 802.22™-2011 as amended by IEEE Std 802.22a™-2014.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard. The editing instructions are shown in **bold italic**. Four editing instructions are used: change, delete, insert, and replace. **Change** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). **Delete** removes existing material. **Insert** adds new material without disturbing the existing material. Insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. **Replace** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.<sup>1</sup>

---

<sup>1</sup>Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.