

# IEEE Standard for Ethernet

## Amendment 3: Physical Layers and Management Parameters for 25 Gb/s and 40 Gb/s Operation, Types 25GBASE-T and 40GBASE-T

IEEE Computer Society

Sponsored by the  
LAN/MAN Standards Committee

---

IEEE  
3 Park Avenue  
New York, NY 10016-5997  
USA

**IEEE Std 802.3bq™-2016**  
(Amendment to  
IEEE Std 802.3™-2015  
as amended by  
IEEE Std 802.3bw™-2015, and  
IEEE Std 802.3by™-2016)

**IEEE Std 802.3bq™-2016**

(Amendment to  
IEEE Std 802.3™-2015  
as amended by  
IEEE Std 802.3bw™-2015, and  
IEEE Std 802.3by™-2016)

# **IEEE Standard for Ethernet**

## **Amendment 3: Physical Layer and Management Parameters for 25 Gb/s and 40 Gb/s Operation Types 25GBASE-T and 40GBASE-T**

Sponsor

**LAN/MAN Standards Committee  
of the  
IEEE Computer Society**

Approved 30 June 2016

**IEEE-SA Standards Board**

**Abstract:** This amendment to IEEE Std 802.3-2015 specifies new Physical Coding Sublayer (PCS) interfaces and new Physical Medium Attachment (PMA) sublayer interfaces for 25 Gb/s Ethernet and 40 Gb/s Ethernet. 25GBASE-T and 40GBASE-T specify LAN interconnects for up to 30 m of balanced twisted-pair structured cabling, for 25 Gb/s and 40 Gb/s, respectively.

**Keywords:** 25GBASE-T, 25 Gigabit Ethernet, 25GMII, 40GBASE-T, 40 Gigabit Ethernet, Auto-Negotiation, Ethernet, IEEE 802<sup>®</sup>, IEEE 802.3<sup>™</sup>, IEEE 802.3bq<sup>™</sup>, Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, structured cabling, XLGMII

---

The Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2016 by The Institute of Electrical and Electronics Engineers, Inc.  
All rights reserved. Published 8 September 2016. Printed in the United States of America.

IEEE and 02 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

Print: ISBN 978-1-5044-2282-6 STD21086  
PDF: ISBN 978-1-5044-2283-3 STDPD21086

*IEEE prohibits discrimination, harassment, and bullying.*

*For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

## Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

### Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory, not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

## Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

## Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

## Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board  
445 Hoes Lane  
Piscataway, NJ 08854 USA

## Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

## Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

## Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

## Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/Xplore/home.jsp> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

## Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

## Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

## Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3by Working Group ballot. Individuals may have not voted, voted for approval, disapproval or abstained on this standard.

**David J. Law, IEEE 802.3 Working Group Chair**  
**Adam Healey, IEEE 802.3 Working Group Vice-Chair**

**Peter Anslow, IEEE 802.3 Working Group Secretary**  
**Steven B. Carlson, IEEE 802.3 Working Group Executive Secretary**  
**Valerie Maguire, IEEE 802.3 Working Group Treasurer**

**David Chalupsky, IEEE P802.3bq 25G/40GBASE-T Task Force Chair**  
**George Zimmerman, IEEE P802.3bq 25G/40GBASE-T Task Force Editor-in-Chief**

John Abbott	Eugene Dai	Brian Holden
David Abramson	Shaoan Dai	Rita Horner
Shadi Abughazaleh	John D'Ambrosia	Bernard Hornmeyer
Faisal Ahmad	Mike Darling	Viktor Horvath
Dale Amason	Yair Darshan	Chui Hua
J. Michael Andrewartha	Piers Dawe	Liang-wei Huang
Oleksandr Babenko	Fred Dawson	Scott Irwin
Kwang-Hyun Baek	Ian Dedic	Kazuhiko Ishibe
Amrik Bains	Chris Diminico	Hideki Isono
Koussalya Balasubramanian	Thuyen Dinh	Tom Issenhuth
Thananya Baldwin	Curtis Donahue	Kenneth Jackson
Denis Beaudoin	Dan Dove	Jack Jewell
Christian Beia	Mike Dudek	Wenbin Jiang
Yakov Belopolsky	David Dwell	Andrew Jimenez
Michael Bennett	Hesham Elbawaby	Chad Jones
Vipul Bhatt	David Estes	Antony Joseph
William Bliss	John Ewer	Yasuaki Kawatsu
Brad Booth	John Faller	Michael Kelsen
Martin Bouda	Shoshana Feldman	Yongbum Kim
David Brandt	German Feyh	Jonathan King
Ralf-Peter Braun	Alan Flatman	Scott Kipp
Theodore Brillhart	Howard Frazier	Michael Klempa
Paul Brooks	Richard Frosch	Avi Kliger
David Brown	Michael Furlong	Curtis Knittle
Matthew Brown	Andrew Gardner	Shigeru Kobayashi
Thomas Brown	Mike Gardner	Keisuke Kojima
Phillip Brownlee	Ali Ghiasi	Paul Kolesar
Mark Bugg	Joel Goergen	Tom Kolze
Juan-Carlos Calderon	Zhigang Gong	Glen Kramer
J. Martin Carroll	Steven Gorshe	Albert Kuo
Clark Carty	James Graba	Hans Lackner
Mandeep Chadha	Robert Grow	Efstathios Larios
Jacky Chang	Mark Gustlin	Wayne Larsen
Yin Chang	Marek Hajduczenia	Mark Laubach
David Chen	Bernie Hammond	Greg Le Cheminant
Wheling Cheng	Jeffrey Heath	Arthur Lee
Ahmad Chini	Carl Herman	David Lewis
Golam Choudhury	David Hess	Lei Li
Peter Cibula	Yasuo Hidaka	Mike Peng Li
Christopher R. Cole	Riu Hirai	Shaohua Li
Keith Conroy	Thomas Hogenmueller	Thomas Lichtenegger

Ru Jian Lin  
Robert Lingle  
James Liu  
Zhenyu Liu  
William Lo  
Miklos Lukacs  
Kent Lusted  
Jeffery Maki  
James Malkemus  
Yonatan Malkiman  
Edwin Mallette  
Arthur Marris  
Chris Mash  
Kirsten Matheus  
Erdem Matoglu  
Laurence Matola  
Brett McClellan  
Thomas McDermott  
John McDonough  
Richard Mei  
Richard Mellitz  
Bryan Moffitt  
Leo Montreuil  
Paul Mooney  
Charles Moore  
Andy Moorwood  
Thomas Mueller  
Ron Muir  
Dale Murray  
Henry Muysshondt  
Edward Nakamoto  
Gary Nicholl  
Paul Nikolich  
Kevin Noll  
Ronald Nordin  
Mark Nowell  
David Ofelt  
Ichiro Ogura  
Tom Palkert  
Sujan Pandey  
Sesha Panguluri  
Carlos Pardo  
Moon Park  
Pravin Patel  
Petar Pepeljugoski  
Gerald Pepper  
Ruben Perez De Aranda Alonso  
Michael Peters

John Petrilla  
Rick Pimpinella  
Neven Pischl  
Rainer Poehmerer  
William Powell  
Richard Prodan  
Rick Rabinovich  
Saifur Rahman  
Adee Ran  
Ram Rao  
Alon Regev  
Duane Remein  
Victor Renteria  
Michael Ressler  
Poldi (Pavlick) Rimboim  
Christopher Roth  
Salvatore Rotolo  
Hisaya Sakamoto  
Vineet Salunke  
Sam Sambasivan  
Yasuo Sasaki  
Fred Schindler  
Stefan Schneelee  
Peter Scruton  
Alexander Seiger  
Naoshi Serizawa  
Megha Shanbhag  
Masood Shariff  
Stephen Shellhammer  
Bazhong Shen  
Mizuki Shirai  
Kapil Shrikhande  
Jeff Slavick  
Scott Sommers  
Yoshiaki Sone  
Xiaohu Song  
Tom Souvignier  
Bryan Sparrowhawk  
Edward Sprague  
Peter Stassar  
Leonard Stencil  
Robert Stone  
Steve Swanson  
Andre Szczepanek  
William Szeto  
Bharat Tailor  
Akio Tajima  
Takayuki Tajima

Tomoo Takahara  
Satoshi Takahashi  
Kiyoto Takahata  
Alexander Tan  
Toshiki Tanaka  
Mehmet Tazebay  
Brian Teipen  
Geoffrey Thompson  
Alan Tipper  
Pirooz Toyserkani  
Nathan Tracy  
David Tremblay  
Albert Tretter  
Stephen Trowbridge  
Wen-Cheng Tseng  
Yoshihiro Tsurumaru  
Mike Tu  
Alan Ugolini  
John Ullrich  
Eckhard Ullrich  
Sterling A. Vadten  
Sergio Valle  
Paul Vanderlaan  
Robert Wagner  
Robert Wang  
Tongtong Wang  
Xiaofeng Wang  
Xinyuan Wang  
Zhong Feng Wang  
Markus Weber  
Brian Welch  
Yang Wen  
Matthias Wendt  
Oded Wertheim  
Natalie Wienckowski  
Ludwig Winkel  
Peter Wu  
Yu Xu  
Lennart Yseboodt  
Liquan Yuan  
Hayato Yuki  
Garold Yurko  
Andrew Zambell  
Jin Zhang  
Yan Zhuang  
Helge Zinner  
Pavel Zivny  
Gaoling Zou

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Shadi Abughazaleh	David Hess	Arumugam Paventhan
Thomas Alexander	Yasuo Hidaka	Michael Peters
Richard Alfvin	Guido Hiertz	Adee Ran
Carol Ansley	Werner Hoelzl	R. K. Rannow
Peter Anslow	Rita Horner	Alon Regev
Butch Anton	Tetsushi Ikegami	Maximilian Riegel
Stefan Aust	Noriyuki Ikeuchi	Robert Robinson
Amrik Bains	Sergiu Iordanescu	Benjamin Rolfe
Saman Behtash	Scott Irwin	Martin Rossbach
Michael Bennett	Osamu Ishida	Frank Schewe
Gennaro Boggia	Atsushi Ito	Dieter Schicketanz
Ralf-Peter Braun	Peter Jones	Takeshi Shimizu
Nancy Bravin	Adri Jovin	Kapil Shrikhande
Theodore Brillhart	Shinkyu Kaku	David Solomon
Matthew Brown	Piotr Karocki	Ju-Hyung Song
Jairo Bustos Heredia	John Kay	Thomas Starai
William Byrd	Stuart Kerry	Peter Stasas
Steven B. Carlson	Yongbum Kim	Eugene Stroudmire
Juan Carreon	Scott Kipp	Walter Struppler
Clark Carty	Bruce Kraemer	Hirotoshi Sugawara
Mandeep Chadha	Mark Laubach	Patricia Thaler
David Chalupsky	David L. Law	James Theodoras
Minho Cheong	David Lewis	David Thompson
Keng Hua Chuang	Jon Lewis	Geoffrey Thompson
Peter Cibula	Arthur H. Light	Michael Thompson
Charles Cook	William Lo	Sterling Vaden
John D'Ambrosia	Elvis Maculuba	Dmitri Varsanofiev
Christopher Diminico	Valerie Maguire	Prabodh Varshney
Yezid Donoso	Jeffery Maki	Balasubramanian Vittal
Sourav Dutta	Arthur Mars	George Vlantis
German Feyh	Brett McClennan	Roy Wang
Matthias Fritsche	Thomas Mcdermott	Hung-Yu Wei
Yukihiro Fujimoto	Richard Mellitz	Peter Wu
James Graba	Eric Mofatt	Oren Yuen
Randall Groves	Charles Moorwood	Andrew Zambell
Marek Hajduczenia	Michael Newman	Zhen Zhou
Adam Healey	Nick S. A. Nikjoo	George Zimmerman
Marco Hernandez	Satoshi Obara	

When the IEEE-SA Standards Board approved this standard on 30 June 2016, it had the following membership:

**Jean-Philippe Faure**, *Chair*  
**Ted Burse**, *Vice Chair*  
**John D. Kulick**, *Past Chair*  
**Konstantinos Karachalios**, *Secretary*

Chuck Adams  
Masayuki Ariyoshi  
Stephen Dukes  
Jianbin Fan  
Ronald W. Hotchkiss  
J. Travis Griffith

Gary Hoffman  
Michael Janezic  
Joseph L. Koepfinger\*  
Hung Ling  
Kevin Lu  
Gary Robinson  
Annette D. Reilly

Mehmet Ulema  
Yingli Wen  
Howard Wolfman  
Don Wright  
Yu Yuan  
Daidi Zhong

\*Member Emeritus

## Introduction

This introduction is not part of IEEE Std 802.3bq™-2016, IEEE Standard for Ethernet—Amendment 3: Physical Layer and Management Parameters for 25 Gb/s and 40 Gb/s Operation, Types 25GBASE-T and 40GBASE-T.

IEEE Std 802.3 was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel, and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z™ added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae™ added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile), and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2015 and are not maintained as separate documents.

At the date of IEEE Std 802.3bq-2016 publication, IEEE Std 802.3 is composed of the following documents:

### IEEE Std 802.3-2015

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats, and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted-pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines services and protocol elements that enable the exchange of IEEE 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

#### IEEE Std 802.3bw-2015

Amendment 1—This amendment includes changes to IEEE Std 802.3-2015 and adds Clause 96. This amendment adds 100 Mb/s Physical Layer (PHY) specifications and management parameters for operation on a single balanced twisted-pair copper cable.

#### IEEE Std 802.3by-2016

Amendment 2—This amendment includes changes to IEEE Std 802.3-2015 and adds Clause 105 through Clause 112, Annex 109A, Annex 109B, Annex 109C, Annex 110A, Annex 110B, and Annex 110C. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 25 Gb/s.

#### IEEE Std 802.3bq-2016

Amendment 3—This amendment includes changes to IEEE Std 802.3-2015 and adds Clause 113 and Annex 113A. This amendment adds new Physical Layers for 25 Gb/s and 40 Gb/s operation over balanced twisted-pair structured cabling systems.

A companion document IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.1 is updated to add management capability for enhancements to IEEE Std 802.3 after approval of the enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.



# Contents

1.	Introduction.....	24
1.3	Normative references.....	24
1.4	Definitions.....	24
1.5	Abbreviations.....	25
28.	Physical Layer link signaling for Auto-Negotiation on twisted pair.....	26
28.3	State diagrams and variable definitions.....	26
28.3.1	State diagram variables.....	26
28.3.2	State diagram timers.....	26
28.5	Protocol implementation conformance statement (PICS) proforma for Clause 28, Physical Layer link signaling for Auto-Negotiation on twisted pair.....	26
28.5.3	Major capabilities/options.....	26
28.5.4	PICS proforma tables for Physical Layer link signaling for Auto-Negotiation on twisted pair.....	27
28.5.4.8	State diagrams.....	27
30.	Management.....	28
30.2	Managed objects.....	28
30.2.5	Capabilities.....	28
30.3	Layer management for DTEs.....	28
30.3.2	PHY device managed object class.....	28
30.3.2.1	PHY device attributes.....	28
30.3.2.1.2	aPhyType.....	28
30.3.2.1.3	aPhyTypeList.....	29
30.5	Layer management for medium attachment units (MAUs).....	29
30.5.1	MAU managed object class.....	29
30.5.1.1	MAU attributes.....	29
30.5.1.1.2	aMAUType.....	29
30.5.1.1.4	aMediaAvailable.....	29
30.5.1.1.19	aSNROpMarginChnIA.....	29
30.5.1.1.20	aSNROpMarginChnIB.....	30
30.5.1.1.21	aSNROpMarginChnIC.....	30
30.5.1.1.22	aSNROpMarginChnID.....	30
30.5.1.1.24	aLDFastRetrainCount.....	31
30.5.1.1.25	aLPFastRetrainCount.....	31
30.6	Management for link Auto-Negotiation.....	31
30.6.1	Auto-Negotiation managed object class.....	31
30.6.1.1	Auto-Negotiation attributes.....	31
30.6.1.1.5	aAutoNegLocalTechnologyAbility.....	31
45.	Management Data Input/Output (MDIO) Interface.....	32
45.2	MDIO Interface Registers.....	32
45.2.1	PMA/PMD registers.....	32
45.2.1.6	PMA/PMD control 2 register (Register 1.7).....	33
45.2.1.7	PMA/PMD status 2 register (Register 1.8).....	33
45.2.1.7.4	Transmit fault (1.8.11).....	33
45.2.1.7.5	Receive fault (1.8.10).....	33

45.2.1.8	PMD transmit disable register (Register 1.9) .....	34
45.2.1.12	40G/100G PMA/PMD extended ability register (Register 1.13) .....	34
45.2.1.9a	40GBASE-T ability (1.13.6) .....	34
45.2.1.14b	25G PMA/PMD extended ability register (Register 1.19) .....	35
45.2.1.14b.a	25GBASE-T ability (1.19.5) .....	35
45.2.1.62	10MultiGBASE-T status (Register 1.129).....	35
45.2.1.62.1	LP information valid (1.129.0).....	35
45.2.1.63	10MultiGBASE-T pair swap and polarity register (Register 1.130).....	35
45.2.1.64	10MultiGBASE-T TX power backoff and PHY short reach setting (Register 1.131).....	36
45.2.1.64.1	10MultiGBASE-T TX power backoff settings (1.131.15:10) .....	36
45.2.1.64.2	PHY short reach mode (1.131.0).....	36
45.2.1.65	10MultiGBASE-T test mode register (Register 1.132) .....	36
45.2.1.65.1	Test mode control (1.132.15:13) .....	37
45.2.1.65.2	Transmitter test frequencies (1.132.12:10).....	37
45.2.1.66	SNR operating margin channel A register (Register 1.133).....	37
45.2.1.67	SNR operating margin channel B register (Register 1.134).....	37
45.2.1.68	SNR operating margin channel C register (Register 1.135).....	37
45.2.1.69	SNR operating margin channel D register (Register 1.136).....	37
45.2.1.74	RX signal power channel A register (Register 1.141).....	38
45.2.1.75	RX signal power channel B register (Register 1.142).....	38
45.2.1.76	RX signal power channel C register (Register 1.143).....	38
45.2.1.77	RX signal power channel D register (Register 1.144).....	38
45.2.1.78	10MultiGBASE-T skew delay register (Registers 1.145 and 1.146) ....	38
45.2.1.79	10MultiGBASE-T fast retrain status and control register (Register 1.147) .....	39
45.2.1.79.1	LP fast retrain count (1.147.15:11).....	39
45.2.1.79.2	LD fast retrain count (1.147.10:6).....	39
45.2.1.79.5	Fast retrain signal type (1.147.2:1).....	39
45.2.1.79.6	Fast retrain enable (1.147.0).....	39
45.2.3	PCS registers .....	40
45.2.3.1	PCS control 1 register (Register 3.0).....	40
45.2.3.1.2	Loopback (3.0.14).....	40
45.2.3.2	PCS status 1 register (Register 3.1) .....	40
45.2.3.2.7	PCS receive link status (3.1.2).....	40
45.2.3.6	PCS control 2 register (Register 3.7).....	41
45.2.3.6.1	PCS type selection (3.7.23:0) .....	41
45.2.3.7	PCS status 2 register (Register 3.8).....	42
45.2.3.7.3aa	25GBASE-T capable (3.8.9) .....	42
45.2.3.7.3b	40GBASE-T capable (3.8.6) .....	42
45.2.3.9	EEE control and capability 1 (Register 3.20) .....	42
45.2.3.9.4a	40GBASE-T EEE supported (3.20.7).....	43
45.2.3.9a	EEE control and capability 2 (Register 3.21) .....	43
45.2.3.9a.1	25GBASE-T EEE supported (3.21.2).....	43
45.2.3.13	BASE-R and 10MultiGBASE-T PCS status 1 register (Register 3.32) .....	43
45.2.3.13.1	BASE-R and 10MultiGBASE-T receive link status (3.32.12) .....	44
45.2.3.13.4	BASE-R and 10MultiGBASE-T PCS high BER (3.32.1).....	44
45.2.3.13.5	BASE-R and 10MultiGBASE-T block lock (3.32.0).....	45
45.2.3.14	BASE-R and 10MultiGBASE-T PCS status 2 register (Register 3.33) .....	45

	45.2.3.14.1	Latched block lock (3.33.15).....	45
	45.2.3.14.2	Latched high BER (3.33.14).....	46
	45.2.3.14.3	BER (3.33.13:8).....	46
	45.2.3.14.4	Errored blocks (3.33.7:0).....	46
45.2.7	Auto-Negotiation registers .....		46
	45.2.7.10	10MultiGBASE-T AN control 1 register (Register 7.32).....	47
	45.2.7.10.4a	40GBASE-T capability (7.32.11).....	48
	45.2.7.10.4b	25GBASE-T capability (7.32.10).....	48
	45.2.7.10.4c	25GBASE-T Fast retrain ability (7.32.9) .....	48
	45.2.7.10.4d	40GBASE-T Fast retrain ability (7.32.3) .....	48
	45.2.7.10.5	10GBASE-T LD PMA training reset request (7.32.2).....	48
	45.2.7.10.6	10GBASE-T Fast retrain ability (7.32.1) .....	49
	45.2.7.10.7	10GBASE-T LD loop timing ability (7.32.0).....	49
	45.2.7.11	10MultiGBASE-T AN status 1 register (Register 7.33).....	49
	45.2.7.11.1	MASTER-SLAVE configuration fault (7.33.15) .....	49
	45.2.7.11.2	MASTER-SLAVE configuration resolution (7.33.14).....	50
	45.2.7.11.7	10GBASE-T Link partner PMA training reset request (7.33.9) .....	50
	45.2.7.11.7a	Link partner 40GBASE-T capability (7.33.8) .....	50
	45.2.7.11.7b	Link partner 25GBASE-T capability (7.33.7) .....	50
	45.2.7.11.7c	25GBASE-T Fast retrain ability (7.33.2) .....	50
	45.2.7.11.8	10GBASE-T Fast retrain ability (7.33.1) .....	51
	45.2.7.11.9	40GBASE-T Fast retrain ability (7.33.0) .....	51
	45.2.7.13	EEE advertisement (Register 7.60).....	51
	45.2.7.13.4a	40GBASE-T EEE supported (7.60.9).....	52
	45.2.7.13.12a	25GBASE-T EEE supported (7.60.0).....	52
	45.2.7.14	EEE link partner ability (Register 7.61) .....	52
	45.2.7.14a	MultiGBASE-T AN control 2 (Register 7.64).....	52
	45.2.7.14a.1	25GBASE-T THP Bypass Request .....	53
	45.2.7.14a.2	40GBASE-T THP Bypass Request .....	53
	45.2.7.14b	MultiGBASE-T AN status 2 (Register 7.65).....	53
	45.2.7.14b.1	25GBASE-T Link Partner THP Bypass Request .....	54
	45.2.7.14b.2	40GBASE-T Link Partner THP Bypass Request .....	54
45.5	Protocol implementation conformance statement (PICS) proforma for Clause 45, Management Data Input/Output (MDIO) interface .....		55
	45.5.3	PICS proforma tables for the Management Data Input Output (MDIO) interface .....	55
	45.5.3.2	PMA/PMD MMD options .....	55
	45.5.3.3	PMA/PMD Management functions .....	55
	45.5.3.6	PCS options.....	55
	45.5.3.7	PCS management functions .....	56
	45.5.3.8	Auto-Negotiation options .....	56
	45.5.3.9	Auto-Negotiation management functions .....	57
55.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 10GBASE-T .....		58
	55.3.4	PMA training side-stream scrambler polynomials .....	58
55.6	Management interfaces .....		58
	55.6.1.2	10GBASE-T Auto-Negotiation page use .....	58
	55.6.2	MASTER-SLAVE configuration resolution .....	58
	55.12.3	Physical Coding Sublayer (PCS) .....	59

78.	Energy-Efficient Ethernet (EEE).....	60
78.1	Overview.....	60
78.1.3	Reconciliation sublayer operation.....	60
78.1.3.3.1	PHY LPI transmit operation.....	60
78.1.4	PHY types optionally supporting EEE.....	60
78.2	LPI mode timing parameters description.....	60
78.3	Capabilities Negotiation.....	61
78.5	Communication link access latency.....	61
80.	Introduction to 40 Gb/s and 100 Gb/s networks.....	62
80.1	Overview.....	62
80.1.3	Relationship of 40 Gigabit and 100 Gigabit Ethernet to the ISO OSI reference model.....	62
80.1.4	Nomenclature.....	62
80.1.5	Physical Layer signaling systems.....	63
80.4	Delay Constraints.....	64
81.	Reconciliation Sublayer (RS) and Media Independent Interface for 40 Gb/s and 100 Gb/s operation (XLGMII and CGMII).....	65
81.1	Overview.....	65
81.1.7.3	Mapping of PLS_CARRIER.indication.....	65
81.3.4	Link fault signaling.....	66
81.3.4.1	Variables and counters.....	66
81.3.4.2	State diagram.....	67
81.5	Protocol implementation conformance statement (PICS) proforma for Clause 81, Reconciliation Sublayer (RS) and Media Independent Interface for 40 Gb/s and 100 Gb/s operation.....	68
81.5.3.7	Link Interruption.....	68
105.	Introduction to 25 Gb/s networks.....	69
105.1	Overview.....	69
105.1.1	Scope.....	69
105.1.2	Relationship of 25 Gigabit Ethernet to the ISO OSI reference model.....	69
105.1.3	Nomenclature.....	70
105.2	Physical Layer signaling systems.....	70
105.3	Summary of 25 Gigabit Ethernet sublayers.....	71
105.3.1	Reconciliation Sublayer (RS) and 25 Gigabit Media Independent Interface (25GMII).....	71
105.3.6	Auto-Negotiation (AN).....	71
105.5	Delay constraints.....	71
113.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, types 25GBASE-T and 40GBASE-T.....	72
113.1	Overview.....	72
113.1.1	Nomenclature.....	72
113.1.2	Relationship of 25GBASE-T and 40GBASE-T to other standards.....	73
113.1.3	Operation of 25GBASE-T and 40GBASE-T.....	73
113.1.3.1	Summary of Physical Coding Sublayer (PCS).....	77
113.1.3.2	Summary of Physical Medium Attachment (PMA) sublayer.....	78

113.1.3.3	Summary of EEE capability .....	78
113.1.4	Signaling.....	79
113.1.5	Interfaces .....	80
113.1.6	Conventions in this clause.....	80
113.2	25GBASE-T and 40GBASE-T service primitives and interfaces .....	80
113.2.1	Technology Dependent Interface .....	81
113.2.1.1	PMA_LINK.request.....	81
113.2.1.1.1	Semantics of the primitive .....	81
113.2.1.1.2	When generated .....	81
113.2.1.1.3	Effect of receipt .....	81
113.2.1.2	PMA_LINK.indication .....	81
113.2.1.2.1	Semantics of the primitive .....	81
113.2.1.2.2	When generated .....	82
113.2.1.2.3	Effect of receipt .....	82
113.2.2	PMA service interface .....	82
113.2.2.1	PMA_TXMODE.indication.....	83
113.2.2.1.1	Semantics of the primitive .....	83
113.2.2.1.2	When generated .....	84
113.2.2.1.3	Effect of receipt .....	84
113.2.2.2	PMA_CONFIG.indication .....	84
113.2.2.2.1	Semantics of the primitive .....	84
113.2.2.2.2	When generated .....	84
113.2.2.2.3	Effect of receipt .....	84
113.2.2.3	PMA_UNITDATA.request.....	84
113.2.2.3.1	Semantics of the primitive .....	85
113.2.2.3.2	When generated .....	85
113.2.2.3.3	Effect of receipt .....	85
113.2.2.4	PMA_UNITDATA.indication .....	85
113.2.2.4.1	Semantics of the primitive .....	85
113.2.2.4.2	When generated .....	86
113.2.2.4.3	Effect of receipt .....	86
113.2.2.5	PMA_SCRSTATUS.request.....	86
113.2.2.5.1	Semantics of the primitive .....	86
113.2.2.5.2	When generated .....	86
113.2.2.5.3	Effect of receipt .....	86
113.2.2.6	PMA_PCSSTATUS.request .....	86
113.2.2.6.1	Semantics of the primitive .....	86
113.2.2.6.2	When generated .....	86
113.2.2.6.3	Effect of receipt .....	87
113.2.2.7	PMA_RXSTATUS.indication .....	87
113.2.2.7.1	Semantics of the primitive .....	87
113.2.2.7.2	When generated .....	87
113.2.2.7.3	Effect of receipt .....	87
113.2.2.8	PMA_REMRXSTATUS.request .....	87
113.2.2.8.1	Semantics of the primitive .....	87
113.2.2.8.2	When generated .....	87
113.2.2.8.3	Effect of receipt .....	88
113.2.2.9	PMA_ALERTDETECT.indication.....	88
113.2.2.9.1	Semantics of the primitive .....	88
113.2.2.9.2	When generated .....	88
113.2.2.9.3	Effect of receipt .....	88
113.2.2.10	PCS_RX_LPI_STATUS.request .....	88
113.2.2.10.1	Semantics of the primitive .....	88
113.2.2.10.2	When generated .....	88

113.2.2.10.3	Effect of receipt .....	88
113.2.2.11	PMA_PCSDATAMODE.indication .....	89
113.2.2.11.1	Semantics of the primitive .....	89
113.2.2.11.2	When generated .....	89
113.2.2.11.3	Effect of receipt .....	89
113.2.2.12	PMA_FR_ACTIVE.indication .....	89
113.2.2.12.1	Semantics of the primitive .....	89
113.2.2.12.2	When generated .....	89
113.2.2.12.3	Effect of receipt .....	89
113.3	Physical Coding Sublayer (PCS) .....	89
113.3.1	PCS service interface (25GMII/XLGMII) .....	89
113.3.2	PCS functions .....	90
113.3.2.1	PCS Reset function .....	91
113.3.2.2	PCS Transmit function .....	91
113.3.2.2.1	Use of blocks .....	92
113.3.2.2.2	65B-LDPC transmission code .....	92
113.3.2.2.3	Notation conventions .....	92
113.3.2.2.4	Transmission order .....	95
113.3.2.2.5	Block structure .....	95
113.3.2.2.6	Control codes .....	95
113.3.2.2.7	Ordered sets .....	100
113.3.2.2.8	Idle (/I) .....	100
113.3.2.2.9	LPI (/LI) .....	100
113.3.2.2.10	Start (/S) .....	100
113.3.2.2.11	Terminate (/T) .....	101
113.3.2.2.12	ordered set (/O) .....	101
113.3.2.2.13	Error (/E) .....	101
113.3.2.2.14	Transmit process .....	101
113.3.2.2.15	64B/65B to 512B/513B Transcoder .....	101
113.3.2.2.16	Aggregation .....	104
113.3.2.2.17	PCS Scrambler .....	104
113.3.2.2.18	LDPC framing and LDPC encoder .....	106
113.3.2.2.19	Reed Solomon encoder .....	106
113.3.2.2.20	DSQ128 bit mapping .....	107
113.3.2.2.21	DSQ128 to 4D-PAM16 .....	109
113.3.2.2.22	Block-LDPC framer .....	109
113.3.2.2.23	EEE capability .....	109
113.3.2.3	PCS Receive function .....	110
113.3.2.3.1	Frame and block synchronization .....	111
113.3.2.3.2	PCS descrambler .....	112
113.3.2.3.3	Invalid blocks .....	112
113.3.3	Test-pattern generators .....	112
113.3.4	PMA training side-stream scrambler polynomials .....	113
113.3.4.1	Generation of bits $S_{an}$ , $S_{bn}$ , $S_{cn}$ , $S_{dn}$ .....	113
113.3.4.2	Generation of 4D symbols $TA_n$ , $TB_n$ , $TC_n$ , $TD_n$ .....	113
113.3.4.3	PMA training mode descrambler polynomials .....	113
113.3.5	LPI signaling .....	114
113.3.5.1	LPI Synchronization .....	115
113.3.5.2	Quiet period signaling .....	116
113.3.5.3	Refresh period signaling .....	116
113.3.6	Detailed functions and state diagrams .....	117
113.3.6.1	State diagram conventions .....	117
113.3.6.2	State diagram parameters .....	117
113.3.6.2.1	Constants .....	117

	113.3.6.2.2	Variables .....	118
	113.3.6.2.3	Timers .....	120
	113.3.6.2.4	Functions .....	120
	113.3.6.2.5	Counters .....	122
	113.3.6.3	State diagrams .....	123
113.3.7	PCS management .....		123
	113.3.7.1	Status .....	123
	113.3.7.2	Counters .....	124
	113.3.7.3	Loopback .....	130
113.4	Physical Medium Attachment (PMA) sublayer .....		130
	113.4.1	PMA functional specifications .....	130
	113.4.2	PMA functions .....	131
	113.4.2.1	PMA Reset function .....	131
	113.4.2.2	PMA Transmit function .....	131
		113.4.2.2.1 Alert signal .....	131
		113.4.2.2.2 Link failure signal .....	133
	113.4.2.3	PMA transmit disable function .....	133
		113.4.2.3.1 Global PMA transmit disable function .....	133
		113.4.2.3.2 PMA pair by pair transmit disable function .....	133
		113.4.2.3.3 PMA MDIO function mapping .....	133
	113.4.2.4	PMA Receive function .....	134
	113.4.2.5	PHY Control function .....	135
		113.4.2.5.1 Infocfield notation .....	136
		113.4.2.5.2 Start of Frame Delimiter .....	136
		113.4.2.5.3 Current transmitter settings .....	136
		113.4.2.5.4 Next transmitter settings .....	137
		113.4.2.5.5 Requested transmitter settings .....	137
		113.4.2.5.6 Message Field .....	137
		113.4.2.5.7 SNR_margin .....	138
		113.4.2.5.8 Transition counter .....	139
		113.4.2.5.9 Coefficient exchange handshake .....	139
		113.4.2.5.10 Ability Fields .....	139
		113.4.2.5.11 Reserved fields .....	139
		113.4.2.5.12 Vendor-specific field .....	139
		113.4.2.5.13 Coefficient Field .....	140
		113.4.2.5.14 CRC16 .....	140
		113.4.2.5.15 Startup sequence .....	140
		113.4.2.5.16 Fast retrain function .....	143
	113.4.2.6	Link Monitor function .....	144
	113.4.2.7	Refresh Monitor function .....	144
	113.4.2.8	Clock Recovery function .....	144
113.4.3	MDI .....		144
	113.4.3.1	MDI signals transmitted by the PHY .....	144
	113.4.3.2	Signals received at the MDI .....	145
113.4.4	Automatic MDI/MDI-X configuration .....		146
113.4.5	State variables .....		146
	113.4.5.1	State diagram variables .....	146
	113.4.5.2	Timers .....	149
	113.4.5.3	Functions .....	150
	113.4.5.4	Counters .....	150
113.4.6	State diagrams .....		151
	113.4.6.1	PHY Control state diagram .....	151
	113.4.6.2	Transition counter state diagrams .....	152
	113.4.6.3	Link Monitor state diagram .....	154

113.4.6.4	EEE Refresh monitor state diagram.....	155
113.4.6.5	Fast retrain state diagram.....	156
113.5	PMA electrical specifications.....	156
113.5.1	Isolation requirement.....	156
113.5.2	Test modes.....	156
113.5.2.1	Test fixtures.....	159
113.5.3	Transmitter electrical specifications.....	160
113.5.3.1	Maximum output droop.....	160
113.5.3.2	Transmitter nonlinear distortion.....	160
113.5.3.3	Transmitter timing jitter.....	161
113.5.3.4	Transmitter power spectral density (PSD) and power level.....	161
113.5.3.5	Transmit clock frequency.....	162
113.5.4	Receiver electrical specifications.....	162
113.5.4.1	Receiver differential input signals.....	162
113.5.4.2	Receiver frequency tolerance.....	163
113.5.4.3	Rejection of External EM Fields.....	163
113.5.4.4	Alien crosstalk noise rejection.....	163
113.5.4.5	Short reach mode.....	164
113.6	Management interfaces.....	164
113.6.1	Support for Auto-Negotiation.....	164
113.6.1.1	25G/40GBASE-T use of registers during Auto-Negotiation.....	165
113.6.1.2	25G/40GBASE-T Auto-Negotiation page use.....	165
113.6.1.3	Sending Next Pages.....	165
113.6.2	MASTER-SLAVE configuration resolution.....	167
113.7	Link segment characteristics.....	169
113.7.1	Cabling system characteristics.....	170
113.7.2	Link segment transmission parameters.....	170
113.7.2.1	Insertion loss.....	170
113.7.2.2	Differential characteristic impedance.....	171
113.7.2.3	Return loss.....	171
113.7.2.4	Coupling parameters between duplex channels comprising one link segment.....	171
113.7.2.4.1	Differential near-end crosstalk.....	171
113.7.2.4.2	Multiple disturber near-end crosstalk (MDNEXT) loss.....	172
113.7.2.4.3	Multiple disturber power sum near-end crosstalk (PSNEXT) loss.....	173
113.7.2.4.4	Attenuation to crosstalk ratio, far end (ACRF).....	174
113.7.2.4.5	Multiple disturber attenuation to crosstalk ratio, far-end (MDACRF).....	174
113.7.2.4.6	Multiple disturber power sum attenuation to crosstalk ratio, far-end (PS-ACRF).....	175
113.7.2.5	Maximum link delay.....	175
113.7.2.6	Link delay skew.....	175
113.7.3	Coupling parameters between link segments.....	175
113.7.3.1	Multiple disturber alien near-end crosstalk (MDANEXT) loss.....	176
113.7.3.1.1	Multiple disturber power sum alien near-end crosstalk (PSANEXT) loss.....	176
113.7.3.2	Multiple disturber alien far-end crosstalk (MDAFEXT) loss.....	176
113.7.3.2.1	Multiple disturber power sum alien attenuation to crosstalk, far end crosstalk (PSAACRF).....	177
113.7.4	Direct attach cable assembly—Short Reach Mode.....	177
113.7.4.1	Insertion loss.....	177
113.7.4.2	Return loss.....	178

113.7.4.3	Coupling parameters between direct attach cable assembly duplex channels comprising one link segment .....	178
113.7.4.3.1	Differential near-end crosstalk .....	178
113.7.4.3.2	Multiple disturber near-end crosstalk (MDNEXT) loss .....	179
113.7.4.3.3	Multiple disturber power sum near-end crosstalk (PSNEXT) loss .....	179
113.7.4.3.4	Attenuation to crosstalk ratio, far end (ACRF) .....	179
113.7.4.3.5	Multiple disturber attenuation to crosstalk ratio, far-end (MDACRF) .....	180
113.7.4.3.6	Maximum link delay.....	180
113.7.4.3.7	Link delay skew.....	180
113.7.4.3.8	Multiple disturber alien near-end crosstalk (MDANEXT) loss .....	180
113.7.4.3.9	Multiple disturber power sum alien near-end crosstalk (PSANEXT) loss .....	180
113.7.4.3.10	Multiple disturber power sum alien attenuation to crosstalk, far end crosstalk (PSAACRF) .....	181
113.7.5	Noise environment.....	182
113.8	MDI specification .....	182
113.8.1	MDI connectors .....	182
113.8.2	MDI electrical specifications.....	182
113.8.2.1	MDI return loss.....	184
113.8.2.2	MDI impedance balance .....	184
113.8.2.3	MDI fault tolerance.....	185
113.9	Environmental specifications.....	185
113.9.1	General safety .....	185
113.9.2	Network safety.....	185
113.9.3	Installation and maintenance guidelines.....	186
113.9.4	Telephone voltages.....	186
113.9.5	Electromagnetic compatibility.....	186
113.9.6	Temperature and humidity .....	186
113.10	PHY labeling.....	186
113.11	Delay constraints.....	186
113.12	Protocol implementation conformance statement (PICS) proforma for Clause 113, Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, types 25GBASE-T and 40GBASE-T .....	188
113.12.1	Identification.....	188
113.12.1.1	Implementation identification .....	188
113.12.1.2	Protocol summary .....	188
113.12.2	Major capabilities/options .....	189
113.12.3	Physical Coding Sublayer (PCS) .....	189
113.12.3.1	PCS Receive functions.....	191
113.12.3.2	Other PCS functions .....	191
113.12.4	Physical Medium Attachment (PMA).....	191
113.12.5	Management interface .....	194
113.12.6	PMA Electrical Specifications .....	195
113.12.7	Characteristics of the link segment.....	197
113.12.8	Characteristics of the direct attach cable assembly .....	197
113.12.9	MDI requirements .....	198
113.12.10	General safety and environmental requirements .....	198
113.12.11	Timing requirements.....	199

Annex 28B (normative) IEEE 802.3 Selector Base Page definition .....	200
28B.3 Priority resolution .....	200
Annex 28C (normative) Next Page Message Code field definitions .....	201
28C.11 Message code 9—10MultiGBASE-T and 1000BASE-T technology message code ..	201
Annex 28D (normative) Description of extensions to Clause 28 and associated annexes .....	202
28D.8 Extensions required for Clause 113 (25GBASE-T and 40GBASE-T).....	202
Annex 113A (informative) Description of cable clamp and test setup.....	203
113A.1 Overview .....	203
113A.2 Description of cable clamp .....	203
113A.3 Cable clamp measurement, calibration, and validation .....	205
113A.4 Test setup .....	208
Annex A (informative) Bibliography .....	209