

IEEE Standard for Ethernet

Amendment 2: Physical Layer and Management Parameters for Power over Ethernet over 4 pairs

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE Std 802.3bt™-2018
(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018)

IEEE Std 802.3bt™-2018
(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018)

IEEE Standard for Ethernet

Amendment 2: Physical Layer and Management Parameters for Power over Ethernet over 4 Pairs

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 27 September 2018

IEEE-SA Standards Board

Abstract: The maximum Powered Device (PD) power available is increased by this amendment to IEEE Std 802.3-2018 by utilizing all four pairs in the specified structured wiring plant. This represents a substantial change to the capabilities of Ethernet with standardized power. The power classification information exchanged during negotiation is extended to allow meaningful power management capability. These enhancements solve the problem of higher power and more efficient standardized Power over Ethernet (PoE) delivery systems.

Keywords: amendment, DTE power via MDI, Ethernet, IEEE 802.3™, IEEE 802.3bt™, PoE, Power over Ethernet

*This standard is dedicated to the memory
of our friend and colleague Martin Patoka.*

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2019 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 31 January 2019. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

National Electrical Code, NEC, and NFPA 70 are registered trademarks in the U.S. Patent & Trademark Office, owned by the National Fire Protection Association.

PDF: ISBN 978-1-5044-5276-2 STD23390
Print: ISBN 978-1-5044-5277-9 STDPD23390

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing various viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, manufacture, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are copied for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3bt Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*
Adam Healey, *IEEE 802.3 Working Group Vice-Chair*
Pete Anslow, *IEEE 802.3 Working Group Secretary*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Chad Jones, *IEEE P802.3bt DTE Power via MDI over 4-Pair Task Force Chair*
Koussalya Balasubramanian¹, *IEEE P802.3bt DTE Power via MDI over 4-Pair Task Force
Chief Editor (1st phase)*

Lennart Yseboodt, *IEEE P802.3bt DTE Power via MDI over 4-Pair Task Force
Chief Editor (2nd phase)*

David Abramson, *IEEE P802.3bt DTE Power via MDI over 4-Pair Task Force Comment Editor*

Justin Abbott	Yair Darshan	Wita Jorner
Shadi Abughazaleh	Piers Dawe	Bend Horrmeyer
Mohammad Ahmed	Fred Dawson	Victor Hou
Eric Baden	Wael Diab	Yasuhiro Hyakutake
Amrik Bains	Eric DiBiaso	Hideki Isono
Thananya Baldwin	John Dillard	Tom Issenhuth
Denis Beaudoin	Daniel Dillow	Kenneth Jackson
Christian Beia	Thuyen Dinh	Andrew Jimenez
Michael Bennett	Curtis Donahue	Peter Jones
Vipul Bhatt	Dan Dove	Manabu Kagami
William Bliss	Mike Dudek	Upen Kareti
Brad Booth	David Dwelley	Keisuke Kawahara
Martin Bouda	Frank Effenberger	Yasuaki Kawatsu
Ralf-Peter Braun	Heba Elbakoury	Michael Kelsen
Theodore Brillhart	David Estes	Scott Kipp
Paul Brooks	John Ewen	Michael Klempa
Alan Brown	Ramin Farjad	Curtis Knittle
Matthew Brown	Shahar Feldman	Shigeru Kobayashi
Chris Bullock	James Fife	Daniel Koehler
Jairo Bustos Heredia	Alan Flatman	Paul Kolesar
Adrian Butter	Matthias Fritsche	Tom Kolze
Francesco Caggiano	Richard Frosch	Glen Kramer
Anthony Calbo	Andrew Gardner	Hans Lackner
Clark Carty	Claude Gauthier	Jeffrey Lapak
Craig Chant	Ali Ghiasi	Mark Laubach
Geoffrey Chacon Simon	Joel Goergen	Han Hyub Lee
Mandeep Chadha	Volker Goetzfried	David Lewis
David Chalupsky	Zhigang Gong	Jon Lewis
Jacky Chang	Steven Gorshe	Mike Peng Li
Xin Chang	Robert Grow	Jane Lim
Amad Chini	Mark Gustlin	Dekun Liu
Keng Hua Chuang	Marek Hajduczenia	Hai-Feng Liu
Christopher R. Cole	Takehiro Hayashi	William Lo
John D'Ambrosia	Yasuo Hidaka	Miklos Lukacs
		Kent Lusted

¹Not a member of the IEEE 802.3 working group at the beginning of the working group ballot.

Jeffery Maki
David Malicoat
Yonatan Malkiman
Arthur Marris
Takeo Masuda
Erdem Matoglu
Naoki Matsuda
Mick McCarthy
Brett McClellan
Thomas McDermott
John McDonough
Larry McMillan
Richard Mei
Richard Mellitz
Bryan Moffitt
Ardeshir Mohammadian
Paul Mooney
Dale Murray
Henry Muysshondt
James Nadolny
Edward Nakamoto
Gary Nicholl
Kevin Noll
Mark Nowell
David Ofelt
Thomas Palkert
Hui Pan
Sesha Panguluri
Vasu Parthasarathy
Petar Pepeljugoski
Gerald Pepper
Ruben Perez De Aranda Alonso
Michael Peters
Phong Pham

Jean Picard
William Powell
Rick Rabinovich
Adee Ran
Alon Regev
Duane Remein
Victor Renteria
Christopher Roth
Salvatore Rotolo
Toshiaki Sakai
Jorge Salinger
Sam Sambasivan
Edward Sayre
Dieter Schicketanz
Fred Schindler
Hossein Sedarat
Naoshi Serizawa
Masood Shariff
ramin Shirani
Tom Skaar
Jeff Slavick
Daniel Smith
Scott Sommers
Yoshiaki Sone
Tom Souvignier
Peter Stassar
Heath Stewart
Robert Stone
David Stover
Junqing Sun
Ken-Ichi Suzuki
Steve Swanson
Andre Szczepaniak
William Szeto

Bharat Tailor
Takayuki Tajima
Satoshi Takahashi
Kohichi Tamura
Brian Teipen
Geoffrey Thompson
Pirooz Tooyserkani
Albert Tretter
Stephen Trowbridge
Yoshihiro Tsukamoto
Ed Ulrichs
Alexander Umnov
Sterling A. Vaden
Stefano Valle
Paul Vanderlaan
Robert Wagner
Dylan Walk
Haifei Wang
Roy Wang
Tongtong Wang
Xin Wang
Matthias Wendt
Oscar Wertheim
Katalie Wienckowski
Ludwig Winkel
Peter Wu
Dayin Xu
Yu Xu
Jun Yi
Hayato Yuki
Andrew Zambell
Yan Zhuang
George Zimmerman

The following members of the individual balloting committee voted on this amendment. Balloters may have voted for approval, disapproval, or abstention.

David Abramson	Yasuhiro Hyakutake	Adee Ran
Shadi Abughazaleh	Noriyuki Ikeuchi	R. K. Rannow
Iwan Adhicandra	Atsushi Ito	Maximilian Riegel
Andrea Agnes	Raj Jain	Robert Robinson
Thomas Alexander	Sang Kwon Jeong	Benjamin Rolfe
Dale Amason	Chad Jones	Veselin Skendzic
Peter Anslow	Peter Jones	Daniel Smith
John Ballingall	Piotr Karocki	Dorothy Stanley
Christian Boiger	Stuart J. Kerry	Thomas Starai
Ralf-Peter Braun	Yongbum Kim	Heath Stewart
Nancy Bravin	Mark Laubach	David Stover
Theodore Brillhart	David J. Law	Walter Struppler
Demetrio Bucaneg	Hyeong Ho Lee	Mitsutoshi Sugawara
Chris Bullock	Joris Lemahieu	Kohichi Tamaki
Jairo Bustos Heredia	Jon Lewis	Geoffrey Thompson
William Byrd	Shen Loh	Nathan Tracy
Steven B. Carlson	Miklos Lukacs	David Treublay
Juan Carreon	Elvis Maculuba	Mano-Rena Uchida
Clark Carty	Valerie Maguire	Alexander Umnov
Mandeep Chadha	Jeffery Maki	Dmitry Varsanofiev
Keith Chow	Jeffery Masters	George Vlantis
Keng Hua Chuang	Michael Maytum	Mhurrum Waheed
Ian Crayford	Mick McCarthy	Dylan Walker
Sourav Dutta	Brett McClellan	Lisa Ward
Avraham Freedman	Thomas McDermott	Keith Waters
Matthias Fritsche	Richard Mellitz	Stephen Webb
Yukihiro Fujimoto	Tremont Miao	Matthias Wendt
Joel Goergen	Charles Moorwood	Andreas Wolf
Zhigang Gong	Rick Murphy	Peter Wu
Eric W. Gray	Satoshi Obara	Dayin Xu
Randall Groves	Thomas Palkert	Lennart Yseboodt
Adam Healey	Bansi Patel	Oren Yuen
Marco Hernandez	Archie Peke	Andrew Zambell
David Hess	Richard Peters	Zhen Zhou
Werner Hoelzl	Jean Picard	George Zimmerman
Rita Horner	Rock Pimpinella	Pavel Zivny

When the IEEE-SA Standards Board approved this amendment on 27 September 2018, it had the following membership:

Jean-Philippe Faure, *Chair*
Gary Hoffman, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Teri Beale
 Guo-R. Hertz
 Christa Hunter
 Joseph L. Koepfinger*
 Thomas Koshy
 Hong Ling
 Dong Liu

Xiaohui Liu
 Kevin Lu
 Daleep Mohla
 Andrew Myles
 Paul Nikolich
 Ronald C. Petersen
 Annette D. Reilly

Robby Robson
 Dorothy Stanley
 Mehmet Ulema
 Phil Wennblom
 Philip Winston
 Howard Wolfman
 Jingyi Zhou

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3bt-2018, IEEE Standard for Ethernet—Amendment 2: Physical Layer and Management Parameters for Power over Ethernet over 4 Pairs.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel, and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of publication for IEEE Std 802.3bt-2018, IEEE Std 802.3 was composed of the following documents:

IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines

services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

IEEE Std 802.3bt-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

A companion document, IEEE Std 802.3.1, describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.1 is updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Contents

1.	Introduction.....	21
1.3	Normative references.....	21
1.4	Definitions.....	21
1.5	Abbreviations.....	22
14.	Twisted-pair medium attachment unit (MAU) and baseband medium, type 10BASE-T including type 10BASE-Te.....	23
14.3	MAU electrical specifications.....	23
14.3.1	MAU-to-MDI interface characteristics.....	23
14.3.1.1	Isolation requirement.....	23
25.	Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX.....	24
25.4	Specific requirements and exceptions.....	24
25.4.5	Change to 9.1.7, “Worst case droop of transformer”.....	24
25.4.6	Replacement of 8.4.1, “UTP isolation requirements”.....	24
25.4.7	Addition to 10.1, “Receiver”.....	24
25.6	Protocol implementation conformance statement (PICS) proforma for Clause 25, Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX.....	25
25.6.3	Major capabilities/options.....	25
25.6.3.1	DTE Power via MDI Power over Ethernet major capabilities/options.....	25
25.6.4	PICS proforma tables for the Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX.....	25
25.6.4.4	DTE Power via MDI Power over Ethernet compliance.....	25
30.	Management.....	26
30.2	Managed objects.....	26
30.2.2	Overview of managed objects.....	26
30.2.2.1	Text description of managed objects.....	26
30.2.3	Containment.....	26
30.2.5	Capabilities.....	27
30.9	Management for DTE Power via MDI Power over Ethernet.....	35
30.9.1	PSE managed object class.....	35
30.9.1.1	PSE attributes.....	35
30.9.1.1.2	aPSEAdminState.....	35
30.9.1.1.3	aPSEPowerPairsControlAbility.....	35
30.9.1.1.4	aPSEPowerPairs.....	35
30.9.1.1.5	aPSEPowerDetectionStatus.....	36
30.9.1.1.5a	aPSEPowerDetectionStatusA.....	36
30.9.1.1.5b	aPSEPowerDetectionStatusB.....	37
30.9.1.1.6	aPSEPowerClassification.....	37
30.9.1.1.6a	aPSEPowerClassificationA.....	38
30.9.1.1.6b	aPSEPowerClassificationB.....	38
30.9.1.1.7	aPSEInvalidSignatureCounter.....	39
30.9.1.1.7a	aPSEInvalidSignatureCounterA.....	39
30.9.1.1.7b	aPSEInvalidSignatureCounterB.....	39
30.9.1.1.8	aPSEPowerDeniedCounter.....	39
30.9.1.1.8a	aPSEPowerDeniedCounterA.....	40

30.9.1.1.8b	aPSEPowerDeniedCounterB	40
30.9.1.1.9	aPSEOverLoadCounter.....	40
30.9.1.1.9a	aPSEOverLoadCounterA.....	40
30.9.1.1.10	aPSEShortCounter aPSEOverLoadCounterB.....	41
30.9.1.1.11	aPSEMPSAbsentCounter.....	41
30.9.1.1.11a	aPSEMPSAbsentCounterA.....	41
30.9.1.1.11b	aPSEMPSAbsentCounterB.....	42
30.9.1.2	PSE actions	42
30.9.1.2.1	acPSEAdminControl.....	42
30.12	Layer Management for Link Layer Discovery Protocol (LLDP)	42
30.12.2	LLDP Local System Group managed object class	42
30.12.2.1	LLDP Local System Group attributes	42
30.12.2.1.6	aLldpXdot3LocPowerMDISupported	42
30.12.2.1.7	aLldpXdot3LocPowerMDIEnabled.....	42
30.12.2.1.8	aLldpXdot3LocPowerPairControllable	43
30.12.2.1.9	aLldpXdot3LocPowerPairs.....	43
30.12.2.1.10	aLldpXdot3LocPowerClass	43
30.12.2.1.14	aLldpXdot3LocPowerType	44
30.12.2.1.17	aLldpXdot3LocPDRequestedPowerValue	44
30.12.2.1.17a	aLldpXdot3LocPDRequestedPowerValueA	44
30.12.2.1.17b	aLldpXdot3LocPDRequestedPowerValueB.....	45
30.12.2.1.18	aLldpXdot3LocPSEAllocatedPowerValue.....	45
30.12.2.1.18a	aLldpXdot3LocPSEAllocatedPowerValueA.....	45
30.12.2.1.18b	aLldpXdot3LocPSEAllocatedPowerValueB.....	45
30.12.2.1.18c	aLldpXdot3LocPSEPoweringStatus.....	46
30.12.2.1.18d	aLldpXdot3LocPDPoweredStatus.....	46
30.12.2.1.18e	aLldpXdot3LocPowerPairsExt.....	46
30.12.2.1.18f	aLldpXdot3LocPowerClassExtA.....	46
30.12.2.1.18g	aLldpXdot3LocPowerClassExtB.....	47
30.12.2.1.18h	aLldpXdot3LocPowerClassExt	47
30.12.2.1.18i	aLldpXdot3LocPowerTypeExt.....	48
30.12.2.1.18j	aLldpXdot3LocPDLoad.....	48
30.12.2.1.18k	aLldpXdot3LocPD4PID	48
30.12.2.1.18l	aLldpXdot3LocPSEMaxAvailPower.....	48
30.12.2.1.18m	aLldpXdot3LocPSEAutoclassSupport.....	48
30.12.2.1.18n	aLldpXdot3LocAutoclassCompleted.....	49
30.12.2.1.18o	aLldpXdot3LocAutoclassRequest	49
30.12.2.1.18p	aLldpXdot3LocPowerDownRequest	49
30.12.2.1.18q	aLldpXdot3LocPowerDownTime	49
30.12.2.1.18r	aLldpXdot3LocMeasVoltageSupport.....	49
30.12.2.1.18s	aLldpXdot3LocMeasCurrentSupport	50
30.12.2.1.18t	aLldpXdot3LocMeasPowerSupport	50
30.12.2.1.18u	aLldpXdot3LocMeasEnergySupport	50
30.12.2.1.18v	aLldpXdot3LocMeasurementSource	50
30.12.2.1.18w	aLldpXdot3LocMeasVoltageRequest.....	50
30.12.2.1.18x	aLldpXdot3LocMeasCurrentRequest	50
30.12.2.1.18y	aLldpXdot3LocMeasPowerRequest	51
30.12.2.1.18z	aLldpXdot3LocMeasEnergyRequest.....	51
30.12.2.1.18aa	aLldpXdot3LocMeasVoltageValid.....	51
30.12.2.1.18ab	aLldpXdot3LocMeasCurrentValid	51
30.12.2.1.18ac	aLldpXdot3LocMeasPowerValid	51
30.12.2.1.18ad	aLldpXdot3LocMeasEnergyValid.....	52
30.12.2.1.18ae	aLldpXdot3LocMeasVoltageUncertainty.....	52
30.12.2.1.18af	aLldpXdot3LocMeasCurrentUncertainty.....	52

30.12.2.1.18ag	aLldpXdot3LocMeasPowerUncertainty	52
30.12.2.1.18ah	aLldpXdot3LocMeasEnergyUncertainty	52
30.12.2.1.18ai	aLldpXdot3LocVoltageMeasurement	53
30.12.2.1.18aj	aLldpXdot3LocCurrentMeasurement	53
30.12.2.1.18ak	aLldpXdot3LocPowerMeasurement	53
30.12.2.1.18al	aLldpXdot3LocEnergyMeasurement	53
30.12.2.1.18am	aLldpXdot3LocPSEPowerPriceIndex	53
30.12.3	LLDP Remote System Group managed object class	54
30.12.3.1	LLDP Remote System Group attributes	54
30.12.3.1.6	aLldpXdot3RemPowerMDISupported	54
30.12.3.1.7	aLldpXdot3RemPowerMDIEnabled	54
30.12.3.1.8	aLldpXdot3RemPowerPairControllable	54
30.12.3.1.9	aLldpXdot3RemPowerPairs	54
30.12.3.1.10	aLldpXdot3RemPowerClass	55
30.12.3.1.14	aLldpXdot3RemPowerType	55
30.12.3.1.17	aLldpXdot3RemPDRrequestedPowerValue	55
30.12.3.1.17a	aLldpXdot3RemPDRrequestedPowerValueA	56
30.12.3.1.17b	aLldpXdot3RemPDRrequestedPowerValueB	56
30.12.3.1.18	aLldpXdot3RemPSEAllocatedPowerValue	56
30.12.3.1.18a	aLldpXdot3RemPSEAllocatedPowerValueA	57
30.12.3.1.18b	aLldpXdot3RemPSEAllocatedPowerValueB	57
30.12.3.1.18c	aLldpXdot3RemPSEPoweringStatus	57
30.12.3.1.18d	aLldpXdot3RemPDPoweredStatus	57
30.12.3.1.18e	aLldpXdot3RemPowerPairsExt	58
30.12.3.1.18f	aLldpXdot3RemPowerClassExtA	58
30.12.3.1.18g	aLldpXdot3RemPowerClassExtB	58
30.12.3.1.18h	aLldpXdot3RemPowerClassExt	59
30.12.3.1.18i	aLldpXdot3RemPowerTypeExt	59
30.12.3.1.18j	aLldpXdot3RemPDLload	59
30.12.3.1.18k	aLldpXdot3RemPD4PID	60
30.12.3.1.18l	aLldpXdot3RemPSEMaxAvailPower	60
30.12.3.1.18m	aLldpXdot3RemPSEAutoclassSupport	60
30.12.3.1.18n	aLldpXdot3RemAutoclassCompleted	60
30.12.3.1.18o	aLldpXdot3RemAutoclassRequest	60
30.12.3.1.18p	aLldpXdot3RemPowerDownRequest	60
30.12.3.1.18q	aLldpXdot3RemPowerDownTime	61
30.12.3.1.18r	aLldpXdot3RemMeasVoltageSupport	61
30.12.3.1.18s	aLldpXdot3RemMeasCurrentSupport	61
30.12.3.1.18t	aLldpXdot3RemMeasPowerSupport	61
30.12.3.1.18u	aLldpXdot3RemMeasEnergySupport	61
30.12.3.1.18v	aLldpXdot3RemMeasurementSource	62
30.12.3.1.18w	aLldpXdot3RemMeasVoltageRequest	62
30.12.3.1.18x	aLldpXdot3RemMeasCurrentRequest	62
30.12.3.1.18y	aLldpXdot3RemMeasPowerRequest	62
30.12.3.1.18z	aLldpXdot3RemMeasEnergyRequest	62
30.12.3.1.18aa	aLldpXdot3RemMeasVoltageValid	63
30.12.3.1.18ab	aLldpXdot3RemMeasCurrentValid	63
30.12.3.1.18ac	aLldpXdot3RemMeasPowerValid	63
30.12.3.1.18ad	aLldpXdot3RemMeasEnergyValid	63
30.12.3.1.18ae	aLldpXdot3RemMeasVoltageUncertainty	63
30.12.3.1.18af	aLldpXdot3RemMeasCurrentUncertainty	63
30.12.3.1.18ag	aLldpXdot3RemMeasPowerUncertainty	64
30.12.3.1.18ah	aLldpXdot3RemMeasEnergyUncertainty	64
30.12.3.1.18ai	aLldpXdot3RemVoltageMeasurement	64

	30.12.3.1.18aj aLldpXdot3RemCurrentMeasurement.....	64
	30.12.3.1.18ak aLldpXdot3RemPowerMeasurement.....	64
	30.12.3.1.18al aLldpXdot3RemEnergyMeasurement	65
	30.12.3.1.18am aLldpXdot3RemPSEPowerPriceIndex	65
33.	<u>Data Terminal Equipment (DTE) Power via Media Dependent Interface (MDI) Power over Ethernet over 2 Pairs</u>	66
33.1	Overview.....	66
33.1.1	Objectives	66
33.1.3	Relationship of <u>DTE Power via MDI Power over Ethernet</u> to the IEEE 802.3 Architecture	67
33.2	Power sourcing equipment (PSE).....	68
33.2.1	PSE location.....	68
33.2.2	Midspan PSE types	68
33.3	Powered devices (PDs).....	69
33.3.1	PD PI.....	69
33.4	Additional electrical specifications.....	69
33.4.2	Fault tolerance.....	69
33.4.3	Impedance balance.....	69
33.4.4	Common-mode output voltage	70
33.4.6	Differential noise voltage.....	71
33.4.7	Return loss	71
33.4.9	Midspan PSE device additional requirements	71
33.4.9.1	“Connector” or “telecom outlet” Midspan PSE device transmission requirements.....	71
33.4.9.1.1	Near End Crosstalk (NEXT).....	72
33.4.9.1.2	Insertion loss	73
33.4.9.1.3	Return loss	73
33.4.9.1a	<u>33.4.9.1.4 Work area or equipment cable Cord</u> Midspan PSE	73
33.4.9.1a.1	Maximum link delay	74
33.4.9.1a.2	Maximum link delay skew.....	74
33.4.9.1b	Coupling parameters between link segments.....	74
33.4.9.1b.1	Multiple disturber power sum alien near-end crosstalk (PSANEXT) loss.....	75
33.4.9.1b.2	Multiple disturber power sum alien far-end crosstalk (PSAFEXT) loss	75
33.6	Data Link Layer classification.....	75
33.6.3	Power control state diagrams	75
33.6.3.3	Variables	75
33.8	Protocol implementation conformance statement (PICS) proforma for Clause 33, <u>DTE Power via MDI Power over Ethernet over 2 Pairs</u>	76
33.8.1	Introduction.....	76
33.8.2	Identification.....	76
33.8.2.2	Protocol summary	76
33.8.3	PICS proforma tables for DTE Power via MDI Power over Ethernet over 2 Pairs	77
33.8.3.4	Electrical specifications applicable to the PSE and PD.....	77
40.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 1000BASE-T	78
40.6	PMA electrical specifications	78
40.6.1	PMA-to-MDI interface tests	78
40.6.1.1	Isolation requirement	78

55.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 10GBASE-T.....	79
55.5	PMA electrical specifications	79
55.5.1	Isolation requirement	79
79.	IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements	80
79.1	Overview.....	80
79.1.1	IEEE 802.3 LLDP frame format.....	80
79.1.1.3	Length/Type field	80
79.3	IEEE 802.3 Organizationally Specific TLVs	80
79.3.2	Power Via MDI TLV	80
79.3.2.1	MDI power support.....	82
79.3.2.1.1	Port class	82
79.3.2.1.2	PSE MDI power support.....	82
79.3.2.1.3	PSE MDI power state	82
79.3.2.1.4	PSE pairs control ability	82
79.3.2.2	PSE power pair	83
79.3.2.3	Power class	83
79.3.2.4	Requested pPower type/source/priority	84
79.3.2.4.1	Power type	84
79.3.2.4.2a	PD 4PID.....	84
79.3.2.5	PD requested power value	85
79.3.2.6	PSE allocated power value	85
79.3.2.6a	Dual-signature PD requested power value for Mode A and Mode B.....	86
79.3.2.6b	PSE allocated power value Alternative A and Alternative B	86
79.3.2.6c	Power status	87
79.3.2.6c.1	PSE powering status	88
79.3.2.6c.2	PD powered status	88
79.3.2.6c.3	PSE power pairs ext.....	88
79.3.2.6c.4	Dual-signature power Class ext Mode A	88
79.3.2.6c.5	Dual-signature power Class ext Mode B	89
79.3.2.6c.6	Power Class ext.....	89
79.3.2.6d	System setup	89
79.3.2.6d.1	Power Type ext	89
79.3.2.6d.2	PD Load	89
79.3.2.6e	PSE maximum available power value	89
79.3.2.6f	Autoclass.....	90
79.3.2.6f.1	PSE Autoclass support.....	90
79.3.2.6f.2	Autoclass completed	90
79.3.2.6f.3	Autoclass request	90
79.3.2.6g	Power down	91
79.3.2.6g.1	Power down request.....	91
79.3.2.6g.2	Power down time	91
79.3.8	Power via MDI Measurements TLV	91
79.3.8.1	Measurements	91
79.3.8.2	PSE power price index.....	93
79.3.8.3	Power Via MDI Measurements TLV usage rules.....	94
79.4	IEEE 802.3 Organizationally Specific TLV selection management	94
79.4.2	IEEE 802.3 Organizationally Specific TLV/LLDP Local and Remote System group managed object class cross references.....	94

79.5	Protocol implementation conformance statement (PICS) proforma for IEEE 802.3 Organizational Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements	98
79.5.3	Major capabilities/options.....	98
79.5.8	Power Via MDI TLV	99
79.5.12	Power via MDI Measurements TLV	102
126.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, types 2.5GBASE-T and 5GBASE-T	103
126.5	PMA electrical specifications	103
126.5.1	Isolation requirement	103
145.	Power over Ethernet.....	104
145.1	Overview.....	104
145.1.1	Compatibility considerations	105
145.1.2	Relationship of Power over Ethernet to the IEEE 802.3 Architecture	105
145.1.3	System parameters	106
145.1.4	Cabling requirements	108
145.2	Power sourcing equipment (PSE)	109
145.2.1	PSE Type descriptions	109
145.2.2	PSE location.....	110
145.2.3	Midspan PSE variants	110
145.2.4	PSE PI.....	117
145.2.5	PSE state diagrams.....	118
145.2.5.1	State diagram overview and timing	118
145.2.5.2	Conventions	119
145.2.5.3	Constants.....	120
145.2.5.4	Variables	120
145.2.5.5	Timers	130
145.2.5.6	Functions.....	132
145.2.5.7	State diagrams.....	137
145.2.6	PSE detection of PDs	152
145.2.6.1	PSE detection validation circuit.....	152
145.2.6.2	Detection probe requirements	153
145.2.6.3	Detection criteria.....	154
145.2.6.4	Rejection criteria.....	154
145.2.6.5	Open circuit criteria	155
145.2.7	Connection check.....	155
145.2.8	PSE classification of PDs and mutual identification	155
145.2.8.1	PSE Multiple-Event Physical Layer classification	159
145.2.8.2	Autoclass (optional).....	162
145.2.9	4PID requirements	163
145.2.10	Power supply output	163
145.2.10.1	Output voltage in the power on states.....	167
145.2.10.2	Output voltage pair-to-pair difference	167
145.2.10.3	Voltage transients	167
145.2.10.4	Reflected voltage	167
145.2.10.5	Power feeding ripple and noise.....	167
145.2.10.6	Continuous current capability in the power on states	167
145.2.10.6.1	PSE pair-to-pair current unbalance.....	170
145.2.10.7	Current during power up.....	172
145.2.10.8	Overload current	174

145.2.10.9	Short circuit current	174
145.2.10.10	Turn off time	177
145.2.10.11	Turn off voltage	177
145.2.10.12	Intra-pair current unbalance.....	177
145.2.10.13	Type power	177
145.2.10.14	Power turn on time.....	178
145.2.10.15	Error delay timing.....	178
145.2.10.16	PSE stability.....	178
145.2.11	Power supply allocation.....	178
145.2.12	PSE Maintain Power Signature (MPS) requirements	178
145.3	Powered devices (PDs)	179
145.3.1	PD Type descriptions.....	180
145.3.2	PD PI.....	180
145.3.3	PD state diagrams	182
145.3.3.1	Conventions	182
145.3.3.2	Mode designation.....	182
145.3.3.3	Single-signature PD state diagrams	182
145.3.3.3.1	Constants.....	182
145.3.3.3.2	Variables	182
145.3.3.3.3	Timers	185
145.3.3.3.4	Functions.....	186
145.3.3.3.5	State diagrams	187
145.3.3.4	Dual-signature PD state diagram	189
145.3.3.4.1	Constants.....	189
145.3.3.4.2	Variables	189
145.3.3.4.3	Timers	192
145.3.3.4.4	Functions.....	192
145.3.3.4.5	State diagram	193
145.3.4	PD valid and non-valid detection signatures	194
145.3.5	PD signature configurations.....	196
145.3.6	PD classification	197
145.3.6.1	PD Multiple-Event class signature	198
145.3.6.1.1	Mark Event behavior	200
145.3.6.2	Autoclass (optional).....	200
145.3.7	PSE Type identification	201
145.3.8	PD power	201
145.3.8.1	Input voltage	204
145.3.8.2	Input average power.....	204
145.3.8.2.1	Input average power exceptions	205
145.3.8.2.2	System stability test conditions during startup and steady state operation	205
145.3.8.3	Input inrush current.....	205
145.3.8.4	Peak operating power.....	206
145.3.8.4.1	Peak operating power exceptions	207
145.3.8.5	Input current slew rate	207
145.3.8.6	PD behavior during transients at the PSE PI	207
145.3.8.7	Ripple and noise.....	208
145.3.8.8	Reflected voltage	208
145.3.8.9	PD pair-to-pair current unbalance.....	209
145.3.9	PD Maintain Power Signature	211
145.4	Additional electrical specifications.....	213
145.4.1	Isolation	213
145.4.1.1	Electrical isolation environments.....	213
145.4.1.1.1	Environment A requirements.....	214

145.4.1.1.2	Environment B requirements	214
145.4.2	Fault tolerance.....	214
145.4.3	Impedance balance.....	215
145.4.4	Common-mode output voltage	216
145.4.5	Pair-to-pair output noise voltage.....	218
145.4.6	Differential noise voltage.....	218
145.4.7	Return loss	219
145.4.8	100BASE-TX transformer droop.....	219
145.4.9	Midspan PSE device additional requirements	219
145.4.9.1	Connector Midspan PSE device transmission requirements	221
145.4.9.1.1	Near End Crosstalk (NEXT).....	221
145.4.9.1.2	Insertion loss	222
145.4.9.1.3	Return loss	222
145.4.9.2	Cord Midspan PSE.....	222
145.4.9.2.1	Maximum link delay	223
145.4.9.2.2	Maximum link delay skew.....	223
145.4.9.3	Midspan signal path requirements	223
145.4.9.3.1	Alternative A Midspan PSE signal path transfer function.....	223
145.4.9.4	Coupling parameters between link segments.....	224
145.4.9.4.1	Multiple disturber power sum alien near-end crosstalk (PSANEXT) loss.....	224
145.4.9.4.2	Multiple disturber power sum alien far-end crosstalk (PSAFEXT) loss	224
145.5	Data Link Layer classification.....	225
145.5.1	TLV frame definition.....	225
145.5.2	Data Link Layer classification timing requirements.....	225
145.5.3	Power control state diagrams	225
145.5.3.1	Conventions	226
145.5.3.2	PSE power control state diagrams	226
145.5.3.2.1	Alternative designation	226
145.5.3.2.2	Variables	226
145.5.3.2.3	Functions.....	230
145.5.3.2.4	Attribute to state diagram variable mapping.....	231
145.5.3.2.5	State diagrams.....	232
145.5.3.3	Single-signature PD power control state diagrams.....	236
145.5.3.3.1	Variables	236
145.5.3.3.2	Timers	238
145.5.3.3.3	Functions.....	238
145.5.3.3.4	Attribute to state diagram variable mapping.....	239
145.5.3.3.5	State diagrams.....	240
145.5.3.4	Dual-signature PD power control state diagrams	241
145.5.3.4.1	Mode designation.....	241
145.5.3.4.2	Variables	242
145.5.3.4.3	Functions.....	244
145.5.3.4.4	Attribute to state diagram variable mapping.....	245
145.5.3.4.5	State diagrams.....	246
145.5.4	Power requests and allocations	248
145.5.5	State change procedure across a link (single-signature).....	248
145.5.5.1	PSE state change procedure across a link (single-signature).....	249
145.5.5.2	PD state change procedure across a link (single-signature)	249
145.5.6	State change procedure across a link (dual-signature).....	250
145.5.6.1	Transitions between 2-pair and 4-pair mode (dual-signature).....	250
145.5.6.2	PSE state change procedure across a link (dual-signature)	251
145.5.6.3	PD state change procedure across a link (dual-signature)	251

145.5.7	Autoclass.....	251
145.6	Environmental.....	252
145.6.1	General safety	252
145.6.2	Network safety.....	252
145.6.3	Installation and maintenance guidelines	252
145.6.4	Patch panel considerations.....	253
145.6.5	Electromagnetic emissions	253
145.6.6	Temperature and humidity.....	253
145.6.7	Labeling	253
145.7	Protocol implementation conformance statement (PICS) proforma for Clause 145, Power over Ethernet.....	254
145.7.1	Introduction.....	254
145.7.2	Identification.....	254
145.7.2.1	Implementation identification.....	254
145.7.2.2	Protocol summary	254
145.7.2.3	PD Major capabilities/options	255
145.7.2.4	PSE Major capabilities/options.....	256
145.7.3	PICS proforma tables for Power over Ethernet	257
145.7.3.1	Power sourcing equipment.....	257
145.7.3.2	Powered devices	262
145.7.3.3	Electrical specifications applicable to the PSE and PD.....	267
145.7.3.4	Electrical specifications applicable to the PSE.....	269
145.7.3.5	Electrical specifications applicable to the PD.....	271
145.7.3.6	Data Link Layer classification requirements	271
145.7.3.7	Environmental specifications applicable to PSEs and PDs	272
145.7.3.8	Environmental specifications applicable to the PSE	272
	Annex A (informative) Bibliography	273
	Annex 145A (informative) Resistance and current unbalance	274
145A.1	Intra pair resistance unbalance.....	274
145A.2	Pair-to-pair unbalance overview	274
145A.3	Pair-to-pair link section resistance unbalance requirements for 4-pair operation	276
145A.4	PSE resistance and current unbalance	276
145A.4.1	Direct RPSE measurement	277
145A.5	PD resistance and current unbalance	278
	Annex 145B (informative) Timing diagrams	279
145B.1	CC_DET_SEQ timing diagrams.....	279
145B.1.1	CC_DET_SEQ=0 timing diagrams.....	279
145B.1.2	CC_DET_SEQ=1 timing diagrams.....	280
145B.1.3	CC_DET_SEQ=2 timing diagrams.....	281
145B.1.4	CC_DET_SEQ=3 timing diagrams.....	282
145B.2	PSE Single-Event Physical Layer classification timing diagram	283
145B.3	PSE Multiple-Event Physical Layer classification timing diagram.....	283
	Annex 145C (informative) Power system and parameters	285
145C.1	Constant power	285
145C.2	Current	287
145C.3	Direct current resistance (DCR)	288
145C.4	Bundled cabling applications.....	289

IEEE Standard for Ethernet

Amendment 2: Physical Layer and Management Parameters for Power over Ethernet over 4 Pairs

[This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018.]

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in *bold italic*. Four editing instructions are used: change, delete, insert, and replace. *Change* is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). *Delete* removes existing material. *Insert* adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. *Replace* is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.¹

¹ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.