

IEEE Standard for Ethernet

Amendment 2: Media Access Control Parameters, Physical Layers, and Management Parameters for 25 Gb/s Operation

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE Std 802.3by™-2016
(Amendment to
IEEE Std 802.3™-2015
as amended by
IEEE Std 802.3bw™-2015)

IEEE 802.3by™-2016

(Amendment to
IEEE Std 802.3™-2015
as amended by
IEEE Std 802.3bw™-2015)

IEEE Standard for Ethernet

Amendment 2: Media Access Control Parameters, Physical Layers, and Management Parameters for 25 Gb/s Operation

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 30 June 2016

IEEE-SA Standards Board

Abstract: This amendment to IEEE Std 802.3-2015 adds Physical Layer (PHY) specifications and management parameters for 25 Gb/s operation over twinaxial copper cabling (25GBASE-CR and 25GBASE-CR-S), electrical backplanes (25GBASE-KR and 25GBASE-KR-S), and multimode fiber (25GBASE-SR). This amendment also specifies a 25 Gigabit Attachment Unit Interface (25GAUI) and optional Energy Efficient Ethernet (EEE).

Keywords: 25 Gigabit Ethernet, 25GAUI, 25GBASE-CR, 25GBASE-CR-S, 25GBASE-KR, 25GBASE-KR-S, 25GBASE-SR, 25GMII, Auto-Negotiation (AN), Backplane Ethernet, Energy Efficient Ethernet (EEE), Ethernet, Forward Error Correction (FEC), IEEE 802[®], IEEE 802.3[™], IEEE 802.3by[™], multimode fiber (MMF), Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, Physical Medium Dependent (PMD) sublayer, Reconciliation Sublayer (RS)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2016 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 29 July 2016. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

Print: ISBN 978-1-5044-2169-0 STD21020
PDF: ISBN 978-1-5044-2170-6 STDPD21020

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory, not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/Xplore/home.jsp> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IOWA's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3by Working Group ballot. Individuals may have not voted, voted for approval, disapproval or abstained on this standard.

David J. Law, *IEEE 802.3 Working Group Chair*

Adam Healey, *IEEE 802.3 Working Group Vice Chair*

Peter Anslow, *IEEE 802.3 Working Group Secretary*

Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*

Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Mark Nowell, *IEEE P802.3by 25 Gb/s Ethernet Task Force Chair*

Matthew Brown, *IEEE P802.3by 25 Gb/s Ethernet Task Force Editor-in-Chief*

John Abbott	Eugene Dai	Brian Holden
David Abramson	Shaoan Dai	Rita Homer
Shadi Abughazaleh	John D'Ambrosia	Bernhard Hermeyer
Faisal Ahmad	Mike Darling	Viktor Holm
Dale Amason	Yair Darshan	Xiangwei Huang
J. Michael Andrewartha	Piers J. G. Dawe	Yoshihiro Hyakutake
Oleksandr Babenko	Fred Dawson	Scott Irwin
Kwang-Hyun Baek	Ian Dedic	Kazuhiko Ishibe
Amrik Bains	Christopher Diminico	Hideki Isono
Koussalya Balasubramanian	Thuyen Dinh	Tom Issenhuth
Thananya Baldwin	Curtis Donahue	Kenneth Jackson
Denis Beaudoin	Dan Dove	Andrew Jimenez
Christian Beia	Michael Dudek	Chad Jones
Yakov Belopolsky	Nick Duer	Peter Jones
Michael Bennett	David Dwelle	Antony Joseph
Vipul Bhatt	Frank Effent Berger	Manabu Kagami
William Bliss	Hesham Elbakoury	Upen Kareti
Brad Booth	David Estes	Keisuke Kawahara
Martin Bouda	John Evens	Yasuaki Kawatsu
David Brandt	Joseph Feller	Michael Kelsen
Ralf-Peter Braun	Shmuel Feldman	Yongbum Kim
Theodore Brillhart	Cerman Feyh	Jonathan King
Paul Brooks	Alan Flatman	Scott Kipp
David Brown	Howard Frazier	Michael Klempa
Thomas Brown	Richard Frosch	Curtis Knittle
Phillip Brownlee	Andrew Gardner	Shigeru Kobayashi
Juan-Carlos Calderon	Mike Gardner	Keisuke Kojima
J. Martin Carroll	Ali Ghiasi	Paul Kolesar
Clark Carty	Joel Goergen	Tom Kolze
Mandeep Chadha	Zhigang Gong	Glen Kramer
David Chalupsky	Steven Gorshe	Hans Lackner
Jacky Chen	James Graba	Brett Lane
Xin Chen	Robert Grow	Jeff Lapak
David Chen	Mark Gustlin	Efstathios Larios
Whelton Cheng	Marek Hajduczenia	Mark Laubach
Ahmad Chini	Bernie Hammond	Greg Le Cheminant
Colam Choudhury	Takehiro Hayashi	Arthur Lee
Kuang Hua Chuang	David Hess	David Lewis
Peter Cibula	Yasuo Hidaka	Jon Lewis
Christopher R. Cole	Riu Hirai	Lei Li
Keith Conroy	Thomas Hogenmueller	Mike Peng Li

Shaohua Li
Thomas Lichtenegger
Ru Jian Lin
Robert Lingle
James Liu
Zhenyu Liu
William Lo
Miklos Lukacs
Kent Lusted
Jeffery Maki
James Malkemus
Yonatan Malkiman
Edwin Mallette
Arthur Marris
Chris Mash
Kirsten Matheus
Erdem Matoglu
Laurence Matola
Brett McClellan
Thomas McDermott
John McDonough
Richard Mei
Richard Mellitz
Bryan Moffitt
Leo Montreuil
Paul Mooney
Andy Moorwood
Thomas Mueller
Ron Muir
Dale Murray
Henry Muysshondt
Edward Nakamoto
Gary Nicholl
Paul Nikolich
Kevin Noll
Ronald Nordin
David Ofelt
Ichiro Ogura
Tom Palkert
Hui Pan
Sujan Pandey
Sesha Panguluri
Carlos Pardo
Moon Park
Petar Pepeljugin
Gerald Pepper
Ruben Perez Del Aranda Alonso
Michael Peters
John Perrin
Rich Pinheiro

Neven Pischl
Rainer Poehmerer
William Powell
Richard Prodan
Rick Rabinovich
Saifur Rahman
Adee Ran
Ram Rao
Alon Regev
Duane Remein
Victor Renteria
Michael Ressler
Poldi (Pavlick) Rimboim
Martin Rossbach
Christopher Roth
Salvatore Rotolo
Hisaya Sakamoto
Vineet Salunke
Sam Sambasivan
Yasuo Sasaki
Fred Schindler
Stefan Schneele
Peter Scruton
Alexander Seiger
Naoshi Serizawa
Megha Shanbhag
Masood Shariff
Stephen J. Shellhammer
Bazhong Shen
Mizuki Shirao
Kapil Shrikhande
Jeff Slavick
Scott Sommer
Yoshiaki Sone
Xiao Song
Tom Souvignier
Brian Sparrowhawk
Edward Sprague
Peter Stassar
Leonard Stencel
Robert Stone
Steve Swanson
Andre Szczepanek
William Szeto
Bharat Tailor
Akio Tajima
Takayuki Tajima
Tomoo Takahara
Satoshi Takahashi
Kiyoto Takahata

Alexander Tan
Toshiki Tanaka
Mehmet Tazebay
Brian Teipen
Geoffrey Thompson
Alan Tipper
Pirooz Tooyserkani
Nathan Tracy
David Tremblay
Albert Tretter
Stephen Trowbridge
Wen-Cheng Tseng
Yoshihiro Tsukamoto
Mike Tu
Alan Ugolini
Ed Ulrichs
Sterling A. Vaden
Stefano Valle
Paul Verlaan
Robert Warner
Robert Wang
Roy Wang
Jongtong Wang
Xiaofeng Wang
Xinyuan Wang
Zhong Feng Wang
Markus Weber
Brian Welch
Yang Wen
Matthias Wendt
Oded Wertheim
Martin White
Natalie Wienckowski
Ludwig Winkel
Peter Wu
Yu Xu
Lennart Yseboodt
Ting-Fa Yu
Liquan Yuan
Hayato Yuki
Garold Yurko
Andrew Zambell
Jin Zhang
Yan Zhuang
George Zimmerman
Helge Zinner
Pavel Zivny
Gaoling Zou

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Shadi Abughazaleh	Marco Hernandez	Tomas Pajda
Thomas Alexander	Yasuo Hidaka	Thomas Palkert
Richard Alfvin	Werner Hoelzl	Arumugam Paventhan
Carol Ansley	Rita Horner	Michael Peters
Peter Anslow	Tetsushi Ikegami	Adee Ran
Butch Anton	Noriyuki Ikeuchi	R. K. Rannow
Stefan Aust	Sergiu Iordanescu	Alon Regev
Eric Baden	Scott Irwin	Duane Remein
Amrik Bains	Osamu Ishida	Maximilian Riegel
John Ballingall	Atsushi Ito	Robert Robinson
Saman Behtash	Michael Johas Teener	Benjamin Rolfe
Jacob Ben Ary	Peter Jones	Christopher Roth
Michael Bennett	Adri Jovin	Frank Schewe
Gennaro Boggia	Shinkyō Kaku	Dieter Schiek
Brad Booth	Piotr Karocki	Takeshi Shimizu
Ralf-Peter Braun	Stuart Kerry	Kapil Shrikhande
Nancy Bravin	Yongbum Kim	Jeff Slack
Theodore Brillhart	Jonathan King	David Solomon
Matthew Brown	Scott Kipp	Thomas Strai
Jairo Bustos Heredia	Bruce Kraemer	Pete Stassar
William Byrd	Kumaran Krishnasamy	Robert Stone
Steven B. Carlson	Mark Laubach	Eugene Stoudenmire
Juan Carreon	David J. Law	Walter Struppler
Mandeep Chadha	David Lewis	Mitsutoshi Sugawara
Keng Hua Chuang	Jon Lewis	Junqing Sun
Peter Cibula	Arthur H. Light	Patricia Thaler
Charles Cook	William Lo	James Theodoras
John D'Ambrosia	Kent Lusted	David Thompson
Piers J. G. Dawe	Elvis Maculuba	Geoffrey Thompson
Christopher Diminico	Valerie Maire	Michael Thompson
Daniel Dove	Jeffery Mak	Sterling A. Vaden
Michael Dudek	Arthur Marris	Dmitri Varsanofiev
Constantin Dumitrescu	Brian McClellan	Balasubramanian Vittal
Sourav Dutta	Thomas McDermott	George Vlantis
Liu Fangfang	Richard Mellitz	Roy Wang
German Feyh	Bryan Moffitt	Hung-Yu Wei
Yukihiro Fujimoto	Charles Moorwood	Peter Wu
Eric W. Gray	Michael Newman	Jun Xu
Randall Groves	Nick S. A. Nikjoo	Oren Yuen
Marek Hajduczenia	Mark Nowell	Andrew Zambell
Adam Healey	Satoshi Obara	Zhen Zhou

When the IEEE-SA Standards Board approved this standard on 30 June 2016, it had the following membership:

Jean-Philippe Faure, *Chair*
Ted Burse, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams
Masayuki Ariyoshi
Stephen Dukes
Jianbin Fan
Ronald W. Hotchkiss
J. Travis Griffith

Gary Hoffman
Michael Janezic
Joseph L. Koepfinger*
Hung Ling
Kevin Lu
Gary Robinson
Annette D. Reilly

Mehmet Ulema
Yingli Wen
Howard Wolfman
Don Wright
Yu Yuan
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3by™-2016, IEEE Standard for Ethernet—Amendment 2: Media Access Control Parameters, Physical Layers, and Management Parameters for 25 Gb/s Operation.

IEEE Std 802.3 was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel, and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z™ added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae™ added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile), and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2015 and are not maintained as separate documents.

At the date of IEEE Std 802.3by-2016 publication, IEEE Std 802.3 is composed of the following documents:

IEEE Std 802.3-2015

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats, and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted-pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber

access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines services and protocol elements that enable the exchange of IEEE 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

IEEE Std 802.3bw-2015

Amendment 1—This amendment includes changes to IEEE Std 802.3-2015 and adds Clause 96. This amendment adds 100 Mb/s Physical Layer (PHY) specifications and management parameters for operation on a single balanced twisted-pair copper cable.

IEEE Std 802.3by-2016

Amendment 2—This amendment includes changes to IEEE Std 802.3-2015 and adds Clause 105 through Clause 112, Annex 109A, Annex 109B, Annex 109C, Annex 110A, Annex 110B, and Annex 110C. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 25 Gb/s.

A companion document IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.1 is updated to add management capability for enhancements to IEEE Std 802.3 after approval of the enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Contents

1. Introduction.....	28
1.1 Overview.....	28
1.1.3 Architectural perspectives.....	28
1.1.3.2 Compatibility interfaces.....	28
1.3 Normative references.....	28
1.4 Definitions.....	28
1.5 Abbreviations.....	29
4. Media Access Control.....	30
4.4 Specific implementations.....	30
4.4.2 MAC parameters.....	30
30. Management.....	31
30.3 Layer management for DTEs.....	31
30.3.2 PHY device managed object class.....	31
30.3.2.1 PHY device attributes.....	31
30.3.2.1.2 aPhyType.....	31
30.3.2.1.3 aPhyTypeList.....	31
30.3.2.1.5 aSymbolErrorDuringCarrier.....	31
30.5 Layer management for medium attachment units (MAUs).....	31
30.5.1 MAU managed object class.....	31
30.5.1.1 MAU attributes.....	31
30.5.1.1.2 aMAUType.....	31
30.5.1.1.4 aMediaAvailable.....	32
30.5.1.1.15 aFECAbility.....	32
30.5.1.1.16 aFECMode.....	33
30.5.1.1.17 aFECCorrectedBlocks.....	33
30.5.1.1.18 aFECUncorrectableBlocks.....	34
30.6 Management for link Auto-Negotiation.....	34
30.6.1 Auto-Negotiation managed object class.....	34
30.6.1.1 Auto-Negotiation attributes.....	34
30.6.1.1.5 aAutoNegLocalTechnologyAbility.....	34
45. Management Data Input/Output (MDIO) Interface.....	35
45.2 MDIO Interface Registers.....	35
45.2.1 PMA/PMD registers.....	35
45.2.1.1 PMA/PMD control 1 register (Register 1.0).....	36
45.2.1.1.3 Speed selection (1.0.13, 1.0.6, 1.0.5:2).....	36
45.2.1.2 PMA/PMD status 1 register (Register 1.1).....	36
45.2.1.2.3 Fault (1.1.7).....	36
45.2.1.4 PMA/PMD speed ability (Register 1.4).....	37
45.2.1.4.a 25G capable (1.4.11).....	37
45.2.1.6 PMA/PMD control 2 register (Register 1.7).....	37
45.2.1.7 PMA/PMD status 2 register (Register 1.8).....	38
45.2.1.7.4 Transmit fault (1.8.11).....	38
45.2.1.7.5 Receive fault (1.8.10).....	38
45.2.1.8 PMD transmit disable register (Register 1.9).....	38

45.2.1.10 PMA/PMD extended ability register (Register 1.11)	39
45.2.1.10.aa 25G extended abilities (1.11.12)	39
45.2.1.14 EEE capability (Register 1.16)	39
45.2.1.14.4a 25GBASE-R deep sleep (1.16.2)	39
45.2.1.14b 25G PMA/PMD extended ability register (Register 1.19)	40
45.2.1.14b.1 25GBASE-SR ability (1.19.4)	40
45.2.1.14b.2 25GBASE-CR ability (1.19.3)	40
45.2.1.14b.3 25GBASE-CR-S ability (1.19.2)	40
45.2.1.14b.4 25GBASE-KR ability (1.19.1)	40
45.2.1.14b.5 25GBASE-KR-S ability (1.19.0)	41
45.2.1.80 BASE-R PMD control register (Register 1.150)	41
45.2.1.81 BASE-R PMD status register (Register 1.151)	41
45.2.1.82 BASE-R LP coefficient update, lane 0 register (Register 1.152)	41
45.2.1.83 BASE-R LP status report, lane 0 register (Register 1.153)	41
45.2.1.84 BASE-R LD coefficient update, lane 0 register (Register 1.154)	41
45.2.1.85 BASE-R LD status report, lane 0 register (Register 1.155)	41
45.2.1.94 <u>Single-lane PHY 40GBASE-R FEC corrected blocks counter</u> (Register 1.172, 1.173)	42
45.2.1.95 <u>Single-lane PHY 40GBASE-R FEC uncorrected blocks counter</u> (Register 1.174, 1.175)	42
45.2.1.96 <u>CAUI-4 chip-to-module C2M and 25GAUI C2M recommended CTLE register</u> (Register 1.179)	42
45.2.1.96.1 Recommended CTLE peaking (1.179.4:1)	42
45.2.1.97 <u>25GAUI C2C and lane 0 CAUI-4 chip-to-chip C2C transmitter equalization,</u> <u>receive direction, lane 0</u> register (Register 1.180)	42
45.2.1.97.1 Request flag (1.180.15)	43
45.2.1.97.2 Post-cursor request (1.180.14:12)	43
45.2.1.97.3 Pre-cursor request (1.180.11:10)	43
45.2.1.97.4 Post-cursor remote setting (1.180.9:7)	43
45.2.1.97.5 Pre-cursor remote setting (1.180.6:5)	43
45.2.1.97.6 Post-cursor local setting (1.180.4:2)	43
45.2.1.97.7 Pre-cursor local setting (1.180.1:0)	43
45.2.1.99 <u>25GAUI C2C and lane 0 CAUI-4 chip-to-chip C2C transmitter equalization,</u> <u>transmit direction, lane 0</u> register (Register 1.184)	44
45.2.1.99.1 Request flag (1.184.15)	44
45.2.1.99.2 Post-cursor request (1.184.14:12)	44
45.2.1.99.3 Pre-cursor request (1.184.11:10)	44
45.2.1.99.4 Post-cursor remote setting (1.184.9:7)	44
45.2.1.99.5 Pre-cursor remote setting (1.184.6:5)	44
45.2.1.99.6 Post-cursor local setting (1.184.4:2)	45
45.2.1.99.7 Pre-cursor local setting (1.184.1:0)	45
45.2.1.101 RS-FEC control register (Register 1.200)	45
45.2.1.101.a 25G RS-FEC enable (1.200.2)	45
45.2.1.101.1 FEC bypass indication enable (1.200.1)	45
45.2.1.101.2 FEC bypass correction enable (1.200.0)	45
45.2.1.102 RS-FEC status register (Register 1.201)	46
45.2.1.102.1 PCS align status (1.201.15)	46
45.2.1.102.2 RS-FEC align status (1.201.14)	46
45.2.1.102.7 RS-FEC high SER (1.201.2)	46
45.2.1.102.8 FEC bypass indication ability (1.201.1)	46
45.2.1.102.9 FEC bypass correction ability (1.201.0)	46
45.2.1.103 RS-FEC corrected codewords counter (Register 1.202, 1.203)	47
45.2.1.104 RS-FEC uncorrected codewords counter (Register 1.204, 1.205)	47
45.2.1.106 RS-FEC symbol error counter lane 0 (Register 1.210, 1.211)	47

45.2.3 PCS registers.....	47
45.2.3.1 PCS control 1 register (Register 3.0)	47
45.2.3.2 PCS status 1 register (Register 3.1)	48
45.2.3.2.7 PCS receive link status (3.1.2).....	48
45.2.3.4 PCS speed ability (Register 3.4).....	48
45.2.3.4.5 25G capable (3.4.4).....	48
45.2.3.6 PCS control 2 register (Register 3.7)	48
45.2.3.6.1 PCS type selection (3.7.2:0)	49
45.2.3.7 PCS status 2 register (Register 3.8)	49
45.2.3.7.3a 25GBASE-R capable (3.8.7).....	49
45.2.3.9 EEE control and capability (Register 3.20)	49
45.2.3.9.2a 25GBASE-R deep sleep (3.20.11)	50
45.2.3.9.2b 25GBASE-R fast wake (3.20.10)	50
45.2.3.13 BASE-R and 10GBASE-T PCS status 1 register (Register 3.32)	50
45.2.3.13.1 BASE-R and 10GBASE-T receive link status (3.32.12)	50
45.2.3.13.4 BASE-R and 10GBASE-T PCS high BER (3.32.1).....	50
45.2.3.13.5 BASE-R and 10GBASE-T PCS block lock (3.32.0).....	50
45.2.3.14 BASE-R and 10GBASE-T PCS status 2 register (Register 3.33)	50
45.2.3.14.1 Latched block lock (3.33.15)	50
45.2.3.14.2 Latched high BER (3.33.14).....	51
45.2.3.14.3 BER (3.33.13:8).....	51
45.2.3.14.4 Errored blocks (3.33.7:0).....	51
45.2.3.15 10/25GBASE-R PCS test pattern seed A (Registers 3.34 through 3.37)	51
45.2.3.16 10/25GBASE-R PCS test pattern seed B (Registers 3.38 through 3.41).....	51
45.2.3.17 BASE-R PCS test-pattern control register (Register 3.42).....	51
45.2.7 Auto-Negotiation registers.....	52
45.2.7.12 Backplane Ethernet, BASE-R copper status (Register 7.48).....	52
45.2.7.12.1a RS-FEC negotiated (7.48.7).....	53
45.2.7.12.2 Negotiated Port Type (7.48.1, 7.48.2, 7.48.3, 7.48.5, 7.48.6, 7.48.8, 7.48.9, 7.48.10, 7.48.11, 7.48.12, 7.48.13)	53
45.2.7.13 EEE advertisement (Register 7.60).....	53
45.2.7.13.a 25GBASE-R EEE supported (7.60.14).....	53
45.2.7.14 EEE link partner ability (Register 7.61)	54
45.5 Protocol implementation conformance statement (PICS) proforma for Clause 45, Management Data Input/Output (MDIO) interface	55
45.5.3 PICS proforma tables for the Management Data Input Output (MDIO) interface	55
45.5.3.3 PMA/PMD management functions.....	55
69. Introduction to Ethernet operation over electrical backplanes	56
69.1 Overview.....	56
69.1.1 Scope.....	56
69.1.2 Relationship of Backplane Ethernet to the ISO OSI reference model.....	56
69.2 Summary of Backplane Ethernet Sublayers	58
69.2.1 Reconciliation sublayer and media independent interfaces	58
69.2.3 Physical Layer signaling systems	58
69.3 Delay constraints.....	59
69.5 Protocol implementation conformance statement (PICS) proforma.....	59
73. Auto-Negotiation for backplane and copper cable assembly	60
73.2 Relationship to the ISO/IEC Open Systems Interconnection (OSI) reference model	60
73.3 Functional specifications	60
73.6 Link codeword encoding	61

73.6.4 Technology Ability Field	61
73.6.5 FEC capability	62
73.6.5.1 FEC resolution for 25G PHYs	62
73.6.5.2 FEC resolution for 10 Gb/s per lane PHYs	62
73.6.5.3 FEC control variables	63
73.7 Receive function requirements	63
73.7.1 DME page reception	63
73.7.6 Priority Resolution function	63
73.6 Management register requirements	64
73.10 State diagrams and variable definitions	64
73.10.1 State diagram variables	64
74. Forward Error Correction (FEC) sublayer for BASE-R PHYs	66
74.1 Overview	66
74.3 Relationship to other sublayers	67
74.4 Inter-sublayer interfaces	67
74.4.1a Functional block diagram for 25GBASE-R PHYs	68
74.5 FEC service interface	69
74.5.1a 25GBASE-R service primitives	69
74.6 Delay constraints	70
74.7 FEC principle of operation	70
74.7.4 Functions within FEC sublayer	70
74.7.4.1 Reverse gearbox function	70
74.7.4.1.2 Reverse gearbox function for 25GBASE-R, 40GBASE-R, and 100GBASE-R	70
74.7.4.3 FEC transmission bit ordering	71
74.7.4.4 FEC (2112,2080) encoder	72
74.7.4.5 FEC decoder	72
74.7.4.5.1 FEC (2112,2080) decoding	73
74.7.4.6 FEC receive bit ordering	74
74.7.4.8 FEC rapid block synchronization for EEE (optional)	75
74.8 FEC MDIO function mapping	76
74.8.1 FEC capability	76
74.9 BASE-R PHY test-pattern mode	76
74.11 Protocol implementation conformance statement (PICS) proforma for Clause 74, Forward Error Correction (FEC) sublayer for BASE-R PHYs	77
74.11.3 Major capabilities/options	77
74.11.5 FEC Requirements	77
78. Energy-Efficient Ethernet (EEE)	78
78.1 Overview	78
78.1.1 LPI Signaling	78
78.1.3 Reconciliation sublayer operation	78
78.1.3.3 PHY LPI operation	78
78.1.3.3.1 PHY LPI transmit operation	78
78.1.4 PHY types optionally supporting EEE	79
78.2 LPI mode timing parameters description	79
78.5 Communication link access latency	79
78.5.2 25 Gb/s, 40 Gb/s, and 100 Gb/s PHY extension using 25GAUI, XLAUI, or CAUI-n	80

90. Ethernet support for time synchronization protocols.....	81
90.1 Introduction.....	81
105. Introduction to 25 Gb/s networks	82
105.1 Overview.....	82
105.1.1 Scope.....	82
105.1.2 Relationship of 25 Gigabit Ethernet to the ISO OSI reference model.....	82
105.1.3 Nomenclature.....	82
105.2 Physical Layer signaling systems	84
105.3 Summary of 25 Gigabit Ethernet sublayers.....	84
105.3.1 Reconciliation Sublayer (RS) and 25 Gigabit Media Independent Interface (25GMII).....	84
105.3.2 Physical Coding Sublayer (PCS).....	85
105.3.3 Forward Error Correction (FEC) sublayer.....	85
105.3.4 Physical Medium Attachment (PMA) sublayer.....	85
105.3.5 Physical Medium Dependent (PMD) sublayer	85
105.3.6 Auto-Negotiation (AN).....	85
105.3.7 Management interface (MDIO/MDC).....	85
105.3.8 Management.....	85
105.4 Service interface specification method and notation	86
105.4.1 Inter-sublayer service interface.....	86
105.4.2 Instances of the Inter-sublayer service interface.....	86
105.4.3 Semantics of inter-sublayer service interface primitives.....	87
105.4.3.1 IS_UNITDATA.request.....	87
105.4.3.1.1 Semantics of the service primitive.....	87
105.4.3.1.2 When generated	87
105.4.3.1.3 Effect of receipt	87
105.4.3.2 IS_UNITDATA.indication	87
105.4.3.2.1 Semantics of the service primitive.....	87
105.4.3.2.2 When generated	88
105.4.3.2.3 Effect of receipt	88
105.4.3.3 IS_SIGNAL.indication	89
105.4.3.3.1 Semantics of the service primitive.....	89
105.4.3.3.2 When generated	90
105.4.3.3.3 Effect of receipt	90
105.4.3.4 IS_TX_MODE.request	90
105.4.3.4.1 Semantics of the service primitive.....	90
105.4.3.4.2 When generated	90
105.4.3.4.3 Effect of receipt	90
105.4.3.5 IS_RX_MODE.request	90
105.4.3.5.1 Semantics of the service primitive.....	90
105.4.3.5.2 When generated	90
105.4.3.5.3 Effect of receipt	91
105.4.3.6 IS_RX_LPI_ACTIVE.request	91
105.4.3.6.1 Semantics of the service primitive.....	91
105.4.3.6.2 When generated	91
105.4.3.6.3 Effect of receipt	91
105.4.3.7 IS_ENERGY_DETECT.indication	91
105.4.3.7.1 Semantics of the service primitive.....	91
105.4.3.7.2 When generated	91
105.4.3.7.3 Effect of receipt	91
105.4.3.8 IS_RX_TX_MODE.indication	92
105.4.3.8.1 Semantics of the service primitive.....	92

105.4.3.8.2	When generated	92
105.4.3.8.3	Effect of receipt	92
105.5	Delay constraints.....	92
105.6	State diagrams.....	92
105.7	Protocol implementation conformance statement (PICS) proforma.....	93
106.	Reconciliation Sublayer (RS) and Media Independent Interface (25GMII) for 25 Gb/s operation	94
106.1	Overview.....	94
106.1.1	Summary of major concepts	95
106.1.2	Application.....	95
106.1.3	Rate of operation.....	95
106.1.4	Delay constraints.....	95
106.1.5	Allocation of functions	96
106.1.6	25GMII structure	96
106.1.7	Mapping of 25GMII signals to PLS service primitives.....	96
106.1.7.1	Mapping of PLS_DATA.request	96
106.1.7.2	Mapping of PLS_DATA.indication.....	96
106.1.7.3	Mapping of PLS_CARRIER.indication	96
106.1.7.4	Mapping of PLS_SIGNAL.indication	96
106.1.7.5	Mapping of PLS_DATA_VALID.indication	97
106.2	25GMII data stream	97
106.3	25GMII functional specifications	97
106.4	LPI Assertion and Detection.....	97
106.5	Protocol implementation conformance statement (PICS) proforma for Clause 106 Reconciliation Sublayer (RS) and Media Independent Interface (25GMII) for 25 Gb/s operation.....	98
106.5.1	Introduction.....	98
106.5.2	Identification	98
106.5.2.1	Implementation identification	98
106.5.2.2	Protocol summary	98
106.5.2.3	Major capabilities/options	99
106.5.3	PICS proforma Tables for Reconciliation Sublayer and 25 Gigabit Media Independent Interface	99
106.5.3.1	General	99
106.5.3.2	Mapping of PLS service primitives	99
106.5.3.3	25GMII signal functional specifications.....	99
107.	Physical Coding Sublayer (PCS) for 64B/66B, type 25GBASE-R.....	100
107.1	Overview.....	100
107.1.1	Scope.....	100
107.1.2	Relationship of 25GBASE-R to other standards	100
107.1.3	Summary of 25GBASE-R sublayers	100
107.1.3.1	Physical Coding Sublayer (PCS)	100
107.1.4	Inter-sublayer interfaces	100
107.1.4.1	PCS service interface (25GMII)	101
107.1.4.2	Physical Medium Attachment (PMA) service interface	101
107.2	Functions within the PCS	101
107.2.1	Notation conventions	102
107.2.2	Transmission order	102
107.2.3	Test-pattern generator	103
107.3	LPI	103
107.3	Delay constraints.....	104

107.4 Support for Auto-Negotiation.....	104
107.5 Protocol implementation conformance statement (PICS) proforma for Clause 107, Physical Coding Sublayer (PCS) for 64B/66B, type 25GBASE-R	105
107.5.1 Introduction.....	105
107.5.2 Identification.....	105
107.5.2.1 Implementation identification.....	105
107.5.2.2 Protocol summary	105
107.5.3 Major capabilities/options.....	106
107.5.4 25G PCS	106
107.5.4.1 Clause 49 functionality	106
107.5.4.2 Test-pattern generator	106
107.5.4.3 LPI	106
107.5.4.4 Delay Constraints.....	107
108. Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 25GBASE-R PHYs	108
108.1 Overview.....	108
108.1.1 Scope.....	108
108.1.2 Position of RS-FEC in the 25GBASE-R PHY sublayers	108
108.2 FEC service interface.....	108
108.3 PMA compatibility	109
108.4 Delay constraints.....	110
108.5 Functions within the 25GBASE-R RS-FEC sublayer	110
108.5.1 Functional block diagram	110
108.5.2 Transmit function.....	110
108.5.2.1 Block synchronization	110
108.5.2.2 Rate compensation for codeword markers in the transmit direction	110
108.5.2.3 64B/66B to 256B/257B transcoder.....	110
108.5.2.4 Codeword marker insertion	112
108.5.2.5 Reed-Solomon encoder.....	112
108.5.2.6 Codeword serialization	112
108.5.2.7 RS-FEC encoding for rapid codeword lock (EEE deep sleep).....	112
108.5.3 Receive function	114
108.5.3.1 Codeword marker lock.....	114
108.5.3.2 Reed-Solomon decoder.....	114
108.5.3.3 Codeword monitor	115
108.5.3.4 Codeword marker removal	116
108.5.3.5 256B/257B to 64B/66B transcoder.....	116
108.5.3.6 Rate compensation for codeword markers in the receive direction.....	116
108.5.3.7 Rapid codeword lock for EEE deep sleep	116
108.5.3.8 Receive bit ordering.....	117
108.5.4 Detailed functions and state diagrams	117
108.5.4.1 State diagram conventions.....	117
108.5.4.2 State variables	117
108.5.4.3 Functions.....	119
108.5.4.4 Counters	119
108.5.4.5 Timers	120
108.5.4.6 State diagrams.....	121
108.6 25GBASE-R RS-FEC MDIO function mapping.....	122
108.6.1 FEC_bypass_correction_enable.....	123
108.6.2 FEC_bypass_indication_enable.....	123
108.6.3 25G RS-FEC Enable.....	124
108.6.4 FEC_bypass_correction_ability.....	124
108.6.5 FEC_bypass_indication_ability.....	124

108.6.6 FEC_high_ser	124
108.6.7 FEC_corrected_cw_counter.....	124
108.6.8 FEC_uncorrected_cw_counter.....	124
108.6.9 FEC_symbol_error_counter_0.....	125
108.6.10 align_status	125
108.7 Protocol implementation conformance statement (PICS) proforma for Clause 108, Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 25GBASE-R PHYs	126
108.7.1 Introduction.....	126
108.7.2 Identification	126
108.7.2.1 Implementation identification	126
108.7.2.2 Protocol summary	126
108.7.3 Major capabilities/options.....	127
108.7.4 PICS proforma tables for Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 25GBASE-R PHYs.....	127
108.7.4.1 Transmit function.....	127
108.7.4.2 Receive function	128
108.7.4.3 State diagrams.....	129
108.7.4.4 MDIO function mapping	129
109. Physical Medium Attachment (PMA) sublayer, type 25GBASE-R.....	130
109.1 Overview.....	130
109.1.1 Scope.....	130
109.1.2 Position of the PMA in the 25GBASE-R sublayers	130
109.1.3 Summary of functions.....	131
109.1.4 PMA sublayer positioning	132
109.2 PMA service interface	133
109.3 Service interface below PMA	134
109.4 Functions within the PMA	135
109.4.1 Signal drivers	135
109.4.2 PMA local loopback mode	135
109.4.3 PMA remote loopback mode	135
109.4.4 PMA test patterns.....	135
109.4.4.1 Transmit PRBS31 test-pattern generation	136
109.4.4.2 Receive PRBS31 test-pattern generation	136
109.4.4.3 Transmit PRBS31 test-pattern checking	136
109.4.4.4 Receive PRBS31 test-pattern checking	137
109.4.4.5 Transmit PRBS9 test-pattern generation	137
109.4.4.6 Receive PRBS9 test-pattern generation	137
109.4.4.7 Transmit square wave test-pattern generation	137
109.4.5 Energy Efficient Ethernet for 25GAUI.....	138
109.5 Delay constraints.....	138
109.6 PMA MDIO function mapping.....	138
109.7 Protocol implementation conformance statement (PICS) proforma for Clause 109, Physical Medium Attachment (PMA) sublayer, type 25GBASE-R.....	141
109.7.1 Introduction.....	141
109.7.2 Identification	141
109.7.2.1 Implementation identification	141
109.7.2.2 Protocol summary	141
109.7.3 PICS proforma tables for the 25GBASE-R PMA Sublayer	142
109.7.4 Major capabilities/options.....	142
109.7.4.1 PMA functions.....	142
109.7.4.2 PMA characteristics	143

110. Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-CR and 25GBASE-CR-S	144
110.1 Overview	144
110.2 PMD service interface	145
110.3 PCS requirements for Auto-Negotiation (AN) service interface	146
110.4 Delay constraints	146
110.5 PMD MDIO function mapping	147
110.6 FEC modes	147
110.7 PMD functional specifications	148
110.7.1 Link block diagram	148
110.7.2 PMD transmit function	149
110.7.3 PMD receive function	150
110.7.4 Global PMD signal detect function	150
110.7.5 Global PMD transmit disable function	150
110.7.6 Loopback mode	151
110.7.7 PMD fault function	151
110.7.8 PMD transmit fault function	151
110.7.9 PMD receive fault function	151
110.7.10 PMD control function	151
110.8 Electrical characteristics	151
110.8.1 Signal levels	151
110.8.2 Signal paths	152
110.8.3 Transmitter characteristics	152
110.8.4 Receiver characteristics	152
110.8.4.1 Receiver input amplitude tolerance	152
110.8.4.2 Receiver interference tolerance test	152
110.8.4.2.1 Test setup	154
110.8.4.2.2 Test channel	154
110.8.4.2.3 Test channel calibration	154
110.8.4.2.4 Pattern generator and noise injection	156
110.8.4.2.5 Test procedure	156
110.8.4.3 Receiver jitter tolerance	156
110.8.4.4 Signaling rate range	157
110.9 Channel characteristics	157
110.10 Cable assembly characteristics	157
110.10.1 Characteristic impedance and reference impedance	158
110.10.2 Cable assembly insertion loss	158
110.10.3 Cable assembly differential return loss	158
110.10.4 Differential to common-mode return loss	159
110.10.5 Differential to common-mode conversion loss	159
110.10.6 Common-mode to common-mode return loss	159
110.10.7 Cable assembly Channel Operating Margin	159
110.10.7.1 Channel signal and crosstalk path calculations	160
110.10.7.1.1 Channel signal path	161
110.10.7.1.2 Channel crosstalk paths	161
110.10.7.2 Signal and crosstalk paths used in calculation of COM	162
110.10.7.2.1 SFP28 to SFP28	162
110.10.7.2.2 QSFP28 to SFP28	162
110.10.7.2.3 SFP28 to QSFP28	162
110.10.7.2.4 QSFP28 to QSFP28	163
110.11 MDI specification	163
110.11.1 Single-lane MDI connectors	163
110.12 Environmental specifications	164

110.13 Protocol implementation conformance statement (PICS) proforma for Clause 110, Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-CR and 25GBASE-CR-S	165
110.13.1 Introduction	165
110.13.2 Identification	165
110.13.2.1 Implementation identification	165
110.13.2.2 Protocol summary	165
110.13.3 Major capabilities/options	166
110.13.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-CR and 25GBASE-CR-S	167
110.13.4.1 PMD functional specifications	167
110.13.4.2 Management functions	168
110.13.4.3 Transmitter specifications	168
110.13.4.4 Receiver specifications	170
110.13.4.5 Cable assembly specifications	171
110.13.4.6 MDI connector specifications	171
110.13.4.7 Environmental specifications	172
 111. Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-KR and 25GBASE-KR-S	 173
111.1 Overview	173
111.2 PMD service interface	174
111.3 PCS requirements for Auto-Negotiation (AN) service interface	175
111.4 Delay constraints	175
111.5 PMD MDIO function mapping	175
111.6 FEC modes	176
111.7 PMD functional specifications	177
111.7.1 Link block diagram	177
111.7.2 PMD transmit function	177
111.7.3 PMD receive function	178
111.7.4 Global PMD signal detect function	178
111.7.5 Global PMD transmit disable function	178
111.7.6 Loopback mode	178
111.7.7 PMD fault function	179
111.7.8 PMD transmit fault function	179
111.7.9 PMD receive fault function	179
111.7.10 PMD control function	179
111.8 Electrical characteristics	179
111.8.1 MDI	179
111.8.2 Transmitter characteristics	180
111.8.3 Receiver characteristics	180
111.8.3.1 Receiver interference tolerance	180
111.8.3.2 Receiver jitter tolerance	182
111.9 Channel characteristics	183
111.9.1 25GBASE-KR channel	183
111.9.2 25GBASE-KR-S channel	183
111.10 Environmental specifications	184
111.11 Protocol implementation conformance statement (PICS) proforma for Clause 111, Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-KR and 25GBASE-KR-S	185
111.11.1 Introduction	185
111.11.2 Identification	185
111.11.2.1 Implementation identification	185

111.11.2.2 Protocol summary	185
111.11.3 Major capabilities/options.....	186
111.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and baseband medium, type 25GBASE-KR and 25GBASE-KR-S	187
111.11.4.1 Functional specifications	187
111.11.4.2 Transmitter characteristics	188
111.11.4.3 Receiver characteristics	190
111.11.4.4 Channel characteristics	190
111.11.4.5 Environmental specifications.....	191
112. Physical Medium Dependent (PMD) sublayer and medium, type 25GBASE-SR	192
112.1 Overview.....	192
112.1.1 Bit error ratio	193
112.2 Physical Medium Dependent (PMD) service interface	193
112.3 Delay constraints.....	194
112.4 PMD MDIO function mapping.....	194
112.5 PMD functional specifications.....	195
112.5.1 PMD block diagram.....	195
112.5.2 PMD transmit function	196
112.5.3 PMD receive function.....	196
112.5.4 PMD global signal detect function	196
112.5.5 PMD reset function.....	197
112.5.6 PMD global transmit disable function (optional)	197
112.5.7 PMD fault function (optional)	197
112.5.8 PMD transmit fault function (optional)	197
112.5.9 PMD receive fault function (optional).....	197
112.6 PMD to MDI optical specifications for 25GBASE-SR	197
112.6.1 25GBASE-SR transmitter optical specifications	198
112.6.2 25GBASE-SR receive optical specifications	198
112.6.3 25GBASE-SR illustrative link power budget.....	198
112.7 Definition of optical parameters and measurement methods.....	198
112.7.1 Test patterns for optical parameters.....	198
112.7.2 Center wavelength and spectral width	199
112.7.3 Average optical power	199
112.7.4 Optical Modulation Amplitude (OMA).....	199
112.7.5 Transmitter and dispersion eye closure (TDEC)	199
112.7.6 Extinction ratio	199
112.7.7 Transmitter optical waveform (transmit eye)	199
112.7.8 Stressed receiver sensitivity.....	199
112.8 Safety, installation, environment, and labeling.....	199
112.8.1 General safety	199
112.8.2 Laser safety	200
112.8.3 Installation	200
112.8.4 Environment.....	200
112.8.5 Electromagnetic emission	200
112.8.6 Temperature, humidity, and handling.....	200
112.8.7 PMD labeling requirements	200
112.9 Fiber optic cabling model	201
112.10 Characteristics of the fiber optic cabling (channel)	201
112.10.1 Optical fiber cable.....	201
112.10.2 Optical fiber connection.....	201
112.10.2.1 Connection insertion loss.....	202
112.10.2.2 Maximum discrete reflectance.....	202

112.10.3 Medium Dependent Interface (MDI).....	202
112.11 Protocol implementation conformance statement (PICS) proforma for Clause 112, Physical Medium Dependent (PMD) sublayer and medium, type 25GBASE-SR	203
112.11.1 Introduction.....	203
112.11.2 Identification	203
112.11.2.1 Implementation identification.....	203
112.11.2.2 Protocol summary	203
112.11.3 Major capabilities/options.....	204
112.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 25GBASE-SR	204
112.11.4.1 PMD functional specifications.....	204
112.11.4.2 Management functions.....	205
112.11.4.3 PMD to MDI optical specifications for 25GBASE-SR	205
112.11.4.4 Optical measurement methods.....	206
112.11.4.5 Environmental specifications.....	206
112.11.4.6 Characteristics of the fiber optic cabling and MDI.....	206
 Annex 4A (normative) Simplified full duplex media access control	207
4A.4 Specific implementations.....	207
4A.4.2 MAC parameters.....	207
 Annex 31B (normative) MAC Control PAUSE operation	208
31B.3 Detailed specification of PAUSE operation.....	208
31B.3.7 Timing considerations for PAUSE operation	208
31B.4 Protocol implementation conformance statement (PICS) proforma for MAC Control PAUSE operation.....	209
31B.4.3 Major capabilities/options	209
31B.4.6 PAUSE command MAC timing considerations	209
 Annex 93A (normative) Specification methods for electrical channels	210
93A.1 Channel Operating Margin	210
93A.1.4 Filters	211
93A.2 Test channel calibration using COM	211
 Annex 109A (normative) Chip-to-chip 25 Gigabit Attachment Unit Interface (25GAUI C2C).....	212
109A.1 Overview.....	212
109A.2 25GAUI C2C compliance point definition	213
109A.3 25GAUI C2C electrical characteristics.....	213
109A.3.1 25GAUI C2C transmitter characteristics	213
109A.3.2 25GAUI C2C receiver characteristics	213
109A.3.3 Optional EEE operation	213
109A.4 25GAUI C2C channel characteristics.....	213
109A.5 Protocol implementation conformance statement (PICS) proforma for Annex 109A, Chip-to-chip 25 Gigabit Attachment Unit Interface (25GAUI C2C).....	214
109A.5.1 Introduction	214
109A.5.2 Identification	214
109A.5.2.1 Implementation identification.....	214
109A.5.2.2 Protocol summary	214
109A.5.3 Major capabilities/options.....	215

109A.5.4 PICS proforma tables for chip-to-chip 25 Gigabit Attachment Unit Interface (25GAUI C2C)	215
109A.5.4.1 Transmitter	215
109A.5.4.2 Receiver	216
109A.5.4.3 Channel	216
Annex 109B (normative) Chip-to-module 25 Gigabit Attachment Unit Interface (25GAUI C2M)	217
109B.1 Overview	217
109B.1.1 Bit error ratio	218
109B.2 25GAUI C2M compliance point definitions	218
109B.3 25GAUI C2M electrical characteristics	218
109B.3.1 25GAUI C2M host output characteristics	218
109B.3.2 25GAUI C2M module output characteristics	218
109B.3.2.1 25GAUI C2M module output eye opening	219
109B.3.2.1.1 Eye opening using measurement method A	219
109B.3.2.1.2 Eye opening using measurement method B	219
109B.3.3 25GAUI C2M host input characteristics	219
109B.3.4 25GAUI C2M module input characteristics	219
109B.3.4.1 Module stressed input test using measurement method A	220
109B.3.4.2 Module stressed input test using measurement method B	220
109B.4 25GAUI C2M measurement methodology	220
109B.4.1 Eye width, eye height, and eye closure measurement method B	220
109B.5 Protocol implementation conformance statement (PICS) proforma for Annex 109B, Chip-to-module 25 Gigabit Attachment Unit Interface (25GAUI C2M)	222
109B.5.1 Introduction	222
109B.5.2 Identification	222
109B.5.2.1 Implementation identification	222
109B.5.2.2 Protocol summary	222
109B.5.3 Major capabilities/options	223
109B.5.4 PICS proforma tables for chip-to-module 25 Gigabit Attachment Unit Interface (25GAUI C2M)	223
109B.5.4.1 Host output	223
109B.5.4.2 Module output	224
109B.5.4.3 Host input	224
109B.5.4.4 Module input	225
Annex 109C (informative) 25GBASE-R PMA sublayer partitioning examples	226
Annex 110A (informative) TP0 and TP5 test point parameters and channel characteristics for 25GBASE-CR and 25GBASE-CR-S	230
110A.1 Overview	230
110A.2 Transmitter characteristics at TP0	230
110A.3 Receiver characteristics at TP5	230
110A.4 Transmitter and receiver differential printed circuit board trace loss	230
110A.5 Channel insertion loss	230
110A.6 Channel return loss	232
110A.7 Channel Operating Margin (COM)	232
Annex 110B (normative) Test fixtures for 25GBASE-CR, 25GBASE-CR-S, and 25GAUI C2M	233
110B.1 Test fixtures	233
110B.1.1 SFP28 TP2 or TP3 test fixture	233

110B.1.2 SFP28 Cable assembly test fixture.....	233
110B.1.3 SFP28 Mated test fixtures	234
110B.1.3.1 Mated test fixtures differential insertion loss.....	234
110B.1.3.2 Mated test fixtures differential return loss	234
110B.1.3.3 Mated test fixtures common-mode conversion insertion loss.....	234
110B.1.3.4 Mated test fixtures common-mode return loss.....	234
110B.1.3.5 Mated test fixtures common-mode to differential mode return loss.....	234
110B.1.3.7 Mated test fixtures integrated near-end crosstalk noise	234
110B.2 Protocol implementation conformance statement (PICS) proforma for Annex 110B, Test fixtures for 25GBASE-CR, 25GBASE-CR-S, and 25GAUI C2M.....	236
110B.2.1 Introduction	236
110B.2.2 Identification	236
110B.2.2.1 Implementation identification	236
110B.2.2.2 Protocol summary	236
110B.2.3 Major capabilities/options	237
110B.2.4 PICS proforma tables for test fixtures for 25GBASE-CR, 25GBASE-CR-S, and 25GAUI C2M	237
 Annex 110C (informative) Host and cable assembly form factors for 25GBASE-CR and 25GBASE-CR-S PHYs.....	 238
110C.1 Overview	238
110C.2 Host form factors.....	239
110C.2.1 SFP28 host form factor	239
110C.2.2 QSFP28 host form factor	239
110C.3 Cable assembly form factors.....	240
110C.3.1 SFP28 to SFP28 cable assembly form factor.....	240
110C.3.2 QSFP28 to QSFP28 cable assembly form factor	241
110C.3.3 QSFP28 to 4×SFP28 cable assembly form factor.....	242

IEEE Standard for Ethernet

Amendment 2: Media Access Control Parameters, Physical Layers, and Management Parameters for 25 Gb/s Operation

IMPORTANT NOTICE: *IEEE Standards documents are not intended to ensure safety, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.*

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

(This amendment is based on IEEE Std 802.3™-2015 as amended by IEEE 802.3bw™-2015.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in **bold italic**. Four editing instructions are used: change, delete, insert, and replace. **Change** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). **Delete** removes existing material. **Insert** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. **Replace** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.¹

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.

¹Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.