

IEEE Standard for Ethernet

Amendment 13: Physical Layers and Management Parameters for 100 Gb/s Operation over DWDM Systems

IEEE Computer Society

Developed by the
LAN/MAN Standards Committee

IEEE Std 802.3ct™-2021

(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018,
IEEE Std 802.3bt™-2018,
IEEE Std 802.3bd™-2018,
IEEE Std 802.3bf™-2019,
IEEE Std 802.3cg™-2019,
IEEE Std 802.3cq™-2020,
IEEE Std 802.3cm™-2020,
IEEE Std 802.3ch™-2020,
IEEE Std 802.3ca™-2020,
IEEE Std 802.3cr™-2021,
IEEE Std 802.3cu™-2021,
and IEEE Std 802.3cv™-2021)

IEEE Std 802.3ct™-2021
(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018,
IEEE Std 802.3bt™-2018,
IEEE Std 802.3cd™-2018,
IEEE Std 802.3cn™-2019,
IEEE Std 802.3cg™-2019,
IEEE Std 802.3cq™-2020,
IEEE Std 802.3cm™-2020,
IEEE Std 802.3ch™-2020,
IEEE Std 802.3ca™-2020,
IEEE Std 802.3cr™-2021,
IEEE Std 802.3cu™-2021,
and IEEE Std 802.3cv™-2021)

IEEE Standard for Ethernet

Amendment 13: Physical Layers and Management Parameters for 100 Gb/s Operation over DWDM Systems

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 16 June 2021
IEEE SA Standards Board

Abstract: This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 152 through Clause 154 and Annex 154A. This amendment adds 100 Gb/s Physical Layer specifications and management parameters for operation over DWDM systems using a combination of phase and amplitude modulation with coherent detection for reaches of at least 80 km.

Keywords: 100 Gb/s Ethernet, 100GBASE-ZR, DP-DQPSK, dense wavelength division multiplexing (DWDM), DWDM black link, Energy-Efficient Ethernet (EEE), Ethernet, forward error correction (FEC), IEEE 802.3™, IEEE 802.3ct™, Physical Medium Dependent (PMD) sublayer, single-mode fiber (SMF)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2021 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 9 July 2021. Printed in the United States of America.

IEEE and 02 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-7694-2 STD24792
Print: ISBN 978-1-5044-7695-9 STDPD24792

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA, and participate without compensation in IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or completeness of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to results and workmanlike effort. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#). An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These

include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational or classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#). For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#). Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).

IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3ct Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*

Adam Healey, *IEEE 802.3 Working Group Vice-Chair*

Jon Lewis, *IEEE 802.3 Working Group Secretary*

Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*

Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

John D'Ambrosia, *IEEE P802.3ct 100 Gb/s over DWDM systems Task Force Chair*

Tom Issenhuth, *IEEE P802.3ct 100 Gb/s over DWDM systems Task Force Editor-in-Chief,*

Editor for supporting clauses, Phase II

Pete Anslow, *IEEE P802.3ct 100 Gb/s over DWDM systems Task Force*

Editor for supporting clauses, Phase I

Steve Trowbridge, *IEEE P802.3ct 100 Gb/s over DWDM systems Task Force*

Editor for Clause 152, Clause 153, Annex 83C and Annex 135A

Peter Stassar, *IEEE P802.3ct 100 Gb/s over DWDM systems Task Force*

Editor for Clause 154

David Abramson	Takashi Fukuoka	Daniel Koppermueller
Michikazu Aono	Ali Ghiasi	Glen Kramer
Nobuyasu Araki	Joel Goergen	Taketo Kumada
Tim Baggett	Steven Gorshe	Hans Lackner
Thananya Baldwin	Hideki Goto	Frank Lambrecht
Steven Baumgartner	Steffen Graber	Mark Laubach
Denis Beaudoin	Olaf Grau	Greg Le Cheminant
Gitesh Bhagwat	Robert Grow	David Lewis
Rich Boyer	Martin Gubow	Mike-Peng Li
David Brandt	Mark Gustlin	Alex Lin
Ralf-Peter Braun	Marek Hajduczenia	Robert Lingle
Theodore Brillhart	Howard Hock	Hai-Feng Liu
Paul Brooks	David Hsu	William Lo
Matthew Brown	Brian Hildebrand	Yuanqiu Luo
Leon Bruckman	Gerard Hormmeyer	Kent Lusted
Jairo Bustos Heredia	Hiromichi Hyakutake	Jeffery Maki
Adrian Butter	Jonathan Ingham	David Malicoat
John Calvin	Kazuhiko Ishibe	Eric Maniloff
Clark Carty	Hideki Isono	Flavio Marques
David Chalupsky	Hiroaki Ito	Arthur Marris
Jacky Chang	Kenneth Jackson	Takeo Masuda
Xin Chang	Andrew Jimenez	Mick McCarthy
Chan Chen	John Johnson	Brett McClellan
Golam Choudhury	Chad Jones	Larry McMillan
Keng Hua Chuang	Peter Jones	Greg McSorley
Piers J. C. Davies	Lokesh Kabra	Richard Mellitz
Fred Edwards	Haysam Kadry	Shimon Muller
Gerrit de Boesten	Manabu Kagami	Sean Murphy
Claudio DeSanti	Upen Kareti	James Nadolny
Curtis Donahue	Athanasios Kasapi	Edward Nakamoto
Liang Du	Yong Kim	Raymond Nering
Kathryn Dube	Mark Kimber	Paul Neveux
Mike Dudek	Michael Klempa	Gary Nicholl
Frank Effenberger	Curtis Knittle	Shawn Nicholl
David Estes	Elizabeth Kochuparambil	Kevin Noll
John Ewen	Sam Kocsis	Mark Nowell
Vincent Ferretti	Wojciech Koczwar	David Ofelt
Brian Franchuk	Paul Kolesar	Ryo Okabe
Matthias Fritsche	Taiji Kondo	

Tom Palkert
 Carlos Pardo
 Earl Parsons
 Gerald Pepper
 Rubén Perez De Aranda Alonso
 David Piehler
 Fabio Pittala
 Christopher Pohl
 William Powell
 Rick Rabinovich
 Parthasarathy Raju
 Adee Ran
 Alon Regev
 Duane Remein
 Victor Renteria
 Thomas Rettig
 Toshiaki Sakai
 Hamid Salehi
 Sam Sambasivan
 Edward Sayre
 Matthew Schmitt
 Hossein Sedarat
 Masood Shariff

Masato Shiino
 Ramin Shirani
 Kapil Shrikhande
 Jeff Slavick
 Scott Sommers
 Massimo Sorbara
 Edward Sprague
 Heath Stewart
 Junqing Sun
 Steve Swanson
 Tomoo Takahara
 Satoshi Takahashi
 Tadashi Takahashi
 Kazuya Takayama
 Michael Takefman
 Masaru Terada
 Geoffrey Thompson
 Pirooz Tooyserkani
 Nathan Tracy
 Viet Tran
 David Tremblay
 Mike Tu
 Ed Ulrichs

Alexander Umnov
 Prasad Venugopal
 Edward Walter
 Roy Wang
 Xuehuan Wang
 James Weaver
 Dong Wei
 Brian Welch
 Matthias Wendt
 Natalie Wienckowski
 Dance Wu
 Peter Wu
 Dayin Xu
 Yu Xu
 James Young
 Lennart Yseboodt
 Conrad Zerna
 Xingxin Zhang
 Chunhui Zhang
 Yan Zhuang
 Martin Zielinski
 George Zimmerman
 Pavel Zolovny

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Robert Aiello
 Thomas Alexander
 Greg Armstrong
 Rich Boyer
 Ralf-Peter Braun
 Theodore Brillhart
 Matthew Brown
 Jairo Bustos Heredia
 William Byrd
 Steven B. Carlson
 Juan Carreon
 Clark Carty
 Pin Chang
 Chan Chen
 Charles Cook
 John D'Ambrosia
 Piers J. G. Dawe
 John Deandrea
 Christopher Diminico
 Frank Effendy
 Avram Friedman
 Matthias Fritzsche
 Limin Gong
 Ali Ghiasi
 Zhenqiang Gong
 Marcin Hajduczenia
 Xiang He
 Adam Healey
 Marco Hernandez
 David Hess
 Shui Heung

Werner Hoelzl
 Thomas Huber
 Gergely Huszak
 Yasuhiro Hyakutake
 Jonathan Ingham
 Osamu Isida
 Hideki Iwasaki
 Tomasz Juchacz
 Sun Kwon Jeong
 Mark Jewell
 Peter Jones
 Lokesh Kabra
 Stuart Kerry
 Yong Kim
 Mark Laubach
 Pi-Cheng Law
 David Lewis
 Jon Lewis
 Karen Liu
 Valerie Maguire
 Jeffery Maki
 Richard Mellitz
 Nick S. A. Nikjoo
 Mark Nowell
 Satoshi Obara
 Tom Palkert
 Carlos Pardo
 Bansi Patel
 Arumugam Paventhan
 David Piehler
 Patty Polpattana

Adee Ran
 R. K. Rannow
 Lakshman Raut
 Robert Robinson
 Benjamin Rolfe
 Toshiaki Sakai
 Olindo Savi
 Matthew Schmitt
 Qingya She
 Scott Sommers
 Dorothy Stanley
 Peter Stassar
 Walter Struppler
 Mitsutoshi Sugawara
 Kohichi Tamura
 James Theodoras
 Nathan Tracy
 David Tremblay
 Stephen Trowbridge
 Mark-Rene Uchida
 Dmitri Varsanofiev
 Ruoxu Wang
 Xinyuan Wang
 Lisa Ward
 Keith Waters
 James Weaver
 James Young
 Yu Yuan
 Oren Yuen
 Bo Zhang

When the IEEE SA Standards Board approved this standard on 16 June 2021, it had the following membership:

Gary Hoffman, *Chair*
Jon Walter Rosdahl, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Edward A. Addy
Doug Edwards
Ramy Ahmed Fathy
J. Travis Griffith
Thomas Koshy
Joseph L. Koepfinger*
David J. Law

Howard Li
Daozhuang Lin
Kevin Lu
Daleep C. Mohla
Chenhui Niu
Damir Novosel
Annette Reilly
Dorothy Stanley

Mehmet Ulema
Lei Wang
F. Keith Waters
Karl Weber
Sha Wei
Howard Wolfman
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3ct-2021, IEEE Standard for Ethernet—Amendment 13: Physical Layers and Management Parameters for 100 Gb/s Operation over DWDM Systems.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel, and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of IEEE Std 802.3ct-2021 publication, IEEE Std 802.3 was composed of the following documents:

IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines

services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

IEEE Std 802.3cg™-2019

Amendment 5—This amendment includes changes to IEEE Std 802.3-2018 and its amendments and adds Clause 146 through Clause 148 and Annex 146A and Annex 146B. This amendment adds 10 Mb/s Physical Layer specifications and management parameters for operation on a single balanced pair of conductors.

IEEE Std 802.3cq™-2020

Amendment 6—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 33 and related portions of the standard.

IEEE Std 802.3cm™-2020

Amendment 7—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 150. This amendment adds Physical Layer (PHY) specifications and management parameters for 400 Gb/s operation on four pairs (400GBASE-SR4.2) and eight pairs (400GBASE-SR8) of multimode fiber, over reaches of at least 100 m.

IEEE Std 802.3ch™-2020

Amendment 8—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 149, Annex 149A, Annex 149B, and Annex 149C. This amendment adds physical layer specifications and management parameters for operation at 2.5 Gb/s, 5 Gb/s, and 10 Gb/s over a single balanced pair of conductors.

IEEE Std 802.3ca™-2020

Amendment 9—This amendment to IEEE Std 802.3-2018 extends the operation of Ethernet passive optical networks (EPONs) to multiple channels of 25 Gb/s providing both symmetric and asymmetric operation for the following data rates (downstream/upstream): 25/10 Gb/s, 25/25 Gb/s, 50/10 Gb/s, 50/25 Gb/s, and 50/50 Gb/s. This amendment specifies the 25 Gb/s EPON Multi-Channel Reconciliation Sublayer (MCRS), Nx25G-EPON Physical Coding Sublayers (PCSs), Physical Media Attachment (PMA) sublayers, and Physical Medium Dependent (PMD) sublayers that support both symmetric and asymmetric data rates while maintaining backward compatibility with already deployed 10 Gb/s EPON equipment. The EPON operation is defined for distances of at least 20 km, and for a split ratio of at least 1:32.

IEEE Std 802.3cr™-2021

Amendment 10—This amendment includes changes to IEEE Std 802.3-2018 and adds Annex J. This amendment replaces references to the IEC 60950 series of standards (including IEC 60950-1 “Information technology equipment—Safety—Part 1: General requirements”) with appropriate references to the IEC 62368 “Audio/video, information and communication technology equipment” series and makes appropriate changes to the standard corresponding to the new references.

IEEE Std 802.3cu™-2021

Amendment 11—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 151. This amendment adds Physical Layer (PHY) specifications and management parameters for 100 Gb/s and 400 Gb/s operation over single-mode fiber, based on 100 Gb/s per wavelength optical signaling.

IEEE Std 802.3cv™-2021

Amendment 12—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 145, Power over Ethernet, and related portions of the standard.

IEEE Std 802.3ct™-2021

Amendment 13—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 152 through Clause 154 and Annex 154A. This amendment adds 100 Gb/s Physical Layer specifications and management parameters for operation over DWDM systems with reaches of at least 80 km.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Contents

1. Introduction.....	21
1.3 Normative references	21
1.4 Definitions	21
1.5 Abbreviations.....	22
30. Management.....	23
30.2 Managed Objects	23
30.2.5 Capabilities.....	23
30.5 Layer management for medium attachment units (MAUs).....	23
30.5.1 MAU managed object class.....	23
30.5.1.1 MAU attributes	23
30.5.1.1.2 aMAUType	23
30.5.1.1.15 aFECAbility	24
30.5.1.1.16 aFECmode.....	24
30.5.1.1.17 aFECCorrectedBlocks.....	24
30.5.1.1.18 aFECUncorrectableBlocks.....	25
30.5.1.1.26 aRSFECBIPErrrorCount	25
30.5.1.1.27 aRSFECLaneMapping	26
30.5.1.1.27a aSCFECLaneMapping	26
30.5.1.1.28 aRSFECBypassAbility.....	26
30.5.1.1.29 aRSFECBypassIndicationAbility.....	27
30.5.1.1.32 aPCSFECBypassIndicationAbility	27
45. Management Data Input/Output (MDIO) Interface.....	28
45.2 MDIO Interface Registers.....	28
45.2.1 PMA/PMD registers.....	28
45.2.1.6 PMA/PMD control 2 register (Register 1.7)	29
45.2.1.7 PMA/PMD status 2 register (Register 1.8).....	29
45.2.1.7.4 Transmit fault (1.8.11)	29
45.2.1.7.5 Receive fault (1.8.10).....	30
45.2.1.8 PMD transmit disable register (Register 1.9)	30
45.2.1.21b 40G/100G PMA/PMD extended ability 2 register (Register 1.26)	30
45.2.1.21b.3aa 100GBASE-ZR ability (1.26.6)	31
45.2.1.133a Tx optical channel control register (Register 1.800)	31
45.2.1.133a.1 Tx optical channel index (1.800.5:0)	31
45.2.1.133b Tx optical channel ability 1 register (Register 1.801)	31
45.2.1.133b.1 Tx index ability 0 through 15 (1.801.0 through 1.801.15).....	32
45.2.1.133c Tx optical channel ability 2 register (Register 1.802)	32
45.2.1.133c.1 Tx index ability 16 through 31 (1.802.0 through 1.802.15).....	33
45.2.1.133d Tx optical channel ability 3 register (Register 1.803)	34
45.2.1.133d.1 Tx index ability 32 through 47 (1.803.0 through 1.803.15).....	34
45.2.1.133e Rx optical channel control register (Register 1.820).....	35
45.2.1.133e.1 Tx Rx different optical channel ability (1.820.15).....	35
45.2.1.133e.2 Rx optical channel index (1.820.5:0)	35
45.2.1.133f Rx optical channel ability 1 register (Register 1.821).....	36
45.2.1.133f.1 Rx index ability 0 through 15 (1.821.0 through 1.821.15)	36
45.2.1.133g Rx optical channel ability 2 register (Register 1.822).....	37
45.2.1.133g.1 Rx index ability 16 through 31 (1.822.0 through 1.822.15)	38

45.2.1.133h	Rx optical channel ability 3 register (Register 1.823)	38
45.2.1.133h.1	Rx index ability 32 through 47 (1.823.0 through 1.823.15)	39
45.2.1.186aa	IFEC control register (Register 1.2200)	39
45.2.1.186aa.1	IFEC bypass indication enable (1.2200.1)	39
45.2.1.186aa.2	IFEC bypass correction enable (1.2200.0)	39
45.2.1.186ab	IFEC status register (Register 1.2201)	39
45.2.1.186ab.1	PCS align status (1.2201.15)	40
45.2.1.186ab.2	IFEC align status (1.2201.14)	40
45.2.1.186ab.3	IFEC AM lock 3 (1.2201.11)	40
45.2.1.186ab.4	IFEC AM lock 2 (1.2201.10)	41
45.2.1.186ab.5	IFEC AM lock 1 (1.2201.9)	41
45.2.1.186ab.6	IFEC AM lock 0 (1.2201.8)	41
45.2.1.186ab.7	IFEC high SER (1.2201.2)	41
45.2.1.186ab.8	IFEC bypass indication ability (1.2201.1)	41
45.2.1.186ab.9	IFEC bypass correction ability (1.2201.0)	41
45.2.1.186ac	IFEC corrected codewords counter (Register 1.2202, 1.2203)	41
45.2.1.186ad	IFEC uncorrected codewords counter (Register 1.2204, 1.2205)	42
45.2.1.186ae	IFEC lane mapping register (Register 1.2206)	42
45.2.1.186af	IFEC symbol error counter, lane 0 (Register 1.2210, 1.2211)	43
45.2.1.186ag	IFEC symbol error counter, lane 1 through 3 (Register 1.2212, 1.2213, 1.2214, 1.2215, 1.2216, 1.2217)	43
45.2.1.186ah	SC-FEC alignment status 1 register (Register 1.2246)	43
45.2.1.186ah.1	SC-FEC align status (1.2246.12)	43
45.2.1.186ah.2	SC-FEC FAS lock 7 (1.2246.7)	44
45.2.1.186ah.3	SC-FEC FAS lock 6 (1.2246.6)	44
45.2.1.186ah.4	SC-FEC FAS lock 5 (1.2246.5)	44
45.2.1.186ah.5	SC-FEC FAS lock 4 (1.2246.4)	45
45.2.1.186ah.6	SC-FEC FAS lock 3 (1.2246.3)	45
45.2.1.186ah.7	SC-FEC FAS lock 2 (1.2246.2)	45
45.2.1.186ah.8	SC-FEC FAS lock 1 (1.2246.1)	45
45.2.1.186ah.9	SC-FEC FAS lock 0 (1.2246.0)	45
45.2.1.186ai	SC-FEC alignment status 2 register (Register 1.2247)	45
45.2.1.186ai.1	SC-FEC FAS lock 19 (1.2247.11)	46
45.2.1.186ai.2	SC-FEC FAS lock 18 (1.2247.10)	46
45.2.1.186ai.3	SC-FEC FAS lock 17 (1.2247.9)	46
45.2.1.186ai.4	SC-FEC FAS lock 16 (1.2247.8)	47
45.2.1.186ai.5	SC-FEC FAS lock 15 (1.2247.7)	47
45.2.1.186ai.6	SC-FEC FAS lock 14 (1.2247.6)	47
45.2.1.186ai.7	SC-FEC FAS lock 13 (1.2247.5)	47
45.2.1.186ai.8	SC-FEC FAS lock 12 (1.2247.4)	47
45.2.1.186ai.9	SC-FEC FAS lock 11 (1.2247.3)	47
45.2.1.186ai.10	SC-FEC FAS lock 10 (1.2247.2)	47
45.2.1.186ai.11	SC-FEC FAS lock 9 (1.2247.1)	47
45.2.1.186ai.12	SC-FEC FAS lock 8 (1.2247.0)	48
45.2.1.186aj	SC-FEC lane mapping, lane 0 register (Register 1.2250)	48
45.2.1.186ak	SC-FEC lane mapping, lane 1 through 19 registers (Registers 1.2251 through 1.2269)	48
45.2.1.186al	SC-FEC corrected codewords counter (Register 1.2276, 1.2277)	48
45.2.1.186am	SC-FEC uncorrected codewords counter (Register 1.2278, 1.2279)	49
45.2.1.186an	SC-FEC total bits register (Register 1.2280, 1.2281, 1.2282, 1.2283)	49
45.2.1.186ao	SC-FEC corrected bits register (Register 1.2284, 1.2285, 1.2286, 1.2287)	49

78. Energy-Efficient Ethernet (EEE)	51
-------------------------------------	----

78.1	Overview.....	51
78.1.4	PHY types optionally supporting EEE.....	51
80.	Introduction to 40 Gb/s and 100 Gb/s networks.....	52
80.1	Overview.....	52
80.1.3	Relationship of 40 Gigabit and 100 Gigabit Ethernet to the ISO OSI reference model.....	52
80.1.4	Nomenclature	52
80.1.5	Physical Layer signaling systems.....	53
80.2	Summary of 40 Gigabit and 100 Gigabit Ethernet sublayers	53
80.2.2	Physical Coding Sublayer (PCS).....	53
80.2.3	Forward Error Correction (FEC) sublayers.....	54
80.2.4	Physical Medium Attachment (PMA) sublayer	54
80.2.5	Physical Medium Dependent (PMD) sublayer.....	54
80.3	Service interface specification method and notation	54
80.3.2	Instances of the Inter-sublayer service interface	54
80.4	Delay constraints.....	56
80.5	Skew constraints	56
80.7	Protocol implementation conformance statement (PICS) proforma.....	57
82.	Physical Coding Sublayer (PCS) for 64B/66B, type 40GBASE-R and 100GBASE-R.....	58
82.2	Physical Coding Sublayer (PCS).....	58
82.2.3	64B/66B transmission code.....	58
82.2.3.3	Block structure.....	58
152.	Inverse RS-FEC sublayer.....	59
152.1	Overview.....	59
152.1.1	Scope	59
152.1.2	Position of Inverse RS-FEC in the 100GBASE-R sublayers.....	59
152.2	Inverse RS-FEC service interface.....	59
152.3	PMA or FEC sublayer compatibility	59
152.4	Delay constraints.....	59
152.5	Functions within the Inverse RS-FEC sublayer.....	60
152.5.1	Functional block diagram.....	60
152.5.2	Transmit function	61
152.5.2.1	Alignment lock and deskew	61
152.5.2.2	Lane reorder.....	62
152.5.2.3	Reed-Solomon decoder.....	62
152.5.2.4	Alignment marker removal.....	62
152.5.2.5	256B/257B to 64B/66B transcoder.....	62
152.5.2.6	Block distribution	63
152.5.2.7	Alignment marker mapping and insertion	63
152.5.2.8	Transmit bit ordering	64
152.5.3	Receive function.....	66
152.5.3.1	Lane block synchronization.....	66
152.5.3.2	Alignment lock and deskew	66
152.5.3.3	Lane reorder.....	66
152.5.3.4	Alignment marker removal.....	66
152.5.3.5	64B/66B to 256B/257B transcoder.....	66
152.5.3.6	Alignment marker mapping and insertion	67
152.5.3.7	Reed-Solomon encoder.....	69

152.5.3.8	Symbol distribution	69
152.5.3.9	Receive bit ordering.....	69
152.5.4	Detailed functions and state diagrams.....	71
152.5.4.1	State diagram conventions.....	71
152.5.4.2	State variables.....	71
152.5.4.2.1	Variables	71
152.5.4.2.2	Functions.....	72
152.5.4.2.3	Counters	73
152.5.4.3	State diagrams.....	73
152.6	Inverse RS-FEC MDIO function mapping.....	73
152.6.1	IFEC_bypass_correction_enable.....	73
152.6.2	IFEC_bypass_indication_enable.....	74
152.6.3	IFEC_bypass_correction_ability.....	74
152.6.4	IFEC_bypass_indication_ability.....	75
152.6.5	hi_ser.....	75
152.6.6	amps_lock<x>.....	75
152.6.7	IFEC_align_status.....	75
152.6.8	IFEC_corrected_cw_counter.....	75
152.6.9	IFEC_uncorrected_cw_counter.....	75
152.6.10	IFEC_lane_mapping<x>.....	75
152.6.11	IFEC_symbol_error_counter_i.....	76
152.6.12	align_status.....	76
152.6.13	BIP_error_counter_i.....	76
152.6.14	lane_mapping<x>.....	76
152.6.15	block_lock<x>.....	76
152.6.16	am_lock<x>.....	76
152.7	Protocol implementation conformance statement (PICS) proforma for Clause 152, Inverse RS-FEC sublayer.....	77
152.7.1	Introduction	77
152.7.2	Identification	77
152.7.2.1	Implementation identification.....	77
152.7.2.2	Protocol summary	77
152.7.3	Major capabilities/options	78
152.7.4	PICS proforma tables for Inverse RS-FEC sublayer.....	78
152.7.4.1	Transmit function	78
152.7.4.2	Receive Function	79
152.7.4.3	State diagrams.....	80
153.	SC-FEC and 100GBASE-ZR Physical Medium Attachment (PMA) sublayer for 100GBASE-ZR PHys.....	81
153.1	Overview.....	81
153.1.1	Scope.....	81
153.1.2	Position of SC-FEC and 100GBASE-ZR PMA in the 100GBASE-R sublayers.....	81
153.2	SC-FEC sublayer	81
153.2.1	FEC service interface	81
153.2.2	Delay constraints	82
153.2.3	Functions within the SC-FEC sublayer.....	83
153.2.3.1	Functional block diagram	83
153.2.3.2	Transmit function	83
153.2.3.2.1	Lane block synchronization	83
153.2.3.2.2	Alignment lock and deskew	84
153.2.3.2.3	Lane reorder	84
153.2.3.2.4	GMP mapper.....	84

153.2.3.2.5	SC-FEC encoder	87
153.2.3.2.6	Scrambler	87
153.2.3.2.7	Lane distribution	88
153.2.3.3	Receive function	89
153.2.3.3.1	Lane lock and deskew	89
153.2.3.3.2	Lane reorder	89
153.2.3.3.3	De-scrambler	89
153.2.3.3.4	SC-FEC decoder	89
153.2.3.3.5	GMP demapper	89
153.2.3.3.6	Block alignment	90
153.2.3.3.7	Block distribution.....	90
153.2.4	Detailed functions and state diagrams.....	90
153.2.4.1	State variables.....	90
153.2.4.1.1	Variables	90
153.2.4.2	Functions	91
153.2.4.3	Counters.....	92
153.2.4.4	State diagrams.....	92
153.2.5	SC-FEC MDIO function mapping	94
153.2.5.1	FEC_corrected_cw_counter	94
153.2.5.2	FEC_uncorrected_cw_counter	94
153.2.5.3	FEC_total_bits_counter.....	94
153.2.5.4	FEC_corrected_bits_counter	95
153.3	100GBASE-ZR PMA sublayer.....	95
153.3.1	100GBASE-ZR PMA service interface	95
153.3.2	Functions within the 100GBASE-ZR PMA sublayer	96
153.3.2.1	Functional block diagram	96
153.3.2.2	Transmit function	96
153.3.2.2.1	Lane interleave.....	96
153.3.2.2.2	DQPSK encode	96
153.3.2.3	Receive function	97
153.3.2.3.1	DQPSK decode	97
153.3.2.3.2	Lane de-interleave.....	97
153.4	Protocol implementation conformance statement (PICS) proforma for Clause 153, SC-FEC and 100GBASE-ZR Physical Medium Attachment (PMA) sublayer for 100GBASE-ZR PHYs.....	98
153.4.1	Introduction	98
153.4.2	Identification	98
153.4.2.1	Implementation identification.....	98
153.4.2.2	Protocol summary	98
153.4.3	Major capabilities/options	99
153.4.4	PICS proforma tables for SC-FEC sublayer for 100GBASE-ZR PHYs.....	99
153.4.4.1	Transmit function	99
153.4.4.2	Receive function	100
153.4.4.3	State diagrams.....	100
154.	Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-ZR.....	101
154.1	Overview.....	101
154.1.1	Bit error ratio.....	102
154.2	Physical Medium Dependent (PMD) service interface	103
154.3	Delay and Skew	103
154.3.1	Delay constraints	103
154.3.2	Skew constraints.....	103
154.4	PMD MDIO function mapping.....	104

154.5	PMD functional specifications.....	105
154.5.1	PMD block diagram	105
154.5.2	PMD transmit function.....	105
154.5.3	PMD receive function	106
154.5.4	PMD global signal detect function.....	106
154.5.5	PMD reset function	106
154.5.6	PMD global transmit disable function (optional).....	106
154.5.7	PMD fault function (optional).....	106
154.5.8	PMD transmit fault function (optional).....	107
154.5.9	PMD receive fault function (optional)	107
154.6	DWDM channel over a DWDM black link	107
154.7	PMD to MDI optical specifications for 100GBASE-ZR.....	109
154.7.1	100GBASE-ZR transmitter optical specifications	110
154.7.2	100GBASE-ZR receive optical specifications.....	111
154.8	100GBASE-ZR DWDM black link transfer characteristics.....	111
154.9	Definition of optical parameters and measurement methods.....	111
154.9.1	Test patterns for optical parameters	111
154.9.2	Optical center frequency (wavelength) and side-mode suppression ratio (SMSR)	113
154.9.3	Average channel output power.....	113
154.9.4	Spectral excursion	113
154.9.5	Laser linewidth.....	113
154.9.6	Offset between the carrier and the nominal center frequency.....	114
154.9.7	Power difference between X and Y polarizations	114
154.9.8	Skew between X and Y polarizations	114
154.9.9	Error vector magnitude.....	114
154.9.10	I-Q offset	114
154.9.11	Optical signal-to-noise ratio (OSNR).....	114
154.9.12	Transmitter in-band OSNR	114
154.9.13	Average receive power.....	114
154.9.14	Receiver sensitivity	115
154.9.15	Receiver OSNR.....	115
154.9.16	Receiver OSNR tolerance	115
154.9.17	Ripple	115
154.9.18	Optical path OSNR penalty	115
154.9.19	Optical path power penalty	115
154.9.20	Polarization dependent loss.....	115
154.9.21	Polarization rotation speed.....	116
154.9.22	Inter-channel crosstalk at TP3.....	116
154.9.23	Interferometric crosstalk at TP3.....	116
154.10	Safety, installation, environment, and labeling.....	116
154.10.1	General safety.....	116
154.10.2	Laser safety	116
154.10.3	Installation.....	116
154.10.4	Environment.....	116
154.10.5	Electromagnetic emission	117
154.10.6	Temperature, humidity, and handling	117
154.10.7	PMD labeling requirements	117
154.11	Medium Dependent Interface (MDI).....	117
154.12	Protocol implementation conformance statement (PICS) proforma for Clause 154, Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-ZR.....	118
154.12.1	Introduction	118
154.12.2	Identification	118
154.12.2.1	Implementation identification.....	118
154.12.2.2	Protocol summary.....	118

154.12.3	Major capabilities/options	119
154.12.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-ZR	119
154.12.4.1	PMD functional specifications	119
154.12.4.2	Management functions	120
154.12.4.3	PMD to MDI optical specifications for 100GBASE-ZR.....	120
154.12.4.4	Optical measurement methods.....	121
154.12.4.5	Environmental specifications	121
154.12.4.6	Characteristics of DWDM black link and MDI.....	121
Annex A (informative) Bibliography		122
Annex 83C (informative) PMA sublayer partitioning examples.....		123
83C.4	Partitioning examples with SC-FEC.....	123
83C.4.1	CAUI-4 with SC-FEC.....	123
Annex 135A (informative) 50 Gb/s and 100 Gb/s PMA sublayer partitioning examples.....		124
135A.3	Partitioning examples of 100GAUI-n with Inverse RS-FEC	124
135A.3.1	100GAUI-n with Inverse RS-FEC.....	124
135A.3.2	CAUI-4 chip-to-chip and 100GAUI-n chip-to-module with Inverse RS-FEC.....	125
Annex 154A (informative) Examples of 100GBASE-ZR compliant DWDM black links		126
154A.1	Introduction.....	126
154A.2	Relationship between OSNR and average optical power	127
154A.3	Examples of DWDM black link applications with OSNR at TP3 between 19.5 dB (12.5 GHz) and 35 dB (12.5 GHz).....	128
154A.4	Example of DWDM black link applications with OSNR at TP3 greater than or equal to 35 dB (12.5 GHz)	129

IEEE Standard for Ethernet

Amendment 13: Physical Layers and Management Parameters for 100 Gb/s Operation over DWDM Systems

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, IEEE Std 802.3cd™-2018, IEEE Std 802.3cn™-2019, IEEE Std 802.3cg™-2019, IEEE Std 802.3cq™-2020, IEEE Std 802.3cm™-2020, IEEE Std 802.3ch™-2020, IEEE Std 802.3ca™-2020, IEEE Std 802.3cr™-2021, IEEE Std 802.3cu™-2021, and IEEE Std 802.3cv™-2021.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strikethrough~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, ~~renumbering~~ instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.¹

¹ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

1. Introduction

1.3 Normative references

Insert the following three references into 1.3 in alphanumeric order:

ITU-T Recommendation G.698.2—Amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces.²

ITU-T Recommendation G.709—Interfaces for the optical transport network.

ITU-T Recommendation G.709.2—OTU4 long-reach interface.

1.4 Definitions

Insert the following two new definitions after 1.4.35 “100GBASE-SR4”:

1.4.35a 100GBASE-Z: An IEEE 802.3 family of Physical Layer devices using 100GBASE-R encoding, a combination of phase and amplitude modulation, and coherent detection. (See IEEE Std 802.3, Clause 154.)

1.4.35b 100GBASE-ZR: IEEE 802.3 Physical Layer specification for a 100 Gb/s dense wavelength division multiplexing (DWDM) PHY using 100GBASE-R encoding, dual polarization differential quadrature phase shift keying (DP-DQPSK) modulation, and coherent detection with reach up to at least 80 km. (See IEEE Std 802.3, Clause 154.)

Insert the following new definition after 1.4.160 “bit time (BT)”:

1.4.160a black link approach: The specification of the input, output, and transfer characteristics of the unidirectional transmission path from TP2 to TP3 for a given dense wavelength division multiplexing (DWDM) channel within a DWDM black link, without specifying how the transmission path is implemented. (See, for example, IEEE Std 802.3, Clause 154, Figure 154–3.)

Insert the following new definition after 1.4.181 “Channel Operating Margin (COM)”:

1.4.181a channel spacing: The center-to-center difference in frequency or wavelength between adjacent channels in a WDM application. Dense wavelength division multiplexing (DWDM) channel spacings are based on the grid found in ITU-T G.694.1.

Insert the following new definition after 1.4.227 “defect”:

1.4.227a dense wavelength division multiplexing: An optical WDM technology where the frequency spacing is less than or equal to 1000 GHz.

Insert the following three new definitions after 1.4.237 “duplex channel”:

1.4.237a DWDM black link: An aggregate of pairs of dense wavelength division multiplexing (DWDM) channels, with each pair supporting one full duplex connection where the implementation of the transmission paths is not specified.

²ITU-T publications are available from the International Telecommunications Union (<https://www.itu.int/>).