

# IEEE Standard for Ethernet

## Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength

IEEE Computer Society

Developed by the  
LAN/MAN Standards Committee

### IEEE Std 802.3cu™-2021

(Amendment to IEEE Std 802.3™-2018  
as amended by IEEE Std 802.3cb™-2018,  
IEEE Std 802.3cf™-2018,  
IEEE Std 802.3co™-2018,  
IEEE Std 802.3cn™-2019,  
IEEE Std 802.3cg™-2019,  
IEEE Std 802.3cq™-2020,  
IEEE Std 802.3cm™-2020,  
IEEE Std 802.3ch™-2020,  
IEEE Std 802.3ca™-2020,  
and IEEE Std 802.3cr™-2021)

**IEEE Std 802.3cu™-2021**

(Amendment to IEEE Std 802.3™-2018  
as amended by IEEE Std 802.3cb™-2018,  
IEEE Std 802.3bt™-2018,  
IEEE Std 802.3cd™-2018,  
IEEE Std 802.3cn™-2019,  
IEEE Std 802.3cg™-2019,  
IEEE Std 802.3cq™-2020,  
IEEE Std 802.3cm™-2020,  
IEEE Std 802.3ch™-2020,  
IEEE Std 802.3ca™-2020,  
and IEEE Std 802.3cr™-2020)

# IEEE Standard for Ethernet

## Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength

Developed by the

**LAN/MAN Standards Committee**  
of the  
**IEEE Computer Society**

Approved 9 February 2021

**IEEE SA Standards Board**

**Abstract:** This amendment to IEEE Std 802.3-2018 adds Physical Layer specifications and management parameters for 100 Gb/s and 400 Gb/s Ethernet optical interfaces for reaches up to 10 km based on 100 Gb/s per wavelength optical signaling.

**Keywords:** 100 Gb/s Ethernet, 100GBASE-FR1, 100GBASE-LR1, 400 Gb/s Ethernet, 400GBASE-FR4, 400GBASE-LR4-6, Energy-Efficient Ethernet (EEE), Ethernet, forward error correction (FEC), IEEE 802.3™, IEEE 802.3cu™, PAM4, Physical Medium Dependent (PMD) sublayer, single-mode fiber (SMF)

---

The Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2021 by The Institute of Electrical and Electronics Engineers, Inc.  
All rights reserved. Published 26 February 2021. Printed in the United States of America.

IEEE and 02 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-7383-5 STD24602  
Print: ISBN 978-1-5044-7384-2 STDPD24602

*IEEE prohibits discrimination, harassment and bullying.*

*For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

## Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

### Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning this standard, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

### Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

## Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

## Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretation, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is encouraged to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#). An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.

## Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

## Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

## Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

## Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

## Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#). For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

### Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#). Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

### Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/submit/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

### IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

## Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3cu Working Group ballot.

**David J. Law**, *IEEE 802.3 Working Group Chair*

**Adam Healey**, *IEEE 802.3 Working Group Vice-Chair*

**Jon Lewis**, *IEEE 802.3 Working Group Secretary*

**Steven B. Carlson**, *IEEE 802.3 Working Group Executive Secretary*

**Valerie Maguire**, *IEEE 802.3 Working Group Treasurer*

**Mark Nowell**, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Chair*

**Gary Nicholl**, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Editor-in-Chief*

**David Lewis**, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Editor*

David Abramson  
Pete Anslow  
Michikazu Aono  
Nobuyasu Araki  
Tim Baggett  
Thananya Baldwin  
Steven Baumgartner  
Denis Beaudoin  
Gitesh Bhagwat  
Rich Boyer  
David Brandt  
Ralf-Peter Braun  
Theodore Brillhart  
Paul Brooks  
Matthew Brown  
Jairo Bustos Heredia  
Adrian Butter  
Clark Carty  
David Chalupsky  
Jacky Chang  
Xin Chang  
Chan Chen  
Golam Choudhury  
Keng Hua Chuang  
John D'Ambrosio  
Piers Dawe  
Fred Dawson  
Gerrit de Resten  
Claudio Desanti  
Curtis Deane  
Liang Du  
Kathryn Dube  
Frank Effenberger  
David Estes  
John Ewen  
Vincent Ferretti  
Brian Franchuk  
Matthias Fritsche  
Takashi Fukuoka  
Ali Ghiasi  
Joel Goergen  
Steven Gorshe

Hideki Goto  
Steffen Graber  
Olaf Grau  
Robert Grow  
Martin Gubow  
Mark Gustlin  
Marek Hajduczenia  
Howard Heck  
Brian Holden  
Bernd Horrmeyer  
Yasuhiro Hyata  
Jonathan Ingram  
Kazuhiko Ishio  
Hideki Isono  
Tom Iversen  
Hiroyuki Ito  
Kenneth Jackson  
Andrew Jimenez  
John Johnson  
Chad Jones  
Peter Jones  
Lokesh Kabra  
Haysam Kadry  
Manabu Kagami  
Upen Kareti  
Athanasios Kasapi  
Yong Kim  
Mark Kimber  
Michael Klempa  
Curtis Knittle  
Elizabeth Kochuparambil  
Sam Kocsis  
Wojciech Koczwar  
Paul Kolesar  
Taiji Kondo  
Daniel Koppermueller  
Glen Kramer  
Taketo Kumada  
Hans Lackner  
Frank Lambrecht  
Mark Laubach  
Greg Le Cheminant

Mike-Feng Li  
Alex Lior  
Hu-Feng Liu  
William Lo  
Kent Lusted  
Jeffery Maki  
David Malicoat  
Eric Maniloff  
Flavio Marques  
Arthur Marris  
Takeo Masuda  
Mick McCarthy  
Brett McClellan  
Larry McMillan  
Richard Mellitz  
Shimon Muller  
James Nadolny  
Edward Nakamoto  
Paul Neveux  
Gary Nicholl  
Shawn Nicholl  
Kevin Noll  
David Ofelt  
Ryo Okabe  
Tom Palkert  
Carlos Pardo  
Earl Parsons  
Gerald Pepper  
David Piehler  
Fabio Pittala  
Christopher Pohl  
William Powell  
Rick Rabinovich  
Parthasarathy Raju  
Adee Ran  
Alon Regev  
Duane Remein  
Victor Renteria  
Thomas Rettig  
Hamid Salehi  
Sam Sambasivan  
Edward Sayre  
Matthew Schmitt

Hossein Sedarat  
Masood Shariff  
Masato Shiino  
Ramin Shirani  
Kapil Shrikhande  
Jeff Slavick  
Scott Sommers  
Edward Sprague  
Peter Stassar  
Heath Stewart  
Junqing Sun  
Steve Swanson  
Tomoo Takahara  
Satoshi Takahashi

Tadashi Takahashi  
Kazuya Takayama  
Michael Takefman  
Masaru Terada  
Geoffrey Thompson  
Pirooz Tooyserkani  
Nathan Tracy  
David Tremblay  
Stephen Trowbridge  
Mike Tu  
Ed Ulrichs  
Alexander Umnov  
Edward Walter  
Roy Wang

Xuehuan Wang  
Dong Wei  
Matthias Wendt  
Natalie Wienckowski  
Dance Wu  
Peter Wu  
Dayin Xu  
Yu Xu  
Lennart Yseboodt  
Conrad Zerna  
Xingxin Zhang  
Chunhui Zhu  
Yan Zhuang  
Martin Zielinski  
George Zimmerman

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Robert Aiello  
Thomas Alexander  
Ralf-Peter Braun  
Theodore Brillhart  
Matthew Brown  
Jairo Bustos Heredia  
William Byrd  
Steven B. Carlson  
Clark Carty  
Pin Chang  
Chan Chen  
Charles Cook  
Piers Dawe  
John Deandrea  
Michael Dudek  
Avraham Freedman  
Matthias Fritsche  
Robert Grow  
Joseph Gwinn  
Xiang He  
Adam Healey  
Marco Hernandez  
David Hess  
Werner Hoelzl  
Thomas Huber  
Yasuhiro Hyakumake  
Jonathan Ingham  
Osamu Ishida  
Hideki Jones  
Chad Jones

Peter Jones  
Lokesh Kabra  
Piotr Karocki  
Stuart Kerry  
Yong Kim  
Mark Laubach  
David J. Law  
Pi-Cheng Law  
Hyeong Ho Lee  
David Lewis  
Jon Lewis  
Karen Liu  
Kent Lusted  
Valerie Maguire  
Jeffery Maki  
Michael Maytum  
Brian McClellan  
Jonathan McLendon  
Richard Mellitz  
Guangcan Mi  
Tremont Miao  
Raymond Nering  
Gary Nicholl  
Nick S. A. Nikjoo  
Mark Nowell  
Satoshi Obara  
Tom Palkert  
Carlos Pardo  
Earl Parsons  
Bansi Patel

David Pöhler  
Rick Pimpelle  
Pavel Piskunov  
Alon Regev  
Maximilian Riegel  
Robert Robinson  
Roberto Rodes  
Toshiaki Sakai  
Olindo Savi  
Jason Shriver  
Scott Sommers  
Peter Stassar  
Walter Struppler  
Mitsutoshi Sugawara  
Kohichi Tamura  
James Theodoras  
Nathan Tracy  
David Tremblay  
Stephen Trowbridge  
Mark-Rene Uchida  
John Vergis  
Ruoxu Wang  
Brian Welch  
Andreas Wolf  
Peter Wu  
James Young  
Yu Yuan  
Oren Yuen  
Bo Zhang  
Pavel Zivny

When the IEEE SA Standards Board approved this standard on 9 February 2021, it had the following membership:

**Gary Hoffman, *Chair***  
**Vacant Position, *Vice Chair***  
**John D. Kulick, *Past Chair***  
**Konstantinos Karachalios, *Secretary***

Edward A. Addy  
Doug Edwards  
Ramy Ahmed Fathy  
J. Travis Griffith  
Joseph L. Koepfinger\*  
Thomas Koshy  
David J. Law  
Howard Li

Daozhuang Lin  
Kevin Lu  
Daleep C. Mohla  
Chenhui Niu  
Damir Novosel  
Annette Reilly  
Jon Walter Rosdahl

Dorothy Stanley  
Mehmet Ulema  
Lei Wang  
F. Keith Waters  
Karl Weber  
Sha Wei  
Howard Wolfman  
Daidi Zhong

\*Member Emeritus

## Introduction

This introduction is not part of IEEE Std 802.3cu-2021, IEEE Standard for Ethernet—Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel, and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of IEEE Std 802.3cu-2021 publication, IEEE Std 802.3 was composed of the following documents:

### IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber

access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

#### IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

#### IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

#### IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

#### IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

#### IEEE Std 802.3cg™-2019

Amendment 5—This amendment includes changes to IEEE Std 802.3-2018 and its amendments and adds Clause 146 through Clause 148 and Annex 146A and Annex 146B. This amendment adds 10 Mb/s Physical Layer specifications and management parameters for operation on a single balanced pair of conductors.

#### IEEE Std 802.3cq™-2020

Amendment 6—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 33 and related portions of the standard.

#### IEEE Std 802.3cm™-2020

Amendment 7—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 150. This amendment adds Physical Layer (PHY) specifications and management parameters for 400 Gb/s operation on four pairs (400GBASE-SR4.2) and eight pairs (400GBASE-SR8) of multimode fiber, over reaches of at least 100 m.

#### IEEE Std 802.3ch™-2020

Amendment 8—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 149, Annex 149A, Annex 149B, and Annex 149C. This amendment adds physical layer specifications and management parameters for operation at 2.5 Gb/s, 5 Gb/s, and 10 Gb/s over a single balanced pair of conductors.

#### IEEE Std 802.3ca™-2020

Amendment 9—This amendment to IEEE Std 802.3-2018 extends the operation of Ethernet passive optical networks (EPONs) to multiple channels of 25 Gb/s providing both symmetric and asymmetric operation for the following data rates (downstream/upstream): 25/10 Gb/s, 25/25 Gb/s, 50/10 Gb/s, 50/25 Gb/s, and 50/50 Gb/s. This amendment specifies the 25 Gb/s EPON Multi-Channel Reconciliation Sublayer (MCRS), Nx25G-EPON Physical Coding Sublayers (PCSs), Physical Media Attachment (PMA) sublayers, and Physical Medium Dependent (PMD) sublayers that support both symmetric and asymmetric data rates while maintaining backward compatibility with already deployed 10 Gb/s EPON equipment. The EPON operation is defined for distances of at least 20 km, and for a split ratio of at least 1:32.

#### IEEE Std 802.3cr™-2021

Amendment 10—This amendment includes changes to IEEE Std 802.3-2018 and adds Annex J. This amendment replaces references to the IEC 60950 series of standards (including IEC 60950-1 “Information technology equipment—Safety—Part 1: General requirements”) with appropriate references to the IEC 62368 “Audio/video, information and communication technology equipment” series and makes appropriate changes to the standard corresponding to the new references.

#### IEEE Std 802.3cu™-2021

Amendment 11—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 151. This amendment adds Physical Layer (PHY) specifications and management parameters for 100 Gb/s and 400 Gb/s operation over single-mode fiber, based on 100 Gb/s per wavelength optical signaling.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management

Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

# Contents

1. Introduction.....	18
1.4    Definitions .....	18
30. Management.....	19
30.5    Layer management for medium attachment units (MAUs).....	19
30.5.1    MAU managed object class.....	19
30.5.1.1    MAU attributes .....	19
30.5.1.1.2    aMAUType .....	19
45. Management Data Input/Output (MDIO) Interface.....	20
45.2    MDIO Interface Registers.....	20
45.2.1    PMA/PMD registers.....	20
45.2.1.6    PMA/PMD control 2 register (Register 1.7) .....	20
45.2.1.7    PMA/PMD status 2 register (Register 1.8).....	20
45.2.1.7.4    Transmit fault (1.8.11) .....	20
45.2.1.7.5    Receive fault (1.8.10).....	21
45.2.1.8    PMD transmit disable register (Register 1.9).....	21
45.2.1.21    400G PMA/PMD extended ability register (Register 1.24) .....	22
45.2.1.21.1a1    400GBASE-LR4-6 ability (1.24.9).....	22
45.2.1.21.1a2    400GBASE-FR4 ability (1.24.8) .....	22
45.2.1.21b    40G/100G PMA/PMD extended ability 2 (Register 1.26) .....	23
45.2.1.21b.3a    100GBASE-LR1 ability (1.26.5) .....	23
45.2.1.21b.3b    100GBASE-FR1 ability (1.26.4) .....	23
78. Energy-Efficient Ethernet (EEE).....	24
78.1    Overview.....	24
78.1.4    PHY types optionally supporting EEE.....	24
80. Introduction to 40 Gb/s and 100 Gb/s networks.....	25
80.1    Overview.....	25
80.1.3    Relationship of 40 Gigabit and 100 Gigabit Ethernet to the ISO OSI reference model.....	25
80.1.4    Nomenclature .....	25
80.1.5    Physical Layer signaling systems.....	26
80.2    Summary of 40 Gigabit and 100 Gigabit Ethernet sublayers .....	26
80.2.3    Forward Error Correction (FEC) sublayers.....	26
80.4    Delay constraints.....	27
91. Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs .....	28
91.5    Functions within the RS-FEC sublayer .....	28
91.5.2.7    Reed-Solomon encoder.....	28
91.5.3    Receive function.....	28
91.5.3.3    Reed-Solomon decoder.....	28
91.5.3.3.1    FEC Degraded SER (optional).....	28
91.6    RS-FEC MDIO function mapping.....	29

91.6.2a	four_lane_pmd .....	29
91.7	Protocol implementation conformance statement (PICS) proforma for Clause 91, Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs.....	30
91.7.3	Major capabilities/options .....	30
91.7.4	PICS proforma tables for Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs.....	30
91.7.4.1	Transmit function .....	30
91.7.4.2	Receive function .....	31
116.	Introduction to 200 Gb/s and 400 Gb/s networks .....	32
116.1	Overview.....	32
116.1.2	Relationship of 200 Gigabit and 400 Gigabit Ethernet to the ISO OSI reference model.....	32
116.1.3	Nomenclature .....	32
116.1.4	Physical Layer signaling systems.....	33
116.4	Delay constraints.....	33
116.5	Skew constraints .....	34
140.	Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 .....	36
140.1	Overview.....	36
140.2	Physical Medium Dependent (PMD) service interface .....	37
140.3	Delay and Skew .....	38
140.3.1	Delay constraints .....	38
140.5	PMD functional specifications.....	38
140.5.1	PMD block diagram .....	38
140.6	PMD to MDI optical specifications for 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 .....	38
140.6.1	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 transmitter optical specifications.....	39
140.6.2	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 receive optical specifications.....	41
140.6.3	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 illustrative link power budgets .....	43
140.7	Definition of optical parameters and measurement methods.....	46
140.7.1	Test patterns for optical parameters .....	46
140.7.5	Transmitter and dispersion eye closure for PAM4 (TDECQ).....	46
140.7.5.1	TDECQ reference equalizer .....	47
140.7.5.2	Channel requirements .....	47
140.7.5a	Transmitter eye closure for PAM4 (TECQ).....	47
140.7.5b	Over/under-shoot.....	48
140.7.5c	Transmitter power excursion.....	48
140.7.8	Relative intensity noise (RIN <sub>15.5xOMA</sub> ) .....	49
140.7.9	Receiver sensitivity .....	49
140.7.9.1	Receiver sensitivity for 100GBASE-DR.....	49
140.7.9.2	Receiver sensitivity for 100GBASE-FR1 and 100GBASE-LR1 .....	49
140.7.10	Stressed receiver sensitivity .....	50
140.8	Safety, installation, environment, and labeling.....	50
140.8.2	Laser safety .....	50
140.8.4	Environment .....	50
140.8.5	Electromagnetic emission .....	50
140.9	Fiber optic cabling model .....	51

140.10	Characteristics of the fiber optic cabling (channel) .....	51
140.10.1	Optical fiber cable .....	52
140.10.2	Optical fiber connection .....	52
140.10.2.1	Connection insertion loss.....	52
140.10.2.2	Maximum discrete reflectance.....	52
140.10.3	Medium Dependent Interface (MDI) .....	53
140.10a	Interoperation between 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 .....	53
140.10a.1	Interoperation between 100GBASE-FR1 and 100GBASE-DR.....	53
140.10a.2	Interoperation between 100GBASE-LR1 and 100GBASE-DR.....	54
140.10a.3	Interoperation between 100GBASE-LR1 and 100GBASE-FR1 .....	54
140.11	Protocol implementation conformance statement (PICS) proforma for Clause 140, Physical Medium Dependent (PMD) sublayer and medium, types 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 .....	55
140.11.1	Introduction .....	55
140.11.2	Identification .....	55
140.11.2.2	Protocol summary .....	55
140.11.3	Major capabilities/options .....	56
140.11.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 .....	56
140.11.4.3	PMD to MDI optical specifications for 100GBASE-DR .....	56
140.11.4.3a	PMD to MDI optical specifications for 100GBASE-FR1 .....	56
140.11.4.3b	PMD to MDI optical specifications for 100GBASE-LR1.....	57
140.11.4.4	Optical measurement methods.....	57
140.11.4.6	Characteristics of the fiber optic cabling and <del>MDI</del> MDI. ....	58
151.	Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6.....	59
151.1	Overview.....	59
151.1.1	Bit error ratio.....	60
151.2	Physical Medium Dependent (PMD) service interface .....	60
151.3	Delay and Skew .....	61
151.3.1	Delay constraints .....	61
151.3.2	Skew constraints.....	61
151.4	PMD MDIO function mapping.....	62
151.5	PMD functional specifications.....	62
151.5.1	PMD block diagram .....	62
151.5.2	PMD transmit function.....	63
151.5.3	PMD receive function .....	63
151.5.4	PMD global signal detect function.....	64
151.5.5	PMD lane-by-lane signal detect function.....	64
151.5.6	PMD reset function .....	64
151.5.7	PMD global transmit disable function (optional).....	64
151.5.8	PMD lane-by-lane transmit disable function .....	65
151.5.9	PMD fault function (optional).....	65
151.5.10	PMD transmit fault function (optional).....	65
151.5.11	PMD receive fault function (optional) .....	65
151.6	Wavelength-division-multiplexed lane assignments .....	66
151.7	PMD to MDI optical specifications for 400GBASE-FR4 and 400GBASE-LR4-6 .....	66
151.7.1	400GBASE-FR4 and 400GBASE-LR4-6 transmitter optical specifications.....	66
151.7.2	400GBASE-FR4 and 400GBASE-LR4-6 receive optical specifications .....	68
151.7.3	400GBASE-FR4 and 400GBASE-LR4-6 illustrative link power budgets .....	70
151.8	Definition of optical parameters and measurement methods.....	72
151.8.1	Test patterns for optical parameters .....	72

151.8.2	Wavelength and side mode suppression ratio (SMSR).....	73
151.8.3	Average optical power .....	73
151.8.4	Outer Optical Modulation Amplitude (OMA <sub>outer</sub> ).....	73
151.8.5	Transmitter and dispersion eye closure for PAM4 (TDECQ).....	73
151.8.5.1	Channel requirements .....	73
151.8.6	Transmitter eye closure for PAM4 (TECQ).....	74
151.8.7	Over/under-shoot.....	74
151.8.8	Transmitter power excursion.....	74
151.8.9	Extinction ratio .....	74
151.8.10	Transmitter transition time .....	74
151.8.11	Relative intensity noise (RIN <sub>17.1OMA</sub> and RIN <sub>15.6OMA</sub> ) .....	75
151.8.12	Receiver sensitivity .....	75
151.8.13	Stressed receiver sensitivity .....	76
151.9	Safety, installation, environment, and labeling.....	76
151.9.1	General safety.....	76
151.9.2	Laser safety .....	76
151.9.3	Installation.....	76
151.9.4	Environment.....	77
151.9.5	Electromagnetic emission .....	77
151.9.6	Temperature, humidity, and handling .....	77
151.9.7	PMD labeling requirements .....	77
151.10	Fiber optic cabling model .....	77
151.11	Characteristics of the fiber optic cabling (channel) .....	78
151.11.1	Optical fiber cable .....	78
151.11.2	Optical fiber connection.....	78
151.11.2.1	Connection insertion loss.....	79
151.11.2.2	Maximum discrete reflectance.....	79
151.11.3	Medium Dependent Interface (MDI) requirements .....	79
151.12	Interoperation between 400GBASE-LR4-6 and 400GBASE-FR4 .....	79
151.13	Protocol implementation conformance statement (PICS) proforma for Clause 151, Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6.....	81
151.13.1	Introduction .....	81
151.13.2	Identification .....	81
151.13.2.1	Implementation identification.....	81
151.13.2.2	Protocol summary .....	81
151.13.3	Major capabilities/options .....	82
151.13.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6.....	82
151.13.4.1	PMD functional specifications .....	82
151.13.4.2	Management functions .....	83
151.13.4.3	PMD to MDI optical specifications for 400GBASE-FR4.....	84
151.13.4.4	PMD to MDI optical specifications for 400GBASE-LR4-6 .....	84
151.13.4.5	Optical measurement methods.....	84
151.13.4.6	Environmental specifications .....	85
151.13.4.7	Characteristics of the fiber optic cabling and MDI .....	85

# IEEE Standard for Ethernet

## Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, IEEE Std 802.3cd™-2018, IEEE Std 802.3cn™-2019, IEEE Std 802.3cg™-2019, IEEE Std 802.3cq™-2020, IEEE Std 802.3cm™-2020, IEEE Std 802.3ch™-2020, IEEE Std 802.3ca™-2020, and IEEE Std 802.3cr™-2020.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.<sup>1</sup>

---

<sup>1</sup> Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

## 1. Introduction

### 1.4 Definitions

*Insert the following new definition after 1.4.27 “100GBASE-ER4”:*

**1.4.27a 100GBASE-FR1:** IEEE 802.3 Physical Layer specification for 100 Gb/s serial transmission using 100GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 2 km. (See IEEE Std 802.3, Clause 140.)

*Insert the following new definition after 1.4.29 “100GBASE-KR4”:*

**1.4.29a 100GBASE-LR1:** IEEE 802.3 Physical Layer specification for 100 Gb/s serial transmission using 100GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 10 km. (See IEEE Std 802.3, Clause 140.)

*Insert the following new definition after 1.4.106a “400GBASE-ER8” as inserted by IEEE Std 802.3cn-2019:*

**1.4.106b 400GBASE-FR4:** IEEE 802.3 Physical Layer specification for 400 Gb/s using 400GBASE-R encoding and 4-level pulse amplitude modulation over four WDM lanes on single-mode fiber, with reach up to at least 2 km. (See IEEE Std 802.3, Clause 151.)

*Insert the following new definition after 1.4.107 “400GBASE-FR8”:*

**1.4.107a 400GBASE-LR4-6:** IEEE 802.3 Physical Layer specification for 400 Gb/s using 400GBASE-R encoding and 4-level pulse amplitude modulation over four WDM lanes on single-mode fiber, with reach up to at least 6 km. (See IEEE Std 802.3, Clause 151.)