



APPROVED METHOD:
**SPECTRORADIOMETRIC
MEASUREMENT METHODS
FOR LIGHT SOURCES**
AN AMERICAN NATIONAL STANDARD

Currently in preview, click buy full version



ANSI/IES LM-58-20

**APPROVED METHOD:
SPECTRORADIOMETRIC MEASUREMENT
METHODS FOR LIGHT SOURCES
AN AMERICAN NATIONAL STANDARD**

Publication of this document
has been approved by IES.
Suggestions for revisions
should be directed to IES.

**Prepared by
The IES Testing Procedures Committee**



Copyright 2020 by the Illuminating Engineering Society.

Approved by the IES Standards Committee August 23, 2019 as a Transaction of the Illuminating Engineering Society.

Approved February 7, 2020 as an American National Standard.

All rights reserved. No part of this publication may be reproduced in any form, in any electronic retrieval system or otherwise, without prior written permission of the IES

Published by the Illuminating Engineering Society, 120 Wall Street, New York, New York 10005

IES Standards are developed through committee consensus and produced by the IES Office in New York. Careful attention is given to style and accuracy. If any errors are noted in this document, please forward them to Brian Liebel, Director of Standards, at standards@ies.org or the above address for verification and correction. The IES welcomes and urges feedback and comments.

Printed in the United States of America.

ISBN# 978-0-87995-040-8

DISCLAIMER

IES publications are developed through the consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on lighting recommendations. While the IES administers the process and establishes policies and procedures to promote fairness in the development of consensus, it makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IES disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and making this document available, the IES is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IES undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IES has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IES list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IES and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether that person has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation to any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Prepared by the IES Testing Procedures Committee

Becky Kuebler, *Chair*

Andrew Jackson, *Vice Chair*

David N. Randolph, *Secretary*

Jianzhong Jiao, *Treasurer*

Members

C. K. Andersen

R. P. Bergin

R. S. Bergman

E. Bretschneider

P. Elizondo

D. J. Ellis

K. C. Fletcher

M. L. Grather

Y. H. Hiebert

J. Hospodarsky

J. N. Hulett

P.-C. Hung

M. Kotrebai

J. E. Leland

S. Longo

J. P. Marella

P. McCarthy

G. McKee

C. C. Miller

E. Radkov

M. B. Sapcoe

J. E. Walker

Advisory Members

L. M. Ayers

J. Baker

C. A. Bloomfield

P.-T. Chou

M. Damle

L. Davis

J. J. Demirjian

M. E. Duffy

V. Eberhard

J. Frazer

K. J. Hemmi

S. Hua

G. John

H. Kashaninejad

T. Kawabata

R. Kelley

K. C. Lerbs

K. M. Liepmann

J. Lockner

Y. Ohno

E. Page

D. Park

E. S. Perkins

M. Piscitelli

D. Rogers

M. P. Rorer

T. Schneider

R. W. S. Sures

J. A. Steinberg

L. Swainston

J. S. Swiernik

A. Thorseth

R. C. Tuttle

J. C. Vollers

Y. Zong

CONTENTS

Foreword	1
1.0 Introduction and Scope	1
1.1 Introduction	1
1.1.1 Safety Precautions	1
1.2 Scope	2
2.0 Normative References	2
3.0 Definitions and Nomenclature	2
4.0 Spectroradiometers	2
4.1 Characteristics	2
4.1.1 Wavelength Dispersion.....	2
4.1.2 Wavelength Calibration	2
4.1.3 Bandpass	3
4.1.4 Slit Scattering Function (Bandpass Function).....	3
4.1.5 Wavelength Interval.....	3
4.1.6 Stray Light	3
4.1.7 Input Geometry.....	4
4.1.8 Calibration Sources	4
4.1.8.1 Spectral Irradiance.....	4
4.1.8.2 Spectral Radiance	4
4.1.8.3 Total Spectral Radiant Flux.....	5
4.2 Array Spectrometry	5
4.2.1 Design	6
4.2.1.1 CCD Array Spectrometers	6
4.2.1.2 Linear Diode Array Spectrometers.....	6
4.2.2 Integration Time	6
4.2.3 A/D Converter Data Rate	6
4.2.4 Dynamic Range	6
4.2.5 Signal-to-Noise Ratio (S/N Ratio).....	6
4.2.6 Linearity	7
4.2.7 Dark Measurements.....	7
4.2.8 Spectral Resolution	7
4.2.9 Trigger Capability	7

4.2.10	Wavelength Uncertainty	7
4.2.11	Bandpass Determination	7
4.3	Scanning Spectrometry	8
4.3.1	Continuous Scanning	8
4.3.2	Sequential Scanning	8
5.0	Detectors	9
5.1	General	9
5.2	Ultraviolet-Visible Region (UV-VIS)	9
5.2.1	Photomultipliers	9
5.2.2	Silicon Photodiodes	9
5.2.3	Other Photodiodes	9
5.3	Near-Infrared (NIR) Region	10
5.3.1	Germanium Photodiodes	10
5.3.2	Indium Gallium Arsenide (InGaAs) Photodiodes	10
5.3.3	Other NIR Photodiodes	10
6.0	Correction Methods	10
6.1	Flicker and Corrections	10
6.2	Bandpass Correction	10
6.3	Stray Light and Stray-Light Correction	11
7.0	Calculations	11
7.1	Spectral Radiometric Quantities	11
7.2	Radiometric Quantities	12
7.3	Photometric Quantities	12
8.0	Reporting Requirements	12
Additional Reading	13
References	14

Foreword

This guide is a revision of *IES LM-58-15, IES Guide to Spectroradiometric Measurements* with editorial changes only.

1.0 Introduction and Scope

1.1 Introduction

In evaluating the color performance of light sources, there are two factors to be considered:

- The light source color appearance (hue and saturation)
- Its color rendering ability (the effect of the light source on the appearance of objects, compared to their appearance under a reference source)

The perceived color of a light source is its appearance as a separate consideration from its luminance, geometry, and time variations. This in turn depends upon the relative spectral power distribution (SPD) of the radiant energy from the source and on observer adaptation. Two sources with entirely different spectral power distributions may produce the same color appearance when illuminating one surface (i.e., they produce a metameric match) but can look quite different when illuminating a surface with different spectral reflectance characteristics.

The SPD constitutes the basic data needed for the computation of chromaticity coordinates and the metrics that describe color rendering. These data are obtained by spectroradiometry, whereby the light from the source is dispersed into its component wavelengths and the power in each narrow band of wavelengths is measured. Spectroradiometry has been practiced since Newton discovered the dispersive properties of a prism on light. Spectroradiometry is now recognized as the most accurate, precise, and dependable method of determining the chromaticity of any light source.

Where visual phenomena such as color are involved, the SPD usually is determined between the wavelengths

of 380 nm and 780 nm, and should be measured with sufficiently narrow bandpass to show the desired resolution. For more-complete coverage, the SPD should be determined between the wavelengths of 360 nm and 830 nm. The curves are often plotted at five-nanometer intervals and are based on a spectral bandpass of approximately five nanometers. Computer plotted spectral power distributions are common at intervals much smaller than five nanometers. For sources containing line spectra, it has been found necessary for accurate resolution of spectra to utilize a bandpass of approximately two nanometers.

All photometric, colorimetric, and radiometric values can be calculated using the SPDs measured by a spectroradiometer. Sufficient accuracy is attainable with modern spectroradiometric systems such that they can be used for defining standards for other methods of colorimetry (e.g., with tristimulus colorimeters). In general, a spectroradiometer consists of a monochromator (dispersing instrument), a detector to measure the power at the output of the monochromator, and a device for recording data. A standard light source or known spectral power distribution is used for calibration.

The spectroradiometric method is advantageous because once calibration has been carried out against one standard source (usually an incandescent filament lamp), the spectroradiometer can determine—with equal accuracy—the SPD of light sources of any color, providing only that the unknown SPD is within the range of calibration. This range can comfortably run from 380 nm to 780 nm—or preferably from 360 nm to 830 nm—and therefore covers the visible region of interest for determining chromaticity.

1.1.1 Safety Precautions. Since overexposure to bactericidal (and/or germicidal) and erythematous ultraviolet radiation may result in erythema (reddening of the skin) or keratoconjunctivitis (inflammation of the cornea and conjunctiva, the exposed eye membranes), it is imperative that suitable eye protection and clothing be used when conducting measurements in these spectral regions. Lamp manufacturers' recommendations for safety precautions should be followed.¹