

**INSTITUTE OF  
ENVIRONMENTAL  
SCIENCES AND  
TECHNOLOGY**

---

---

**Contamination Control Division  
Recommended Practice 008.2**

**IEST-RP-CC008.2**

---

**High-efficiency Gas-phase  
Adsorber Cells**

---

---

**INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY**

---

1827 Walden Office Square, Suite 400 |

Schaumburg, IL 60173 USA

Phone: (847) 981-0100 • Fax: (847) 981-4130

E-mail: [iest@iest.org](mailto:iest@iest.org) • Web: [www.iest.org](http://www.iest.org)



---

COPYING IS ILLEGAL  
Currently in preview, click buy full version

---

This Recommended Practice is published by the INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY to advance the technical and engineering sciences. Its use is entirely voluntary, and determination of its applicability and suitability for any particular use is solely the responsibility of the user.

This Recommended Practice was prepared by and is under the jurisdiction of Working Group 003 of the IEST Contamination Control Division.

Copyright © 2007 by the **INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY**

Second printing, July 2017

ISBN 978-0-9787868-2-3

**PROPOSAL FOR IMPROVEMENT:** The Working Group of the INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY are continually working on improvements to their Recommended Practices and Reference Documents. Suggestions from those who use these documents are welcome. If you have a suggestion regarding this document, please use the online Proposal for Improvement form found on the IEST website at [www.iest.org/proposal/form.html](http://www.iest.org/proposal/form.html).

**INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY**

1027 Walden Office Square, Suite 400 | Schaumburg, IL 60173 USA

Phone: (847) 981-0100 • Fax: (847) 981-4130

E-mail: [iest@iest.org](mailto:iest@iest.org) • Web: [www.iest.org](http://www.iest.org)



---

COPYING IS ILLEGAL  
Currently in preview, click buy full version

---

# High-efficiency Gas-phase Adsorber Cells

## IEST-RP-CC008.2

### CONTENTS

#### SECTION

1	SCOPE AND LIMITATIONS .....	7
2	REFERENCES .....	7
3	TERMS AND DEFINITIONS .....	9
4	ALLOWABLE MATERIALS .....	9
5	DESIGN .....	11
6	CONSTRUCTION .....	11
7	QUALITY ASSURANCE REQUIREMENTS .....	16
8	PACKAGING AND SHIPPING .....	18

#### FIGURE

1	TYPE I CELL .....	11
2	TYPE II CELL .....	13
3	TYPE IV CELL .....	14
A1	TYPICAL HOLDING RACK FOR TYPE I CELL .....	19
A2	TYPICAL HOLDING RACK FOR TYPE II CELL .....	20

#### APPENDIX

A	RECOMMENDED INSTALLATION REQUIREMENTS .....	19
B	CALCULATION OF RESIDENCE TIME OF ADSORBER CELLS .....	21
C	RECOMMENDATIONS FOR ORDERING, MARKING, AND SHIPPING .....	22
D	BIBLIOGRAPHY .....	23

---

COPYING IS ILLEGAL  
Currently in preview, click buy full version

# High-efficiency Gas-phase Adsorber Cells

## IEST-RP-CC008.2

### 1 SCOPE AND LIMITATIONS

This Recommended Practice (RP) covers the design and testing of modular gas-phase adsorber cells in single pass or recirculating air-cleaning systems where the need for high-efficiency removal of gaseous contaminants is a requirement. Three types of modular cells are discussed in detail.

#### 1.1 Classification

Adsorber cells described in this RP have been classified into four types, namely:

- Type I (serpentine-bed) cell (application specific)
- Type II (flat-bed or tray-type) cell
- Type III (not discussed in detail)
- Type IV (vee-bed) cell

The four types of adsorber cells, though differing in their respective configurations, have common features and components.

#### 1.2 Adsorbent specifications

Test requirements of this RP cover the cell as filled with granular activated carbon. Typically, the carbon used in adsorber cells manufactured in accordance with this RP is sized to 8 × 16 US mesh. Performance of the cell for a specific contaminant is a function of the adsorbent used and the operating conditions. These conditions should be specified in addition to the requirements outlined in this RP.

#### 1.3 Limitations

This RP is limited to gas-phase adsorbers used for nuclear, military, and heavy industrial applications. These adsorber cells require prior qualification of the cell design and carbon filling method. The manufac-

turer should perform production airflow resistance and leak testing.

**NOTE:** Products and procedures discussed in this RP may involve hazardous materials, operations, and equipment. This RP does not purport to address all of the safety problems associated with the use of the RP. It is the sole responsibility of the user to consult and establish appropriate safety and health practices and to determine the applicability of regulatory limitations prior to use of this RP.

### 2 REFERENCES

The following documents are incorporated into this RP to the extent specified herein. Users should apply the most recent editions of the references.

#### 2.1 American National Standards Institute (ANSI)

*ANSI A208.1 (1999): Particle Board, Mat-Formed Wood*

#### 2.2 American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE)

*ASHRAE Standard 34-2004: Designation and Safety Classification of Refrigerants (ANSI Approved)*

#### 2.3 American Society of Mechanical Engineers (ASME)

*ASME/ANSI B1.1-2003: Unified Inch Screw Threads (UN & UNR Thread Form)*

*ASME BPVC SEC IX-2004 Boilers and Pressure Vessels: Section IX, Welding and Brazing Qualification*