

*Institute of Environmental Sciences and Technology*

## IEST-RP-PR003.1

Product Reliability Division  
Recommended Practice 003.1

# HALT and HASS



1027 Walden Office Square, Suite 400 |  
Schaumburg, IL 60173 USA  
Phone: (847) 981-0100 • Fax: (847) 981-4130  
E-mail: [information@iest.org](mailto:information@iest.org) • Web:  
[www.iest.org](http://www.iest.org)

---

This Recommended Practice is published by the Institute of Environmental Sciences and Technology to advance the technical and engineering sciences. Use of this document is entirely voluntary, and determination of its applicability and suitability for any particular use is solely the responsibility of the user. Use of this Recommended Practice does not imply any warranty or endorsement by IEST.

This Recommended Practice was prepared by and is under the jurisdiction of Working Group 003 of the IEST Product Reliability Division.

Copyright © 2012 by the Institute of Environmental Sciences and Technology

Second printing, July 2017

ISBN: 978-1-937280-07-9 (Electronic Format)

ISBN: 978-1-937280-06-2 (Print Format)

**PROPOSAL FOR IMPROVEMENT:** The Working Groups of the Institute of Environmental Sciences and Technology are continually working on improvements to their Recommended Practices and Reference Documents. Suggestions from users of these documents are welcome. If you have a suggestion regarding this document, please use the online Proposal for Improvement form found on the IEST website at [www.iest.org](http://www.iest.org).

Institute of Environmental Sciences and Technology  
1800 Walden Office Square, Suite 400 |  
Schaeferburg, IL 60173 USA  
Phone: (847) 981-0100 • Fax: (847) 981-4130  
E-mail: [information@iest.org](mailto:information@iest.org) • Web: [www.iest.org](http://www.iest.org)

---

# HALT and HASS

## IEST-RP-PR003.1

### CONTENTS

#### SECTION

1	SCOPE.....	4
2	REFERENCES.....	4
3	TERMS AND DEFINITIONS.....	4
4	BACKGROUND AND PURPOSE.....	5
5	HALT.....	5
6	HASS.....	14
7	DIFFERENCES BETWEEN HALT AND HASS.....	15
8	EQUIPMENT USED FOR HALT AND HASS.....	16
9	FIXTURING.....	17
10	OTHER CONSIDERATIONS.....	19
11	SUBJECTS OF CONCERN.....	21
12	ADDITIONAL RESOURCES.....	22
13	ACKNOWLEDGEMENTS.....	22

#### FIGURE

1	EXAMPLE FOR DETERMINING HOW MANY SAMPLES TO TEST.....	7
2	THERMAL STEP STRESS TESTING.....	8
3	COLD STEP STRESS TEST EXAMPLE.....	8
4	HOT STEP STRESS TEST EXAMPLE.....	9
5	RAPID THERMAL CYCLING TESTING.....	9
6	REPETITIVE SHOCK TABLE TEST SETUP EXAMPLE.....	10
7	ELECTRODYNAMIC SHAKER TEST SETUP EXAMPLE.....	10
8	APPLICABILITY OF SHAKER TYPE.....	10
9	VIBRATION STEP STRESS TESTING.....	11
10	LEGACY ESS INPUT.....	11
11	SKEWED-AXIS TEST FIXTURE.....	12
12	COMBINED VIBRATION AND THERMAL STEP STRESS TESTING.....	12
13	EXAMPLE FIXTURING FOR REPETITIVE SHOCK.....	17
14	EXAMPLE OF FIXTURING FOR ELECTRODYNAMIC SHAKER.....	18
15	EXAMPLE PRODUCT THERMAL RANGES.....	19

#### TABLE

1	LEGACY ESS INPUT.....	12
2	EXAMPLE OF HASS THERMAL LEVELS.....	14
3	DIFFERENCES BETWEEN HALT AND HASS.....	15

# HALT and HASS

## IEST-RP-PR003.1

### 1 SCOPE

#### 1.1 Scope

This Recommended Practice (RP) defines and describes HALT (Highly Accelerated Life Testing) and HASS (Highly Accelerated Stress Screening). This RP contains information on the philosophy behind the testing, generic examples of tests, the differences between standard testing equipment and equipment used for highly accelerated testing, fixturing considerations, alternative approaches, additional environments, and lessons learned, along with other useful information. This style of testing takes a Qualitative approach (looking for the quality of the design and workmanship) rather than a Quantitative approach (being able to use the results to calculate length of life in service). This RP is not meant to take the place of a test specification but to be used in conjunction with a test specification or as general guidance.

### 2 REFERENCES

The cited editions of the following documents are incorporated into this RP to the extent specified herein. Users are encouraged to investigate the possibility of applying the most recent editions of the references.

*MIL-STD-810: Test Method Standard for Environmental Engineering Considerations and Laboratory Tests*

#### Military Standards

Standardization Document Order Desk  
700 Robbins Avenue  
Bldg #4, Section D  
Harrisburg, PA 17111, USA  
<http://dodssp.daps.dla.mil/>

### 3 TERMS AND DEFINITIONS

#### acceleration

The rate of change of velocity with respect to time. For vibration testing, acceleration is usually expressed in gravitational units (g) but may also be expressed as m/sec<sup>2</sup>.

#### accelerometer

A sensor for converting acceleration into an electrical signal; a transducer featuring instantaneous output proportional to the instantaneous acceleration input.

#### bathtub curve

A plot of product failures versus time, which has three regions: The first shows decreasing “infant mortality” (early failures); the second, constant random failures; and the third, increasing wear-out failures.

#### dwel

The length of time during which a test article is subjected to an environment (e.g., thermal or vibration).

#### electrodynamic (ED) shaker

A type of shaker that uses electrical energy to create dynamic motion. In physics, the technology used is referred to as the “voice coil principle.”

#### environmental stress screening (ESS)

The application of forcing function to a product for the purpose of characterizing the environmental performance of the product.

#### Failure Modes and Effects Analysis (FMEA)

A methodology conducted during product development to identify and classify potential reliability problems, and to define a course of action to mitigate failures according to priority.

#### fixture

An intermediate structure used to attach a test unit to a test platform such as a vibration table.