



ASSOCIATION CONNECTING
ELECTRONICS INDUSTRIES®

IPC-7351A

Generic Requirements for
Surface Mount Design and
Land Pattern Standard

IPC-7351A

February 2007

A standard developed by IPC

Supersedes IPC-7351
February 2005

3000 Lakeside Drive, Suite 309S, Bannockburn, IL 60015-1249
Tel. 847.615.7100 Fax 847.615.7105
www.ipc.org

The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publication development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2872.

Thank you for your continued support.



ASSOCIATION CONNECTING
ELECTRONICS INDUSTRIES®

IPC-7351A

Generic Requirements for Surface Mount Design and Land Pattern Standard

Developed by the Surface Mount Land Patterns Subcommittee (1-13)
of the Printed Board Design Committee (1-10) of IPC

Supersedes:

IPC-7351 - February 2005

IPC-782A with
Amendments 1 & 2 -
December 1999

Users of this publication are encouraged to participate in the
development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 309S
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources. While the principal members of the Surface Mount Land Patterns Subcommittee (1-13) of the Printed Board Design Committee (1-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

Printed Board Design Committee

Chair
Lionel Fullwood
WKK Distribution, Ltd.

Surface Mount Land Patterns Subcommittee

Chair
Karen E. McConnell, C.I.D.
Lockheed Martin

Vice-Chair
Gary M. Ferrari C.I.D.+
FTG Circuits

Technical Liaisons of the IPC Board of Directors

Peter Bigelow
IMI Inc.

Sammy Yi
Flextronics International

Surface Mount Land Patterns Subcommittee

Jasbir Bath, Solectron Corporation
James Mark Bird, Amkor Technology Inc.
Phillip Chen, L-3 Communications Electronic Systems
Yves Desrochers, Flextronics
William C. Dieffenbacher, BAE Systems Platform Solutions
John Dusl, Lockheed Martin Information & Technlgy
Werner Engelmaier, Engelmaier Associates, L.C.
Howard S. Feldmesser, Johns Hopkins University
Michael R. Green, Lockheed Martin Space Systems Company

Thomas J. Hausherr, C.I.D.+, PCB Libraries Inc.
William Hazen, Raytheon Company
Frank N. Kimmey, C.I.D.+, PowerWave Technologies, Inc.
Narinder Kumar, C.I.D., Solectron Invotronics
Clifford H. Lamson, C.I.D.+, Plexus Technology Group
Wesley R. Malewicz, Draeger Medical Systems, Inc.
Kenneth J. Manning, Raytheon Company
Jeff Melquist, C.I.D.+, PCB Libraries

Frank Mortari, Texas Instruments Inc.
Deepak K. Pai, C.I.D.+, General Dynamics-Advanced Information
Jeff Shubrooks, Raytheon Company
JaMi Smith, C.I.D.
Vern Solberg, Micro Electronic Engineering Services
Rick Thompson, CTS Electronics Mfg. Solutions
Frank Williams, Jr., C.I.D., Harris Broadcast Communications Div.
James V. Yohe, C.I.D., Yohe Design Services
Michael W. Yuen, Foxconn EMS, Inc.

Table of Contents

1 SCOPE	1	3.5 Outer Layer Surface Finishes	32
1.1 Purpose	1	3.5.1 Solder Mask Finishes	32
1.2 Documentation Hierarchy	1	3.5.2 Solder Mask Clearances	32
1.2.1 Component and Land Pattern Family Structure	1	3.5.3 Land Pattern Surface Finishes	34
1.3 Performance Classification	2	4 COMPONENT QUALITY VALIDATION	36
1.3.1 Producibility Levels	2	4.1 Validation Techniques	36
1.4 Land Pattern Determination	2	5 TESTABILITY	37
1.5 Terms and Definitions	3	5.1 Board and Assembly Test	37
1.6 Revision Level Changes	5	5.1.1 Bare-Board Test	37
2 APPLICABLE DOCUMENTS	5	5.1.2 Assembled Board Test	37
2.1 IPC	5	5.2 Nodal Access	37
2.2 Electronic Industries Association	6	5.2.1 Test Philosophy	37
2.3 Joint Industry Standards (IPC)	6	5.2.2 Test Strategy for Bare Boards	38
2.4 International Electrotechnical Commission	6	5.3 Full Nodal Access on Assembled Board	38
2.5 Joint Electron Device Engineering Council (JEDEC)	6	5.3.1 In-Circuit Test Accommodation	39
3 DESIGN REQUIREMENTS	6	5.3.2 Multi-Probe Testing	39
3.1 Dimensioning Systems	6	5.4 Limited Nodal Access	39
3.1.1 Component Tolerancing	6	5.5 No Nodal Access	39
3.1.2 Land Tolerancing	9	5.6 Chamfer Fixtures Impact	39
3.1.3 Fabrication Allowances	10	5.7 Printed Board Test Characteristics	39
3.1.4 Assembly Tolerancing	10	5.7.1 Test Land Pattern Spacing	39
3.2 Design Producibility	20	5.7.2 Test Land Size and Shape	39
3.2.1 SMT Land Pattern	20	5.7.3 Design for Test Parameters	39
3.2.2 Standard Component Selection	20	6 PRINTED BOARD STRUCTURE TYPES	41
3.2.3 Circuit Substrate Development	20	6.1 General Considerations	41
3.2.4 Assembly Considerations	20	6.1.1 Categories	41
3.2.5 Provision for Automated Test	20	6.1.2 Thermal Expansion Mismatch	41
3.2.6 Documentation for SMT	20	6.2 Organic-Base Material	41
3.3 Environmental Constraints	20	6.3 Nonorganic Base Materials	41
3.3.1 Moisture Sensitive Components	20	6.4 Alternative Printed Board Structures	41
3.3.2 End-Use Environment Considerations	20	6.4.1 Supporting-Plane Printed Board Structures	41
3.4 Design Rules	22	6.4.2 High-Density Printed Board Technology	41
3.4.1 Component Spacing	22	6.4.3 Constraining Core Structures	41
3.4.2 Single- and Double-Sided Board Assembly	22	6.4.4 Porcelainized Metal (Metal Core) Structures	41
3.4.3 Component Stand-Off Height for Cleaning	24	7 ASSEMBLY CONSIDERATION FOR SURFACE MOUNT TECHNOLOGY (SMT)	44
3.4.4 Fiducial Marks	24	7.1 SMT Assembly Process Sequence	44
3.4.5 Conductors	26	7.2 Substrate Preparation	44
3.4.6 Via Guidelines	26	7.2.1 Adhesive Application	44
3.4.7 Standard Printed Board Fabrication Allowances	29	7.2.2 Conductive Adhesive	44
3.4.8 Panelization	31	7.2.3 Solder Paste Application	45
		7.2.4 Solder Preforms	45

7.3	Component Placement	45	8.5.4	Resistance to Soldering Process Temperature	52
7.3.1	Component Data Transfer	46	8.6	SOT23	52
7.4	Soldering Processes	46	8.6.1	Basic Construction	52
7.4.1	Wave Soldering	46	8.6.2	Marking	52
7.4.2	Vapor Phase (VP) Soldering	47	8.6.3	Carrier Package Format	52
7.4.3	IR Reflow Soldering	47	8.6.4	Resistance to Soldering Process Temperatures	52
7.4.4	Hot Air/Gas Convection Soldering	47	8.7	SOT89	53
7.4.5	Laser Reflow Soldering	47	8.7.1	Basic Construction	53
7.4.6	Conduction Reflow Soldering	47	8.7.2	Marking	53
7.5	Cleaning	47	8.7.3	Carrier Package Format	53
7.6	Repair/Rework	48	8.7.4	Resistance to Soldering Process Temperatures	53
7.6.1	Heatsink Effects	48	8.8	SOD123	53
7.6.2	Dependence on Printed Board Material Type	48	8.8.1	Basic Construction	53
7.6.3	Dependence on Copper Land and Conductor Layout	48	8.8.2	Marking	53
8	IPC-7352 DISCRETE COMPONENTS	49	8.8.3	Carrier Package Format	53
8.1	Chip Resistors (RESC)	49	8.8.4	Resistance to Soldering Process Temperatures	53
8.1.1	Basic Construction	49	8.9	SOD12	53
8.1.2	Marking	49	8.9.1	Basic Construction	54
8.1.3	Carrier Package	49	8.9.2	Marking	54
8.1.4	Resistance to Soldering Process Temperatures	49	8.9.3	Carrier Package Format	54
8.2	Chip Capacitors (CAPC)	50	8.9.4	Resistance to Soldering Process Temperatures	54
8.2.1	Basic Construction	50	8.10	SOT223	54
8.2.2	Marking	50	8.10.1	Basic Construction	54
8.2.3	Carrier Package	50	8.10.2	Marking	54
8.2.4	Resistance to Soldering Process Temperatures	50	8.10.3	Carrier Package Format	54
8.3	Inductors (INDC, INDM, INDL)	51	8.10.4	Resistance to Soldering Process Temperatures	54
8.3.1	Basic Construction	51	8.11	TO252 (DPAK Type)	54
8.3.2	Marking	51	8.11.1	Basic Construction	54
8.3.3	Carrier Package Format	51	8.11.2	Marking	54
8.3.4	Resistance to Soldering Process Temperatures	51	8.11.3	Carrier Package Format	54
8.4	Tantalum Capacitors (CAPT)	51	8.11.4	Resistance to Soldering Process Temperatures	54
8.4.1	Basic Construction	51	9	IPC-7353 GULLWING LEADED COMPONENTS, TWO SIDES	55
8.4.2	Marking	51	9.1	SOIC	55
8.4.3	Carrier Package Format	52	9.1.1	Basic Construction	55
8.4.4	Resistance to Soldering Process Temperatures	52	9.1.2	Marking	55
8.5	Metal Electrode Face Diodes (DIOMELF, RESMELF)	52	9.1.3	Carrier Package Format	55
8.5.1	Basic Construction	52	9.1.4	Resistance to Soldering Process Temperatures	56
8.5.2	Marking	52	9.2	SOP8/SOP63 (SSOIC)	56
8.5.3	Carrier Package Format	52	9.2.1	Basic Construction	56

9.2.2	Marking	56	13.3	Carrier Package Format	65
9.2.3	Carrier Package Format	56	13.4	Resistance to Soldering Process Temperatures	65
9.2.4	Resistance to Soldering Process Temperatures	56	14	IPC-7358 AREA ARRAY COMPONENTS (BGA, FBGA, CGA, LGA, Chip Array)	66
9.3	SOP127 (SOP-IPC-782)	56	14.1	Area Array Configurations	66
9.3.1	Marking	57	14.1.1	BGA Packages	66
9.3.2	Carrier Package Format	57	14.1.2	Fine Pitch BGA Package (FBGA)	67
9.3.3	Resistance to Soldering Process Temperatures	57	14.1.3	Ceramic Column Grid Arrays (CGA)	68
9.4	TSSOPS	57	14.1.4	Plastic Land Grid Arrays (LGA)	68
9.4.1	Marking	57	14.2	General Configuration Issues	68
9.4.2	Carrier Packages Format	57	14.2.1	Device Outlines	68
9.4.3	Resistance to Soldering Process Temperatures	57	14.2.2	Contact Matrix Options	68
9.5	CFP127	57	14.2.3	Selective Depopulation	69
9.5.1	Marking	58	14.2.4	Attachment Site Planning	69
9.5.2	Carrier Packages Format	58	14.2.5	Defining Contact Assignment	70
9.5.3	Resistance to Soldering Process Temperatures	58	14.3	Handling and Shipping	70
10	IPC-7354 J-LEADED COMPONENTS, TWO SIDES	58	14.4	Land Pattern Analysis	70
10.1	Basic Construction	58	14.4.1	Land Approximation	71
10.2	Marking	58	14.4.2	Total Variation	72
10.3	Carrier Package Format	58	14.4.3	Land Pattern Calculator	72
10.4	Process Considerations	59	14.5	Chip Array Component Lead Packages	72
11	IPC-7355 GULL-WING LEADED COMPONENTS, FOUR SIDES	60	14.5.1	Concave Chip Array Packages	72
11.1	BQFP (PQFP)	61	14.5.2	Convex Chip Array Packages	72
11.1.1	Carrier Package Format	61	14.5.3	Flat Chip Array Packages	73
11.2	SQFP/QFP	61	15	IPC-7359 NO LEAD COMPONENTS (QFN, PQFN, SON, PSON, LCC)	74
11.2.1	Carrier Package Format	61	15.1	LCC	74
11.3	QFPR	61	15.1.1	Marking	74
11.3.1	Carrier Package Format	61	15.1.2	Carrier Package Format	74
11.4	CQFP	61	15.1.3	Process Considerations	74
11.4.1	Carrier Package Format	62	15.2	Quad Flat No-Lead (QFN)	74
12	IPC-7356 J LEADED COMPONENTS, FOUR SIDES	62	15.2.1	Marking	76
12.1	PLCC	63	15.2.2	Carrier Package Format	76
12.1.1	Premolded Plastic Chip Carriers	63	15.2.3	Process Considerations	76
12.1.2	Postmolded Plastic Chip Carriers	63	15.2.4	Solder Mask Considerations	76
12.2	PLCCR	64	15.3	Small Outline No-Lead (SON)	76
12.2.1	Premolded Plastic Chip Carriers	64	15.3.1	Marking	76
12.2.2	Postmolded Plastic Chip Carriers	64	15.3.2	Carrier Package Format	77
13	IPC-7357 POST (DIP) LEADS, TWO SIDES	64	15.3.3	Process Considerations	77
13.1	Termination Materials	64	15.3.4	Solder Mask Considerations	77
13.2	Marking	65	15.4	Small Outline and Quad Flat No Lead with Pullback Leads (PQFN, PSON)	77
			16	ZERO COMPONENT ORIENTATIONS	77

APPENDIX A (Informative) Test Patterns - Process Evaluations	83	Figure 8-6 Metal Electrode Face Component Construction	52
APPENDIX B (Informative) Abbreviations and Definitions	85	Figure 8-7 Break-Away Diagram of MELF Components	52
APPENDIX C IPC-7351 Land Pattern Viewer	86	Figure 8-8 SOT23 Construction	53
Figures			
Figure 3-1 Profile Tolerancing Method	7	Figure 8-9 SOT89 Construction	53
Figure 3-2 Example of 3216 (1206) Capacitor Dimensioning for Optimum Solder Fillet Condition	8	Figure 8-10 SOD123 Construction	53
Figure 3-3 Profile Dimensioning of Gull-Wing Leaded SOIC	9	Figure 8-11 SOT143 Construction	54
Figure 3-4 Pitch for Multiple Leaded Components	11	Figure 8-12 SOT223 Construction	54
Figure 3-5 Courtyard Boundary Area Condition	17	Figure 8-13 TO252 (DPAK Type) Construction	54
Figure 3-6 Component Orientation for Wave-Solder Applications	23	Figure 9-1 SOIC Construction	55
Figure 3-7 Alignment of Similar Components	23	Figure 9-2 SOP8/SOP63 Construction	56
Figure 3-8 Panel/Local Fiducials	24	Figure 9-3 SOP127 Construction	57
Figure 3-9 Local Fiducials	25	Figure 9-4 TSSOP Construction	57
Figure 3-10 Fiducial Locations on a Printed Board	25	Figure 9-5 CFP127 Construction	57
Figure 3-11 Fiducial Size and Clearance Requirements	26	Figure 10-1 SOJ Construction	58
Figure 3-12 Use of Vias in High Component Density Printed Circuit Boards	27	Figure 11-1 BQFP Construction	61
Figure 3-13 Conductor Routing Capability Test Pattern	27	Figure 11-2 SQFP and QFP Construction	61
Figure 3-14 Land Pattern to Via Relationship	28	Figure 11-3 QFN Construction	61
Figure 3-15 Examples of Via Positioning Concepts	28	Figure 11-4 CQFP Construction	62
Figure 3-16 Vias Under Components	29	Figure 12-1 PLCC Construction	63
Figure 3-17 Filled and Capped Via Structure	29	Figure 12-2 PLCCR Construction	64
Figure 3-18 Via-in-Pad Process Description	29	Figure 13-1 DIP Construction	64
Figure 3-19 Conductor Description	30	Figure 14-1 Ball Grid Array (BGA) IC Package Example	66
Figure 3-20 Examples of Modified Landscapes	31	Figure 14-2 Example of Plastic BGA Package Configurations	66
Figure 3-21 Typical Copper Glass Laminate Panel	32	Figure 14-3 Ceramic Column Grid Array (CGA) Package (Cross-Sectional View)	68
Figure 3-22 Conductor Clearance for V-Cut Scoring	33	Figure 14-4 Plastic Land Grid Array (LGA) Package Construction	68
Figure 3-23 Breakaway (Routed Pattern) with Routed Slots	33	Figure 14-5 Bottom View of BGA Devices	69
Figure 3-24 Gang Solder Mask Window	34	Figure 14-6 One Package Size, Two Full Matrices	69
Figure 3-25 Pocket Solder Mask Window	34	Figure 14-7 Perimeter and Thermally Enhanced Matrices	70
Figure 4-1 Component Operating Temperature Limits	36	Figure 14-8 Staggered Matrix	70
Figure 5-1 Test Via Grid Concepts	38	Figure 14-9 Selective Depopulation	70
Figure 5-2 General Relationship Between Test Contact Size and Test Probe Misses	40	Figure 14-10 Device Orientation and Contact A1 Position	71
Figure 5-3 Test Probe Feature Distance from Component	40	Figure 14-11 Side Concave Chip Component	72
Figure 7-1 Typical Process Flow for One-Sided SMT	44	Figure 14-12 Corner Concave Chip Component	73
Figure 7-2 Assembly Process Flow for Two-Sided Surface Mount with PIH	45	Figure 14-13 Convex Chip Component "E Version"	73
Figure 8-1 Packaging of Discrete Components	49	Figure 14-14 Convex Chip Component "S Version"	73
Figure 8-2 Chip Resistor Construction	50	Figure 14-15 Flat Chip Component	73
Figure 8-3 Chip Capacitor Construction	51	Figure 15-1 LCC Component	74
Figure 8-4 Inductor Construction	51	Figure 15-2 Quad Flat No-Lead (QFN) Construction	75
Figure 8-5 Tantalum Capacitor Construction	52	Figure 15-3 Quad Flat No-Lead (QFN) Construction (Cross-Sectional View)	76
		Figure 15-4 Small Outline No-Lead (SON) Construction	76

Figure 15-5 Pullback Quad Flat No Lead (PQFN) and Small Outline No Lead (PSON) Construction 77

Figure 16-1 Zero Component Rotations for Common Package Outlines 78

Figure A-1 General Description of Process Validation Contact Pattern and Interconnect 83

Figure A-2 Photoimage of IPC-A-49 Test Board for Primary Side 84

Tables

Table 3-1 Tolerance Analysis Elements for Chip Devices 12

Table 3-2 Flat Ribbon L and Gull-Wing Leads (greater than 0.625 mm pitch) (unit: mm) 12

Table 3-3 Flat Ribbon L and Gull-Wing Leads (less than or equal to 0.625 mm pitch) (unit: mm) 13

Table 3-4 J Leads (unit: mm) 13

Table 3-5 Rectangular or Square-End Components (Capacitors and Resistors) Equal to or Larger than 1608 (0603) (unit: mm) 13

Table 3-6 Rectangular or Square-End Components (Capacitors and Resistors) Smaller than 1608 (0603) (unit: mm) 14

Table 3-7 Cylindrical End Cap Terminations (MELF) (unit: mm) 14

Table 3-8 Bottom Only Terminations (unit: mm) 14

Table 3-9 Leadless Chip Carrier with Castellated Terminations (unit: mm) 14

Table 3-10 Concave Chip Array Component Lead Package (unit: mm) 14

Table 3-11 Convex Chip Array Component Lead Package (unit: mm) 14

Table 3-12 Flat Chip Array Component Lead Package (unit: mm) 15

Table 3-13 Butt Joints (unit: mm) 15

Table 3-14 Inward Flat Ribbon L-Leads (Molded Inductors, Diodes & Polarized Capacitors) (unit: mm) 15

Table 3-15 Flat Lug Leads (unit: mm) 15

Table 3-16 Quad Flat No-Lead (unit: mm) 15

Table 3-17 Small Outline No-Lead (unit: mm) 15

Table 3-18 Ball Grid Array Components (unit: mm) 16

Table 3-19 Small Outline and Quad Flat No-Lead with Pullback Leads (unit: mm) 16

Table 3-20 Corner Concave Component Oscillator Lead Package (unit: mm) 16

Table 3-21 IPC-7351 Land and Pattern Naming Convention 18

Table 3-22 Product Categories and Worst-Case Case Environments for Surface Mounted Electronics (For Reference Only) 21

Table 3-23 Conductor Width Tolerances, 0.046 mm [0.00181 in] Copper, mm [in] 30

Table 3-24 Feature Location Accuracy (units: mm [in]) 30

Table 3-25 Key Attributes for Various Board Surface Finishes 35

Table 6-1 Printed Board Structure Comparison 42

Table 6-2 PCB Structure Selection Considerations 43

Table 6-3 PCB Structure Material Properties 43

Table 8-1 Solderability Tests for Discrete Components 49

Table 8-2 Solderability, Bath Method: Test Severities (duration and temperature) 50

Table 8-3 Package Peak Reflow Temperatures 50

Table 9-1 Solderability Tests for Gullwing Leaded Components, Two Sides 55

Table 9-2 Solderability, Bath Method: Test Severities (duration and temperature) 56

Table 9-3 Package Peak Reflow Temperatures 56

Table 10-1 Solderability Tests for J-Leaded Components, Two Sides 58

Table 10-2 Solderability, Bath Method: Test Severities (duration and temperature) 59

Table 10-3 Package Peak Reflow Temperatures 59

Table 11-1 Solderability Tests for Gullwing Components, Four Sides 60

Table 11-2 Solderability, Bath Method: Test Severities (duration and temperature) 60

Table 11-3 Package Peak Reflow Temperatures 61

Table 12-1 Solderability Tests for J-Leaded Components, Four Sides 62

Table 12-2 Solderability, Bath Method: Test Severities (duration and temperature) 63

Table 12-3 Package Peak Reflow Temperatures 63

Table 13-1 Solderability Tests for Post (DIP) Leads, Two Sides 65

Table 13-2 Solderability, Bath Method: Test Severities (duration and temperature) 65

Table 13-3 Package Peak Reflow Temperatures 65

Table 14-1 Solderability Tests for Discrete Components 67

Table 14-2 Package Peak Reflow Temperatures 67

Table 14-3 JEDEC Standard JEP95 Allowable Ball Diameter Variations for FBGA (mm) 67

Table 14-4 Ball Diameter Sizes (mm) 71

Table 14-5 Land Approximation (mm) for Collapsible Solder Balls 71

Table 14-6 Land Approximation (mm) for Noncollapsible Solder Balls 71

Table 14-7 BGA Variation Attributes (mm) 72

Table 14-8 Land-to-Ball Calculations for Current and Future BGA Packages (mm) 72

Table 15-1 Solderability Tests for No Lead Components ... 74

Table 15-2 Solderability, Bath Method: Test Severities (duration and temperature) 75

Table 15-3 Package Peak Reflow Temperatures 75

Generic Requirements for Surface Mount Design and Land Pattern Standard

1 SCOPE

This document provides information on land pattern geometries used for the surface attachment of electronic components. The intent of the information presented herein is to provide the appropriate size, shape and tolerance of surface mount land patterns to insure sufficient area for the appropriate solder fillet to meet the requirements of IPC J-STD-001, and also to allow for inspection, testing, and rework of those solder joints.

1.1 Purpose Although, in many instances, the land pattern geometries can be different based on the type of soldering used to attach the electronic part, wherever possible, land patterns are defined with consideration to the attachment process being used. Designers can use the information contained herein to establish standard configurations not only for manual designs but also for computer-aided design systems. Whether parts are mounted on one or both sides of the board, subjected to wave, reflow, or other type of soldering, the land pattern and part dimensions should be optimized to insure proper solder joint and inspection criteria.

Land patterns are dimensionally defined and are a part of the printed board circuitry geometry, as they are subject to the producibility levels and tolerances associated with plating, etching, assembly or other conditions. The producibility aspects also pertain to the use of solder mask and the registration required between the solder mask and the conductor patterns.

Note 1: The dimensions used for component descriptions have been extracted from standards developed by industrial and/or standards bodies. Designers should refer to these standards for additional or specific component package dimensions.

Note 2: For a comprehensive description of the given printed board and for achieving the best possible solder joints to the devices assembled, the whole set of design elements includes, beside the land pattern definition:

- Soldermask
- Solder paste stencil
- Clearance between adjacent components
- Clearance between bottom of component and printed board surface, if relevant
- Keepout areas, if relevant
- Suitable rules for adhesive applications

The whole of design elements is commonly defined as “mounting conditions.” This standard defines land patterns

and includes recommendations for clearances between adjacent components and for other design elements.

Note 3: Elements of the mounting conditions, particularly the courtyard, given in this standard are related to the reflow soldering process. Adjustments for wave or other soldering processes, if applicable, have to be carried out by the user. This may also be relevant when solder alloys other than eutectic tin lead solders are used.

Note 4: This standard assumes that the land pattern follows the principle that, even under worst case conditions, the overlap of the component termination and the corresponding soldering land will be complete.

Note 5: Heat dissipation aspects have not been taken into account in this standard. Greater mass may require slower process speed to allow heat transfer.

Note 6: Heavier components (greater weight per land) require larger lands; thus, adding additional land pattern surface will increase surface area of molten solder to enhance capabilities of extra weight. In some cases the lands shown in the standard may not be large enough; in these cases, considering additional measures may be necessary.

1.2 Documentation Hierarchy This standard identifies the generic physical design principles involved in the creation of land patterns for surface mount components, and is supplemented by a shareware IPC-7351 Land Pattern viewer that provides, through the use of a graphical user interface, the individual component dimensions and corresponding land pattern recommendations based upon families of components. The IPC-7351 Land Pattern Viewer is provided on CD-ROM as part of this standard. Updates to land pattern dimensions, including patterns for new component families, can be found on the IPC website (www.ipc.org) under “PCB Tools and Calculators.” See Appendix C for more information on the IPC-7351 Land Pattern Viewer.

1.2.1 Component and Land Pattern Family Structure

The IPC-7351 provides the following number designation within this standard for each major family of surface mount components to indicate similarities in solder joint engineering goals:

IPC-7352 – Discrete Components (CAP, RES, IND, DIO, LED)

IPC-7353 – Gullwing Leaded Components, Two Sides (SOP, SOIC, SOD, SOT, TO)