




IPC-HERMES-9852
Version 1.2



IPC-HERMES-9852

The Global Standard for Machine-to-Machine Communication in SMT Assembly

Developed by The Hermes Standard Initiative and approved by IPC

Supersedes:
HERMES-9852 Version 1.1

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

IPC

Figure 10	Communication Sequence in Scenario U3	10
Figure 11	Communication Sequence in Scenario D1	11
Figure 12	Communication Sequence in Scenario D2	12
Figure 13	Communication Sequence in Scenario D3	13
Figure 14	Example of Communication Sequence for BoardForecast	14
Figure 15	Example of Communication Sequence for BoardForecast with RevokeMachineReady	14
Figure 16	Example of Communication Sequence with Several BoardForecast	15
Figure 17	Example of Communication Sequence in Case with Error Handling	16
Figure 18	Example of Communication Sequence BoardForecast Without Product Change	16
Figure 19	Hermes Interface States on Horizontal Channel	17
Figure 20	Connection, Handshake and Connection Loss Detection on Vertical Channel	19
Figure 21	Example for Connection Loss Detection with FeatureCheckAliveResponse on Vertical Channel	20
Figure 22	Hermes Interface States on Vertical Channel	21
Figure 23	Explanation for Top and Bottom Clearance Height.....	25
Figure 24	Line Setup with Barcode Readers and Repair Station	37
Figure 25	Line Setup with Fixed and Mobile Barcode Readers	38

The Global Standard for Machine-to-Machine Communication in SMT Assembly

1 SCOPE

The aim of this specification is to create a state-of-the-art communication protocol for surface-mount technology (SMT) production lines. Therefore, this new communication protocol has to cope with the following:

- Replace the electrical SMEMA interface as specified in IPC-SMEMA-9851
- Extend the interface to communicate (including):
 - Unique identifiers (IDs) for the handled printed boards
 - Equipment identifiers of the first machine noticing a printed board
 - Barcodes
 - Conveyor speed
 - Product type specific information (including):
 - Product type identifier
 - Length
 - Width
 - Thickness

With respect to version numbers IPC-HERMES-9852 adheres to the rules of Semantic Versioning 2.0.0 (SemVer_2.0.0).

Hints on naming

- Wherever a feature is described by the word “**shall**” it is mandatory.
- The word “machine” is used for any equipment which can be found in a SMT production line (e.g., printers, placement machines, ovens, automatic optical inspections (AOIs), transport modules, shuttles, stackers, etc.).
- The term “printed board” may also refer to carriers transporting printed boards.
- The word “Hermes” is used as abbreviation for “IPC-HERMES-9852”.
- “The Hermes Standard” and IPC-HERMES-9852 are synonyms for the standard specified in this document and might be used interchangeably.