



**IPC J-STD-001**  
**Revision F with Amendment 1**

# **Requirements for Soldered Electrical and Electronic Assemblies**

If a conflict occurs between the English and translated versions of this document, the English version will take precedence.

A joint standard developed by the J-STD-001 development team including Task Group Europe (5-22A), Task Group Asia (5-22ACN) and Task Group India (5-22AIN) of the Assembly and Joining Committees (5-20 and 5-21) of IPC.

Users of this publication are encouraged to participate in the development of future revisions.

Contact:  
**IPC**

## Table of Contents

|  |   |   |    |
|--|---|---|----|
| <b>1 GENERAL</b> .....                               | 1 | <b>3 MATERIALS, COMPONENTS AND EQUIPMENT REQUIREMENTS</b> ..... | 7  |
| 1.1 Scope .....                                      | 1 | 3.1 Materials .....   | 7  |
| 1.2 Purpose .....                                    | 1 | 3.2 Solder .....  | 7  |
| 1.3 Classification .....                             | 1 | 3.2.1 Solder – Lead Free .....                                  | 7  |
| 1.4 Measurement Units and Applications .....         | 1 | 3.2.2 Solder Purity Maintenance .....                           | 7  |
| 1.4.1 Verification of Dimensions .....               | 1 | 3.3 Flux .....  | 8  |
| 1.5 Definition of Requirements .....                 | 2 | 3.3.1 Flux Application .....                                    | 8  |
| 1.5.1 Hardware Defects and Process Indicators .....  | 2 | 3.4 Solder Paste .....  | 8  |
| 1.5.2 Material and Process Nonconformance .....      | 2 | 3.5 Solder Preforms .....                                       | 8  |
| 1.6 General Requirements .....                       | 3 | 3.6 Adhesives .....   | 8  |
| 1.7 Order of Precedence .....                        | 3 | 3.7 Chemical Strippers .....                                    | 8  |
| 1.7.1 Conflict .....                                 | 3 | 3.8 Components .....  | 9  |
| 1.7.2 Clause References .....                        | 3 | 3.8.1 Component and Solder Damage .....                         | 9  |
| 1.7.3 Appendices .....                               | 3 | 3.8.2 Coating Processes .....                                   | 9  |
| 1.8 Terms and Definitions .....                      | 3 | 3.9 Soldering Tools and Equipment .....                         | 9  |
| 1.8.1 Disposition .....                              | 3 | <b>4 GENERAL SOLDERING AND ASSEMBLY REQUIREMENTS</b> .....      | 9  |
| 1.8.2 Electrical Clearance .....                     | 3 | 4.1 Electrostatic Discharge (ESD) .....                         | 9  |
| 1.8.3 FOD (Foreign Object Debris) .....              | 3 | 4.2 Facilities .....  | 9  |
| 1.8.4 High Voltage .....                             | 4 | 4.2.1 Environmental Controls .....                              | 9  |
| 1.8.5 Manufacturer (Assembler) .....                 | 4 | 4.2.2 Temperature and Humidity .....                            | 9  |
| 1.8.6 Objective Evidence .....                       | 4 | 4.2.3 Lighting .....  | 10 |
| 1.8.7 Process Control .....                          | 4 | 4.2.4 Field Assembly Operations .....                           | 10 |
| 1.8.8 Proficiency .....                              | 4 | 4.3 Solderability .....   | 10 |
| 1.8.9 Solder Destination Side .....                  | 4 | 4.4 Solderability Maintenance .....                             | 10 |
| 1.8.10 Solder Source Side .....                      | 4 | 4.5 Removal of Component Surface Finishes .....                 | 10 |
| 1.8.11 Supplier .....                                | 4 | 4.5.1 Gold Removal .....  | 10 |
| 1.8.12 User .....                                    | 4 | 4.5.2 Other Metallic Surface Finishes Removal .....             | 10 |
| 1.8.13 Wire Overwrap .....                           | 4 | 4.6 Thermal Protection .....                                    | 10 |
| 1.8.14 Wire Overlap .....                            | 4 | 4.7 Rework of Nonsolderable Parts .....                         | 11 |
| 1.9 Requirements Flowchart .....                     | 4 | 4.8 Preprocessing Cleanliness Requirements .....                | 11 |
| 1.10 Personnel Proficiency .....                     | 5 | 4.9 General Part Mounting Requirements .....                    | 11 |
| 1.11 Acceptance Requirements .....                   | 5 | 4.9.1 General Requirements .....                                | 11 |
| 1.12 General Assembly Requirements .....             | 5 | 4.9.2 Lead Deformation Limits .....                             | 11 |
| 1.13 Miscellaneous Requirements .....                | 5 | 4.10 Hole Obstruction .....                                     | 11 |
| 1.13.1 Health and Safety .....                       | 5 | 4.11 Metal-Cased Component Isolation .....                      | 11 |
| 1.13.2 Procedures for Specialized Technologies ..... | 5 | 4.12 Adhesive Coverage Limits .....                             | 11 |
| <b>2 APPLICABLE DOCUMENTS</b> .....                  | 6 | 4.13 Mounting of Parts on Parts (Stacking of Components) .....  | 11 |
| 2.1 EIA .....  | 6 | 4.14 Connectors and Contact Areas .....                         | 11 |
| 2.2 IPC .....  | 6 | 4.15 Handling of Parts .....                                    | 11 |
| 2.3 Joint Industry Standards .....                   | 7 |   |    |
| 2.4 ASTM .....                                       | 7 |   |    |
| 2.5 Electrostatic Discharge Association .....        | 7 |   |    |

|          |  |           |          |  |           |
|----------|--|-----------|----------|--|-----------|
| 4.15.1   | Preheating .....   | 11        | 5.6.3    | Wire Staking .....   | 21        |
| 4.15.2   | Controlled Cooling .....                                   | 12        | 5.6.4    | Unpopulated Land or Via – Lap Soldered .....                                 | 22        |
| 4.15.3   | Drying/Degassing .....                                     | 12        | 5.6.5    | Supported Holes .....  | 22        |
| 4.15.4   | Holding Devices and Materials .....                        | 12        | 5.6.6    | SMT .....  | 22        |
| 4.16     | Machine (Nonreflow) Soldering .....                        | 12        | <b>6</b> | <b>THROUGH-HOLE MOUNTING AND TERMINATIONS .....</b>                          | <b>23</b> |
| 4.16.1   | Machine Controls .....                                     | 12        | 6.1      | Through-Hole Terminations – General .....                                    | 23        |
| 4.16.2   | Solder Bath .....  | 12        | 6.1.1    | Lead Forming .....   | 24        |
| 4.17     | Reflow Soldering .....                                     | 12        | 6.1.2    | Termination Requirements .....   | 24        |
| 4.17.1   | Intrusive Soldering (Paste-in-Hole) .....                  | 12        | 6.1.3    | Lead Trimming .....  | 25        |
| 4.18     | Solder Connection .....                                    | 12        | 6.1.4    | Interfacial Connections .....  | 25        |
| 4.18.1   | Exposed Surfaces .....                                     | 13        | 6.1.5    | Coating Meniscus In Solder .....   | 25        |
| 4.18.2   | Solder Connection Anomalies .....                          | 13        | 6.2      | Supported Holes .....  | 26        |
| 4.18.3   | Partially Visible or Hidden Solder Connections .....       | 13        | 6.2.1    | Solder Application .....   | 26        |
| 4.19     | Heat Shrinkable Soldering Devices .....                    | 14        | 6.2.2    | Through-Hole Component Lead Soldering .....                                  | 26        |
| <b>5</b> | <b>WIRES AND TERMINAL CONNECTIONS .....</b>                | <b>14</b> | 6.3      | Unsupported Holes .....  | 26        |
| 5.1      | Wire and Cable Preparation .....                           | 14        | 6.3.1    | Lead Termination Requirements for Unsupported Holes .....                    | 26        |
| 5.1.1    | Insulation Damage .....                                    | 14        | <b>7</b> | <b>SURFACE MOUNTING OF COMPONENTS .....</b>                                  | <b>27</b> |
| 5.1.2    | Strand Damage .....  | 14        | 7.1      | Surface Mount Device Lead .....  | 27        |
| 5.1.3    | Tinning of Stranded Wire .....                             | 14        | 7.1.1    | Plastic Components .....   | 27        |
| 5.2      | Solder Terminals .....                                     | 15        | 7.1.2    | Forming .....  | 27        |
| 5.3      | Bifurcated, Turret and Slotted Terminal Installation ..... | 15        | 7.1.3    | Unintentional Bending .....  | 28        |
| 5.3.1    | Shank Damage .....   | 15        | 7.1.4    | Flat Pack Parallelism .....  | 28        |
| 5.3.2    | Flange Damage .....  | 15        | 7.1.5    | Surface Mount Device Lead Bends .....  | 28        |
| 5.3.3    | Flared Flange Angles .....                                 | 15        | 7.1.6    | Flattened Leads .....  | 28        |
| 5.3.4    | Terminal Mounting – Mechanical .....                       | 15        | 7.1.7    | Parts Not Configured for Surface Mounting ...                                | 28        |
| 5.3.5    | Terminal Mounting – Electrical .....                       | 15        | 7.2      | Leaded Component Body Clearance .....  | 28        |
| 5.3.6    | Terminal Mounting – Soldering .....                        | 15        | 7.2.1    | Axial-Leaded Components .....  | 28        |
| 5.4      | Mounting to Terminals .....                                | 16        | 7.3      | Parts Configured for Butt/I Lead Mounting ...                                | 28        |
| 5.4.1    | General Requirements .....                                 | 16        | 7.4      | Hold Down of Surface Mount Leads/Components .....                            | 28        |
| 5.4.2    | Turret and Straight Pin Terminals .....                    | 18        | 7.5      | Soldering Requirements .....   | 28        |
| 5.4.3    | Bifurcated Terminals .....                                 | 18        | 7.5.1    | Misaligned Components .....  | 29        |
| 5.4.4    | Slotted Terminals .....                                    | 19        | 7.5.2    | Unspecified and Special Requirements .....                                   | 29        |
| 5.4.5    | Hook Terminals .....                                       | 20        | 7.5.3    | Bottom Only Chip Component Terminations .....                                | 30        |
| 5.4.6    | Pierced or Perforated Terminals .....                      | 20        | 7.5.4    | Rectangular or Square End Chip Components – 1, 3 or 5 Side Termination ..... | 31        |
| 5.4.7    | Cup and Hollow Cylindrical Terminals – Placement .....     | 21        | 7.5.5    | Cylindrical End Cap Terminations .....                                       | 32        |
| 5.5      | Soldering to Terminals .....                               | 21        | 7.5.6    | Castellated Terminations .....   | 33        |
| 5.5.1    | Bifurcated Terminals .....                                 | 21        | 7.5.7    | Flat Gull Wing Leads .....   | 34        |
| 5.5.2    | Slotted Terminal .....                                     | 21        | 7.5.8    | Round or Flattened (Coined) Gull Wing Leads .....                            | 35        |
| 5.5.3    | Cup and Hollow Cylindrical Terminals – Soldering .....     | 21        | 7.5.9    | J-Lead Terminations .....  | 36        |
| 5.6      | Jumper Wires .....   | 21        |          |  |           |
| 5.6.1    | Insulation .....   | 21        |          |  |           |
| 5.6.2    | Wire Routing .....   | 21        |          |  |           |


|           |  |    |                   |   |    |
|-----------|--|----|-------------------|---|----|
| 7.5.10    | Butt/I Terminations .....  | 37 | 10.2              | Conformal Coating – Masking .....   | 51 |
| 7.5.11    | Flat Lug Leads .....   | 39 | 10.3              | Conformal Coating – Application .....   | 51 |
| 7.5.12    | Tall Profile Components Having Bottom<br>Only Terminations .....   | 40 | 10.3.1            | Conformal Coating on Components .....   | 51 |
| 7.5.13    | Inward Formed L-Shaped Ribbon Leads .....                          | 41 | 10.3.2            | Thickness .....   | 52 |
| 7.5.14    | Surface Mount Area Array Packages .....                            | 42 | 10.3.3            | Uniformity .....  | 52 |
| 7.5.15    | Bottom Termination Components (BTC) .....                          | 44 | 10.3.4            | Transparency .....  | 52 |
| 7.5.16    | Components with Bottom Thermal Plane<br>Terminations (D-Pak) ..... | 45 | 10.3.5            | Bubbles and Voids .....   | 52 |
| 7.5.17    | Flattened Post Connections .....                                   | 46 | 10.3.6            | Delamination .....  | 52 |
| 7.5.18    | P-Style Terminations .....   | 47 | 10.3.7            | Foreign Objects Debris .....  | 52 |
| 7.6       | Specialized SMT Terminations .....                                 | 47 | 10.3.8            | Other Visual Conditions .....   | 52 |
| <b>8</b>  | <b>CLEANING PROCESS REQUIREMENTS</b> .....                         | 48 | 10.3.9            | Inspection .....  | 52 |
| 8.1       | Cleanliness Exemptions .....                                       | 48 | 10.3.10           | Rework or Touchup of Conformal Coating .....  | 53 |
| 8.2       | Ultrasonic Cleaning .....  | 48 | 10.4              | Encapsulation .....   | 53 |
| 8.3       | Post-Solder Cleanliness .....                                      | 48 | 10.4.1            | Application .....   | 53 |
| 8.3.1     | Foreign Object Debris (FOD) .....                                  | 48 | 10.4.2            | Performance Requirements .....  | 53 |
| 8.3.2     | Flux Residues and Other Ionic or Organic<br>Contaminants .....     | 48 | 10.4.3            | Rework of Encapsulated Material .....   | 53 |
| 8.3.3     | Post-Soldering Cleanliness Designator .....                        | 48 | 10.4.4            | Encapsulant Application .....   | 53 |
| 8.3.4     | Cleaning Option .....  | 48 | 10.5              | Staking .....   | 53 |
| 8.3.5     | Test for Cleanliness .....   | 48 | 10.5.1            | Staking – Application .....   | 53 |
| 8.3.6     | Testing .....  | 49 | 10.5.2            | Staking – Adhesive .....  | 54 |
| <b>9</b>  | <b>PCB REQUIREMENTS</b> .....                                      | 50 | 10.5.3            | Staking – Inspection .....  | 54 |
| 9.1       | Printed Circuit Board Damage .....                                 | 50 | <b>11</b>         | <b>WITNESS (TORQUE/ANTI-TAMPERING)<br/>STRIPE</b> .....                                 | 54 |
| 9.1.1     | Blistering/Delamination .....                                      | 50 | <b>12</b>         | <b>PRODUCT ASSURANCE</b> .....  | 54 |
| 9.1.2     | Weave Exposure/Cut Fibers .....                                    | 50 | 12.1              | Hardware Defects Requiring Disposition .....  | 54 |
| 9.1.3     | Haloing .....  | 50 | 12.2              | Inspection Methodology .....  | 54 |
| 9.1.4     | Edge Delamination .....  | 50 | 12.2.1            | Process Verification Inspection .....   | 54 |
| 9.1.5     | Land/Conductor Separation .....                                    | 50 | 12.2.2            | Visual Inspection .....   | 55 |
| 9.1.6     | Land/Conductor Reduction in Size .....                             | 50 | 12.2.3            | Sampling Inspection .....   | 55 |
| 9.1.7     | Flexible Circuitry Deformation .....                               | 50 | 12.3              | Process Control Requirements .....  | 55 |
| 9.1.8     | Flexible Circuitry Damage .....                                    | 50 | 12.3.1            | Opportunities Determination .....   | 55 |
| 9.1.9     | Burns .....  | 50 | 12.4              | Statistical Process Control .....   | 56 |
| 9.1.10    | Non-Soldered Edge Contacts .....                                   | 50 | <b>13</b>         | <b>REWORK AND REPAIR</b> .....  | 56 |
| 9.1.11    | Measles .....  | 50 | 13.1              | Rework .....  | 56 |
| 9.1.12    | Crazing .....  | 51 | 13.2              | Repair .....  | 56 |
| 9.2       | Marking .....  | 51 | 13.3              | Post Rework/Repair Cleaning .....   | 56 |
| 9.3       | Bow and Twist (Warpage) .....                                      | 51 | <b>APPENDIX A</b> | <b>Guidelines for Soldering Tools<br/>and Equipment</b> .....                           | 57 |
| 9.4       | Depanelization .....   | 51 | <b>APPENDIX B</b> | <b>Minimum Electrical Clearance –<br/>Electrical Conductor Spacing</b> .....            | 59 |
| <b>10</b> | <b>COATING, ENCAPSULATION AND STAKING<br/>(ADHESIVE)</b> .....     | 51 | <b>APPENDIX C</b> | <b>J-STD-001 Guidance on<br/>Objective Evidence of<br/>Material Compatibility</b> ..... | 61 |
| 10.1      | Conformal Coating – Materials .....                                | 51 |                   |   |    |


| <b>Figures</b> |  |    |               |   |    |
|----------------|--|----|---------------|---|----|
| Figure 1-1     | Overwrap .....   | 4  | Figure 7-17   | Bottom Thermal Plane Termination .....  | 45 |
| Figure 1-2     | Overlap .....  | 4  | Figure 7-18   | Flattened Post Termination .....  | 46 |
| Figure 4-1     | Hole Obstruction .....   | 11 | Figure 7-19   | P-Style Termination .....   | 47 |
| Figure 4-2     | Acceptable Wetting Angles .....  | 13 |               |   |    |
| Figure 5-1     | Flange Damage .....  | 15 | <b>Tables</b> |   |    |
| Figure 5-2     | Flare Angles .....   | 15 | Table 1-1     | Design, Fabrication and Acceptability<br>Specification .....  | 3  |
| Figure 5-3     | Terminal Mounting – Mechanical .....   | 16 | Table 3-1     | Maximum Limits of Solder Bath Contaminant ....  | 8  |
| Figure 5-4     | Terminal Mounting .....  | 16 | Table 4-1     | Solder Anomalies .....  | 13 |
| Figure 5-5     | Insulation Clearance Measurement .....   | 16 | Table 5-1     | Allowable Strand Damage .....   | 15 |
| Figure 5-6     | Service Loop for Lead Wiring .....   | 17 | Table 5-2     | Terminal Mounting Minimum Soldering<br>Requirements .....   | 16 |
| Figure 5-7     | Stress Relief Examples .....   | 17 | Table 5-3     | Turret and Straight Pin Wire Placement .....  | 18 |
| Figure 5-8     | Wire and Lead Wrap Around .....  | 18 | Table 5-4     | AWG 30 and Smaller Wire Wire<br>Requirements .....  | 18 |
| Figure 5-9     | Bifurcated Terminal Side Route Placement<br>with Wrap .....                    | 18 | Table 5-5     | Bifurcated Terminal Wire Placement –<br>Side Route with Wrap .....  | 18 |
| Figure 5-10    | Bifurcated Terminal Side Route Placement –<br>Straight Though and Staked ..... | 19 | Table 5-6     | Bifurcated Terminal Side Route<br>Straight-Through Soldering Requirements .....                           | 19 |
| Figure 5-11    | Bifurcated Terminal Top and Bottom Route<br>Connection .....                   | 19 | Table 5-7     | Bifurcated Terminal Wire Placement –<br>Bottom Route .....  | 19 |
| Figure 5-12    | Slotted Terminal .....   | 19 | Table 5-8     | Hook Terminal Wire Placement .....  | 20 |
| Figure 5-13    | Hook Terminal Connections .....  | 20 | Table 5-9     | Pierced or Perforated Terminal Wire<br>Placement .....  | 20 |
| Figure 5-14    | Pierced or Perforated Terminal Wire<br>Placement .....                         | 20 | Table 5-10    | Solder Requirements Wire to Post .....  | 21 |
| Figure 5-15    | Solder Height .....  | 21 | Table 6-1     | Component to Land Clearance .....   | 23 |
| Figure 6-1     | Component Lead Stress Relief Examples ....                                     | 23 | Table 6-2     | Components with Spacers .....   | 23 |
| Figure 6-2     | Lead Bends .....   | 24 | Table 6-3     | Lead Bend Radius .....  | 24 |
| Figure 6-3     | Lead Trimming .....  | 25 | Table 6-4     | Protrusion of Leads in Supported Holes .....  | 24 |
| Figure 6-4     | Vertical Fill Example .....  | 25 | Table 6-5     | Protrusion of Leads in Unsupported Holes .....  | 24 |
| Figure 7-1     | Surface Mount Device Lead Forming .....  | 27 | Table 6-6     | Supported Holes with Component Leads,<br>Minimum Acceptable Conditions .....                              | 25 |
| Figure 7-2     | Surface Mount Device Lead Forming .....  | 27 | Table 6-7     | Unsupported Holes with Component Leads,<br>Minimum Acceptable Conditions .....                            | 26 |
| Figure 7-3     | Bottom Only Terminations .....   | 30 | Table 7-1     | SMT Lead Forming Minimum Lead<br>Length (L) .....   | 27 |
| Figure 7-4     | Rectangular or Square End Chip<br>Components .....                             | 31 | Table 7-2     | Surface Mount Components .....  | 29 |
| Figure 7-5     | Cylindrical End Cap Termination .....  | 32 | Table 7-3     | Dimensional Criteria – Bottom Only Chip<br>Component Terminations .....                                   | 30 |
| Figure 7-6     | Castellated Terminations .....   | 33 | Table 7-4     | Dimensional Criteria – Rectangular or<br>Square End Chip Components – 1, 3 or 5<br>Side Termination ..... | 31 |
| Figure 7-7     | Flat Gull Wing Leads .....   | 34 | Table 7-5     | Dimensional Criteria – Cylindrical End<br>Cap Terminations .....  | 32 |
| Figure 7-8     | Round or Flattened (Coined) Gull<br>Wing Leads .....                           | 35 | Table 7-6     | Dimensional Criteria – Castellated<br>Terminations .....  | 33 |
| Figure 7-9     | J Leads .....  | 36 | Table 7-7     | Dimensional Criteria – Flat Gull Wing Leads ...   | 34 |
| Figure 7-10    | Butt/I Connection for Modified Through-<br>Hole Leads .....                    | 37 | Table 7-8     | Dimensional Criteria – Round or Flattened<br>(Coined) Gull Wing Leads .....                               | 35 |
| Figure 7-11    | Butt/I Connection for Solder Charged<br>Lead .....                             | 38 | Table 7-9     | Dimensional Criteria – J Leads .....  | 36 |
| Figure 7-12    | Flattening Leads .....   | 39 | Table 7-10    | Dimensional Criteria – Butt/I Connections .....   | 37 |
| Figure 7-13    | Profile Components Having Bottom<br>Only Terminations .....                    | 40 |               |   |    |
| Figure 7-14    | Inward Formed L-Shaped Ribbon Lead .....                                       | 41 |               |   |    |
| Figure 7-15    | BGA Solder Ball Clearance .....  | 43 |               |   |    |
| Figure 7-16    | Bottom Termination Component .....   | 44 |               |   |    |

|            |  |    |
|------------|--|----|
| Table 7-11 | Dimensional Criteria – Butt/I Terminations –<br>Solder Charged Terminations .....          | 38 |
| Table 7-12 | Dimensional Criteria – Flat Lug Leads .....  | 39 |
| Table 7-13 | Dimensional Criteria – Tall Profile<br>Components Having Bottom Only<br>Terminations ..... | 40 |
| Table 7-14 | Dimensional Criteria – Inward Formed<br>L-Shaped Ribbon Leads .....                        | 41 |
| Table 7-15 | Dimensional Criteria – Ball Grid Array<br>Components with Collapsing Balls .....           | 43 |
| Table 7-16 | Ball Grid Array Components with<br>Noncollapsing Balls .....                               | 43 |
| Table 7-17 | Column Grid Array .....  | 43 |
| Table 7-18 | Dimensional Criteria – BTC .....   | 44 |
| Table 7-19 | Dimensional Criteria – Bottom Thermal<br>Plane Terminations .....                          | 45 |
| Table 7-20 | Dimensional Criteria Flattened Post<br>Connections .....                                   | 46 |
| Table 7-21 | Dimensional Criteria – P-Style Terminations ....   | 47 |
| Table 8-1  | Designation of Surfaces to be Cleaned .....  | 48 |
| Table 8-2  | Cleanliness Testing Designators .....  | 48 |
| Table 10-1 | Coating Thickness .....  | 52 |
| Table 12-1 | Magnification Aid Applications for Solder<br>Connections .....                             | 55 |
| Table 12-2 | Magnification Aid Applications – Other .....   | 55 |

# Requirements for Soldered Electrical and Electronic Assemblies

## 1 GENERAL

 **1.1 Scope** This standard prescribes practices and requirements for the manufacture of soldered electrical and electronic assemblies. For a more complete understanding of this document's recommendations and requirements, one may use this document in conjunction with IPC-HDBK-001 and IPC-A-610.

 **1.2 Purpose** This standard describes materials, methods and acceptance criteria for producing soldered electrical and electronic assemblies. The intent of this document is to rely on process control methodology to ensure consistent quality levels during the manufacture of products. It is not the intent of this standard to exclude any procedure for component placement or for applying flux and solder used to make the electrical connection.

**1.3 Classification** This standard recognizes that electrical and electronic assemblies are subject to classifications by intended end-item use. Three general end-product classes have been established to reflect differences in producibility, complexity, functional performance requirements, and verification (inspection/test) frequency. It should be recognized that there may be overlaps of equipment between classes.

The User, see 1.8.12, is responsible for defining the product class. The product class should be stated in the procurement documentation package.

### **CLASS 1 General Electronic Products**

Includes products suitable for applications where the major requirement is function of the completed assembly.

### **CLASS 2 Dedicated Service Electronic Products**

Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically the end-use environment would not cause failures.

### **CLASS 3 High Performance/Harsh Environment Electronic Products**

Includes products where continued high performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support or other critical systems.

**1.4 Measurement Units and Applications** All dimensions and tolerances, as well as other forms of measurement (temperature, weight, etc.) in this standard are expressed in SI (System International) units (with Imperial English equivalent dimensions provided in brackets). Dimensions and tolerances use millimeters as the main form of dimensional expression; micrometers are used when the precision required makes millimeters too cumbersome. Celsius is used to express temperature. Weight is expressed in grams.

**1.4.1 Verification of Dimensions** Actual measurement of specific part mounting and solder fillet dimensions and determination of percentages are not required except for referee purposes. For the purposes of determining conformance to this specification, all specified limits in this standard are absolute limits as defined in ASTM E29.